
# DLG Test Report 7196

# Geyer & Hosaja Sp. z o.o. Mattress Superior 33

Deformability/Elasticity, Permanent Tread Load



GEYER HOSAJA MATTRESS SUPERIOR 33 Deformability/Elasticity Permanent Tread Load DLG Test Report 7196





### **Overview**

A test mark "DLG-APPROVED for individual criteria" is awarded for agricultural products which have successfully fulfilled a scope-reduced usability testing conducted by DLG according to independent and recognised evaluation criteria. The test is intended to highlight particular innovations and key criteria of the test object. The test may contain criteria from the DLG test scope for overall tests, or focus on other value-determining



**MATTRESS SUPERIOR 33** Deformability/Elasticity Permanent Tread Load

characteristics and properties of the test subject. The minimum requirements, test conditions and procedures as well as the evaluation bases of the test results will be specified in consultation with an expert group of DLG. They correspond to the recognised rules of technology, as well as scientific and agricultural knowledge and requirements. The successful testing is concluded with the publication of a test report, as well as the awarding of the test mark which is valid for five years from the date of awarding.

The DLG Appoved Test "Deformability/Elasticity, Permanent Tread Load" includes technical measurements on test stands of the DLG Test Center. The deformability and elasticity were measured and a permanent tread load was applied. The test was based on the DLG Testing Framework for elastic stable flooring, as of December 2018 and DIN 3763:2020-04 (Elastic floorings for cattle and dairy cows walking and rest surfaces - Requirements and testing).

Other criteria were not investigated.

### Assessment in brief

The "Mattress Superior 33" tested here, is an elastic floor covering for the resting area in cubicle houses, was investigated with regard to durability and comfort properties on test stands in the DLG Test. The deformability and elasticity of the cubicle mat and a permanent tread load was applied. Requirements of DIN 3763 are fulfilled.

Deformation and Elasticity corresponds to class 3 DIN 3763.

#### Table 1: Assessment in brief

DLG QUALITY PROFILE	Evaluation*
Deformability and elasticity in new condition	
Deformability and elasticity following endurance test	
Lasting deformation following endurance test	
Wear following endurance test	

DLG Evaluation range:

or better = meets, exceeds or significantly exceeds the established DLG standards, 
= meets the legal requirements for marketability, 
= failed

# **The Product**

Manufacturer and Applicant	Description and technical data
Geyer & Hosaja Sp. z o.o. Partynia 12 39-310 Radomysl Wielki Poland	The "Mattress Superior 33" tested here, is an elastic floor covering for the resting area in cubicle houses.
	Cubicle Mattress Superior 33
Product: Mattress Superior 33	<ul> <li>Black rubber mat with a three-layer structure. On a rubber mat with a thickness of approx. 25 mm there is a PU foam about 25 mm thick and on the foam an approx. 9 mm thick rubber mat with hammer impact profiling. In the edge area, the two rubber mats are vulcanized together so that the foam is completely enclosed with rubber.</li> <li>Thickness complete: approx. 59 mm</li> <li>Shore A hardness: approx. 60</li> </ul>
Contact: Telephone +48 14680 6755 slawomir.haag@geyer-hosaja.com.pl www.geyer-hosaja.com	

# **The Method**

#### **Deformability and elasticity**

The deformability is measured in new condition and following permanent tread load using ball penetration tests with a calotte (r = 120 mm) and a penetration force of 2,000 N (corresponding to approx. 200 kg).

#### Permanent tread load

The permanent tread load is measured on a test stand with a round steel foot in the standard test programme with 100,000 alternating loads at 10,000 N (corresponding to approx. 1,000 kg).

The steel foot is adapted to the natural conditions as an "artificial cow foot". The foot has a diameter of 105 mm and therefore a contact area of 75 cm<sup>2</sup>; the carrying edge of the hoof is simulated by a 5 mm wide ring on the periphery of the sole that projects 1 mm above the rest of the surface.


# **Detailed account of the test results**


#### **Deformability and elasticity**

In the ball penetration tests in new condition with a calotte (r = 120 mm), penetration depth was 20.9 mm. The resulting calculated bearing pressure of 12.7 N/cm<sup>2</sup> indicates a low load on the carpal joints when lying down and getting up.

Elasticity was measured following a permanent tread load exerted by a steel foot (contact area: 75 cm<sup>2</sup>) with 100,000 alternating loads at 10,000 N.

Following the endurance test, the penetration depth of the calotte increased from 20.9 mm to 22.2 mm. The bearing pressure decreased from 12.7 N/cm<sup>2</sup> to 12.0 N/cm<sup>2</sup> (see Fig. 2). This





means that deformability and elasticity slightly increase.

#### Permanent tread load

No noticeable wear was observed following exposure to permanent tread load on a test stand with 100,000 alternating loads at 10,000 N. No lasting deformation was observed.



Figure 3: Deformation measurement



Figure 4: Permanent tread load test

# Summary

Based on test-stand investigations, the criteria tested in this DLG Approved Test evaluate the comfort and durability properties of the "Mattress Superior 33" for use in the resting area of high cubicles in cubicle houses.

The tested cow mattress met the requirements of DIN 3763 and the DLG Testing Framework with respect to the investigated criteria.

# **Further information**

#### **Testing agency**

DLG TestService GmbH, Gross-Umstadt location

The tests are conducted on behalf of DLG e.V.

#### **DLG test framework**

DLG Testing Framework for elastic stable flooring, as of April 2010

DIN 3763:2020-04 (Elastic floorings for cattle and dairy cows walking and rest surfaces – Requirements and testing)

#### Department

Agriculture

Division head

Dr. Ulrich Rubenschuh

## Test engineer(s)

Dr. Harald Reubold\*

\* Author

### DLG – the open network and professional voice

Founded in 1885 by the German engineer Max Eyth, DLG (Deutsche Landwirtschafts-Gesellschaft – German Agricultural Society) is an expert organisation in the fields of agriculture, agribusiness and the food sector. Its mission is to promote progress through the transfer of knowledge, quality standards and technology. As such, DLG is an open network and acts as the professional voice of the agricultural, agribusiness and food sectors.

As one of the leading organisations in the agricultural and food market, DLG organises international trade fairs and events in the specialist areas of crop production, animal husbandry, machinery and equipment for farming and forestry work as well as energy supply and food technology. DLG's quality tests for food, agricultural equipment and farm inputs are highly acclaimed around the world.

For more than 130 years, our mission has also been to promote dialogue between academia, farmers and

the general public across disciplines and national borders. As an open and independent organisation, our network of experts collaborate with farmers, academics, consultants, policymakers and specialists in administration in the development of futureproof solutions for the challenges facing the agriculture and the food industry.

# Leaders in the testing of agricultural equipment and input products

The DLG Test Center Technology and Farm Inputs and its test methods, test profiles and quality seals hold a leading position in testing and certifying equipment and inputs for the agricultural industry. Our test methods and test profiles are developed by an independent and impartial commission to simulate in-field applications of the products. All tests are carried out using state-of-the-art measuring and test methods applying also international standards.

Internal test code DLG: 2106-0037 Copyright DLG: © 2022 DLG



#### DLG TestService GmbH Groß-Umstadt location

Max-Eyth-Weg 1 • 64823 Groß-Umstadt • Germany Phone: +49 69 24788-600 • Fax: +49 69 24788-690 Tech@DLG.org • www.DLG.org Download of all DLG test reports free of charge at: www.DLG-Test.de