

DeLaval

# Cubicle Roll CR 20

Deformability/Elasticity, Permanent Tread Load,  
Abrasion, Slip resistance



**DELAVAL  
CUBICLE ROLL CR 20**

- ✓ Deformability/Elasticity
- ✓ Permanent Tread Load
- ✓ Abrasion
- ✓ Slip resistance

DLG Test Report 7522

## Overview

A test mark “DLG APPROVED for individual criteria” is awarded for agricultural products which have successfully fulfilled a scope-reduced usability testing conducted by DLG according to independent and recognised evaluation criteria. The test is intended to highlight particular innovations and key criteria of the test object. The test may contain criteria from the DLG test scope for overall tests, or focus on other value-determining characteristics and properties of the test subject. The minimum requirements, test conditions and procedures as well as the evaluation bases of the test results will be specified in consultation with an expert group of DLG. They correspond to the recognised rules of technology, as well as scientific and agricultural knowledge and requirements. The successful testing is concluded with the publication of a test report, as well as the awarding of the test mark which is valid for five years from the date of awarding. The DLG Approved Test “Deformability/Elasticity, Permanent Tread Load, Abrasion, Slip resistance” includes technical measurements on test stands of the DLG Test Center. The deformability and elasticity, the abrasion resistance, the slip resistance, were measured and a permanent tread load was applied. The test was based on the DLG Testing Framework for elastic stable flooring, as of December 2018 and DIN 3763:2022-08 (Elastic floorings for cattle and dairy cows walking and rest surfaces – Requirements and Testing). Other criteria were not investigated.



**DELAVAL  
CUBICLE ROLL CR 20**  
 ✓ Deformability/Elasticity  
 ✓ Permanent Tread Load  
 ✓ Abrasion  
 ✓ Slip resistance  
 DLG Test Report 7522

## Test results

DLG QUALITY PROFIL	Evaluation
Deformability and elasticity – in new condition and following endurance test	■ ■ ■ ■ □ *
Deformability and elasticity – following endurance test	■ ■ ■ ■ □ *
Lasting deformation following endurance test	■ ■ ■ ■ ■ *
Wear following endurance test	■ ■ ■ □ □ *
Abrasion	■ ■ ■ ■ □ *
Slip resistance	■ ■ **

Requirements of DIN 3763 fulfilled in the examined criteria.  
 Deformability and elasticity class 2 according to DIN 3763.

The DLG test framework specifies the following evaluation range::

\* ■ ■ ■ or better = meets, exceeds or clearly exceeds the specified DLG standard,

■ ■ = meets the statutory requirements for marketing the product, ■ = failed

\*\* Single criteria slip resistance: ■ ■ = passed, ■ = failed

## Manufacturer and contact information

DeLaval International AB site Glinde, P.O. Box 1136, DE-21509 Glinde/Germany

Phone +49 (0)40 303344-308, Fax +49 (0)40 303344-349

Mathias.Reichert@delaval.com, www.delaval.com

The CR 20 already received the DLG Approved test mark in 2018. The results presented in the report are based on DLG test report 6821. According to the applicant the CR 20 is manufactured unchanged in the tested version.



**DLG TestService GmbH**

**Groß-Umstadt location**

Max-Eyth-Weg 1 • 64823 Groß-Umstadt • Germany

Phone +49 69 24788-600 • Fax +49 69 24788-690

Tech@DLG.org • www.DLG.org

**All DLG test reports are  
 available for download free of  
 charge at: [www.DLG-Test.de](http://www.DLG-Test.de)**