Prüfstelle für Landmaschinen



REPORT on test in accordance with OECD STANDARD CODE 2 for the Official Testing of Agricultural Tractor Performance

OECD No. 2/1894
21st March 2000

Agricultural Tractor

CASE IH CX 60 (4WD) 40 km/h version

Manufacturer

CASE United Kingdom Limited
Doncaster, DN2 4PG, England

This is a report on a tractor test in accordance with OECD STANDARD CODE for the Official Testing of Agricultural Tractor Performance "Yellow Code", January 1998, Code 2 (Restricted Code).

It does not contain an evaluation of the tractor on practical work.

Duration of tests: May till August 1999

DLG-Testing Station for Agricultural Machinery, Max-Eyth-Weg 1,
D-64823 Groß-Umstadt

This report has been approved by the OECD Co-Ordinating Centre (CEMAGREF, France) as being in accordance with the OECD STANDARD CODE.

Date of approval: 21st March 2000

OECD No. 2/1894
Restricted Code

In this report all performance characteristics are given corresponding to the International System of Units.

The reference to the former used Technical System of Units is given by the following relations:

Forces	1 kN	=	1000 N	=	102 kp
Powers			1 kW	=	1,36 PS
Pressures	1 MPa	=	10 bar	=	10,2 kp/cm^2
	100 kPa	=	1000 mbar	=	750,10 mm Hg

All rights including the right of translation, reprint and photo-mechanical copying - also of excerpts - reserved by the editor.

Printed in Germany, May 2000
DLG-No. 320

CASE IH CX 60 (4WD) **DLG-Test No 99-090**

TABLE OF CONTENTS

		Page
1	SPECIFICATION OF TRACTOR	4 to17
	TEST CONDITIONS	18 to 20
3	COMPULSORY TESTS RESULTS	
3.1	MAIN POWER TAKE OFF PERFORMANCE	21 to 24
3.2	HYDRAULIC POWER AND LIFTING FORCE	25
3.3	DRAWBAR POWER TEST	26 and 27
4	OPTIONAL TESTS RESULTS	None
5	REPAIRS	None
6	REMARKS	None

CASE IH CX 60 (4WD) **DLG-Test No 99-090**

Tractor manufacturer:	CASE United Kingdom Limited Doncaster, DN2 4PG, England
Location of tractor assembly:	Doncaster, DN2 4PG, England
Submitted for test by:	CASE United Kingdom Limited
Selected by:	Manufacturer with agreement by DLG
Place of running-in:	Doncaster and Groß-Umstadt
Duration of running-in:	Engine and tractor approximate 53 h
Location of test:	DLG-Testing Station, D-64823 Groß-Umstadt

1 SPECIFICATION OF TRACTOR

1.1 Identification

- Make/Model/Type:	CASE IH / CX 60 / wheel tractor, unit construction, four wheel driven
- Trade name:	CX 60 A, 40 km/h version
- Number of driving- wheels:	4
- Serial No.:	JJE 100 1817
- 1st serial No.:	JJE 100 001

1.2 Engine

Make/Model:	PERKINS / 1942/2250 (Case - model 903.27T)
Type:	Water-cooled 4-stroke Diesel-engine, direct injection, supercharged
Serial no.:	U 323977D

1.2.1 Cylinders

Number/disposition:	3 / in line
Bore/stroke:	95 / 127 mm
Capacity:	2700 cm^3
Compression ratio:	17.25 ± 1 :1
Arrangement of valves:	Overhead valves
Cylinder liners:	Dry

1.2.2 Supercharging

- Make/Model:	SCHWITZER / -
- Type:	Exhaust driven supercharger
- Pressure:	Max. 83.8 kPa

CASE IH CX 60 (4WD) **DLG-Test No 99-090**

1.2.3 Fuel system

- Fuel feed system:	Diaphragm fuel supply pump
- Fuel filter	
Make/Model:	PERKINS / - /
Type :	1 replaceable filter
- Capacity of fuel tank:	155 dm³
- Injection pump	
Make/Model:	LUCAS/8922 A 161 T
Type :	DP 200, distributor pump
Serial no.:	39095 ARG
Manufacturer's production setting:	66 ± 2 mm³/stroke at full load and rated speed;
Flow rate:	13.4 ± 0.4 dm³/h at 2250 min⁻¹ and full load
Timing:	Commencement of delivery: TDC ± 2°
- Injectors	
Make/Model:	LUCAS / KS L 068 PBA
Type :	multi hole
Injection pressure:	29.4 ± 0.5 MPa

1.2.4 Governor

- Make/Model/Type:	LUCAS / - / mechanical, centrifugal variable speed governor, integral with injection pump
- Governed range of engine speed:	800 ± 50 to 2407 ± 50 min⁻¹
- Rated engine speed:	2250 min⁻¹

1.2.5 Air cleaner

- Pre-cleaner	
- Make/Model/Type:	DONALDSON / - / Cylone type, integrated in main cleaner housing
Location of air intake:	In front of engine, below bonnet
- Main cleaner	
Make/Model:	DONALDSON / 133 721 A
Type:	Dry paper element filter with additional safety cartridge
- Maintenance indicator:	Warning light on dashboard

1.2.6	Lubrication system:	Pressure lubrication with engine oil / cooling water heat exchanger in oil filter socket
	- Type of feed pump:	Internal gear pump
	- Type of filter:	Full flow, replaceable (metallic cartridge)
	- Number of filter:	1
1.2.7	Cooling system	
	- Type of coolant:	Water cooling
	- Type of pump:	Impeller pump
	- Specification of fan	
	Number of fan blades:	7
	Fan diameter:	475 mm
	- Coolant capacity:	13.4 dm³
	- Type of temperature control:	Thermostat and by-pass circuit, viscous drive fan EATON, model 610, belt driven, variable fan speed controlled by air flow temperature
	- Superpressure system:	110 kPa
1.2.8	Starting system	
	- Make/Model/Type:	MAGNETI MARELLI / - / electrical, solenoid pre-engaged drive starter motor 2.8 kW;
	- Cold starting aid:	Flame glow plug in air intake manifold
	- Safety device:	Forward/reverse lever in neutral position p.t.o. clutch disengaged
1.2.9	Electrical system	
	- Voltage:	12 V
	- Generator	
	Make/Model/Type:	MAGNETI MARELLI/ A 127-65 / 3-phase alternator
	Power:	1 kW
	- Battery:	1 lead acid battery, 95 Ah at 20 hours rating
1.2.10	Exhaust system	
	- Make/Model/Type:	DONALDSON / M050125 / multi-chamber absorption type silencer, 118 mm dia, 1110 mm long
	- Location:	On the right, beside the engine, in front of the steps, vertical stack, mouth showing upwards/45°
	Optionally	
	- Make/Model/Type:	DONALDSON / M050126 / multi-chamber absorption type silencer, 152x103 mm oval, 597 mm long
	- Location:	Through tractor hood
1.2.11	Operating hours meter	Electronic, counts real hours when engine is running

1.3 Transmission

1.3.1 Clutch (travel alone)

- Make/Model/Type: LUK / 223 808 A / dry multi-plate
- Diameter of discs: 305 mm
- Method of operation: By pedal, hydraulical

1.3.2 Gear box

- Make/Model/Type: CASE / KT / mechanical, power shift, 40 km/h version
- Description:
  1. Synchro-mesh gearbox with 4 speeds
  2. synchro-mesh range gear with 2 ranges (Hi/Lo)
  3. power shifted range gear with 2 ranges (TA/DD)
  4. synchro-mesh reversing gear (F/R)
     reversing operation only for range TA

	forward	reverse
no. of gears	4	4
no. of ranges	2x2	2
total of arrangements	16	8

3 levers, 1 toggle switch

- Available options: CASE / NT / mechanical, power shift 30 km/h version

  CASE / QT / mechanical,
  30 km/h version, 8 forward / 8 reverse
- Lubrication: Forced-feed lubrication, oil cooler in front of engine's water cooler

1.3.3 Rear axle and final drives

- Make/Model/Type: CASE / - / bevel gear drive with bevel gear differential and planetary final drives
- Differential lock
  - Type: Dog clutch
  - Engagement: By toggle switch, electro-hydraulical (through low pressure hydraulic circuit)
  - Disengagement: By service brake operation or engine cut off or by toggle switch

1.3.4 Front axle and final drives

- Make/Model/Type: CARRARO / 707S4 164 / bevel gear drive with bevel gear differential and planetary final drives, driven by wet multi plate clutch and central shaft, clutch electro-hydraulically operated by toggle switch (through low pressure hydraulic circuit)

- Differential lock

Type:	Limited slip multi-disc type
Engagement:	Automatic
Disengagement:	Automatic

1.3.5 Total ratios and travelling speeds

Range	Gear	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed*) at rated engine speed 2250 min^{-1} km/h
Forward Speeds			
Lo - TA	1	301.24	2.17
Lo - DD		249.82	2.61
Lo - TA	2	171.03	3.82
Lo - DD		141.83	4.60
Lo - TA	3	115.43	5.66
Lo - DD		95.73	6.82
Lo - TA	4	73.64	8.87
Lo - DD		61.07	10.70
Hi - TA	1	80.33	8.13
Hi - DD		66.62	9.80
Hi - TA	2	45.61	14.32
Hi - DD		37.82	17.27
Hi - TA	3	30.78	21.22
Hi - DD		25.53	25.59
Hi - TA	4	19.64	33.26
Hi - DD		16.29	40.11
Reverse Speeds			
Lo - TA	1	276.14	2.37
Hi - TA		73.64	8.87
Lo - TA	2	156.77	4.17
Hi - TA		41.81	15.62
Lo - TA	3	105.81	6.17
Hi - TA		28.22	23.15
Lo - TA	4	67.50	9.68
Hi - TA		18.00	36.29

*) calculated with the radius index (ISO 4251-1:1992) 770 mm

Number of revolutions of front wheels for one revolution of rear wheels: 1.407

1.4 Power take-off

1.4.1 Main power take-off

- Type: Independent
- Method of engagement: Driven by wet multi-plate clutch with 125 mm dia; by lever hydraulically operated
- Number of shafts: 1
- Method of changing power take-off shaft ends and speeds: One shaft, not changeable, 2 different standard speeds shiftable by separate lever

1.4.1.1 Power take-off proportional to engine speed, 540 and 540 E min^{-1}

- Location: At rear of tractor
- Diameter of p.t.o. shaft end: 35 mm
- Number of splines: 6 in conformity with ISO 500:1991, type 1
- Height above ground: 648 mm
- Distance from the median plane of the tractor: 0 mm
- Distance behind rear-wheel axis: 435 mm

p.t.o. type	p.t.o. transmission ratio	p.t.o. speed min^{-1}	engine speed min^{-1}	power restriction kW
540	3.7159	540 606	2007 2250	-
540 E	2.6818	540 839	1448 2250	-

- Direction of rotation (viewed from behind tractor): Clockwise


1.4.1.2 Power take-off proportional to ground speed: None

1.5 Hydraulic power lift

- Make/Model/Type:	CASE-IH / - / electronic-hydraulic power lift, top link sensing
- Type of hydraulic system:	Open center
- Type and Number of cylinders:	1 internal cylinder, single acting, 89 mm bore, 145 mm stroke
- Type of linkage lock for transport:	Hydraulic, lowering throttle
- Relief valve pressure setting:	17.2 to 18.0 MPa
- Opening pressure of cylinder safety valve:	18.6 MPa
- Lift pump type:	SAUER SUNDSTRAND fixed delivery gear pump
- Transmission between pump and engine:	Pump gear driven by forward end of p.t.o shaft, independent of p.t.o. clutch
- Type and number of filters:	1 filter in feeding line of hydraulic pump, 1 fine screen in feeding line of transfer pump
- Site of oil reservoir:	Transmission housing, common with transmission oil
- Type, number and location of tapping points:	2 pairs, double acting, at rear of tractor; 1 separate low pressure return line coupler
- Maximum volume of oil available to external cylinders:	13.6 dm^3 40.9 dm^3 with overfill

1.6 Three-point linkage:

- Category: 2, in conformity with ISO 730-1:1994
- Category adapter: None



CASE IH CX 60 (4WD) **DLG-Test No 99-090**

Dimensions of rear implement linkage			projected lengths in mm dimensions and range	settings used in test-page 25
Rear tyres 18.4 R 34 Front tyres 13.6 R 24		(r) *) (r') *)	770 560	
Length of lift arms		(A)	298	298
Length of lower links		(B)	814	814
Distance of lift arm pivot points from rear wheel axis	horizontal vertical	(a) (b)	66 288	66 288
Horizontal distance between the 2 lower link pivot points		(u)	455	455
Horizontal distance between the 2 lift arm end points		(v)	540	540
Length of upper link		(S)	from 600 to 800	716
Distance of upper link pivot point from rear wheel axis	horizontal vertical	(c) (d)	300 200	300 200
Distance of lower link pivot points from rear wheel axis	horizontal vertical	(e) (f)	161 170	161 170
Distance of lower link pivot points to lift rod pivot points on lower links		(D)	550	550
Length of lift rods		(L)	from 635 to 750	750

Heights (h, H, H') of lower link hitch points relative to rear wheel axis (situated 770 mm above ground), at different adjustments of L

These data are valid for unloaded power lift

Length of lift rods	(L)	635	750
Linkage distance of lift rods	(D)	550	
Lowest position	(h)	330	570
Highest position	(H)	250	90
Transport position	(H')	250	90

*) Assuming r resp. r' = tyre dynamic radius index of ISO 4251-1:1992

1.7 Swinging drawbar

- Type:	Longitudinally adjustable
- Height above ground:	395 mm
- Type of height adjustment:	None
- Distance of hitch point from rear-wheel axle	700/785/830 mm
- Distance of hitch point from power take-off shaft end	
Vertical	253 mm
Horizontal	265/350/395 mm
- Lateral adjustment (centre of clevis)	
Right and left hand each:	233/277/300 mm
- Distance of pivot point from rear-wheel axis, horizontal (rearward)	240 mm
- Drawbar pin hole diameter	32 mm
- Maximum vertically permissible load (short position)	8.8 kN

1.8 Trailer hitch

- Make/Model/Type:	CRAMER / KU 5410/309 / non-automatical
- Hole diameter:	32 mm
- Height above ground:	Centre of clevis adjustable in 5 steps to 575/675/775/825/875 mm
- Distance of hitch point from rear-wheel axis, horizontal:	594 mm
- Distance of hitch point from power take-off shaft end	
Vertical	below 73 mm, above 27/127/177/227 mm
Horizontal	159 mm
- Maximum vertically permissible load:	15.0 kN

1.9 Holed drawbar

Not fitted

1.10	**Steering**	
	- Make/Model/Type:	DANFOSS / OSPC 100 OR / hydrostatic
	- Method of operation	
	Pump:	Separate SAUER SUNDSTRAND fixed delivery (28 dm^3/min) gear pump, driven by engine
	Ram:	CARRARO, integrated cylinder of symmetrical design; 172 mm stroke, 63 mm bore, 36 mm piston rod dia
	- Working pressure:	15.1 MPa
1.11	**Brakes**	
1.11.1	Service brake:	
	- Make/Model/Type:	CASE / - / muscle power brake with hydraulic transmission, brake fluid provided by hydraulic circuit
	- Method of operation:	Pedal operated, acting on rear wheels, front axle drive is automatically engaged when braking, oil-immersed disc brake with 1 ring-piston on each differential half shaft, disc 259 mm dia
	- Trailer braking take-off:	None Hydraulic trailer braking take-off on request available
1.11.2	Parking brake	
	- Type:	Mechanical, separate brake on front wheel drive shaft
	- Method of operation:	Hand lever with ratchet

1.12 Wheels

- Number

  Front: 2, driving and steering
  Rear. 2, driving

- Wheelbase: 2214 mm

- Track width adjustment:

	Minimum mm	Maximum mm	Adjustment method
Front	1299	1894	adjustable rims
Rear	1420	1922	adjustable rims

1.12.1 - Possible combinations of tyres sizes

Rear	Front
18.4 R 34	12.4 R 24 13.6 R 24 360/70 R 24 380/70 R 24
16.9 R 34	11.2 R 24 12.4 R 24 13.6 R 24 360/70 R 24
13.6 R 38	11.2 R 24 12.4 R 24 360/70 R 24
18.4 R 30	14.9 R 20 375/75 R 20 11.2 R 24 12.4 R 24
16.9 R 30	12.4 R 20 14.9 R 20 335/80 R 20 375/75 R 20 405/70 R 20 9.5 R 24
13.6 R 28	11.2 R 20

This is the list of the most popular tyres combinations, further combinations are available

1.13 Protective structure

- Make/Model:	CASE IH / MX11
- Type:	Four-Post ROPS, may be fitted with optional sun roof (plastics)
- Manufacturer's name and address:	CASE France S.A. BP 109 59964 Croix Cedex France
- Protective device	
Cab/frame/rollguard/other:	Frame, welded to a platform which is mounted by 4 antivibration blocks to the tractor
Tiltable/not tiltable:	not tiltable
- OECD approval	
Approval number:	4/0525
Date of approval:	29th May 1998
- Nos. of minor modification certificates:	Mod 1 (15th September 1998) Mod 2 (08th January 1999)
- Optional protective device:	Not fitted
- Make/Model/Type:	CASE IH / MX11 Standard Cab or MX11 Low Profile Cab
- Manufacturer's name and address:	CASE France S.A. BP 109 59964 Croix Cedex France
- Protective device	
Cab/frame/rollguard/other:	Cab
Tiltable/not tiltable:	not tiltable
- OECD approval	
Approval number:	CSS 0472/9 resp. CSS 0472/10
Date of approval:	21st October 1997
- Nos. of minor modification certificates:	Mod 1 (08th January 1999) Mod 2 (27th August 1999)

1.14 Seat

1.14.1 Driver's seat — Fitted to tractor

- Make/Model: Grammer / DS 85 H/90A
- Type: Upholstered seat with back rest
- Seat and steering wheel reversible: No
- Type of suspension: Mechanical
- Type of damping: Hydraulical
- Range of adjustment
  - Longitudinally: 210 mm
  - Vertically: 60 mm
- Safety belt: On request, not fitted

1.14.2 Optional driver's seats

- Make/Model/Type: Grammer / DS 85H/7L / mechanical suspension
  or
  Grammer / MSG 95A/31C / air suspension

1.14.3 Passenger seat: On request, not fitted

1.15 Lighting Electrical, 12 Volt

	Height above ground of centre	Size	Distance from outside edge of lights to median plane of tractor
	mm	mm	mm
Headlights	1360	180x103	263
Sidelights	1625	113x36	888
Rearlights	1665	67x62	755
Reflectors 1st pair	1665	50x62	805
2nd pair	880	60 dia	300

2. TEST CONDITIONS

2.1 Overall dimensions

Length	Width	Height at top of	
		protective structure	exhaust silencer pipe
mm	mm	mm	mm
3860	2100	2520	2523

2.2 Ground clearance 330 mm

- Clearance-limiting part: Bracket of swinging drawbar

2.3 Tractor mass Unballasted (with frame)

	Without driver kg	With driver kg
Front	1430	1440
Rear	2020	2085
Total	3450	3525

2.4 Track specifications Not applicable

2.5 Tyres and track widths specifications

	Front	Rear
Tyres:	GOODYEAR	GOODYEAR
dimensions	13.6 R 24	18.4 R 34
load index speed index	121 A8	144 A8
type	radial ply	radial ply
maximum load (tyre manufacturer's)	14.2 kN	27.5 kN
at travelling speed	40 km/h	40 km/h
at tyre inflation pressure	160 kPa	160 kPa
radius index (ISO 4251-1 : 1992)	560 mm	770 mm
Chosen track width:	1530 mm	1620 mm
*) Technically permissible axle load:	29.00 kN	41.44 kN
*) Technically permissible total weight:	60.0 kN	

*) without consideration of load restriction, given by the tyres used

2.6 Fuel

- Type: ARAL-Diesel-fuel, in conformity with DIN 51601
- Density at 15°C: At p.t.o. tests 0.830 g/cm³
  at drawbar power tests 0.844 g/cm³

2.7 Oils and lubrication

2.7.1 Capacity and change interval

	Capacity	Oil change	Filter change
	dm³	h	h
Engine	7.6	250	250
Gear box	37	1000	500
Front axle	5.5	1000	-
Rear axle	common with gearbox	common with gearbox	common with gearbox
Final drives (front, each)	0.6	1000	-
Final drives (rear)	common with gearbox	common with gearbox	common with gearbox
Hydraulic system	common with gearbox	common with gearbox	common with gearbox
Steering	common with gearbox	common with gearbox	common with gearbox

2.7.2 Specifications:

	Recommended	Used during test
Engine oil:		
Used in engine		
Type	Multi-grade oil	MS1121*) Case No. 1
Viscosity	SAE 15W-40	SAE 15W-40
Classification	API CG-4 or CF-4	API CG-4 or CF-4
Transmission oil:		
Used in gearbox, rear axle, hydraulic- and steering system		
Type	CASE HY-TRAN PLUS	CASE HY-TRAN PLUS
Viscosity	ISO-VG-46	ISO-VG-46
Classification	MS 1223*)	MS 1223*)
Used in front axle and front final drives		
Type	Gear oil	
Viscosity	SAE 84W-140	
Classification	API-GL5 or MS 1316*)	

*) MS 1121, MS 1223 and MS 1316 = CASE specification

2.7.3 Grease: Multi purpose grease

- number of lubrication points: 9

CASE IH CX 60 (4WD) **DLG-Test No 99-090**

3. COMPULSORY TESTS RESULTS

3.1 MAIN POWER TAKE OFF PERFORMANCE (540 min^{-1})

Date of tests: 20th April 1999
Location of tests: DLG-Testing Station Groß-Umstadt
Type of dynamometer: SCHENCK hydraulic dynamometer U1-40

Power kW	Speed Engine min^{-1}	Speed P.t.o. min^{-1}	Fuel consumption hourly dm³/h	Fuel consumption hourly kg/h	Fuel consumption specific g/kWh	Specific energy kWh/dm³
Maximum power						
3.1.1 At 2-hour test						
42.1	2200	592	12.92	10.72	255	3.26
3.1.2 At rated speed						
41.9	2250	606	13.06	10.84	258	3.21
3.1.3 At standard p.t.o. speed						
41.0	2006	540	11.98	9.94	243	3.42
3.1.4 **Part loads, the governor hand lever in the position corresponding to maximum power at full load (curve a)**						
3.1.4.1 the torque corresponding to maximum power at rated speed						
41.9	2250	606	13.06	10.84	258	3.21
3.1.4.2 85% of the torque obtained in 3.1.4.1						
36.5	2298	618	11.81	9.80	269	3.09
3.1.4.3 75% of the torque defined in 3.1.4.2						
27.8	2333	628	10.05	8.34	300	2.77
3.1.4.4 50% of the torque defined in 3.1.4.2						
18.8	2367	637	7.87	6.53	348	2.39
3.1.4.5 25% of the torque defined in 3.1.4.2						
9.7	2389	643	5.36	4.45	457	1.82
3.1.4.6 unloaded						
-	2417	651	3.25	2.70	-	-

Power kW	Speed Engine min⁻¹	Speed P.t.o. min⁻¹	Fuel consumption hourly dm³/h	Fuel consumption hourly kg/h	Fuel consumption specific g/kWh	Specific energy kWh/dm³
3.1.5 Part loads, the governor hand lever in the position corresponding to standard p.t.o. speed at full load (curve b)						
3.1.5.1 the torque corresponding to maximum power						
41.0	2006	540	11.98	9.94	243	3.42
3.1.5.2 85% of the torque obtained in 3.1.5.1						
35.8	2051	552	10.88	9.03	253	3.29
3.1.5.3 75% of the torque defined in 3.1.5.2						
27.4	2095	564	9.05	7.51	274	3.03
3.1.5.4 50% of the torque defined in 3.1.5.2						
18.7	2140	576	6.93	5.75	308	2.70
3.1.5.5 25% of the torque defined in 3.1.5.2						
9.4	2166	583	4.63	3.84	407	2.04
3.1.5.6 unloaded						
-	2167	583	2.75	2.29	-	-


No load maximum engine speed:	2417 min⁻¹
Equivalent flywheel torque at rated engine speed:	178 Nm
Equivalent flywheel torque at 2-hour test:	183 Nm
at engine speed:	2200 min⁻¹
Maximum equivalent flywheel torque:	218 Nm
at engine speed:	1293 min⁻¹


Mean atmospheric conditions

temperature:	21 °C
pressure:	994 hPa
relative humidity:	55 %

Maximum temperatures

coolant:	84 °C
oil:	112 °C
fuel:	66 °C
air intake:	21 °C


p.t.o. test
p.t.o. power P
kW
M
P
Nm
equivalent torque M
standard p.t.o. speed 540 1/min
Case CX 60
fuel consumption B
kg/h
B
be
g/kWh
spec. fuel consumption be
engine speed
1/min
50
40
35
30
25
20
15
10
5
0
250
200
175
150
125
100
75
50
25
0
9
6
3
260
240
220
200
1000
1200
1400
1600
1800
2000
2200
2600


640
g/kWh
560
520
480
440
400
360
320
280
240
200
specific fuel consumption be
curve a
curve b
be
Case IH CX 60 (4WD)
0
5
10
15
20
25
30
35
40
kW
50
p.t.o. power

3.2 HYDRAULIC POWER AND LIFTING FORCE

- Date of tests: 3rd and 4th August 1999

3.2.1 Hydraulic power test

- Sustained pressure with relief valve open — 17.6 MPa
- Pump delivery rate at minimum pressure — 54.6 dm³/min

	Hydraulic power kW	Flow rate dm³/min	Pressure MPa	Oil Temperature °C
At 90% of the actual relief valve setting	11.6	44.1	15.8	65
Maximum	11.8	43.6	16.3	65

- Tapping point used for test: At rear of tractor, connected with additional control valve no 2

3.2.2 Power lift test

	At the hitch points	On the frame
Height of lower hitch points above ground in down position	200 mm	
Vertical movement without lifting forces	660 mm	890 mm
with lifting forces	640 mm	850 mm
Max. corrected force exerted through full range	15.30 kN	11.70 kN
Corresponding pressure	15.8 MPa	
Moment about rear axle	-	18.50 kNm
Max. tilt angle of mast from vertical		9°

Lifting heights relative to horizontal lower links

mm	-530	-500	-400	-300	-200	-100	0	+100	+200	+240	+300	+320
Lifting forces at hitch points, corrected to 15.8 MPa												
kN			15.30	17.10	18.50	19.10	19.60	19.80	19.80	19.60		
Lifting forces at standard frame, corrected to 15.8 MPa												
kN	11.70	11.90	12.80	13.50	14.00	14.40	14.30	14.00	13.70		13.10	12.60

3.3 DRAWBAR POWER TEST

- Date of test: 11th till 12th May 1999
- Type of track: Concrete

Gear number and range	Power	Drawbar pull	Speed	Engine speed	Slip of wheels	Specific fuel consumption
	kW	kN	km/h	min^{-1}	%	g/kWh
3.3.1	MAXIMUM POWER IN TESTED GEARS (unballasted tractor)					
1 TA - Lo	21.3	39.90	1.92	2332	15.1	415
1 DD - Lo	25.9	40.74	2.29	2306	14.9	389
2 TA - Lo	34.3	35.50	3.48	2199	7.2	313
2 DD - Lo	34.0	28.50	4.30	2190	4.4	317
3 TA - Lo	35.0	23.60	5.34	2197	3.6	309
3 DD - Lo	34.8	19.31	6.49	2195	2.9	309
1 TA - Hi	35.5	16.45	7.76	2195	2.5	304
4 TA - Lo	34.7	14.70	8.49	2197	2.2	311
1 DD - Hi	34.4	13.19	9.39	2193	2.0	314
4 DD - Lo	32.5	11.36	10.29	2194	1.7	332
3.3.2	FUEL CONSUMPTION					
3.3.2.1	in selected gear, at maximum power at rated speed,					
1 TA - Hi	36.08	16.30	7.97	2250	2.4	301
3.3.2.1.1	75 % of pull at maximum power at rated speed					
1 TA - Hi	28.2	12.27	8.26	2323	1.8	338
3.3.2.1.2	50 % of pull at maximum power at rated speed					
1 TA - Hi	19.0	8.16	8.40	2347	1.2	403
3.3.2.1.3	next higher gear at reduced engine speed; same pull and travelling					
4 TA - Lo	28.0	12.27	8.23	2118	1.9	325
3.3.2.1.4	next higher gear at reduced engine speed; same pull and travelling					
4 TA - Lo	18.9	8.09	8.42	2155	1.3	392
3.3.2.2	in selected gear					
4 TA - Lo	34.4	14.24	8.69	2247	2.1	316
3.3.2.2.1	75 % of pull at maximum power at rated speed					
4 TA - Lo	26.6	10.67	8.99	2314	1.7	369
3.3.2.2.2	50 % of pull at maximum power at rated speed					
4 TA - Lo	18.3	7.15	9.19	2348	1.1	402
3.3.2.2.3	next higher gear at reduced engine speed; same pull and travelling					
1 DD - Hi	26.8	10.63	9.09	2112	1.6	336
3.3.2.2.4	next higher gear at reduced engine speed; same pull and travelling					
1 DD - Hi	18.4	7.20	9.20	2124	1.1	372

CASE IH CX 60 (4WD) **DLG-Test No 99-090**

	Height of drawbar above ground	Tyre inflation pressure	
		Front	Rear
unballasted	400 mm	80 kPa	80 kPa

Specific energy	Temperature			Atmospheric conditions		
	Fuel	Coolant	Engine oil	Temperature	Relative humidity	Pressure
kWh/dm³	°C	°C	°C	°C	%	kPa
2.03	61	84	107	18	67	100.0
2.17	70	84	111	19	67	100.0
2.70	73	86	111	19	67	100.0
2.67	71	85	108	18	67	100.0
2.74	75	86	115	22	67	100.0
2.73	76	87	115	21	83	100.0
2.77	75	87	114	19	83	100.0
2.71	73	85	107	18	83	100.0
2.69	75	86	112	18	83	100.0
2.54	75	86	112	19	83	100.0
identical with gear nearest to 7.50 km/h at rated speed						
2.81	75	86	114	21	75	99.5
2.50	72	84	114	20	75	99.5
2.09	69	84	112	20	75	99.5
speed as in 3.3.2.1.1						
2.60	72	85	110	20	75	99.5
speed as in 3.3.2.1.2						
2.16	71	84	110	21	75	99.5
2.67	75	86	109	20	75	99.5
2.29	73	84	112	20	75	99.5
2.10	70	83	111	20	75	99.5
speed as in 3.3.2.2.1						
2.51	73	86	109	21	75	99.5
speed as in 3.3.2.2.2						
2.27	69	84	109	20	75	99.5

4	**OPTIONAL TEST RESULTS**	None
5	**REPAIRS**	None
6	**REMARKS**	None

Head of tractor test section

Dipl.-Ing. Manfred Lober

Date: 19th May 2000

Deutsche Landwirtschafts-Gesellschaft

Test carried out by

Dipl.-Ing. Bodo Huber