LABORATORIO DI MECCANICA AGRARIA

DIPARTIMENTO DI ECONOMIA E INGEGNERIA AGRARIE

MINISTERO DELLE POLITICHE AGRICOLE E COMUNITARIE

Report DEIAGRA - sez. I.A. n° 4463 **O.E.C.D. approval number: 1/2 149**

Report on test in accordance with the O.E.C.D. Standard Code for the Official Testing of Agricultural and Forestry Tractor Performance
O.E.C.D. Code 1




Agricultural tractor
Make: **CASE IH;** Model: **JX 1075 C**
(Two wheel drive tractor 30 km/h version)

Tractor manufacturer:	CNH INTERNATIONAL, S.A., 13 Rue Aldrigen 1118, LUXEMBOURG
Date of test:	October 2003 - February 2004
Date of approval:	22 July 2004

This report has been approved by the O.E.C.D. Co-ordinating Centre (CEMAGREF - France) as being in accordance with the O.E.C.D. Tractors Test Code

ALMA MATER STUDIORUM - UNIVERSITA' DI BOLOGNA
VIA GANDOLFI. 19 - 40057 CADRIANO - BOLOGNA - ITALIA - TEL. 051-766632 - FAX 051-765318

Codification System Case JX Tractors



(*) Symbol X is inserted when the meaning is not relevant in the homologation procedure.

Example: H1C7T1 means an H tractor type, Case IH JX 1060 C trade name, with cab, 4WD, and T1 tractor category (see 2001/3/EC Directive, Annex II Chapter A).

TABLE OF CONTENTS

1. SPECIFICATIONS OF TRACTORS 3

1.1 Identifications 3

1.2 Engine 3

1.3 Transmission 6

1.4 Power take-off 16

1.5 Hydraulic power lift 17

1.6 Three point linkage 18

1.7 Swinging drawbar 19

1.8 Trailer hitch 20

1.9 Holed drawbar 21

1.10 Steering 21

1.11 Brakes 21

1.12 Wheels 21

1.13 Protective structure 22

1.14 Seat 22

1.15 Lighting 23

2. TEST CONDITIONS 24

2.1 Overall dimensions 24

2.2 Ground clearance 24

2.3 Tractor mass 24

2.4 Ballast 24

2.6 Tyres and track width specifications 24

2.7 Fuel 25

2.8 Oils and lubrificants 25

3. COMPULSORY TEST RESULTS 27

3.1 Main power take-off 27

3.2 Hydraulic power and lifting force 29

3.3 Drawbar Power test 32

3.4 Turning area and turning circle 34

3.5 Locations of centre of gravity 34

3.6 Braking 34

3.7 Measurement of external noise 35

4. OTHER TEST RESULTS 35

4.1 Test procedure for measuring hydraulic lift capacity on agricultural tractors equipped with three-point hitch - SAE J 283, Nov. 1999 36

C	- Tractor manufacturer's name and address:	CNH International SA - 13 rue Aldringen L - 1118 Luxembourg
D	- Location of tractor assembly:	CNH Italia SpA, via Leone XIII - Jesi (AN) - Italy
D	- Submitted for test by:	CNH Italia SpA, viale delle Nazioni 55, Modena - Italia
C	- Selected for test by:	The manufacturer with the agreement of the testing station
D	- Place of running-in:	Modena (MO) – Italy
D	- Duration of running-in:	50 hours
C	- Location of test:	Department of Agricultural Economics and Engineering - University of Bologna - Section of Agricultural Engineering - Laboratory of Cadriano (BO - Italy)

1. SPECIFICATIONS OF TRACTOR

1.1 Identification

C	**1.1.1 Make of the tractor:**	CASE IH
C	- Model (trade name):	JX 1075 C
C	- Type:	2WD

1.1.2 Numbers

D	- 1St Serial N° or prototype	HJH297817
C	- Serial N°:	HJH297817

1.1.3 Other specification

D	- Model for other countries:	none
C	- Transmission type:	16+16, mechanical
C	- Speed version:	30 km/h
D	- Manufacturer identification or Technical type number:	H3C2

1.2 Engine

C	- Make/Model/Type:	CNH Italia/IVECO 8035.25/ water-cooled, 4 stroke Diesel engine, direct injection, supercharged
C	- Serial N°:	852058

1.2.1 Cylinders

C	- Number/disposition:	3, vertical, in line
D	- Bore/stroke:	104 mm / 115 mm
D	- Capacity:	2930 cm^3
D	- Compression ratio:	18 ± 0.5 :1
D	- Arrangement of valves:	overhead valves, 2 per cylinder
D	- Cylinder liners:	dry liners
		The engine fitted on the tested tractor is approved according to Directive 2000/25/EC, EURO II (approval number e3*2000/25B*00/000/*6003*00).
		The engine is also in accordance with the requirements of The Environmental Protection Agency (EPA), step II, in terms of emission of gaseous and particulate pollutants

1.2.2 Supercharging

C	- Make/Model/Type:	MITSUBISHI/49377/exhaust driven supercharger and, in alternative, GARRETT/TA25/exhaust driven supercharger
D	- Pressure:	95 kPa

1.2.3 Fuel system

C	- Fuel feed system:	membrane pump
C	- Make/Model/Type of fuel filter:	CNH/not announced/with replaceable cartridge and filter inside the feed fuel pump
D	- Capacity of fuel tank:	70 dm^3 or, as option, 75 dm^3, in plastic material, on the left side, under the tractor footrest
C	- Make/Model/Type of injection pump:	BOSCH/L950/rotary injection pump
C	- Serial N°:	396402
	- Manufacturer's production, setting of injection pump	
C	. Flow rate (rated engine speed and full load):	81 mm^3 per stroke (corresponding to 16.8 dm^3/h)
D	. Timing:	0 ± 0.5°
D	- Make/Model/Type of injectors:	BOSCH/DLLA 132S/multihole injection nozzle
D	- Injection pressure:	26 ± 0.12 MPa

1.2.4 Governor

C	- Make/Model/Type:	BOSCH/integrated in the injection pump/ mechanical type
C	- Governed range of engine speed:	650±30 ÷ 2500±50 min^{-1}(rev/min)
C	- Rated engine speed:	2300 ± 30 min^{-1}(rev/min)

1.2.5 Air cleaner

	- Pre-cleaner	none
	- Main cleaner	
C	. Make/Model/Type:	CNH/document n.1.19.100 AC/ dry air filter, with double cartridge
C	. Location of air intake	in front of the radiator, under the bonnet
C	Maintenance indicator:	warning light on dashboard

1.2.6 Lubrication system

D	- Type of feed pump:	forced feed by means of a gear pump. Engine oil cooled by a heat exchanger with engine coolant
C	- Type of filter:	replaceable cartridge
C	- Number of filters:	1

1.2.7 Cooling system

C	- Type of coolant:	water-anti freeze mixture
D	- Type of pump:	centrifugal pump
	- Specification of fan or blower	propeller fan driven by engine shaft
C	. Number of fan blades:	6
C	. Fan diameter:	420 mm
D	- Coolant capacity:	12 dm^3
C	- Type of temperature control:	thermostat and by-pass circuit, viscous drive fan, belt driven; variable fan with speed controlled by air flow temperature. As option a propeller fan driven by engine shaft.
D	- Superpressure system:	71 kPa

1.2.8 Starting system

C	- Make/Model/Type:	BOSCH/1.74.400.AB /Starter motor
D	- Starter motor power rating:	2.6 kW
C	- Cold starting aid:	CAV, 357/10, as option BERU, 0101

C - Safety device: forward and reverse lever in neutral position and pto disenganged

1.2.9 Electrical system

C - Voltage: 12 V, negative earth

- Generator

C . Make/Model/Type: Denso/ 1.74.000 AC /Alternator

as option Denso/1.74.000 AD / Alternator

D . Power: 1.2 kW

- Battery of accumulators: lead acid type

C . Number: 1

D . Rating: 88 Ah at 20 hours

1.2.10 Exhaust system

C - Make/Model/Type: CNH/document n. 1.15.001AB/ interference type with internal perforated pipe

C - Location: on the left hand side of engine, under the bonnet, with the vertical exhaust pipe or the horizontal exhaust pipe on the left side; as option exhaust pipe with ejector.

1.3 Transmission

1.3.1 Clutch

D - Make/Model/Type: (Only for travelling) LUK/ 11/11 / double clutch with two dry plates included in the same clutch pressure plate, one for the pto and the other for gear box, but independently operated

D - Number of plates: 1

D - Diameter of plates: 280 mm

C - Method of operation: mechanically operated by pedal

1.3.2 Gear box

D - Make/Model/Type: CNH/ not announced/mechanical synchronised constant mesh gears, direct engagement by hand levers

- Description:

	Forward	Reverse
C Number of ranges/groups	4/1	4/1
C Number of gears	4	4
C Total of arrangements	16	16

D - Available options: 44x16 HI-LO

32x16 HI-LO

(when the reverse is engaged the position HI is automatically excluded)

28x16 mechanical

44x16 mechanical

1.3.3 Rear axle and final drives

D - Make/Model/Type: CNH/not announced/bevel gear differential and epicyclical final drivers

- Differential lock

D . Type: mechanical or, as option, electro-hydraulic

C . Method of engagement: pushing the device control pedal on the right side of the floor or, as option, pushing a button

C . Method of disengagement: pushing one of the two brake pedals

1.3.4 Front axle and final drives

D - Make/Model/Type: CNH/not announced/ telescopic axle with hydrostatic steering

- Differential lock not applicable

1.3.5 Total ratios and traveling speeds

	JX 1075 C with 16 forward speeds and 16 reverse speeds (fitted on the tested tractor)			
	Gear No	Group or range	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed(*) at rated engine speed of 2300 min^{-1} (rev/min) km/h
C	1	low	964.506	0.625
C	2	low	647.023	0.931
C	3	low	440.151	1.369
C	4	low	297.102	2.028
C	1	medium low	229.480	2.626
C	2	medium low	153.943	3.914
C	3	medium low	104.723	5.754
C	4	medium low	70.688	8.525
C	1	medium high	187.455	3.215
C	2	medium high	125.751	4.791

C	3	medium high	85.545	7.044
C	4	medium high	57.743	10.436
C	1	high	64.928	9.281
C	2	high	43.556	13.835
C	3	high	29.630	20.338
C	4	high	20.000	30.130
	Reverse			
C	1	low	995.519	0.605
C	2	low	667.894	0.902
C	3	low	454.350	1.326
C	4	low	306.688	1.965
C	1	medium low	236.882	2.544
C	2	medium low	158.909	3.792
C	3	medium low	108.101	5.574
C	4	medium low	72.968	8.258
C	1	medium high	193.502	3.114
C	2	medium high	129.808	4.642
C	3	medium high	88.305	6.824
C	4	medium high	59.606	10.110
C	1	high	67.022	8.991
C	2	high	44.961	13.403
C	3	high	30.585	19.702
C	4	high	20.645	29.189

JX 1075 C with 28 forward speeds, with creeper unit (C), and 16 reverse speeds			
Gear No	Group or range	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed(*) at rated engine speed of 2300 min^{-1} (rev/min) km/h
C 1	C low	3722.650	0.162
C 2	C low	2497.280	0.241
C 3	C low	1698.830	0.355
C 4	C low	1146.710	0.528
C 1	C medium low	885.712	0.680
C 2	C medium low	594.165	1.014

C	3	C medium low	404.194	1.491
C	4	C medium low	272.631	2.209
C	1	C medium high	723.511	0.833
C	2	C medium high	485.355	1.242
C	3	C medium high	330.174	1.825
C	4	C medium high	222.867	2.704
C	1	low	964.506	0.625
C	2	low	647.023	0.931
C	3	low	440.151	1.369
C	4	low	297.102	2.028
C	1	medium low	229.480	2.626
C	2	medium low	153.943	3.914
C	3	medium low	104.723	5.754
C	4	medium low	70.688	8.525
C	1	medium high	187.455	3.215
C	2	medium high	125.751	4.792
C	3	medium high	85.545	7.044
C	4	medium high	57.743	10.436
C	1	high	64.928	9.281
C	2	high	43.556	13.835
C	3	high	29.630	20.338
C	4	high	20.000	30.130
	Reverse			
C	1	low	995.519	0.605
C	2	low	667.894	0.902
C	3	low	454.350	1.326
C	4	low	306.688	1.965
C	1	medium low	236.682	2.544
C	2	medium low	158.909	3.792
C	3	medium low	108.101	5.574
C	4	medium low	72.968	8.258
C	1	medium high	193.502	3.114

C	2	medium high	129.808	4.642
C	3	medium high	88.305	6.824
C	4	medium high	59.606	10.110
C	1	high	67.022	8.991
C	2	high	44.961	13.403
C	3	high	30.585	19.702
C	4	high	20.645	29.189

JX 1075 C with 44 forward speeds, with creeper unit (C), and 16 reverse speeds			
Gear No	Group or range	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed(*) at rated engine speed of 2300 min^{-1} (rev/min) km/h
C 1	C low	3722.650	0.162
C 2	C low	2497.280	0.241
C 3	C low	1698.830	0.355
C 4	C low	1146.710	0.528
C 1	C medium low	885.712	0.680
C 2	C medium low	594.165	1.014
C 3	C medium low	404.194	1.491
C 4	C medium low	272.831	2.209
C 1	C medium high	723.511	0.833
C 2	C medium high	485.355	1.242
C 3	C medium high	330.174	1.825
C 4	C medium high	222.867	2.704
C 1	low	1157.410	0.521
C 2	low	964.506	0.625
C 3	low	776.427	0.776
C 4	low	647.023	0.931
C 5	low	528.182	1.141
C 6	low	440.151	1.369
C 7	low	356.523	1.690

C	8	low	297.102	2.028
C	1	medium low	275.376	2.188
C	2	medium low	229.480	2.626
C	3	medium low	184.731	3.262
C	4	medium low	153.943	3.914
C	5	medium low	125.668	4.795
C	6	medium low	104.723	5.754
C	7	medium low	84.826	7.104
C	8	medium low	70.688	8.525
C	1	medium high	224.946	2.679
C	2	medium high	187.455	3.215
C	3	medium high	150.901	3.993
C	4	medium high	125.751	4.792
C	5	medium high	102.654	5.870
C	6	medium high	85.545	7.044
C	7	medium high	69.291	8.697
C	8	medium high	57.743	10.436
C	1	high	77.913	7.734
C	2	high	64.928	9.281
C	3	high	52.267	11.529
C	4	high	43.556	13.835
C	5	high	35.556	16.948
C	6	high	29.630	20.338
C	7	high	24.000	25.109
C	8	high	20.000	30.130
	Reverse			
C	1	low	995.519	0.605
C	2	low	667.894	0.902
C	3	low	454.350	1.326
C	4	low	306.688	1.965
C	1	medium low	236.882	2.544
C	2	medium low	158.909	3.792
C	3	medium low	108.101	5.574
C	4	medium low	72.968	8.258
C	1	medium high	193.502	3.114

2	medium high	129.808	4.642
3	medium high	88.305	6.824
4	medium high	59.606	10.110
1	high	67.022	8.991
2	high	44.961	13.403
3	high	30.585	19.702
4	high	20.645	29.189

JX 1075 C with 32 forward speeds, with HI-LO, and 16 reverse speeds			
Gear No	Group or range	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed(*) at rated engine speed of 2300 min^{-1} (rev/min) km/h
1	low	1157.410	0.521
2	low	964.506	0.625
3	low	776.427	0.776
4	low	647.023	0.931
5	low	528.182	1.141
6	low	440.151	1.369
7	low	356.523	1.690
8	low	297.102	2.028
1	medium low	275.376	2.188
2	medium low	229.480	2.626
3	medium low	184.731	3.262
4	medium low	153.943	3.914
5	medium low	125.668	4.795
6	medium low	104.723	5.754
7	medium low	84.826	7.104
8	medium low	70.688	8.525
1	medium high	224.946	2.679
2	medium high	187.455	3.215
3	medium high	150.901	3.993
4	medium high	125.751	4.792
5	medium high	102.654	5.870
6	medium high	85.545	7.044

C	7	medium high	69.291	8.697
C	8	medium high	57.743	10.436
C	1	high	77.913	7.734
C	2	high	64.928	9.281
C	3	high	52.267	11.529
C	4	high	43.556	13.835
C	5	high	35.556	16.948
C	6	high	29.630	20.338
C	7	high	24.000	25.109
C	8	high	20.000	30.130
	Reverse			
C	1	low	995.519	0.605
C	2	low	667.894	0.902
C	3	low	454.350	1.326
C	4	low	306.688	1.965
C	1	medium low	236.882	2.544
C	2	medium low	158.909	3.792
C	3	medium low	108.101	5.574
C	4	medium low	72.968	8.258
C	1	medium high	193.502	3.114
C	2	medium high	129.808	4.642
C	3	medium high	88.305	6.824
C	4	medium high	59.606	10.110
C	1	high	67.022	8.991
C	2	high	44.961	13.403
C	3	high	30.585	19.702
C	4	high	20.645	29.189

JX 1075 C with 44 forward speeds, with HI-LO, with creeper unit (C) and 16 reverse speeds

	Gear No	Group or range	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed(*) at rated engine speed of 2300 min^{-1} (rev/min) km/h
C	1	C low	2473.090	0.244
C	2	C low	1659.030	0.363
C	3	C low	1128.590	0.534

C	4	C low	761.801	0.791
C	1	C medium low	588.410	1.024
C	2	C medium low	394.725	1.527
C	3	C medium low	268.520	2.244
C	4	C medium low	181.251	3.325
C	1	C medium high	480.654	1.254
C	2	C medium high	322.439	1.869
C	3	C medium high	219.346	2.747
C	4	C medium high	148.059	4.070
C	1	low	1157.410	0.521
C	2	low	964.506	0.625
C	3	low	776.427	0.776
C	4	low	647.023	0.931
C	5	low	528.182	1.141
C	6	low	440.151	1.369
C	7	low	356.523	1.690
C	8	low	297.102	2.028
C	1	medium low	275.376	2.188
C	2	medium low	229.480	2.626
C	3	medium low	184.731	3.262
C	4	medium low	153.943	3.914
C	5	medium low	125.668	4.795
C	6	medium low	104.723	5.754
C	7	medium low	84.826	7.104
C	8	medium low	70.688	8.525
C	1	medium high	224.946	2.679
C	2	medium high	187.455	3.215
C	3	medium high	150.901	3.993
C	4	medium high	125.751	4.792
C	5	medium high	102.654	5.870
C	6	medium high	85.545	7.044
C	7	medium high	69.291	8.697

C	8	medium high	57.743	10.436
C	1	high	77.913	7.734
C	2	high	64.928	9.281
C	3	high	52.267	11.529
C	4	high	43.556	13.835
C	5	high	35.556	16.948
C	6	high	29.630	20.338
C	7	high	24.000	25.109
C	8	high	20.000	30.130
	Reverse			
C	1	low	995.519	0.605
C	2	low	667.894	0.902
C	3	low	454.350	1.326
C	4	low	306.688	1.965
C	1	medium low	236.882	2.544
C	2	medium low	158.909	3.792
C	3	medium low	108.101	5.574
C	4	medium low	72.968	8.258
C	1	medium high	193.502	3.114
C	2	medium high	129.808	4.642
C	3	medium high	88.305	6.824
C	4	medium high	59.606	10.110
C	1	high	67.022	8.991
C	2	high	44.961	13.403
C	3	high	30.585	19.702
C	4	high	20.645	29.189

(*) Calculated with a dynamic radius index of 695 mm (in conformity with ISO 4295-1:1998)

1.4 Power take-off

1.4.1 Main power take-off

C - Type: independent

C - Method of engagement: by hand lever acting on a dry clutch

C - Number of shafts: 1

C - Method of changing power take-off shaft ends and speeds:

by lever and physically replacing the PTO shaft

1.4.1.1 Power take-off proportional to engine speed

	Type of power take-off	540 min^{-1} (rev/min)	540 min^{-1} economic (rev/min)	1000 min^{-1} (rev/min)
C	- Location:	at the rear of the tractor, in the median plane		
C	- Diameter of power take-off shaft end:	35 mm	35 mm	35 mm
C	- Number of splines (in conformity with ISO 500:1991)	6	6	21
C	- Height above ground:	665 mm	665 mm	665 mm
C	- Distance from the median plane of the tractor:	0 mm	0 mm	0 mm
C	- Distance behind rear-wheel axis:	485 mm	485 mm	485 mm
C	- PTO speed at rated engine speed (2300 rev/min):	565 min^{-1}	809 min^{-1}	1017 min^{-1}
C	- Engine speed at standard power take-off speed:	2196 min^{-1}	2132 min^{-1}	2260 min^{-1}
C	- Ratio of rotation speeds (engine speed/p.t.o. speed):	4.07	2.845	2.26
D	- Power restriction:	none	none	none
D	- Maximum torque transmissible (equivalent crankshaft torque):	320 Nm	320 Nm	330 Nm
C	- Direction of rotation:	clockwise (viewed from behind tractor)		

1.4.1.2 Power take-off proportional to ground speed

	Type of power take-off	540 min^{-1} (rev/min)	540 min^{-1} economic (rev/min)	1000 min^{-1} (rev/min)
C	- Travelling distance for one revolution of take-off shaft	0.355 m	0.244 m	0.194 m
C	- Number of power take-off shaft revolutions for one revolution of (rear) driving wheels:	12.30	17.88	22.48
C	- Direction of rotation with forward gear engaged:	clockwise (viewed from behind tractor)		

1.4.2 Optional power take-off

C	- Give the same description as for the main PTO.	none

1.5 Hydraulic power lift

C	- Make/Model/Type:	CNH/not announced/load, position and mixed control operated by two independent levers; a lift-o-matic device is fitted for raising and lowering quickly the lower links. As option, hydraulic power lift electronically controlled
C	- Type of hydraulic system:	open centre system
C	- Type and number of cylinders:	1, single action, internal
C	- Type of linkage lock for transport:	lift-o-matic device
D	- Relief valve pressure setting:	20.5 + 0.5 Mpa
D	- Opening pressure of cylinder safety valve:	22 + 0.5 Mpa
D	- Lift pump type:	rotative pump driven by the engine shaft (delivery rate of 63.8 l/min with pump at 2484 min^{-1})
D	- Transmission between pump and engine:	mechanical
C	- Type and number of filters:	1, replaceable paper cartridge
C	- Site of oil reservoir:	gear-box
C	- Type, number and location of tapping points:	4 tapping points, single or double acting, at the rear of tractor
D	- Maximum volume of oil available to external cylinders:	21 dm^3

1.6 *Three point linkage*

C	- Category	in conformity with category 2 of ISO 730-1:1994 + Cor.1:1995
C	- Category adapter:	none




Figure 1.1

Lift test - Linkage geometry




Figure 1.2

Lift test - Linkage geometry

			Dimension or range	Settings used in test
			mm	mm
C	Length of lift arms:	(A)	255	255
C	Length of lower links:	(B)	880	880
	Distance of lift arm pivot point from rear wheel axis			
C	- horizontally (rearward)	(a)	145	145
C	- vertically	(b)	276	276
C	Horizontal distance between the 2 lower link points:	(U)	405	405
C	Horizontal distance between the 2 lift arm end points:	(V)	450	450
C	Length of upper link:	(S)	555⊕770	697
	Distance of upper link pivot point from rear wheel axis			
C	- horizontally (rearward)	(c)	340-345	345
C	- vertically	(d)	308-361	308
	Distance of lower link pivot point from rear wheel axis			
C	- horizontally	(e)	155	155
C	- vertically	(f)	189	189
C	Distance of lower link pivot points to lift rod pivot points on lower links:	(D)	523	523
C	Length of lift rods :	(L)	570⊕690	575
	Height of lower hitch points relative to the rear-wheel axis			
C	- in low position	(h)	305⊕650	325
C	- in high position	(H)	15⊕320	314
C	Height above ground of lower hitch points when locked in transport position (*)		710⊕1015	-

*Assuming r=695 mm tyre dynamic radius index of ISO 4251-1:1998

Table 2.1

Dimensions of linkage geometry when connected to the standard frame

1.7 Swinging drawbar

C - Type: CNH, Document n. 1.12.136AA,

		longitudinally adjustable
	- Height above ground	
C	. Maximum:	440 mm
C	. Minimum:	360 mm
C	- Type of adjustment:	by turning the drawbar
C	- Distance of hitch point from rear-wheel axis, horizontally:	691 ÷ 891 mm
	- Distance of hitch point from power take-off shaft end	
C	. Vertically:	250 ÷ 330 mm
C	. Horizontally:	206 ÷ 406 mm
	- Lateral adjustment	
C	. Right hand:	289 mm
C	. Left hand:	289 mm
C	- Distance of pivot point from rear-wheel axis, horizontally:	310 mm
C	- Diameter of drawbar pinhole:	32 mm
D	- Maximum vertical permissible load:	5 kN
D		As option are available the following drawbars: CNH DGM-GA 4036A SAUERMAN HS1000-D-FT-S

1.8 Trailer hitch

C	- Type:	CBM / GTF 30015
C	- Hole diameter:	32 mm
C	- Height above ground:	450 ÷ 900 mm
C	- Distance of hitch point from rear-wheel axis, horizontally:	655 mm
	- Distance of hitch point from power take-off shaft end	
C	. Vertically:	440 mm
C	. Horizontally:	170 mm
D	- Maximum vertical permissible load:	0 kN
D		As option are present the following trailer hitch: CBM / 30014 CBM / D2 CBM / C CNH / D2

		CNH / C SAUERMAN / HS 1000-D-FT-S
	1.9 Holed drawbar	not present on the tested tractor, available as option
	1.10 Steering	
D	- Make/Model/Type:	DANFOSS / ORBITROL OSPC 80 ON / hydrostatic As option OGNIBENE / STH ON80G170LNV/ hydrostatic
	- Method of operation	
D	. Pump:	independent gear pump
D	- Ram:	single acting ram positioned in the right side of the front axle and directly acting on it
D	- Working pressure:	17 Mpa
	1.11 Brakes	
	1.11.1 Service brake	
D	- Make/Model/Type:	CNH/not announced/ 2 oil bath disc, 1 per rear wheel, mounted on the differential shaft
C	- Method of operation:	foot operated bi-pedal braking device, with hydraulic transmission
C	- Trailer braking take-off:	hydraulic brake system
	1.11.2 Parking brake	
C	- Type:	fully independent from service brake, 4 oil bath double face sector discs and 2 oil bath single face sector discs, mounted on the pignon shaft in the gear box
C	- Method of operation:	mechanical hand lever
	1.12 Wheels	
	- Number	
C	. Front	2 steering
C	. Rear	2 driving
C	- Wheelbase:	2130 mm
	- Track width adjustment:	

	Minimum mm	Maximum mm	Adjustment method
D Front	1439	1607	Adjusting the telescopic front axle
D Rear	1232	1949	Changing the position of the rims in respect to the disc

1.13 Protective structure

C	- Make/Model/Type:	CNH/CS33/ cab
C	- Manufacturer's name and address:	CNH International SA – 13 rue Aldringen L – 1118 Luxembourg
	- Protective device	
C	. Cab/frame/rollguard/other:	cab
C	. Tiltable/not tiltable	not tiltable
	- OECD approval	
C	. Approval number:	4/0 465/4
C	. Date of approval:	5 June 2003
C	. N° of minor modification certificates, if any:	3

Optional

D	- Make/Model/Type:	CNH/TS52/ rear roll bar
D	- Manufacturer's name and address:	CNH International SA – 13 rue Aldringen L – 1118 Luxembourg

1.14 Seat

1.14.1 Driver's seat

C	- Make/Model/Type:	MT/SC78-M97/3/pneumatic
C	- Seat and steering wheel reversible:	no
C	- Type of suspension:	adjustable spring
C	- Type of damping:	shock absorber
	- Range of adjustment	
C	. Longitudinally:	150 mm
C	. Vertically:	60 mm
C	- Safety belt:	yes
	. Type	2 point seat belt

1.14.2 Optional driver's seat(s)

D	- Make/Model/Type:	MT/SC78-M91/mechanical
D	- Type of suspension:	adjustable spring
D	- Type of damping:	shock absorber

- Range of adjustment

C . Longitudinally: 150 mm

C . Vertically: 80 mm

D - Make/Model/Type: GRAMMER/MSG83/520/mechanical

D - Type of suspension: adjustable spring

D - Type of damping: shock absorber

- Range of adjustment

C . Longitudinally: 150 mm

C . Vertically: 60 mm

D - Make/Model/Type: GRAMMER/MSG93/520/pneumatic

D - Type of suspension: adjustable spring

D - Type of damping: shock absorber

- Range of adjustment

C . Longitudinally: 150 mm

C . Vertically: 60 mm

1.14.3 Passenger seat

C - Location: on the left of the driving seat

C - Capacity: 1

1.15 Lighting

	Height above ground of centre	Size	Distance from outside edge of lights to median plane of tractor
	mm	mm	mm
C Headlights	1080	170x100	90
C Sidelights	1580	110x70	680
C Rearlights	1450	155x650	680
C Reflectors	1450	45x55	640

2. TEST CONDITIONS

2.1 Overall dimensions

	Length	Width		Height at top of	
		Minimum	Maximum	Protective structure	Exhaust pipe
	mm	mm	mm	mm	mm
Ballasted	3919	1867	2428	2410	2290
Unballasted	3662				

2.2 Ground clearance

- Height: 353 mm
- Clearance-limiting part: front differential: drawbar bracket

2.3 Tractor mass

- Tractor tested: mass with cab CS33

	Ballasted		Unballasted	
	Without driver	With driver	Without driver	With driver
	kg	kg	kg	kg
Front	1265	1280	905	920
Rear	1905	1965	1780	1840
Total	3170	3245	2685	2760

2.4 Ballast

	Weights		Water
	Number	Total mass	
		kg	kg
Front	5	285	none
Rear	4	200	none
Optional	none	none	none

2.6 Tyres and track width specifications

	Front	Rear
Tyres		
- make	TAURUS	TAURUS
- type	Point 8	Point 8
- dimensions	7.50-16	16.9 R30
- ply rating	103 A6	137 A8
- type of casing	Radial	Radial
- maximum load (tyre manufacturer's)	8.75 kN	22.5 kN
- maximum load (tractor manufacturer's)	8.75 kN	17.5 kN
- inflation pressure (tyre manufacturer's)	370 kPa	160 kPa
- dynamic radius index	375	695
Chosen track width	1440	1540

Optional

Dimension	
Front	Rear
6.00-16 97A6	13.6R28 123 A8
6.50-16 97A6	12.4R32 122 A8
6.50-16 97A6	3.80/70R28 127 A8
7.50-16 103A6	420/70R30 134 A8
7.50-16 103A6	14.9R28 128 A8
7.50-16 103A6	14.9R30 129 A8
6.50-16 97A6	12.4R36 124 A8
7.50-16 103A6	16.9R30 137 A8
7.50-16 103A6	480/70R28 140 A8
7.50-16 103A6	380/70R28 127 A8
7.50-16 103A6	420/70R28 133 A8

2.7 Fuel

- type: AGIP diesel oil, in conformity with national standard
- density at 15°C: 0.838 g/cm^3

2.8 Oils and lubricants

2.8.1 Capacity and change interval

	Capacity	Oil change	Filter change
	dm^3	h	h
Engine	7.5	300	300
Gear box , rear axle, rear final drive, brakes, hydraulic system and steering	42	300	1200 hours and 2 years
Front axle	none	none	none
Final drive with brakes (front)	none	none	none

2.7.2 Specifications (SAE,API,CCMC,ACEA,MIL.L.ISO)

	Recommended	Used during test
Engine oil Type Viscosity Classification	 AKCELA No. 15W-40 SAE	As recommended
Transmission oils, hydraulic fluid and steering oil Type Viscosity Classification	 AKCELA NEXPLORE 10W-30 SAE	As recommended
Braking oil Type Viscosity Classification	 AKCELA LHM FLUID 7308 ISO	As recommended

2.7.3 Grease

- number of lubrication points: 15


3. COMPULSORY TEST RESULTS


3.1 Main power take-off


- Date and location of tests: 14.10.2003, Cadriano (BO) - Italy
- Type of dynamometer bench: Schenck U1 - 40


Power	Speed			Fuel consumption			Specific energy
	Engine	P.T.O.	Fan	Hourly		Specific	
kW	min^{-1} (rev/min)			kg/h	l/h	g/kWh	kWh/l
3.1.1	MAXIMUM POWER - TWO-HOUR TEST						
48.1	2246	552	2491	12.6	15.0	261	3.2
3.1.2	POWER AT RATED ENGINE SPEED						
47.6	2298	565	2546	12.5	14.9	263	3.2
3.1.3	STANDARD POWER TAKE-OFF SPEED [540 ± 10 min^{-1} (rev/min)]						
47.5	2197	540	2436	12.4	14.8	261	3.2
3.1.4	PART LOADS						
3.1.4.1	the torque corresponding to maximum power at rated engine speed						
47.6	2298	565	2546	12.5	14.9	263	3.2
3.1.4.2	85% of torque defined in 3.1.4.1						
41.3	2349	577	2600	11.2	13.4	272	3.1
3.1.4.3	75% of torque defined in 3.1.4.2						
31.4	2396	589	2658	9.0	10.8	287	2.9
3.1.4.4	50% of torque defined in 3.1.4.2						
21.3	2422	595	2678	6.8	8.2	322	2.6
3.1.4.5	25% of torque defined in 3.1.4.2						
10.7	2465	606	1943	4.7	5.6	439	1.9
3.1.4.6	unloaded						
/	2501	615	1721	3.1	3.7	/	/
3.1.5	PART LOADS AT STANDARD POWER TAKE-OFF SPEED [540 ± 10 min^{-1} (rev/min)]						
3.1.5.1	the torque corresponding to maximum power						
47.5	2197	540	2436	12.4	14.8	261	3.2
3.1.5.2	85% of torque defined in 3.1.5.1						
41.3	2248	552	2491	11.0	13.1	265	3.2
3.1.5.3	75% of torque defined in 3.1.5.2						
31.8	2306	566	2554	9.0	10.7	283	3.0
3.1.5.4	50% of torque defined in 3.1.5.2						
21.5	2335	574	2583	6.8	8.2	319	2.6
3.1.5.5	25% of torque defined in 3.1.5.2						
10.9	2374	583	1898	4.8	5.7	441	1.9
3.1.5.6	unloaded						
/	2411	592	1579	2.8	3.4	/	/


3.1.6 Curves as a function of engine speed











3.1.7 Other results

No load maximum engine speed:	2501 min^{-1}
Torque (equivalent crankshaft) at maximum power	
At rated engine speed	197.8 Nm
At two-hour test	204.4 Nm
Maximum torque (equivalent crankshaft)	272.5 Nm
(engine speed)	(1421 min^{-1})

Mean atmospheric conditions:	
Temperature	22 °C
Pressure	101.4 kPa
Relative humidity	26 %
Maximum temperature	
Coolant	97 °C
Engine oil	112 °C
Fuel	48 °C
Engine air intake	31 °C

3.2 Hydraulic power and lifting force

- Date of tests: 11.12.2003


3.2.1 Hydraulic power test

3.2.1.1 Hydraulic fluid data

- Hydraulic fluid type: AKCELA NEXPLORE
- Viscosity index: 120
- Viscosity at 65°C: 25 cSt

3.2.1.2 Compulsory Reporting:

	Pressure	Reservoir oil Temperature °C		Engine Speed	Flow rate	Power
	MPa	Min.	Max.	min^{-1}	l/min	kW
Rated Engine Speed						
3.2.1.2.1 Maximum (sustained) pressure with relief valve open as measured at the coupler Pump stalled: No	20.66	61	69	2387		
3.2.1.2.2 Flow rate corresponding to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting and corresponding hydraulic power:	18.60	67		2425	37.05	11.47
3.2.1.2.3 Maximum avaible flow and maximum power from one coupler pair:	16.12	65		2420	56.42	15.16




3.2.2 Power lift test:

- Linkage settings for test - see Table 2.1 and Figures 2.1 and 2.2.

	At the hitch point	On the frame
Height of lower hitch points above ground in down position:	370 mm	352 mm
Vertical movement - with lifting force - without lifting force	 589 mm 640 mm	 648 mm 718 mm
Maximum corrected force exerted through full range	20.65 kN	17.20 kN
Corresponding pressure of hydraulic fluid	18.60 MPa	18.60 MPa
Moment about rear-wheel axis	21.37 kNm	25.28 kNm
Maximum tilt angle of mast from vertical	-	10.2 degrees

Lifting heights relative to the horizontal plane including the lower link pivot points								
Lifting forces:								
mm	-124	-100	0	100	200	300	400	465
at the hitch point in kN:	20.65	21.21	23.61	24.57	24.70	24.04	24.14	24.16
Corresponding pressure: 18.60 MPa								
mm	-138	-100	0	100	200	300	400	510
on the frame in kN:	19.06	20.01	21.17	21.24	20.71	19.42	18.40	17.20
Corresponding pressure: 18.60 MPa								


28000
26000
24000
22000
20000
18000
16000
14000
12000
10000
8000
Force [N]
-200
-100
0
100
200
300
400
500
600
Lifting heights [mm]
At the hitch point
On the frame

3.4 Turning area and turning circle

Wheel equipment if several sets of tyres are tested: not applicable

	Without brakes	
	Right-hand	Left-hand
	m	m
Radius of turning area	3.68	3.63
Radius of turning circle	3.58	3.53

3.5 Location of centre of gravity

- Height above ground 814 mm
- Distance from the vertical plane containing the axis of the rear-wheels 710 mm
- Distance from the median longitudinal plane of the tractor 10 mm (to the left)

3.6 Braking

- date of tests 06.02.04

3.6.1 Cold service braking device test


	Speed before application of brakes	Braking device control force	Mean deceleration	Minimum stopping distance without locking the wheels
	km/h	kN	m/s^2	m
Ballasted tractor	32.5	0.12	1.3	31.4
Ballasted tractor	32.5	0.20	2.8	14.5
Ballasted tractor	32.5	0.33	3.1	13.2
Ballasted tractor	32.5	0.42	3.0	13.5
Unballasted tractor	32.5	0.10	1.8	22.1
Unballasted tractor	32.5	0.22	3.4	11.7
Unballasted tractor	32.5	0.27	3.6	11.5
Unballasted tractor	32.5	0.29	3.1	13.5

- Maximum deviation of tractor from its original course: none
- Abnormal vibration: none

3.6.2 Fade test

Speed before application of brakes	Braking device control force	Mean deceleration	Minimum stopping distance without locking the wheels
km/h	kN	m/s^2	m
32.5	0.12	1.3	31.8
32.5	0.22	2.4	16.7
32.5	0.30	2.8	14.0
32.5	0.41	2.9	14.1

- Maximum deviation of tractor from its original course: none
- Abnormal vibration: none
- Brake heating method: the tractor has been driven for 1 km at a speed of 26.0 km/h and the force for actuating the service brake has been 90 N



3.6.3 Parking braking device test

	Uphill	downhill
Braking device control force	0.38 kN	0.40 kN

3.7 *Measurement of external noise*

- Date of tests: 06.02.04
- Sound level meter: Bruel&Kjaer / 2238
- Type of track: concrete
- Gear number: 4 high
- Travelling speed before acceleration: 24.4 km/h
- Sound level: 83.0 dBA (tractor left side)

4. OTHER TEST RESULTS

Not covered by OECD approval.

4.1 Test procedure for measuring hydraulic lift capacity on agricultural tractors equipped with three-point hitch - SAE J 283, Nov. 1999

4.1.1 Tractor description

See:

Section 1 - Specification of tractor

Section 2 - Test conditions (excepted tyres)

Tested tractor was fitted with 6.50-16 tyres (with maximum overall diameter in service of 788 mm) on the front axle and 12.4R36 tyres (with maximum overall diameter in service of 1529 mm) on the rear axle.

4.1.2 Test conditions

Three-point hitch hydraulic system pressure setting: 20.66 Mpa

Three-point hitch hydraulic system oil temperature: 45 ± 5 °C

Rated engine speed: 2300 min^{-1}

Tests have been performed in accordance with Section 4 - Static lift force of SAE J283. Settings of the three-point hitch specified in the table below. See figure 1.1 and 1.2 for more details on linkage geometry.

		Dimension or range	Settings used in test
		mm	mm
Length of lift arms:	(A)	255	255
Length of lower links:	(B)	880	880
Distance of lift arm pivot point from rear wheel axis			
- horizontally (rearward):	(a)	145	145
- vertically:	(b)	276	276
Horizontal distance between the 2 lower link points:	(U)	405	405
Horizontal distance between the 2 lift arm end points:	(V)	450	450
Length of upper link:	(S)	555⊕770	690
Distance of upper link pivot point from rear wheel axis			
- horizontally (rearward):	(c)	340-345	340
- vertically:	(d)	308-361	361
Distance of lower link pivot point from rear wheel axis			
- horizontally:	(e)	155	155
- vertically:	(f)	189	189
Distance of lower link pivot points to lift rod pivot points on lower links:	(D)	523	523
Length of lift rods :	(L)	570⊕690	570

4.1.3 Static lift force

Position of the hitch	Vertical lift force*	Vertical distance of lower hitch point above ground
	kN	mm
Lowest	21.45	455
1/5	23.46	577
2/5	23.37	699
3/5	22.07	821
4/5	20.73	943
Highest	19.16	1065

* Reported values are 90% of measured

Bologna, 22 December 2003

TEST CARRIED OUT BY

Dr. Valda Rondelli Dr.Ing. Giovanni Molari Dr. Antonio Marocchi

THE DIRECTOR OF DEPARTMENT OF ECONOMICS
AND AGRICULTURAL ENGINEERING
UNIVERSITY OF BOLOGNA (I)
Prof. Gualtiero Baraldi