T.C.
TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI
TEST MERKEZİ MÜDÜRLÜĞÜ

TEST REPORT

REPORT NO: 452/2097 -TGK.9
OECD Approval No: 2/2 016
Date of Approval No: 05 th Nov 2002

Report on test in accordance with the OECD Standard Code 2 for the Official Testing of Agricultural Tractors Performance

CODE 2
Restricted Code



NEWHOLLAND TD 65 D – 2 WD
(12 speeds – 33 km/h)



CASE IH JX 65 – 2 WD
(12 speeds – 33 km/h)

Submitted for Test by : TÜRK TRAKTÖR VE ZİRAAT MAKİNALARI A.Ş.
Gazi/ANKARA

JULY - 2002
ANKARA

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

REPORT NO : 452/2097 TGK.9

TABLE OF CONTENTS

1. SPECIFICATIONS OF TRACTOR ..... 2 to 15

2. TEST CONDITIONS .....16 to 17

3. COMPULSORY TEST RESULTS
3.1 Main power take-off .....18 to 22

3.2 Hydraulic power and lifting force .....23 to 24

3.3 Drawbar power and fuel consumption (unballasted tractor) 25

4. OPTIONAL TEST RESULT..... 25

5. REPAIRS 25

6. REMARKS 25

This is a report on a tractor tested in accordance with OECD standard code for the official Testing of Agricultural Tractor Performance, it doesn't contain an evaluation of the tractor on field activities..

UNITS

Forces	1 kN	= 1000 N	= 102 kp
Powers	1 kW	= 1.36 HP	
Pressures	1 MPa	= 10 bar	= 10.2 kp/cm^2
	100 kPa	= 1000 mbar	= 750.1 mmHg

New Holland TD 65 D (2WD) and Case IH JX 65 (2WD) tractors have same specification but they have different colour, bonnet, rim colour, grill, head lights, grill support and model (trade name).
All tests were carried out on New Holland TD 65 D (2WD)

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

REPORT NO : 452/2097 TGK.9

Tractor Manufacturer's name and address	: TÜRK TRAKTÖR ve ZIRAAT MAKINALARI A.Ş. Güvercin yolu 111-112 Gazi/ANKARA
Location of tractor assembly	: TÜRK TRAKTÖR ve ZIRAAT MAKINALARI A.Ş.
Submitted for test by	: TÜRK TRAKTÖR ve ZIRAAT MAKINALARI A.Ş.
Selected for test by	TÜRK TRAKTÖR ve ZIRAAT MAKINALARI A.Ş.
Place of running in	: DAEMTC
Duration of running in	: 25 hours
Location of test	: DAEMTC (The Directorate of Agricultural Equipment and Machinery Testing Centre)

1. SPECIFICATIONS OF TRACTOR

1.1 IDENTIFICATION

1.1.1.Make of the tractor	: NEW HOLLAND
Model (trade name)	: TD 65 D
Type	: 2 WD
No. of Driving Wheels	: 2
1.1.2. Serial No	
First Serial No or Prototype	: HFD000035
Serial No	: HFD000050
1.1.3.Other Specifications;	
Model (s) for other countries	: None
Transmission Type or Gears x Ranges	: Mechanical, full sencromesh, 12 forward 12 reverse
Speed version	: 33 km/h
Manufacturer identification or Technical type number	: D 2 C 2 AC

1.2 ENGINE

Make, Model and Type	IVECO 8035.05-406 (or ~~TTF 8035.05.406 T~~), water cooled, direct injection 4 cycles, diesel engine
Serial No.	: 090838

1.2.1 Cylinders

Number/disposition	: 3, vertical in line
Bore/stroke	: 104 mm/115 mm
Capacity	: 2931 cm^3
Compression rate	: 17/1
Arrangement of valves	: Overhead
Cylinder liners	: Dry

1.2.2 Supercharging : None

1.2.3 Fuel System

Fuel feed system	: Double diaphragm
Make, type and model of fuel filter (s)	: BOSCH, replaceable paper element cartridge
Capacity of fuel tank	: 90 dm^3
Make, model and type of injection pump	:BOSCH L 814-2 or BOSCH, VE 3/11 F 1250 LV 15123, rotative
Serial no	: 524177
Manufacturer's production setting of injection pump	
Flow rate*	: 11.43-12.15 l/h at rated engine speed and full load
Timing	: 9° before T.D.C
Make,type and model of injectors	:BOSCH 432 291 494
Injection pressure	: 26.0 MPa

**not any setting by manufacturer because of atmospheric pressure*

1.2.4 Governor

Make, model and type	: BOSCH, hydraulic automatic, in corporated in the fuel pump

Governed range of engine speed: 650 – 2795 rev/min

Rated engine speed : 2500 rev/min

1.2.5 Air cleaner

Pre-cleaner	:None
Main cleaner	
Make, model and type	: DONALDSON, P77-2579, dry
Location of air intake	: on front of the radiator under the bonnet cowling
Maintenance indicator	: None

1.2.6 Lubrication system

Type of feed pump	: Forced feed with gear pump
Type of filter(s)	: one is multihole sheet iron the other is replaceable paper cartridge
Number of filters	: 2

1.2.7 Cooling system

Type of coolant	: Water cooled
Type of pump	: Centrifugal, belt driven
Specification of fan	
Number of fan blades	: 4
Fan diameter	: 392 mm
Coolant capacity	: 12 dm^3
Type of temperature control	: Thermostat and thermometer on dashboard
Superpressure system	: 150 kPa

1.2.8 Starting system

Make, model and type	:BOSCH, 2339402140, solenoid engaged
Starter motor power rating	: 2.5 kW
Cold starting aid	: Flame glow plug and additional fuel system
Safety device	: Gear safety switch (when gear is neutral position)

1.2.9 Electrical system

Voltage : 12 V

Generator
make,model and type : MAKO MAGNETTI MARELLI, RTT 119 AC, AA 125 R MKIB alternator
power : 1.0 kW
Battery of accumulators
Number : 1

Rating : 105 Ah (20 h) 420 A

1.2.10 Exhaust system

Make, model and type : ALCOM 5172649 or EBERSPAKER 499 7325

Location : Vertical, on left hand side of engine

1.3 TRANSMISSION

1.3.1 Clutch (travel and power take-off)

Make, model and type :NEWHOLLAND,LUK,dual clutch, dry

Number of plates : 2

Diameter of plates : 280 mm

Method of operation : Pedal operated

1.3.2 Gear box

Make, model and type :NEWHOLLAND, mechanical, full syncromesh

Description :

	Forward	Reverse
Number of gears	4	4
Number of ranges	3	3
Number of groups	None	None
Total of arrangements	12	12

Available options :

	Forward	Reverse
Number of gears	4	4
Number of ranges	3	3
Number of groups	2	None
Total of arrangements	20	12

	Forward	Reverse
Number of gears	4	4
Number of ranges	3	1
Number of groups	None	None
Total of arrangements	12	4

1.3.3 Rear axle and final drives

Make, model and type : NEW HOLLAND, with reducter(model none)

Differantial lock

Type : Mechanical

Method of engagement : Pedal operated

Method of disengagement: Self disengaged

1.3.4 Front Axle

Make, model and type : NEW HOLLAND,telescospically adjustable

1.3.5 Total ratios & travelling speed (tested tractor)

Gear no	Group or range	Number of engine revolutions for one revolution of the driving wheels		Nominal travelling speed (*) at rated engine speed of 2500 rev/min km/h	
		Forward	Reverse	Forward	Reverse
1	I Slow	329.999	329.102	1.90	1.91
2		214.182	213.542	2.93	2.94
3		157.500	157.029	3.98	3.99
4		109.947	109.618	5.70	5.72
1	II Normal	141.289	140.866	4.44	4.45
2		91.702	91.427	6.84	6.86
3		67.433	67.232	9.29	9.32
4		47.074	46.933	13.31	13.35
1	III Fast	60.014	59.834	10.44	10.48
2		38.951	38.835	16.09	16.14
3		28.643	28.557	21.88	21.95
4		19.995	19.935	31.35	31.44

* Calculated with a tyre dynamic index of 665 mm (ISO 4251-1:1998)

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

1.3.5 Total ratios & travelling speed (Optional)

Gear no	Group or range	Number of engine revolutions for one revolution of the driving wheels		Nominal travelling speed (*) at rated engine speed of 2500 rev/min km/h	
		Forward	Reverse	Forward	Reverse
1	I Creeper	1822.753	-	0.34	-
2		1183.037	-	0.53	-
3		869.950	-	0.72	-
4		607.292	-	1.03	-
1	II Creeper	780.408	-	0.80	-
2		506.515	-	1.24	-
3		372.468	-	1.68	-
4		260.011	-	2.41	-
1	I Slow	329.999	329.102	1.90	1.91
2		214.182	213.542	2.93	2.94
3		157.500	157.029	3.98	3.99
4		109.947	109.618	5.70	5.72
1	II Normal	141.289	140.866	4.44	4.45
2		91.702	91.427	6.84	6.86
3		67.433	67.232	9.29	9.32
4		47.074	46.933	13.31	13.35
1	III Fast	60.014	59.834	10.44	10.48
2		38.951	38.835	16.09	16.14
3		28.643	28.557	21.88	21.95
4		19.995	19.935	31.35	31.44

* Calculated with a tyre dynamic index of 665 mm (ISO 4251-1:1998)

1.3.5 Total ratios & travelling speed (Optional)

Gear no	Group or range	Number of engine revolutions for one revolution of the driving wheels		Nominal travelling speed (*) at rated engine speed of 2500 rev/min km/h	
		Forward	Reverse	Forward	Reverse
1	I Slow	329.999	-	1.90	-
2		214.182	-	2.93	-
3		157.500	-	3.98	-
4		109.947	-	5.70	-
1	II Normal	141.289	140.866	4.44	4.45
2		91.702	91.427	6.84	6.86
3		67.433	67.232	9.29	9.32
4		47.074	46.933	13.31	13.35
1	III Fast	60.014	-	10.44	-
2		38.951	-	16.09	-
3		28.643	-	21.88	-
4		19.995	-	31.35	-

* Calculated with a tyre dynamic index of 665 mm (ISO 4251-1:1998)

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

1.4 POWER TAKE-OFF

1.4.1 Main power take-off

Type	: Independant
Method of engagement	: driven by wet multiplate clutch
Number of shafts	: 1
Method of changing power take-off speeds	: By hand lever

1.4.1.1 Power take-off proportional to engine speed

540 rev/min

Location	: At rear of tractor
Diameter of power take-off shaft end	: 34.9 mm
Number of splines	: 6, in conformity with ISO 500:1991
Height above ground	: 660 mm
Distance from the median plane of the tractor	: 0 mm
Distance behind rear-wheel axis	: 330 mm
P.T.O speed at rated engine speed	: 614 rev/min
Engine speed at standard power take-off speed	: 2200 rev/min
Ratio of rotation speeds (engine speed/p.t.o speed)	: 4.074/1
Power restriction and maximum torque	: None
Maximum torque transmissible	: None
Direction of rotation (viewed from behind tractor)	: Clockwise

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

750 rev/min

Location	: At rear of tractor
Diameter of power take-off shaft end	: 34.9 mm
Number of splines	: 6,not in conformity with ISO 500:1991
Height above ground	: 660 mm
Distance from the median plane of the tractor	: 0 mm
Distance behind rear-wheel axis	: 330 mm
P.T.O speed at rated engine speed	: 787 rev/min
Engine speed at standard power take-off speed	: 2382 rev/min
Ratio of rotation speeds (engine speed/p.t.o speed)	: 3.176/1
Power restriction and maximum torque	: None
Maximum torque transmissible	: None
Direction of rotation (viewed from behind tractor)	: Clockwise

1000 rev/min (not fitted on tested tractor)

Location	: At rear of tractor
Diameter of power take-off shaft end	: 34.9 mm
Number of splines	:6,not in conformity withISO 500:1991
Height above ground	: 660 mm
Distance from the median plane of the tractor	: 0 mm
Distance behind rear-wheel axis	: 330 mm
P.T.O speed at rated engine speed	: 1050 rev/min
Engine speed at standard power take-off speed	: 2381 rev/min
Ratio of rotation speeds (engine speed/p.t.o speed)	: 2.381/1
Power restriction and maximum torque	: None
Maximum torque transmissible	: None
Direction of rotation (viewed from behind tractor)	: Clockwise

1.4.1.2 Power take-off proportional to ground speed

	540	750
Travelling distance for 1 revolution of take-off shaft	: 0.559 m	0.432m
Number of power take-off shaft revolutions for one revolution of (rear) driving wheels(14.9 - 30)	:7.475	9.674
Direction of ratation with forward gear engaged (viewed from behind tractor)	: Clockwise	

1.5 HYDRAULIC POWER LIFT


Make, model and type	: NEWHOLLAND Lift-O-matic
Type of hydraulic system	: Open center system
Type and number of cylinders	: 1, single and double acting
Type of linkage lock for transport	: Hydraulic
Relief valve pressure setting	: 19.4-19.9 MPa
Opening pressure of cylinder safety valve	: 23.4-24.5 MPa
Lift pump type	: Gear
Transmission between pump and engine	087 BOSCH.0510.525.348 : With gear,
Type and number of filters	: 1, replaceable cartridge element
Site of oil reservoir	: Gear box
Type, number and location of tapping points	: At rear of tractor,4, single or double acting
Maximum volume of oil available to external cylinders	: None


1.6 Three- point linkage

Category	:1 and 2,ISO standard 730/1-1994 Corrigendum 1:1995
Category adapter	: None

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

Rear Linkage geometry





TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

TABLE 2.1. Dimensions of linkage geometry (when connected to the standard frame)

		Dimension or range (mm)	Settings Used in test (mm)
Length of lift arms	(A)	255	255
Length of lower links	(B)	920	920
Distance of lift arm pivot point from rear wheel axis			
- Horizontally	(a)	6	6
- Vertically	(b)	295	295
Horizontal distance between the two lower link points	(u)	500	500
Horizontal distance between the two lift arm end points			
Length of upper link	(v)	495	495
Distance of upper link pivot point from rear wheel axis	(S)	from 635 to 980	785
- horizontally			
- vertically			
Distance of lower link pivot point from rear wheel axis	(c)	180/195	195
- horizontally	(d)	190/240	190
- vertically			
Distance of lower link pivot points to lift rod pivot points on lower links	(e)	75	75
Length of lift rods	(f)	208	208
Height of lower hitch points relative to the rear wheel axis	(D)	435/510	435
	(L)	from 550 to 615	570
- in low position			
- in high position			
	(h)	from 385 to 555	460
	(H)	from 195 to 310	217
Height above ground of lower hitch points when locked in transport position (*)	Any height within lift range		
(*) Assuming r = 665 mm tire dynamic radius index of ISO 4251-1:1998			

1.7 SWINGING DRAWBAR

Type	: Clevis
Height above ground;	
Maximum	: 488 mm
Minimum	: 386 mm
Type of adjustment	: reversing
Distance of hitch point from rear – wheel axis horizontally	: 780 mm
Distance of hitch point from p.t.o shaft ends	
Vertically	: 167/270 mm
Horizontally	: 450mm
Lateral adjustment (center of clevis)	
Right-hand	: 45 mm
Left-hand	: 58 mm
Distance of pivot point from rear-wheel axis horizontally	: 144 mm
Diameter drawbar pin hole	: 29 mm
Maximum vertical permissible load	: None

1.8 TRAILER HITCH

Type	: Clevis, adjustable FIAT DGM - GA-1087-C-02 6t 1.5
Hole diameter	: 29 mm
Height above ground	: 850/940 mm
Distance of hitch point from rear – wheel axis, horizontally	: 430 mm
Distance of hitch point from PTO shaft end	
Vertically	: 275 mm
Horizontally	: 100 mm
Maximum vertical permissible load	: None

1.9 HOLED DRAWBAR :None

1.10 STEERİNG

Make, model and type : DANFOSS, BOSCH 0.87 0510.525.046, hydraustatic

Method of operation

Pump(s) : NEWHOLLAND,Gear pump

Ram(s) : 1, Double acting

Working pressure : 10.0 MPa

1.11 BRAKES

1.11.1 Service brake

Make, model and type : NEWHOLLAND, mechanical, oil bathed,

Method of operation : Mechanical, pedal operated

Trailer braking take-off : None

1.11.2 Parking brake

Type : Mechanical, with service brake together

Method of operation :By hand lever operated with ratchet

1.12. WHEELS

Number

Front : 2/steering

Rear : 2/driving

Wheelbase : 2175 mm

Track width adjustment

	Minumum mm	Maximum mm	Adjustment method
Front	1422	1822	extending of front axle
Rear	1424	1924	reversing wheels and off-set lug rims

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

1.13 PROTECTIVE, STRUCTURE

Make, model and type : NEWHOLLAND, cab, TD-KAB-1

Manufacturer's name and address : Türk Traktör Ziraat Mak. A.Ş.
Güvercin yolu No:111-112
Gazi/ANKARA

Protective device
Cab / frame / roll guard / other : Cab

Tiltable / not tiltable : Not tiltable

OECD approval :None

1.14 SEAT

1.14.1 Driver's seat

Make, model and type : PILOT,I-II e1 0014 vinlex covered

Seat and steering wheel reversible : No

Type of suspension : coil spring

Type of damping : hydraulic

Range of adjustment
Longitudinally : 90 mm

Vertically : 65 mm

Safety belt : No

1.14.2. Optional drivers seat(s) : No

1.14.3 Passenger seat : No

1.15 LIGHTING

	Height above ground of center mm	Size mm	Distance from outside edge of lights to median plane of tractor mm
Headlights	1260 (1108) *	140x85	195
Sidelights	1345	110x35	846
Rearlights	1514	75x70	656
Reflectors	1514	75x40	695

** in the Case IH*

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

2.TEST CONDITIONS

2.1 OVERALL DIMENSIONS (unballasted tractor)

Length mm	Width		Height at top of	
	minimum mm	maximum mm	Protective structure mm	exhaust pipe mm
3618	1799	2299	2555	2460

2.2 GROUND CLEARANCE (unballasted tractor)

Clearance – limiting part :270 mm (swinging drawbar in lowest position)

2.3 TRACTOR MASS (unballasted tractor)

	Without driver kg	with driver kg
Front	934	941
Rear	1792	1860
Total	2726	2801

2.4 TYRES AND TRACK WİDTH SPECIFICATIONS

	Front	Rear
Tyres :	LASSA	GOOD YEAR
Dimensions	7.50-16 SL	14.9 -30
Ply rating	6	6
Type	-	-
Maximum load (tyre manufacturer's)	7.30 kN	16.32 kN
Maximum load (tractor manufacturer's)	7.30 kN	16.32kN
Inflation pressure (tyre manufacturer's)	280 kPa	140 kPa
Dynamic radius index	376 mm	665 mm
Chosen track width	1422 mm	1424 mm

2.5 OILS AND LUBRICATION

2.5.1 Capacity and change interval

	Capacity dm^3	Oil change h	Filter Change h
Engine	7.3	200	400
Gear box	46	1600	400
Rear axle *			
Final drive (rear) *			
Hydraulic system *			
Steering	1.8	-	800

* Common with gear box

2.5.2 Specifications

	Recommended	Used during test
Engine oil Type Viscocity Classification	BP TERRAC DIESEL 20W/50	Same
Hydraulic Fluid Type Viscocity Classification	BP TERRAC TRACTAN 8 Fluid 8	Same
Transmission oils Type Viscocity Classification	BP TERRAC TRACTAN 8 Fluid 8	Same
Steering Type Viscocity Classification	BP TERRAC TRACTAN 8 Fluid 8	Same

2.5.3 Grease : MOBILUX EP2

Number of lubrication points : 7

2.6 FUEL

Type : P.O Diesel oil, (in conformity with national standard, TS 3082)

Density at 15 °C : PTO :0.8195 g/cm^3
Drawbar :0.827 g/cm^3

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

3. COMPULSORY TEST RESULTS

3.1 MAIN POWER TAKE-OFF

Date and location of tests : 18-25/03/2002, D.A.E.M.T.C

Type of dynamometer bench :AEG Electrical

Power	Speed		Fuel consumption			Specific energy
	Engine	PTO	Hourly		Specific	
kW	rev/min		kg/h	l/h	g/kWh	kWh/ l
3.1.1. MAXIMUM POWER- TWO HOUR TEST						
37.8	2500	614	9.41	11.48	249	3.29
3.1.2. Power at rated engine speed						
37.8	2500	614	9.41	11.48	249	3.29
3.1.3. Standard Power Take-off speed (540 ± 10 rev/min)						
35.6	2200	540	8.53	10.41	240	3.42
3.1.4. PART LOADS						
3.1.4.1.The torque corresponding to maximum power at rated engine speed						
37.8	2500	614	9.41	11.48	249	3.29
3.1.4.2. 85% of torque obtained in 3.1.4.1.						
34.5	2686	659	9.04	11.03	262	3.13
3.1.4.3. 75% of torque defined in 3.1.4.2.						
26.2	2720	668	7.19	8.78	274	2.98
3.1.4.4. 50% of torque defined in 3.1.4.2.						
17.7	2752	676	5.46	6.66	308	2.66
3.1.4.5. 25% of torque defined in 3.1.4.2.						
8.9	2773	681	3.99	4.87	448	1.83
3.1.4.6. No load						
0	2796	686	2.83	3.45	-	-

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

REPORT NO : 452/2097 TGK.9

Power	Speed		Fuel consumption			Specific energy
	Engine	PTO	Hourly		Specific	
kW	rev/min		kg/h	l/h	g/kWh	kWh/l
3.1.5.PART LOADS AT STANDARD POWER TAKE-OFF SPEED (540 ±10 rev/min)						
3.1.5.1. The torque corresponding to maximum power						
35.6	2200	540	8.53	10.41	240	3.42
3.1.5.2. 85% of torque obtained in 3.1.5.1.						
31.8	2316	569	7.76	9.47	244	3.36
3.1.5.3. 75% of torque defined in 3.1.5.2.						
24.4	2371	582	6.32	7.72	259	3.16
3.1.5.4. 50% of torque defined in 3.1.5.2.						
16.9	2419	594	4.82	5.88	285	2.87
3.1.5.5. 25% of torque defined in 3.1.5.2.						
8.4	2454	602	3.45	4.22	411	1.99
3.1.5.6. No load						
0	2489	611	2.31	2.81	-	-


Maximum engine speed at no load : 2796 rev/min
Torque at maximum power(equivalent crank shaft)
At rated engine speed :144.3 Nm
At 2-hour test :144.3 Nm
Maximum torque :175.8 Nm(1300 rev/min engine speed)

Mean atmospheric conditions
Temperature : 23 ^{0}C
Pressure : 91.5 kPa
Relative humidity : 39%

Maximum temperatures (°C)
Cooling water : 76
Engine oil : 115
Fuel : 36
Engine air intake : 28


TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

PTO Power




TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

PTO Power



TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

PTO power



TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

3.2 HYDRAULIC POWER AND LIFTING FORCE

Date of tests : 04.04.2002


3.2.1 Hydraulic power test

Sustained pressure with relief valve open : 18.2 MPa

Pump delivery rate at minimum pressure :33.1 l/min

	Flow rate l/min	Pressure MPa	Power kW
Flow rate corresponding to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting and corresponding hydraulic power	23.0	16.4	6.3
Flow rate and hydraulic pressure corresponding to maximum hydraulic power	31.5	15.0	7.9

Tapping point used for test :Rear of tractor, 4
Temperature of hydraulic fluid :60 °-64 °C
Opening/closing pressure of the unloading valve: -



TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

3.2.2 Power lift test

Linkage settings for test: see 11-12 pages

		At the hitch point	On the frame
Height of lower hitch point above ground in down position	mm	205	205
Vertical movement	mm	677	895
Maximum corrected force exerted through full range	kN	23.9	16.1
Corresponding pressure of hydraulic fluid	MPa	16.4	16.4
Moment about rear wheel axis	kNm	23.8	25.8
Maximum tilt angle of mast from vertical	Degrees	-	15°

Lifting heights relative to the horizontal lower links

mm	-325	-252	-200	-100	0	+100	+200	+300	+400	+425	+570

Lifting forces (the values of force measured shall be corrected to correspond to a hydraulic pressure equivalent to 90 % of the actual relief valve pressure setting of the hydraulic lift system)

At the hitch point: Corresponding pressure:16.4 MPa

kN	-	23.9	24.6	25.0	25.1	25.0	25.3	24.7	25.3	24.7	-

At the frame: Corresponding pressure: 16.4 MPa

kN	18.7	19.1	19.3	19.3	19.1	18.6	18.2	17.6	17.1	17.1	16.1

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

REPORT NO : 452/2097 TGK.9

3.3 DRAWBAR POWER AND FUEL CONSUMPTION (unballasted tractor)

Date of tests : 10-14/06/2002

Type of track: Concrete

Height of drawbar above ground	Tyre inflation pressure	
	Front	Rear
350 mm	220 kPa	150 kPa

Gear and group	Power	Drawbar pull	Speed	Engine speed	Slip of wheels	Specific fuel consump.	Specific energy	Temperature			Atmospheric conditions		
no	kW	kN	km/h	rev/min	%	g/ kWh	kWh / l	Fuel °C	Coolant °C	Engine Oil °C	Temperature °C	Relative humidity %	Pressure kPa
3.3.1. MAXIMUM POWER IN TESTED GEARS (Unballasted tractor)													
I-1	6.3	12.38	1.83	2778	15.0	803	1.03	70	75	87	23	30	91.6
I-2	9.5	12.16	2.80	2761	15.0	594	1.39	70	75	87	23	30	91.6
I-3	12.6	12.02	3.78	2747	15.1	538	1.54	65	75	87	23	30	91.6
II-1	14.2	12.15	4.20	2738	15.1	496	1.67	65	75	90	23	30	91.6
I-4	18.1	12.13	5.37	2721	15.1	449	1.84	70	75	90	19	30	91.6
II-2	21.9	12.19	6.46	2724	14.9	390	2.12	70	75	90	19	38	91.6
II-3	28.2	12.21	8.32	2555	14.0	363	2.28	70	79	93	19	38	91.6
III-1	30.4	11.79	9.28	2501	12.8	333	2.48	70	79	93	19	38	91.6
II-4	31.6	9.25	12.31	2500	9.3	324	2.55	70	79	93	19	38	91.6
III-2	28.6	6.94	14.84	2490	9.1	352	2.34	70	79	93	19	38	91.6
III-3	This gear couldn't be tested because of safety reason												
3.3.2.FUEL CONSUMPTION													
3.3.2.1. In selected gear, at maximum power at rated speed													
II-4	31.6	9.25	12.31	2500	9.3	324	2.55	70	75	87	23	37	91.6
3.3.2.1.1. 75 % of pull at maximum power at rated speed													
II-4	26.2	6.94	13.59	2729	8.2	365	2.27	70	75	87	23	37	91.6
3.3.2.1.2. 50 % of pull at maximum power at rated speed													
II-4	17.7	4.63	13.79	2743	7.4	424	1.95	70	76	87	23	37	91.6
3.3.2.1.3. Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.1.													
III-2	26.4	7.01	13.59	2257	8.3	294	2.81	67	76	89	23	37	91.6
3.3.2.1.4. Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.2.													
III-2	18.0	4.67	13.84	2283	7.5	350	2.37	70	79	89	23	37	91.6
3.3.2.2. in selected gear nearest to 7.5 km/h at rated speed													
II-2	21.9	12.19	6.46	2724	14.9	390	2.17	70	79	93	19	37	91.6
3.3.2.2.1. 75 % of pull at maximum power at rated speed													
II-2	17.7	9.14	6.97	2745	8.9	421	1.97	70	79	93	19	37	91.6
3.3.2.2.2. 50 % of pull at maximum power at rated speed													
II-2	12.0	6.10	7.12	2767	7.6	493	1.68	70	79	93	19	37	91.6
3.3.2.2.3. Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.1.													
II-3	17.7	9.20	6.93	2006	8.8	351	2.36	70	79	93	19	37	91.6
3.3.2.2.4. Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.2.													
II-3	12.1	6.12	7.11	2035	7.8	385	2.15	70	79	93	19	37	91.6

4.OPTIONAL TESTS : **None**

5. REPAIRS : **None**

6. REMARKS : the atmospheric pressure 91.5 kPa and 91.6 kPa less than 96.6 kPa fixed in the OECD Code

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel: (0312) 315 65 74 - 315 56 85 Fax: (0312) 315 04 66
e mail: tamtest @ankara.tagem.gov.tr

TEST COMMISSION

Bekir İLBAN
Agricultural Engineer

Ömer L.DEVEÇİOĞLU
Mechanical Engineer

Ahmet AYGÜL
Departmant Chief

Feridun ULUTAŞ
Chairman of Test Commission

This test report has been prepared and undersigned as 26 pages

Hüseyin YAŞAR
Assistant Director

Signatures that belong to members of test commission above have been approved 08/ 07/2002

Dr. Hamdi TAŞBAŞ
Director