ISTITUTO SPERIMENTALE PER
LA MECCANIZZAZIONE AGRICOLA
SEZIONE DI TREVIGLIO

CASE INTERNATIONAL 2120 E "2WD"
TEST no. 055.

O.E.C.D. no. 1269

Test in accordance with the O.E.C.D. Restricted Standard Code
for the official testing of agricultural tractors.



Report test of: CASE INTERNATIONAL 2120 E "2WD"

Submitted for test by: JI CASE GmbH
Industriestr. 39-40, 4040 Neuss
GERMANY

Date of O.E.C.D. approval: 31.08.1990
Period of test: April 1990

ISMA - SOP Treviglio - Via Milano,43 - (BG) - ITALY

ISTITUTO SPERIMENTALE PER
LA MECCANIZZAZIONE AGRICOLA
SEZIONE DI TREVIGLIO



O.E.C.D. no. 1269

Test in accordance with the O.E.C.D. Restricted Standard Code
for the official testing of agricultural tractors.



Report test of: CASE INTERNATIONAL 2120 E "2WD"

Submitted for test by: JI CASE GmbH
Industriestr. 39-40, 4040 Neuss
GERMANY

Date of O.E.C.D. approval: 31.08.1990
Period of test: April 1990

ISMA - SOP Treviglio - Via Milano,43 - (BG) - ITALY

TABLE OF CONTENTS

- Specification of tractor ..... page 3
- Power take-off performance ..... page 20
- Power lift and hydraulic power test ..... page 24
- Drawbar performance ..... page 25

All stated dimensions and tests referred to tyre sizes 6.50/16 (6 ply) at front and 13.6/28 (6 ply) at rear, as well as to track widths 1000 mm at front and 998 mm at rear.

- Tractor manufacturer
- Name: JI CASE GmbH;
- Address: Industriestr. 39-40, 4040 Neuss GERMANY;
- Location of tractor assembly: CARRARO S.p.A. ROVIGO ITALY;
- Submitted for test by: the manufacturer;
- Selected by: the manufacturer with the agreement of ISMA;
- Place of running in: Campodarsego (PD) - ITALY;
- Duration of running: 50 hours.
- Location of test: I.S.M.A. Via Milano, 43 - Treviglio (BG) ITALY

---

## I - SPECIFICATION OF TRACTOR

### TRACTOR

- Make: CASE INTERNATIONAL;
- Model: 2120 E "2WD";
- Type: Wheeled tractor, unit construction, rear wheels drive tractor;
- Number of driving wheels: 2;
- Serial number: CGC 58502524, Code: 585 ABAGAE;
- First serial number: CGC 58500001, Code: 585 ABAGAE.

### ENGINE

- Make: SAME;
- Model: 1000.3A/45;
- Type: aircooled 4 stroke diesel engine direct injection;
- Serial number: 07627.

Cylinders

- Number/disposition: 3, vertical in line;
- Bore/stroke: 105/115,5 mm;
- Capacity: 3000 $cm^3$;
- Compression ratio: 17.1 / 1;
- Arrangement of valves: overhead;
- Cylinder liners: without liners.

Supercharging none.

Fuel system

- Fuel feed system: AC corone fuel feed pump;
- Make, model and type of fuel filter: FIAMM FNA 160/00 ;
- Capacity of fuel tank: 60 dm³;
- Make, model and type of injection pump: BOSCH PFR 1K 90A 503, immersed pump, one per cylinder, without serial number, in line injection pump;
- Manufacturer's production setting of injection pump:
  .flow rate: 44+/-2 mm³ /stroke at rated speed and full load corresponding to 9.37 dm³/h;
  .timing: 18+/-0.5 before TDC;
- Make, model and type of injectors: BOSCH KBE 58 S 4/4;
- Injectors pressure: 18 +/-1 MPa.

Governor

- Make: SAME;
- Model: 065.1652.4;
- Type: mechanical variable speed;
- Governor range of engine speed: from 675 to 2510 rev/min.;
- Rated engine speed: 2350 rev/min.

Air cleaner

- Main filter
  . make: VF VIRGIS;
  . model: 1967771C1;
  . type: dry paper element filter;
  . location: behind of engine;
- Maintenance indicator: with the warning lamp on the dashboard

Lubrication system

- Type of feed pump: forced feed from gear pump;
- Total oil capacity including filter: 6.7 dm³;
- Oil change period: 150 hrs;
- Type of filter: FIAMM FT 4803 IN;
- Number: 1;
- Filter change period: 300 hrs;
- Oil specifications: see page 18.

Cooling system

- Type and detail: air cooling with axial blower;
- Specification of fan: propeller fan driven by engine shaft;
- Number of fan blades: 13;
- Fan diameter: 220 mm;
- Type of temperature control: none.
- Warming indicator: with the warning lamp on the dashboard.

Starting system

- Make: BOSCH;
- Model: JF R 12 V;
- Type: electromagnetic engagement;
- Starter motor power rating: 2.4 kW;
- Safety device: preventig engine from starting in gear;
- Starting system for low temperatures: none.

Electrical equipement

- Voltage: 12 V;
- Generator:
  . make: BOSCH;
  . model: K1 R 14V 55A;
  . type: alternator;
  .power: 630 W;
- Battery: 1 lead acid;
  .capacity: 100 Ah at 20 hours.

Exhaust system

- Make: IMA SAF;
- Model: 1967893C1;
- Type: at chamber reflection absorption;
- Location: on the left hand side of engine cowling, horizontal position;
- Height of outlet above ground: 500 mm.

TRANSMISSION

Clutch: utilized only for travelling of tractor.

- Make: OMG;
- Model: 121947;
- Type: double disk dry clutch;
- Number of plates: 2;
- Plates diameter: 280 mm;
- Control system: by pedal for transmission, by lever for p.t.o.;

Gear box

- Make: CARRARO;
- Model: 121947;
- Type: mechanical no-syncromesh speed change gear;
- Arrangement: four speeds forward with three ranges of speed and one reverse group;
- Number of speeds : 12 forward and 12 reverse;
- Available options: 8 forward and 8 reverse.

Rear axle and final drives

- Make: CARRARO;
- Model: 121266/1;
- Type: bevel gear differential and epicyclic reduction final drives.

Differential lock

- Make: CARRARO;
- Model: 121266/1;
- Type: mechanical;
- Control system: engaged or disengaged by pedal.

Front axle and final drives

- Make: CARRARO;
- Model: 124607;
- Type: not propelled.

Differential lock

- none

Transmission lubrication

- Gear box, rear axle, final drives, power lift and hydraulic system (in common);
  . total capacity including filter: 36 $dm^3$;
  . change period: 1000 hrs;
  . filter change period: 1000 hrs;

- Recommended oil: see page 18.

Total rations and speeds

| Gear | Group | Number of engine revolutions for one revolution of the driving wheels | Nominal travelling speed at a rated engine speed of 2350 rev/min (*) (km/h) |
|---|---|---|---|
| | FORWARD | | |
| 1 | S | 1140.223 | 0.47 |
| 2 | S | 769.196 | 0.70 |
| 3 | S | 526.198 | 1.03 |
| 4 | S | 374.442 | 1.44 |
| 1 | N | 244.283 | 2.21 |
| 2 | N | 164.982 | 3.27 |
| 3 | N | 112.753 | 4.79 |
| 4 | N | 80.238 | 6.73 |
| 1 | F | 56.375 | 9.58 |
| 2 | F | 38.071 | 14.19 |
| 3 | F | 26.019 | 20.76 |
| 4 | F | 18.516 | 29.18 |
| | REVERSE | | |
| 1 | S | 1359.167 | 0.40 |
| 2 | S | 917.696 | 0.59 |
| 3 | S | 627.336 | 0.86 |
| 4 | S | 446.429 | 1.21 |
| 1 | N | 291.274 | 1.85 |
| 2 | N | 196.702 | 2.75 |
| 3 | N | 134.432 | 4.02 |
| 4 | N | 95.668 | 5.65 |
| 1 | F | 67.216 | 8.05 |
| 2 | F | 45.393 | 11.90 |
| 3 | F | 31.023 | 17.42 |
| 4 | F | 22.077 | 24.47 |

(*) Calculated with a tyre dynamic radius index of 610 mm.
ISO 4251/1 - 1984)

POWER TAKE-OFF

Power take-off proportional to engine speed

- Type: independent, at rear of tractor, in tractor's median plane, engaged or disengaged by hand lever.
  Driven by multiplate wet clutch independent from travel clutch; ISO Standard 500-1979.
- Number of shafts: 1;
- Method of changing of speed: speed selction by external hand lever;
- Location : at rear of tractor;

| | P.T.O. |
|---|---|
| - Height above ground (with tyre size 13.6/28 ) .. | 610 mm |
| - Distance from the median plane of the tractor .. | 0 mm |
| - Distance behind rear axle..... | 387 mm |
| - Direction of rotation (viewed facing driving end): | clockwise |

1) 540 rev/min

- Dimension: ISO Standard 500-1979 type 1 (35 mm - 6 splines);
- PTO speed at rated engine speed .....: 600 rev/min;
- Engine speed at standard power take-off speed: 2115 rev/min;
- Ratio of rotation speeds (engine speed/pto speed): 3.916666;
- Maximum power and torque transmissible: 55 kW and 97 daNm.

2) 1000 rev/min

- Dimension: ISO Standard 500-1979 type 2 (35 mm - 21 splines);
- PTO speed at rated engine speed .....: 1116 rev/min;
- Engine speed at standard power take-off speed: 2105 rev/min;
- Ratio of rotation speeds (engine speed/pto speed): 2.105734;
- Maximum power and torque transmissible: 55 kW and 52 daNm.


Power take-off proportional to ground speed : none.


POWER LIFT

- Make: MITA;
- Model: M 60 SRF;
- Type: load sensing;
- Type of hydraulic system: open centre system;
- Type and number of cylinders: 1 internal hydraulic jack at single effect;
- Type of lock for transport: mechanical, with screwed tie rods that lock the lower links;
- Relief valve pressure setting: 18 +/- 1 MPa;
- Opening pressure of anti-shock valve: 20 MPa;
- Lift pump type: hydraulic rotary pump, driven by engine shaft;
- Transmission between pump and engine: mechanical;
- Type and number of filters: 1, repeaceable paper cartridge;
- Changing: when the filter clogging warning lamp is lighted;
- Oil capacity: 38 dm³ in common with gear box;
- Site of oil reservoir : gear box;
- Position, type and No. of additional oil plugs: 4 ways distributor at rear of tractor;
- Maximum volume of oil available to external cylinders: 4 dm³;
- Recommended oil: see page 18.

Three-point linkage

- Category: 1 in conformity with ISO 730/1 - 1977;
- Category adapter: none.


lift rod
c
L
top. link
lift arm
A
lower link
S
H
b
a
d
rear axis
0
f
B
D
h
e
ground level
rear wheel axis


v
u

Dimensions of linkage geometry (when connected to the standard frame)

| | | Dimension or range (mm) | Settings used in test (mm) |
|---|---|---|---|
| Length of lift arms | (A) | 260 | 260 |
| Length of lower links | (B) | 848 | 848 |
| Distance of lift arm :horizontally | (a) | 25 | 25 |
| Pivot point from rear :vertically | (b) | 306 | 306 |
| wheel axis (behind) | | | |
| Horizontal distance between the 2 lower link points | (u) | 479 | 479 |
| Horizontal distance between the 2 lift arm and points | (v) | 375 | 375 |
| Length of upper link | (S) | from 500 to 780 | 681 |
| Distance of upper link :horizontally | (c) | 244 | 244 |
| pivot point from rear :vertically | (d) | 261 | 261 |
| wheel axis | | | |
| Distance of lower link :horizontally | (e) | 72 | 72 |
| pivot point from rear :vertically | (f) | 192 | 192 |
| wheel axis | | | |
| Distance of lower link pivot point to lift rod pivot points on lower links | (D) | 496 | 496 |
| Length of lift rods | (L) | from 500 to 670 | 600 |
| Height of lower hitch points relative to the rear wheel axis | | | |
| - in Low position | (h) | from 191 to 568 | 410 |
| - in High position | (H) | from 153 to 395 | 260 |
| Height above ground of lower hitch points when locked in transport position (*) | | | 870 |

(*) Assuming the dynamic radius index = 610 mm (ISO 4251/1 - 1984)

SWINGING DRAWBAR : not fitted.

HOLED DRAWBAR : not fitted.

TRAILER HITCH

- Type: J.I CASE;
- Hole diameter: 28 mm;
- Height above ground: 373 min. - 733 max. mm ;
- Distance of hitch point from rear wheel axis, horizontally: 515 mm;
- Distance of hitch point from power take-off shaft end
  . vertically :below 237 mm, above 122 mm;
  . horizontally : 130 mm;
- Maximum vertical permissible load: 1471 daN.

STEERING

- Specification: hydrostatic steering with SAVER SUNDESTRAND gear pump, one steering cylinder at double effect acting directly on front axle.
- Make: DANFOSS;
- Model: OSPC 80 LS with priority valve OLSA 40;
- Type: hydrostatic;
- Working pressure: 1.1 MPa;
- Oil capacity: 17 $dm^3$, in common with hydraulic system;
- Oil change period: 1000 hrs;
- Filter change period: 1000 hrs;
- Recommended oil: see page 18.

BRAKES

Service brake

- Make: SIRMAC;
- Model: 1967573C1;
- Type: oil immersed multiplate disc, 4 per side total 8 discs, mounted before each epicyclic reduction gear. SK Welman HDT 303 lining material, rear disc diameter 165,25 mm;
- Method of operation: mechanical acting with 2 pedals;
- Trailer braking take-off: none.

Parking brake

- Type: mechanical acting on the service brake;
- Method of operation: mechanically by hand lever.

Steering brake : divided pedal of service brake for normal use locked together.

STEERING WHEELS

- Number: 2;
- Location : at front;
- Track widths: 1000 min. - 1500 max. mm;
- Regulation: track adjustable by extending telescopic half axles.

DRIVING WHEELS

- Number: 2;
- Location: at rear;
- Rear track widths: 850 min. 1648 max. mm;
- Regulation: changing the position of the rims with respect to the disc.

WHEELBASE: 1980 mm.

ROLL - BAR

Specifications

- NFU approval number: 013401;
- Make: CARRARO;
- Model: X 260-4;
- Type: tiltable;
- Manufacturer's name: CARRARO S.p.A.;
  . address: Via Olmo, 29 - Campodarsego (PD) ITALY;
- Protective device: roll-bar tiltable.

Materials used in the construction and dimensions

See N.F.U. (France) Test Report on Protective Structures.

DRIVER'S SEAT

- Make: SIFRA;
- Model: 15 M;
- Type: upholstered seat;
- Type of suspension: adjustable spring;
- Type of damping: shock absorber;
- Range of adjustment, longitudinal 210 mm;
  vertical ... 100 mm.

PASSENGER'S SEAT : none.

## LIGHTING

Lighting system in accordance with E.E.C. 78/933

| | Height above ground of centre with tyre (*) (mm) | Size (mm) | Distance from outside edge of tractor to centre at 998 mm track width (mm) |
|---|---|---|---|
| Headligths | 1011 | 155*90 | 548 |
| Front park. lights | 1403 | 120*40 | 85.5 |
| Front finger post | 1443 | 120*40 | 85.5 |
| Rear park. lights | 1443 | 120*40 | 85.5 |
| Rear finger post | 1403 | 120*40 | 85.5 |
| Stop | 1443 | 120*40 | 85.5 |
| Reflectors | 1148 | 88*52 | 214.5 |

(*) Tyre size: 6.50/16 front - 13.6/28 rear.

## TEST CONDITIONS

Overall dimensions with tyres 6.50/16 front and 13.6/28 rear

| | Length (mm) | Width (mm) min | Width (mm) max | Height (mm) at top of protect. struc. |
|---|---|---|---|---|
| Without ballast | 3464 | 1157 | 1977 | 2354 |

- Ground clearance (unballasted tractor): 345 mm;
- Clearance-limiting part: front axle.

Tractor mass (with tanks full, with frame, water in tyres none)

| | Units | Front | Rear | Total |
|---|---|---|---|---|
| Without driver | | | | |
| Without ballast | kg | 795 | 1155 | 1950 |
| With ballast | kg | - | - | - |
| With driver | | | | |
| Without ballast | kg | 805 | 1220 | 2025 |
| With ballast | kg | - | - | - |

Ballast

| | no. of weights | total weight (kg) | water (kg) |
|---|---|---|---|
| front | - | - | - |
| rear | - | - | - |
| additional | - | - | - |

Tyres and track width specifications

| | front | rear |
|---|---|---|
| - Tyres | | |
| . dimensions ..... | 6.50/16 | 13.6/28 |
| . ply rating ..... | 6 | 6 |
| . type ..... | cross-ply | radial |
| . maximum load (tyre manufacturer's) daN | 603 | 1403 |
| . maximum load (tractor manufact.) daN | 603 | 1403 |
| . inflation pressure (tyre manufact.)kPa | 310 | 160 |
| . dynamic radius index .....mm | 350 | 610 |
| - Chosen track width .....mm | 1000 | 998 |
| - Tyres on request ..... | - | pr |
| | - | pr |
| | - | pr |

Oils, lubrication and fuel
Capacity and change interval

| | capacity dm³ | oil change h | filter change h |
|---|---|---|---|
| Engine ..... | 9.2 | 150 | 300 |
| Gear box ..... | 36 | 1000 | 1000 |
| Front axle and final drives ... | --- | --- | --- |
| Rear axle and final drives .... | in common with gear box | | |
| Hydraulic system ..... | " | " | |
| Other (steering, etc.) ..... | " | " | |

Fuel and lubricants recommended and used in tests

Fuel
- Type: AGIP DIESEL, DIN 51601;
  (in accordance with the national standard)
- Specific gravity at 15° C: 0.828 g/cm³.

Engine oil
- Type: AGIP 15/W40 Super Diesel;
- Viscosity: 15.6 cSt;
- Classification: API SE-CD.

Transmission oil

| | front axle and final drive | rear axle, final drive and gear box |
|---|---|---|
| -Type | -- | ELF BF12 |
| -Viscosity | -- | 10.50 cSt |
| -Viscosity index | -- | 146 |
| -Classification | | |

Hydraulic fluid
- Type: ELF BF12;
- Viscosity: 10.50 cSt;
- Classification:

Steering oil
- Type: ELF BF13;
- Viscosity: 10.50 cSt;
- Classification:

Grease
- Type:ESSO BEACON 2;
- Number of lubrication points: 15.

## II - TEST RESULTS

### A. COMPULSORY TESTS RESULTS

#### (1) MAIN POWER TAKE-OFF PERFORMANCE

- Date and location of test: 04.04.1990 TREVIGLIO (BG) - I.S.M.A. ITALY
- Type of dynamometer: ZOELLNER 350 AC

| Power | Speed | | Fuel consumption | | | Specific |
|---|---|---|---|---|---|---|
| | Engine | P.T.O. | Hourly | Specific | | Energy |
| kW | rev/min | rev/min | l/h | kg/h | g/kWh | kWh/l |
| MAXIMUM POWER - 2 HOUR TEST | | | | | | |
| 30.4 | 2346 | 599 | 9.37 | 7.76 | 255 | 3.24 |
| POWER AT RATED ENGINE SPEED | | | | | | |
| 30.4 | 2346 | 599 | 9.37 | 7.76 | 255 | 3.24 |
| STANDARD POWER TAKE-OFF SPEED ( 540 +/- 10 rev/min) | | | | | | |
| 29.4 | 2115 | 540 | 8.09 | 6.70 | 228 | 3.63 |
| PART LOADS | | | | | | |
| i) The torque corresponding to maximum power at rated engine speed | | | | | | |
| 30.4 | 2346 | 599 | 9.37 | 7.76 | 255 | 3.24 |
| ii) 85% of torque obtained in i) | | | | | | |
| 27.1 | 2408 | 615 | 8.76 | 7.25 | 268 | 3.09 |
| iii) 75% of torque defined in ii) | | | | | | |
| 20.2 | 2448 | 625 | 6.88 | 5.70 | 282 | 2.94 |
| iv) 50% of torque defined in ii) | | | | | | |
| 13.8 | 2466 | 630 | 5.83 | 4.83 | 350 | 2.37 |
| v) 25% of torque defined in ii) | | | | | | |
| 6.9 | 2488 | 635 | 5.11 | 4.23 | 613 | 1.35 |
| vi) unloaded | | | | | | |
| 0 | 2510 | 641 | 3.16 | 2.61 | - | - |


PART LOADS AT STANDARD POWER TAKE-OFF SPEED ( 540 rev/min)


| Power | Speed | | Fuel consumption | | | Specific |
|---|---|---|---|---|---|---|
| | Engine | P.T.O. | Hourly | Specific | | Energy |
| kW | rev/min | rev/min | l/h | kg/h | g/kWh | kWh/l |
| i) The torque corresponding to maximum power available | | | | | | |
| 29.4 | 2115 | 540 | 8.09 | 6.70 | 228 | 3.63 |
| ii) 85% of torque obtained at maximum power | | | | | | |
| 25.5 | 2165 | 553 | 7.71 | 6.39 | 251 | 3.31 |
| iii) 75% of torque defined in ii) | | | | | | |
| 19.5 | 2210 | 564 | 6.28 | 5.20 | 267 | 3.10 |
| iv) 50% of torque defined in ii) | | | | | | |
| 13.1 | 2230 | 569 | 5.31 | 4.39 | 335 | 2.47 |
| v) 25% of torque defined in ii) | | | | | | |
| 6.6 | 2264 | 578 | 3.77 | 3.12 | 473 | 1.75 |
| iv) unloaded | | | | | | |
| 0 | 2296 | 586 | 2.86 | 2.37 | - | - |

STANDARD SPECIFIC FUEL CONSUMPTION: 268/350/251/335 g/kWh

- No load maximum engine speed: 2510 rev/min
- Torque (1) at maximum power: 12.37 daNm
- Maximum torque (1) (engine speed: 1402 rev/min) 16.03 daNm
- Mean atmospheric conditions: Temperature ..... 19 C°
  Pressure ..... 99.3 kPa
  Relat. humidity ... 84 %
- Maximum temperatures: Coolant ..... 82 C°
  Engine oil ..... 113 C°
  Fuel ..... 26 C°
  Engine air intake ..... 21 C°

(1) The torque is the equivalent crankshaft torque.


POWER [kW]
FUEL CONSUMPTION [kg/h]
TORQUE [daNm]
SPECIFIC CONSUMPTION [g/kWh]
STANDARD PTO SPEED 540 rev/min
RATED ENGINE SPEED
ENGINE SPEED [rev/min]


P.T.O. PERFORMANCE
SPECIFIC FUEL CONSUMPTION [g/kWh]
650
600
550
500
450
400
350
300
250
200
150
0
2
4
6
8
10
12
14
16
18
20
22
24
26
28
30
32
POWER [kW]

## ) POWER LIFT AND HYDRAULIC POWER TEST

- Date and location of tests: 04.04.1990 - ISMA Treviglio (BG)

### 2.1 POWER LIFT

| | | at hitch point | on the frame |
|---|---|---|---|
| Height of lower hitch point above ground in down position | mm | 200 | 200 |
| vertical movement | mm | 670 | 724 |
| Maximum corrected force exerted trough full range | daN | 2992 | 2261 |
| Corresponding pressure of hydraulic fluid | MPa | 18.0 | 18.0 |
| Moment about rear axle | daNm | 2753 | 3459 |
| Maximum tilt angle of mast over range of lift | degress | -- | 5 |

| Lifting heights relative to the horizontal lower links | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | -218 | -200 | -100 | 0 | 100 | 200 | 300 | 400 | 452 | 500 | 506 |
| Lifting forces at hitch points | | | | | | | | | | | |
| daN | 3105 | 3107 | 3105 | 3109 | 3082 | 3021 | 3013 | 3007 | 2992 | --- | --- |
| Lifting forces at test frame | | | | | | | | | | | |
| daN | 2907 | 2911 | 2904 | 2766 | 2583 | 2407 | 2325 | 2289 | --- | 2258 | 2261 |

### 2.2) HYDRAULIC POWER TEST

Sustained pressure with relief valve open: 18.0 MPa;
Pump delivery rate at min pressure: 40.1 l/min;

| Hydraulic power | kW | flow rate l/min | pressure MPa | oil temp. °C |
|---|---|---|---|---|
| At 90% of the actual relief valve setting ..... | 9.2 | 35.1 | 16.0 | 65 |
| Maximum ..... | 9.2 | 35.1 | 16.0 | 65 |

. opening pressure of the relief valve: 17.5 MPa

Tapping point used for test : at rear of tractor;
Hydraulic fluid: see page 18.

## 3) DRAWBAR PERFORMANCE

- Date of test: 19.04.1990
- Type of track: concrete
- Type and size of tyres front: 6.50/16 - 6 ply
  rear : 13.6/28 - 6 ply

Height of drawbar above ground: 445 mm (unballasted)

Tyre inflation pressure: unballasted .front: 275 kPa .rear: 160 kPa

### 3.1) MAXIMUM POWER IN TESTED GEARS (unballasted tractor)

| Gear | Power | Draw. pull | Speed | Eng. speed | Slip of whell | Specific ener.cons. | fuel | Temperatures cool. | eng. | Atm. temp. | cond. hum. | pres |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | kW | daN | km/h | rev/min | % | kWh/l | g/kWh | °C | °C | °C | % | kPa |
| 1S | 1.4 | 1290 | 0.4 | 2504 | 15 | 0.334 | 2500 | 22 | 50 | 88 | 15 | 86 | 99.8 |
| 2S | 2.2 | 1836 | 0.6 | 2497 | 15 | 0.478 | 1750 | 23 | 50 | 88 | 15 | 86 | 99.8 |
| 3S | 3.2 | 1273 | 0.9 | 2497 | 15 | 0.681 | 1206 | 23 | 50 | 89 | 15 | 86 | 99.9 |
| 4S | 4.8 | 1318 | 1.3 | 2486 | 15 | 0.923 | 896 | 24 | 52 | 89 | 16 | 85 | 99.8 |
| 1N | 7.2 | 1306 | 2.0 | 2474 | 15 | 1.286 | 639 | 24 | 51 | 91 | 16 | 86 | 99.7 |
| 2N | 10.6 | 1315 | 2.9 | 2472 | 15 | 1.682 | 491 | 23 | 52 | 91 | 15 | 85 | 99.9 |
| 3N | 15.2 | 1303 | 4.2 | 2443 | 15 | 1.900 | 434 | 24 | 52 | 92 | 16 | 86 | 99.8 |
| 4N | 19.8 | 1232 | 5.8 | 2400 | 15 | 2.084 | 396 | 25 | 52 | 91 | 16 | 85 | 99.7 |
| 1F | 23.4 | 969 | 8.7 | 2351 | 9 | 2.412 | 342 | 23 | 52 | 91 | 17 | 85 | 99.8 |
| 2F | 20.5 | 539 | 13.7 | 2350 | 3 | 2.113 | 390 | 24 | 51 | 91 | 16 | 85 | 99.7 |

## 4) TRANSMISSION AND FUEL CONSUMPTION CHARACTERISTICS

| Gear | Power | Draw. pull | Speed | Eng. speed | Slip of wheel | Specific ener.cons. | fuel | Temperatures cool. | eng. | temp. | Atm. cond hum. | pres |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | kW | daN | km/h | rev/min | % | kWh/l | g/kWh | °C | °C | °C | % | KPa |
| 4.1.1) Selected gear at maximum power | | | | | | | | | | | | |
| 1F | 23.4 | 969 | 8.7 | 2351 | 9 | 2.412 | 342 | 23 | 52 | 91 | 17 | 85 | 99.8 |
| 4.1.1) 75% of pull at maximum power at rated speed | | | | | | | | | | | | |
| 1F | 18.4 | 727 | 9.1 | 2423 | 7 | 2.190 | 375 | 22 | 52 | 90 | 17 | 84 | 99.7 |
| 4.1.2) 50% of pull at maximum power at rated speed | | | | | | | | | | | | |
| 1F | 12.7 | 485 | 9.4 | 2447 | 5 | 1.764 | 472 | 22 | 52 | 92 | 16 | 84 | 99.7 |
| 4.1.3) next higher gear giving the same pull as in 4.1.1 red. eng. speed | | | | | | | | | | | | |
| 2F | 18.3 | 725 | 9.1 | 1625 | 7 | 2.577 | 322 | 23 | 54 | 92 | 16 | 85 | 99.8 |
| 4.1.4) next higher gear giving the same pull as in 4.1.2. red. eng. speed | | | | | | | | | | | | |
| 1F | 12.7 | 485 | 9.4 | 1653 | 5 | 2.016 | 409 | 22 | 51 | 91 | 16 | 86 | 99.9 |

| Gear | Power | Draw. pull | Speed | Eng. speed | Slip of wheel | Specific ener.cons. | fuel | Temperatures cool.eng. | | Atm. cond temp. | hum. | pres |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | kW | daN | km/h | rev/min | % | kWh/l | g/kWh | °C | °C | °C | % | KPa |
| 4.2) Selected gear nearest to 7.5 Km/h | | | | | | | | | | | | |
| 4N | 19.8 | 1232 | 5.8 | 2400 | 15 | 2.084 | 396 | 25 | 52 | 91 | 16 | 85 | 99.8 |
| 4.2.1) 75% of pull at maximum power at rated speed | | | | | | | | | | | | |
| 4N | 16.2 | 925 | 6.3 | 2430 | 9 | 2.025 | 407 | 23 | 51 | 90 | 17 | 84 | 99.8 |
| 4.2.2) 50% of pull at maximum power at rated speed | | | | | | | | | | | | |
| 4N | 11.3 | 616 | 6.6 | 2453 | 6 | 1.614 | 496 | 23 | 52 | 92 | 16 | 84 | 99.9 |
| 4.2.3) next higher gear giving the same pull as in 4.2.1 red. eng. speed | | | | | | | | | | | | |
| 1F | 16.4 | 921 | 6.4 | 1730 | 9 | 2.523 | 329 | 24 | 51 | 92 | 16 | 85 | 99.9 |
| 4.2.4) next higher gear giving the same pull as in 4.2.2 red. eng. speed | | | | | | | | | | | | |
| 1F | 11.3 | 616 | 6.6 | 1721 | 6 | 2.216 | 375 | 23 | 52 | 92 | 16 | 85 | 99. |

**REPAIRS AND REMARKS:** none.

TEST CARRIED OUT BY
(P.a. Giovanni LAMORATTA)

THE DIRECTOR OF TESTING STATION
(Prof. Giuseppe COLZANI)

HEAD OF ISMA - ROMA
(Prof. Alfio CAMMILLI)

Text and graphics processed by: P.a. Gianluigi ROZZONI
Software written by: Ing. Giampaolo GIACOMETTI