Report on test in accordance
with O.E.C.D. STANDARD CODE

O.E.C.D. No. 676



Agricultural Tractor EICHER 3355
trade name: EICHER 4060

Manufacturer
Gebr. Eicher, Traktoren- und Landmaschinenwerke GmbH
D-8380 Landau a. d. Isar

Deutsche Landwirtschafts-Gesellschaft e.V.
Zimmerweg 16 · D-6000 Frankfurt a. M. 1
Telefon: (0611) 72 07 11 · Telex: 04 131 85 dlg-d

This bulletin is based on engineering tests in accordance with the O.E.C.D. STANDARD CODE for the Official Testing of Agricultural Tractor Performance. It does not contain an evaluation of the tractor performance on practical work.

Duration of tests: January 1979 till January 1980

DLG-Testing-Station for Agricultural Machinery, Max-Eyth-Weg 1, D-6114 Groß Umstadt

This report has been approved by the O.E.C.D. Coordinating Centre (C.N.E.E.M.A., France) as being in accordance with the O.E.C.D STANDARD CODE.

Date of Approval: 16th April 1980 O.E.C.D. No. 676

In this report all performance characteristics are given corresponding to the International System of Units.

The reference to the former used Technical System of Units is given by the following relations:

Forces	1 daN = 10 N = 1,02 kp	or 1 kp	= 0,981 daN
Powers	1 kW = 1,36 PS	or 1 PS	= 0,736 kW
Pressures	1 bar = 1,02 kp/cm²	or 1 kp/cm²	= 0,981 bar
	1000 mbar = 750,1 mm Hg		

All rights including the right of translation, reprint and photomechanical copying – also of excerpts – reserved by the DLG.

Printed in the Federal Republic of Germany
August 1980; DLG-No. 149

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

TABLE OF CONTENTS

	Page
Specification of tractor	4 to 14
Fuel and lubricants used in tests	15
COMPULSORY TESTS	
(1) Main power take-off performance	16 to 19
(2) Drawbar performance on a concrete track	20 and21
(3) Turning space and turning circle	22
(4) Location of centre of gravity	22
(5) Braking performance	23
(6) Ambient noise, emitted by the tractor	24
(7) Noise at the driver's ear level	24
(8) Power lift and hydraulic pump performance	25 to 29
OPTIONAL TESTS	
(9) Engine performance	30 to 33

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

Tractor manufacturer:	GEBRÜDER EICHER GMBH D-8380 Landau
Submitted for test by:	Manufacturer
Selected by:	Manufacturer with agreement by DLG
Place of running-in:	Landau
Duration of running-in:	Engine 50 hours, tractor appr. 90 hours

SPECIFICATION OF TRACTOR

Tractor

Make:	EICHER
Model:	3355 trade name 4060 wheel tractor, unit construction, rear-wheel driven
Serial no.:	150390

Engine

Make:	PERKINS ENGINES S.A.
Model:	A 4.203
Type:	4-stroke Diesel-engine, direct injection, water-cooled
Serial no:	JE 22707 U 516 194 E
Cylinders:	4, in line, bore 91,4 mm, stroke 127 mm, displacement 3333 cm^3; compression ratio 16,4 replaceable dry cylinder liners
Valves:	Overhead
Fuel system:	AC DELCO fuel feed pump CAV distributor injection pump MP 54/600/5/2380 manufacturer's production setting 52 mm^3/stroke at rated engine speed; injection timing 26° before TDC; CAV multihole injection nozzles BDLL 150 S, injection pressure 170 bar; CAV fuel filter with replaceable cartridge; capacity of fuel tank 98 l
Governor:	Mechanically acting centrifugal variable speed governor, incorporated in injection pump; governed range of engine speed 620 to 2220 rev/min, rated engine speed 2100 rev/min

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

Air cleaner:	MANN PICLON dry paper element filter with precleaner, with replaceable cartridge and electrically operating maintenance indicator
Exhaust silencer:	LEISTRITZ multi chamber reflexion-type silencer, 100 mm dia, 640 mm long, on the left hand side of engine cowling, mouth showing upward, mouth 2325 mm above ground
Lubrication system:	Forced feed from gear pump; strainer in Sump; PERKINS oil filter in full flow with replaceable cartridge and by-pass valve; cartridge change at all oil changes; oil capacity 8,3 l; recommended oil quality MIL-L-2104 B; recommended oil viscosities: winter SAE 10W summer SAE 20W/20 tropics SAE 30 oil change interval 150 hours
Cooling system:	Pressurized water cooling system with pump; overpressure set to 0,5 bar; thermostat with by-pass; fan with 4 blades, 394 mm dia, cooling water capacity 11,5 l
Starting system:	Electrical LUCAS screw-push starter motor M50G-12V, 3 kW; CAV flame plug in intake pipe
Electrical equipment:	12 Volt BOSCH 3-phase alternator G1 14V 28A, 1 lead-acid battery 88 Ah at 20 hours rating

Transmission

Clutch:	FICHTEL UND SACHS AG dry dual disc clutch DUT 250/250 gearbox drive pedal operated, p.t.o. drive hand lever operated; both discs 250 mm dia
Gear box:	Own make speed change gear with 4 forward speeds and 1 reverse speed, reverse and 1st gear collar shifted, 2nd gear sliding gear shifted, 3rd and 4th gear synchronized; group gear with 2 groups L and H, L-group collar shifted, H-group sliding gear shifted; additional reduction gear with 2 groups RGL and RGH, collar shifted; totally 16 forward speeds and 4 reverse speeds
Rear axle and final drives:	MASSEY-FERGUSON S.A. bevel gear drive with crown wheel and pinion; bevel gear differential with lock, pedal operated, self disengaging; planetary final drives
Front axle:	Not propelled

Oil capacity: Gear box in common with
rear axle drive and hydraulic system 47 l
rear axle final drives each 2 l
screen filter with cleaning interval
600 hours

Oil changing interval: 600 hours

Recommended oil qualities: Final drives: Transmission oil SAE 90
MIL-L-2105 B

gear box: Multi-purpose
transmission oil SAE 20W/30
acc. to MF specif. M 1139

Total ratios and speeds see page 8

Power take-off Independent p.t.o.
at rear of tractor,
driven through the second disc of the dual disc clutch;
height above ground 563 mm, in tractor's median plane,
300 mm behind rear axle centre line;
2 interchangeable p.t.o. shafts for 540 rev/min and 1000 rev/min p.t.o. speeds;
by interchanging p.t.o.-stub-shafts correct speed ratio is selected:

540 rev/min p.t.o.
35 mm dia, 6 splines DIN 9611
and ISO 500 type 1;
599 rev/min at rated engine speed,
standard p.t.o. speed 540 rev/min at
1893 rev/min engine speed

1000 rev/min p.t.o.
35 mm dia, 21 splines DIN 9611
and ISO 500 type 2;
1105 rev/min at rated engine speed,
standard p.t.o. speed 1000 rev/min at
1900 rev/min engine speed

p.t.o. speeds may be set by aid of tractormeter;
direction of rotation clockwise,
viewed from tractor rear

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

Total ratios and speeds (tyres 16,9 R 30)

Group	Reduction gear	Gear	Total ratio engine : driving wheels	Nominal travelling speed *) at rated engine speed km/h
Forward speeds				
L	RGL	1	555,91	0,99
		2	379,03	1,45
		3	277,50	1,98
		4	206,74	2,66
	RGH	1	238,86	2,30
		2	162,86	3,38
		3	119,23	4,61
		4	88,83	6,19
H	RGL	1	138,98	3,96
		2	94,76	5,81
		3	69,38	7,93
		4	51,69	10,65
	RGH	1	59,71	9,21
		2	40,71	13,51
		3	29,81	18,46
		4	22,21	24,78
Reverse speeds				
L	RGL	R	408,19	1,35
	RGH	R	175,38	3,14
H	RGL	R	102,05	5,39
	RGH	R	43,85	12,55

*) calculated with the RADIUS INDEX 695 mm as per WdK 154

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

Power lift

Hydraulic system:

MASSEY-FERGUSON S.A.
hydraulic power lift in unit construction;
MF piston pump with 27 l/min delivery
at rated engine speed,
in gear box, driven by the disc of the p.t.o. clutch *);
MF control valve for lifting, lowering, draft control, position control and floating position;
top link sensing;
maximum oil pressure 222 bar;
1 single acting main cylinder with 85,6 mm bore and 120,7 mm stroke,
without overpressure relief valve;

MF gear-type pump for auxiliary hydraulic system,
34 l/min delivery at rated engine speed,
in gear box, driven by the disc of the p.t.o. clutch*);
up to 3 single or double acting additional control valves with oil tappings available; oil capacity 47 l in common with gear box; additional oil filter with changing interval 600 hours;
max. 13 l may be taken off through oil tappings when tractor is travelling,
15 l when tractor is working stationary

Implement linkage:

Three point linkage category II DIN 9674

lift rods adjustable from 630 to 740 mm;
lifting range above ground with
short lift rods from 425 to 1030 mm
long lift rods from 125 to 835 mm

*) both pumps stall during manipulation of the p.t.o. clutch hand lever

Holed bar:	Long bar, fitted on clevis of lower links; length between the joint balls 810 mm, width 80 mm, thickness 30 mm; centre hole and 2 holes on either side between the joint balls, 2 holes on either side outside the distance between the joint balls; totally 9 holes, all holes 33 mm diameter; height above ground adjustable by power lift in the range from 200 to 1105 mm, depending on lift rods length, measured at the surface of the bar; distance of holes centre line with lower links in horizontal position: from rear axle centre 943 mm from p.t.o. shaft end 643 mm

Pull attachment

Swinging drawbar:	Height above ground 430 or 480 mm, adjustable by turning drawbar; hitch hole 33 mm diameter; distance of hitch hole centre: from rear axle centre 700 mm from p.t.o. shaft end 400 mm pivot point 145 mm behind rear axle centre; drawbar lateral swingable about 280 mm to either side
Trailer hitch:	CRAMER height above ground adjustable by shifting to 765 mm and 874 mm, hitch hole 33 mm diameter; distance of hitch hole centre to rear axle centre 490 mm; permissible vertical load 1000 kg
Towing hitch:	710 mm above ground

Steering

ZAHNRADFABRIK FRIEDRICHSHAFEN AG
hydrostatic steering model 8450 with
own oil circuit;
PLESSEY gear type pump with 6 cm^3/rev
delivery,
directly driven by engine;
oil capacity 5 l,
transmission oil ATF type A;
oil changing once a year;
1 double acting ram with 57 mm bore
and 150 mm stroke
acting directly on front axle

Brakes

Parking brake: Mechanically acting on the discs of the service brake;
operated by hand lever with ratchet

Service brake: GIRLING
hydraulically acting wet disc brake with
3 lining discs on each differential
half shaft,
disc diameter 222 mm,
pedal operated

Steering brake: 2 additional hand levers on the left hand side of driver's seat, acting on the parking brake

Wheels

Steered wheels: 2 pneumatics at front 7,50-20 6 ply
maximum permissible load per tyre 875 kg
at 2,25 bar inflation pressure and 30 km/h;
track width adjustable in 5 steps from 1330 mm
to 1835 mm by extending telescopic half axles

rims 5.50 F x 20

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

Driving wheels:	2 pneumatics at rear 16,9 R 30 6 ply radial type tyre casing; maximum permissible load per tyre 1900 kg at 1,3 bar inflation pressure and 30 km/h; track width adjustable from 1430 to 2130 mm in steps of 100 mm each by turning wheels and offset lug type rims; rims W 14L x 30
Wheel base:	2285 mm
Safety frame	Own make OECD tested approval no. CSD 0016/2-a (F)
Seat	GRAMMER DS 85 H4 upholstered seat with back rest; adjustable spring with shock absorber; height of driver's platform above ground 785 mm; height of unloaded seat above platform adjustable to 3 positions: 485, 515 and 545 mm; for and aft adjustable about 150 mm

Number of grease points 21

Track setting during tests

front axle	1330 mm
rear axle	1430 mm

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

Dimensions

Total length:	3780 mm	without ballast
	3780 mm	with ballast
Total width:	1840 mm	without ballast
	2080 mm	with ballast
Total height:	2340 mm	to top of safety frame
Ground clearance:	375 mm	below swinging drawbar

Weights

Ready for use as tested, with safety frame

		without driver	with driver
Without ballast:	front	1030 kg	1040 kg
	rear	1820 kg	1895 kg
	total	2850 kg	2935 kg
Front ballast:	5 front weights	40 kg each	200 kg
Rear ballast:	2 weights per wheel	64 kg each	256 kg
	water in the tyres		484 kg
With ballast:	front	1250 kg	1260 kg
	rear	2540 kg	2615 kg
	total	3790 kg	3875 kg

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

Lighting equipment Electrical 12 Volt
as per German legislation

	Dimensions mm	Height above ground to centre mm	Distance from outside edge of tractor to centre mm
Head lights	145 x 90	1035	780
Side lights	70 x 20	1420	215
Rear lights	30 x 65	1435	270
Reflectors			
1st pair	130 x 40	1210	280
2nd pair	60 Ø	635	510

Permissible total weights and axle loads for all available wheel equipment

Wheel equipment front	Wheel equipment rear	Permissible total weight kg	Permissible axle load front kg	Permissible axle load rear kg
7,50 - 16	14,9 - 28 14,9 - 30	4000	1700	3000
7,50 - 18	16,9 - 30		1800	
6,50 - 20	12,4 - 36		1650	
	12,4 - 32			2880
7,50 - 20			1800	
	9,5 - 36			2410

All tyres 6 ply

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

FUELS AND LUBRICANTS USED IN TESTS

Fuel:	ARAL Diesel-fuel DIN 51601	
	specific gravity at 15°C:	
	at engine tests	0,836 kg/l
	at p.t.o. tests	0,826 kg/l
	at drawbar tests	0,826 kg/l
Engine:	ESSO ESSOLUBE HDX	SAE 20W/20
Transmission, rear axle and hydraulic:	ESSO multi purpose oil	20W/30
Rear axle final drives:	ESSO transmission oil	SAE 90
Steering:	OEST ATF oil type A	

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

COMPULSORY TESTS

(1) MAIN POWER TAKE-OFF PERFORMANCE (540 rev/min)

Date of tests: 29th March 1979
Type of dynamometer: SCHENCK hydraulic dynamometer U1-40

Power kW	Speed engine rev/min	Speed p.t.o. rev/min	Fuel consumption total l/h	Fuel consumption total kg/h	Fuel consumption specific g/kWh	Specific energy kWh/l
Maximum power						
At 2-hour test						
39.0	2100	599	13.03	10.77	276	2.99
At standard p.t.o. speed						
37.3	1893	540	12.18	10.06	270	3.06
At the speed recommended for drawbar work						
39.0	2100	599	13.03	10.77	276	2.99
Part loads, the governor hand lever in the position corresponding to the maximum power at full load						
(i) 85% of the torque at maximum power at 2-hour test						
33.8	2141	611	10.87	8.98	266	3.11
(ii) unloaded						
-	2226	635	3.33	2.75	-	-
(iii) 50% of the load defined in (i)						
17.3	2194	626	6.85	5.66	327	2.53
(iv) maximum power						
39.0	2100	599	13.03	10.77	276	2.99
(v) 25% of the load defined in (i)						
8.7	2208	630	5.07	4.19	481	1.72
(vi) 75% of the load defined in (i)						
25.8	2177	621	8.69	7.18	279	2.96

PRÜFUNGS-ABTEILUNG


EICHER 3355 Test No. 78-320

Power kW	Speed engine rev/min	Speed p.t.o. rev/min	Fuel consumption total l/h	Fuel consumption total kg/h	Fuel consumption specific g/kWh	Specific energy kWh/l
Part loads, the governor hand lever in the position corresponding to the standard p.t.o. speed at full load						
(i) 85% of the torque at maximum power at standard p.t.o. speed						
32.5	1939	553	10.21	8.43	260	3.18
(ii) unloaded						
-	2038	581	2.83	2.34	-	-
(iii) 50% of the load defined in (i)						
16.8	2007	573	6.27	5.18	308	2.68
(iv) maximum power						
37.3	1893	540	12.18	10.06	270	3.06
(v) 25% of the load defined in (i)						
8.5	2023	577	4.48	3.70	436	1.89
(vi) 75% of the load defined in (i)						
25.0	1990	567	8.04	6.64	265	3.11

Standard specific fuel consumption (g/kWh): 266/327/260/308

No load maximum engine speed: 2226 rev/min
Equivalent crankshaft torque at maximum power (2 hours): 177 Nm
Maximum equivalent crankshaft torque: 207 Nm at 1402 rev/min of the engine


Mean atmospheric conditions:	temperature	16 °C
	pressure	976 mbar
	relative humidity	55 %
Maximum temperatures:	coolant	82 °C
	engine oil	103 °C
	fuel	19 °C
	engine air intake	19 °C


Zapfwellenleistung
PTO performance
PRÜFUNGS-ABTEILUNG
EICHER 3355
Test No. 78-32o
Zapfwellenleistung P_e kW
PTO power
äquivalentes Drehmoment M equiv Nm
equiv. crankshaft torque
spez. Kraftstoffverbrauch be g/kWh
spec. fuel consumption
Motordrehzahl n engine speed U/min rev/min
M equiv
standard PTO speed
Kraftstoffverbrauchsmessung
fuel consumption
P
B
be

PRÜFUNGS-ABTEILUNG
EICHER 3355

Zapfwellenleistung
P.t.o. performance

Test Nr. 78-320



PRÜFUNGS-ABTEILUNG
EICHER 3355

(2) DRAWBAR PERFORMANCE

Date of tests: 21st till 28th January 1980
Type of track: Concrete

Gear No. and Group	Driving speed km/h	Power kW	Drawbar pull daN	Engine speed rev/min	Slip of wheels %
(i) MAXIMUM POWER with ballast height of drawbar above ground 530 mm					
1 L RGL	0,87	9,5	3924	2191	15,0
2 L RGL	1,26	13,8	3929	2181	15,1
3 L RGL	1,71	18,5	3891	2168	15,1
1 L RGH	1,99	21,6	3908	2161	15,0
4 L RGL	2,28	24,7	3909	2142	15,0
2 L RGH	2,84	30,8	3898	2112	14,9
1 H RGL	3,53	34,2	3495	2098	9,1
3 L RGH	4,21	35,0	2995	2100	7,0
2 H RGL	5,40	35,4	2360	2099	5,2
4 L RGH	5,79	35,1	2185	2099	4,7
3 H RGL	7,49	35,0	1683	2099	3,6
1 H RGH	8,73	35,0	1445	2102	3,1
4 H RGL	10,14	33,9	1202	2101	2,6
2 H RGH	12,91	33,7	941	2099	1,9
(ii) FIVE-HOUR-TEST at 75% of pull at maximum power in 3rd H RGL gear					
3 H RGL	7,71	27,0	1262	2141	2,7
(iii) FIVE-HOUR-TEST at pull corresponding to 15% wheel slip in test (i)					
2 L RGH	2,91	31,8	3929	2102	-
(iv) MAXIMUM POWER without ballast height of drawbar above ground 585 mm					
2 L RGH	2,87	24,7	3104	2145	15,0
1 H RGL	3,34	28,8	3100	2125	14,9
3 L RGH	3,89	32,9	3047	2099	13,9
2 H RGL	5,19	34,5	2396	2098	8,5
4 L RGH	5,57	34,5	2232	2099	7,8
3 H RGL	7,29	35,2	1737	2098	5,5
1 H RGH	8,58	35,8	1502	2097	4,2
4 H RGL	9,96	35,0	1264	2098	3,7
2 H RGH	12,78	34,8	981	2100	2,8

Total oil consumption during ten hours duration of tests (ii) and (iii) 8o g/h

PRÜFUNGS-ABTEILUNG

Test No. 78-320

Tyres size front: 7,50 - 20 6 ply
rear: 16,9 R 30 6 ply

Tread bar height at the beginning of drawbar tests 87 % of the value when new

Specific energy kWh/l	Specific fuel consumpt. g/kWh	Temperatures Fuel °C	Coolant °C	Engine-oil °C	Atmospheric conditions Tempe-rature °C	Relative humidity %	Pressure mbar
tyre inflation pressure o,8 bar							
1,62	515	6	79	80	-2	90	997
2,00	416	5	79	80	0	86	997
2,25	370	5	79	78	0	87	997
2,39	348	5	80	80	1	87	994
2,44	340	5	80	81	1	88	994
2,46	339	5	80	81	2	86	994
2,62	318	5	82	88	2	86	997
2,68	310	5	81	87	0	87	997
2,71	307	5	80	85	0	86	997
2,69	309	5	81	87	0	86	997
2,68	311	6	80	85	-2	90	997
2,68	310	5	80	83	2	87	993
2,59	321	5	80	84	1	87	993
2,58	322	5	80	84	1	84	993
2,68	310	13	82	89	6	79	989
-	-	14	83	92	8	81	987
tyre inflation pressure o,8 bar							
2,55	326	7	80	85	4	82	1009
2,51	330	10	80	80	0	87	1010
2,51	330	8	82	90	2	84	1010
2,66	312	8	82	90	2	84	1010
2,65	313	7	80	85	3	82	1008
2,69	309	7	80	83	4	82	1008
2,74	303	7	80	85	4	82	1008
2,67	311	8	80	85	4	80	1008
2,68	310	8	80	82	4	80	1008

Test (iii) was carried out with additional ballast, the figures not quoted are therefore irrelevant

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No.78-320

(3) TURNING SPACE AND TURNING CIRCLE

Wheel equipment front: 7,50 - 20 6 ply
rear: 16,9 R 30 6 ply

Track of wheels front: 1330 mm
rear: 1430 mm

	With brakes left-hand m	With brakes right-hand m	Without brakes left-hand m	Without brakes right-hand m
Radius of turning space	3,70	3,43	4,39	3,80
Radius of turning circle	3,54	3,27	4,23	3,64

(4) LOCATION OF CENTRE OF GRAVITY

Height above ground	834 mm
Distance forward from rear axle centre	809 mm
Distance from tractor's median plane	2 mm to the left

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

(5) BRAKING PERFORMANCE

A) SERVICE BRAKE

Date of tests: 24th and 25th January 1980
Type of track: Concrete
Type of decelerometer: MOTO-METER-Bremsverzögerungs- und Pedalkraftschreiber

Weight of ballasted tractor with driver 3875 kg

Cold brakes

		With ballast	Without ballast
Travelling speed	km/h	25,0	25,0
Deceleration	m/s^2	3,9	3,8
Stopping distance	m	7,6	7,6
Force on pedal	daN	33	28
Force on pedal to achieve a deceleration of 2,5 m/s^2	daN	23	16

Brake fade characteristics (hot tests)

Deceleration	hot/cold	%	100	100
Stopping distance	cold/hot	%	103	100
Force on pedal	cold/hot	%	173	122

B) PARKING BRAKE

Tractor facing up 16% slope
Pull on hand brake 23 daN, tractor does not roll

Tractor facing down 16% slope
Pull on hand brake 21 daN, tractor does not roll

PRÜFUNGS-ABTEILUNG

EICHER 3355

Test No. 78-320

(6) AMBIENT NOISE EMITTED BY THE TRACTOR

Date of test: 25th January 1980
Type of track: Concrete
Type of sound level meter: BRÜEL AND KJAER model 2209

Results of test

Gear: 4 H RGH
Travelling speed before acceleration: 18,8 km/h
Sound level: 87,0 dB (A)

(7) NOISE AT THE DRIVER'S EAR LEVEL

Date of tests: 29th January 1980
Type of track: Concrete
Type of sound level meter: BRÜEL AND KJAER model 2209

The tractor was fitted with EICHER safety frame

Results of tests

Gear	Drawbar pull at which the tractor develops the maximum sound level	Travelling speed nominal	Travelling speed effective	Sound level
	daN	km/h	km/h	dB(A)
1 L RGL	2876	0,99	0,82	93,0
2 L RGL	2829	1,45	1,16	93,5
3 L RGL	2817	1,98	1,64	94,0
1 L RGH	2961	2,30	1,85	93,5
4 L RGL	2740	2,66	2,26	95,5
2 L RGH	2906	3,38	2,66	94,5
1 H RGL	3102	3,96	3,35	97,0
3 L RGH	2899	4,61	3,92	97,0
2 H RGL	2301	5,81	5,29	97,5
4 L RGH	2213	6,19	5,59	97,5
3 H RGL *)	1661	7,93	7,39	98,0
1 H RGH	1463	9,21	8,62	98,0
4 H RGL	1204	10,65	10,03	97,5
2 H RGH	979	13,51	12,76	98,0
3 H RGH	649	18,46	17,66	98,0
4 H RGH	light load	24,78	25,12	93,5

*) The 3rd H RGL gear corresponds to the travelling speed nearest to 7,5 km/h

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

(8) HYDRAULIC PUMP PERFORMANCE AND POWER LIFT

Date of tests: 17th October and 1st November 1979

HYDRAULIC PUMP

Power lift circuit

(1)	Opening pressure of relief valve in power lift circuit	140 bar
	Sustained pressure by open relief valve	222 bar
(2)	Pump delivery rate at minimum pressure and rated engine speed	26,9 l/min
(3)	Pump delivery rate at max. hydraulic power	20,6 l/min
	corresponding delivery pressure	180 bar
	power	6,2 kW

Auxiliary hydraulic circuit


(1)	Opening pressure of relief valve in remote circuit	160 bar
	Sustained pressure by open relief valve	182 bar
(2)	Pump delivery rate at minimum pressure and rated engine speed	34,1 l/min
(3)	Pump delivery rate at max. hydraulic power	32,9 l/min
	corresponding delivery pressure	160 bar
	power	8,8 kW

PRÜFUNGS-ABTEILUNG
EICHER 3355

Test No. 78-320

POWER LIFT

Dimensions of linkage geometry for the table on page 27



alle Maße in mm
all dimensions in mm

LINKAGE GEOMETRY when connected to the standard frame	Maximum mechanical advantage	Minimum mechanical advantage
Projected length in side view:		
Lower links	975 mm	975 mm
Lift arms	295 mm	295 mm
Lift rods	630 mm	630 mm
Top link	766 mm	753 mm
Distance of lift rod connection point from pivot point of lower link	570 mm	570 mm
The following dimensions are given relative to rear axle centre line 695 mm above ground		
Lower link pivot point	32 mm forward, 212 mm below	32 mm forward, 212 mm below
Top link pivot point	186 mm behind, 205 mm above	200 mm behind, 171 mm above
Lift arm pivot point	196 mm forward, 232 mm above	196 mm forward, 232 mm above
Maximum and minimum height of lower link hitch points	335 mm above, 270 mm below	335 mm above, 270 mm below
Height of lower link hitch points above ground when locked in highest transport position	1030 mm	1030 mm

PRÜFUNGS-ABTEILUNG
EICHER 3355

LIFTING FORCES

Lifting heights relative to horizontal lower links

mm	-358	-300	-200	-100	-68	-63	-58	0	+100
at hitch points	maximum mechanical advantage								
daN							1800	1950	2080
	minimum mechanical advantage								
daN	1520	1580	1690	1770				1840	1860

Max. force exerted throughout the whole range 1800 daN

Front of tractor does not lift

at test frame	maximum mechanical advantage								
daN						1850		1850	1870
	minimum mechanical advantage								
daN					1770			1770	1770

Max. force exerted throughout the whole range 1460 daN

Front of tractor does not lift if front axle is ballasted to its maximum allowable load (1800 kg)

PRÜFUNGS-ABTEILUNG

Test No. 78-320

+200	+300	+352	+400	+500	+547	+600	+647	+692

lift rods 630 mm long

2120	2100		2080	2100	2140			

lift rods 740 mm long

1860	1880	1950						

lift rods 630 mm long, high top link pivot point

1830	1770		1680	1570		1510	1460	

lift rods 630 mm long, low top link pivot point

1720	1660		1570	1490		1400		1340

All values of forces for pressure 180 bar at maximum hydraulic power, see page 25; calculated from measurements at max. oil pressure 222 bar

PRÜFUNGS-ABTEILUNG

EICHER 3355

Test No. 78-320

OPTIONAL TESTS


(9) ENGINE PERFORMANCE

Date of tests: 23rd and 30th January 1979
Type of dynamometer: SCHENCK eddy-current dynamometer W 150


Power kW	Engine speed rev/min	Fuel consumption total l/h	Fuel consumption total kg/h	Fuel consumption specific g/kWh	Specific energy kWh/l
Maximum power					
At 2-hour test					
43.1	2100	12.95	10.83	251	3.33
At standard p.t.o. speed (540 rev/min)					
41.2	1893	12.21	10.20	248	3.37
At the speed recommended for drawbar work					
43.1	2100	12.95	10.83	251	3.33
Part loads					
(i) 85% of the torque at maximum power at 2-hour test					
37.4	2143	10.79	9.02	242	3.46
(ii) unloaded					
-	2222	2.90	2.42	-	-
(iii) 50% of the load defined in (i)					
19.1	2186	6.67	5.58	292	2.86
(iv) maximum power					
43.1	2100	12.95	10.83	251	3.33
(v) 25% of the load defined in (i)					
9.6	2210	4.77	3.99	414	2.02
(vi) 75% of the load defined in (i)					
28.3	2167	8.62	7.20	254	3.29


Optimum fuel consumption: 227 g/kWh at 23,3 kW and 1365 rev/min
No load maximum engine speed: 2222 rev/min
Torque at maximum power (2 hours): 196 Nm
Maximum torque: 227 Nm at 1399 rev/min of the engine

Mean atmospheric conditions:	temperature	17 °C
	pressure	990 mbar
	relative humidity	44 %
Maximum temperatures:	coolant	82 °C
	engine oil	93 °C
	fuel	18 °C
	engine air intake	18 °C


Motorleistung
Engine performance
Test Nr. 78-320
Pe
M
B
be
Kraftstoffverbrauch be g/kWh
spez. fuel consumption
Nm
Motordrehmoment
crankshaft torque
engine speed

ZICHER 3353 **Engine performance** Test Nr. 78-320




227 g/kWh
230
240
250
260
270
300
350
450
Motordrehzahl in % der Nenndrehzahl
engine speed in % of rated engine speed
Test Nr. 78 - 320

Published
with the support of the Federal Minister for Food, Agriculture and Forestry

Deutsche Landwirtschafts-Gesellschaft e.V. (DLG)
Fachbereich Landtechnik — Prüfungsabteilung —
Zimmerweg 16 (DLG-Haus)
D-6000 Frankfurt am Main 1