OECD APPROVAL NO. 2/2 169
CODE 2
DATE OF APPROVAL: 20 September 2004

NEBRASKA TRACTOR TEST LABORATORY
DEPARTMENT OF BIOLOGICAL SYSTEMS ENGINEERING
INSTITUTE OF AGRICULTURE AND NATURAL RESOURCES
UNIVERSITY OF NEBRASKA - EAST CAMPUS
LINCOLN, NEBRASKA 68583-0832, USA

REPORT ON TEST IN ACCORDANCE WITH OECD STANDARD CODE 2 FOR THE OFFICIAL TESTING OF AGRICULTURAL TRACTORS



John Deere 7720 PowrQuad-Plus
Mechanical Front Wheel Drive (MFWD)

MANUFACTURED BY:	**John Deere Tractor Works** **3500 East Donald Street** **Waterloo, IA 50704-0270**
NEBRASKA TEST NO.	**1833**
TEST DATES:	**February 17- April 21, 2004**

This test report provides the results of the tests conducted in accordance with the OECD Standard Test Code for the Official Testing of Agricultural Tractor Performance - C(87)53 Final, Code 2.

This report has been approved by the OECD Coordinating Centre in Paris on 20 September 2004 for the John Deere 7720 PowrQuad-Plus, Mechanical Front Wheel Drive (MFWD) tractor with OECD Number 2/2 169.

No reproduction of this report or any part of it can be made without prior approval by the Nebraska Tractor Test Laboratory, Lincoln, Nebraska USA.

Dr. Leonard L. Bashford, Director
Nebraska Tractor Test Laboratory and
Chair, Nebraska Tractor Test Board

David L. Morgan, Assistant Director
Nebraska Tractor Test Laboratory

Brent T. Sampson, Test Engineer
Nebraska Tractor Test Laboratory

Date: OCT 1 8 2004

TABLE OF CONTENTS

Page

1. **SPECIFICATIONS** 1

2. **TEST CONDITIONS** 16

3. **COMPULSORY TESTS**
   - **3.1** Main Power Take-Off Performance 19
   - **3.2** Hydraulic Power and Lifting Forces 21
   - **3.3** Drawbar Performance 23

4. **OPTIONAL TESTS**
   - **4.1** Drawbar Power (Ballasted-front drive disengaged-2100 rev/min) 24
   - **4.2** Drawbar Power (Ballasted-front drive engaged-1650 rev/min) 25
   - **4.3** Power Lift Test – Region II Linkage (2 x 100 mm cylinders) 26
   - **4.4** Power Lift Test – North American Linkage (2 x 90 mm cylinders) 27
   - **4.5** Power Lift Test – North American Linkage (2 x 100 mm cylinders) 28
   - **4.6** Measurement of External Noise Level 29
   - **4.7** Measurement of Noise Level at Operator's Ear 29

5. **REPAIRS** 29

6. **REMARKS** 29

7. **PTO PERFORMANCE CURVES** 30

SPECIMEN TEST REPORT

Note: Units shown below, which appear in ISO 1000:1992, shall be stated and followed by national units in parentheses, if necessary.

C[1]	- Tractors manufacturer's name and address:	John Deere Tractor Works 3500 East Donald St. P.O. Box 270 Waterloo, IA 50704-0270
D[1]	- Location of tractor assembly:	Same
D	- Submitted for test by:	The Manufacturer
C	- Selected for test by:	The Manufacturer in agreement with the Nebraska Tractor Test Laboratory
D	- Place of running-in:	John Deere Product Engineering Center, Waterloo, Iowa
D	- Duration of running-in (hours):	108 hours
C	- Location of test:	Nebraska Tractor Test Laboratory, Lincoln, Nebraska U.S.A.

1. SPECIFICATIONS OF TRACTOR

1.1 Identification

C	1.1.1	- Make of tractor (*):	John Deere
C		- Model (trade name):	7720
C		- Type: • *2 WD or 4 WD; rubber or steel tracks (if applicable); articulated 4 WD or articulated 4WD with twin (dual) wheels (if applicable)*	4WD

(*) *Possibly different from tractor manufacturer's name*

	1.1.2	Numbers	
D		- 1st Serial No. or prototype:	CONFIDENTIAL
C		- Serial No.:	*RW7720R010686*
	1.1.3	Other specifications (if applicable)	
D		- Model(s) for other countries:	N/A
C		- Transmission type or gears x ranges:	20 speed PowrQuad Plus (4 gears x 5 ranges)
C		- Speed version: • *30, 40, or 50 km/h*	40 km/h
D		- Manufacturer identification or Technical type number:	N/A

1. The information opposite each item shall be validated by the Testing Station. An item marked "C" indicates to the test report user that the information declared by the manufacturer has been checked; an item marked "D" that the manufacturer's declaration has been endorsed. For example, the make of the supercharging device is declared by the manufacturer and checked "C" as consistent with the tractor by the testing station, while the pressure of the supercharging device is simply declared "D" by the manufacturer. Testing station's markings show compliance with article 8 of Appendix 3 to the Decision.

	1.2	Engine	
C		- Make / Model / Type:	John Deere / 6068HRW54 / Diesel; 4-stroke; turbocharged, direct injection, air to air intercooled
C		- Serial No.:	*PE6068H315190*
	1.2.1	Cylinders	
C		- Number / disposition:	6 / inline, vertical
D		- Bore / Stroke (mm / mm):	106.5 x 127.0
D		- Capacity (cm^3):	6788
D		- Compression ratio:	17.0 : 1
D		- Arrangement of valves:	Overhead;4 valves per cylinder
D		- Cylinder liners (wet or dry):	Wet; replaceable
	1.2.2	Supercharging	
C		- Make / Model / Type:	Borg Warner / RE516963 / Exhaust gas driven
D		- Pressure (kPa):	131
	1.2.3	Fuel System	
C		- Fuel feed system:	Mechanical Transfer Pump
		- Make / Model / Type of fuel filter(s)	
C		. Primary:	Stanadyne / RE509032 / 2 micron multilayer water separating
C		. Secondary:	Stanadyne / RE517180 / 10 micron multilayer water separating
D		- Capacity of fuel tank (dm^3):	392; 358 w/RH door
C		- Make / Model / Type of injection pump:	Denso / HP3 / HPCR; electronic
C		- Serial No.:	05E 00441
		- Manufacturer's production setting of injection pump	
C		. Flow rate (rated engine speed and full load) (dm^3/h):	31.6 +/- 1.5
D		. Timing:	Variable
D		- Make / Model / Type of injectors:	Denso / RE507860 / HPCR Injection
D		- Injection pressure (MPa):	100
C		- Make / Model / Type of carburetor:	N/A
	1.2.4	Governor	
C		- Make / Model / Type:	John Deere / FOCUS / Electronic Control
C		- Governed range of engine speed from ____ to ____ (min^{-1} (rev/min)):	875 to 2200
C		- Rated engine speed (min^{-1} (rev/min)):	2100

	1.2.5	Air Cleaner	
		- Pre-cleaner	
C		. Make / Model / Type:	Donaldson / RE196946 / Stratotube precleaner with fan aspirator
C		. Location of air intake:	Under hood, front of tractor
		- Main cleaner	
		. Make / Model / Type	
C		- Primary:	Donaldson / RE196945 / PowerCore pleated paper
C		- Secondary:	Donaldson / RE181915 / PowerCore pleated paper
C		. Location of air intake (in case of no pre-cleaner):	Under hood, front of tractor
C		- Maintenance indicator:	Console mounted warning light and audible signal
	1.2.6	Lubrication system	
D		- Type of feed pump:	Full pressure, positive displacement
C		- Type of filter(s):	Full Flow
C		- Number of filter(s):	1 spin on
	1.2.7	Cooling system	
C		- Type of coolant:	Liquid
D		- Type of pump:	Centrifugal, belt driven
		- Specification of fan or blower	
C		. Number of fan blades:	8
C		. Fan diameter (mm):	660
D		- Coolant capacity (dm^3):	30
C		- Type of temperature control:	Two thermostats and variable speed fan
D		- Superpressure system (Kpa):	70 +/- 2
	1.2.8	Starting system	
C		- Make / Model / Type:	Denso / RE501298 / Solenoid engaged
D		- Starter motor power rating (kW):	4.0
C		- Cold starting aid:	Glow plug thermal assist
C		- Safety device:	Electrical lockout on gearshift lever
	1.2.9	Electrical system	
C		- Voltage (V):	12
		- Generator	
C		. Make / Model / Type:	Denso / RE186320 / Belt driven alternator with built-in regulator
D		. Power (kW):	2.1
		- Battery of accumulators	
C		. Number:	Two; 950 CCA, RC 180
D		. Rating (Ah at ____ hours):	154 Ah at 20 hours

1.2.10 Exhaust system

C	- Make / Model / Type:	Nelson / RE200884 / Expansion Chamber
C	- Location:	Vertical muffler, right front corner of cab

1.3 Transmission

1.3.1 Clutch (travel and power take-off / travel alone)

D	- Make / Model / Type:	John Deere / Multiple plate / Oil cooled
D	- Number of plates:	4 forward / 4 reverse
D	- Diameter of plates (mm):	225 forward; 295 reverse
C	- Method of operation:	Electro-Hydraulic; pedal actuated

1.3.2 Gear box

D	- Make / Model / Type:	John Deere / 40K PowrQuad Plus / Mechanical countershaft and planetary design
	- Description:	5 manually synchronized ranges and a 4 speed planetary gear set with multiple wet disc clutches and brake units

		Forward	Reverse
C	Number of ranges	5	5
C	Number of gears	4	4
C	Total of arrangements	20	20

D	- Available options:	30K, 16 speed PowrQuad Plus 40K, 20 speed AutoQuad Plus 50K, 20 speed AutoQuad Plus- (specialty market) 40K, Infinitely Variable Transmission 50K, Infinitely Variable Transmission- (specialty market)

1.3.3 Rear axle and final drives

D	- Make / Model / Type:	John Deere / AR188107 / Spiral bevel with pinion differential and inboard planetary reduction
	- Differential lock	
D	. Type:	Wet multi-plate
C	. Method of engagement:	Electro-hydraulic foot operated switch
C	. Method of disengagement:	Self disengaging with brake pedal operation

1.3.4 Front axle and final drives

D - Make / Model / Type: John Deere / AR182213 / Spiral bevel and pinion, differential and outboard planetary reduction

- Differential lock

D . Type: Limited slip

C . Method of engagement: Self-engaging

C . Method of disengagement: Self-disengaging

1.3.5 Total ratios and traveling speeds

	Gear No.	Group or range	Number of engine revolutions for one revolution of the driving wheels	Nominal traveling speed (*) at rated engine of 2100 min^{-1} (rev / min) km/h
	Forward			
C	1	A1	285.574	2.41
C	2	A2	237.165	2.90
C	3	A3	198.016	3.48
C	4	A4	161.646	4.26
C	5	B1	134.738	5.11
C	6	B2	111.898	6.16
C	7	B3	93.427	7.37
C	8	C1	84.664	8.14
C	9	B4	76.267	9.03
C	10	C2	70.312	9.80
C	11	C3	58.706	11.73
C	12	C4	47.923	14.37
C	13	D1	45.729	15.06
C	14	D2	37.977	18.14
C	15	D3	31.708	21.72
C	16	E1	30.867	22.31
C	17	D4	25.884	26.61
C	18	E2	25.635	26.87
C	19	E3	21.403	32.18
C	20	E4	17.472	39.42
	(*) Calculated with a tyre dynamic radius index of 870 mm (pneumatic tyred tractors only) (ISO 4251-1:1998)			

C - Number of revolutions of front wheels for one revolution of rear-wheels (For 4WD tractors only): 1.3247

Gear No.	Group or range	Number of engine revolutions for one revolution of the driving wheels	Nominal traveling speed (*) at rated engine of 2100 min^{-1} (rev / min) km/h
Reverse			
1	A1	-273.675	-2.52
2	A2	-227.283	-3.03
3	A3	-189.765	-3.63
4	A4	-154.910	-4.45
5	B1	-129.124	-5.33
6	B2	-107.235	-6.42
7	B3	-89.534	-7.69
8	C1	-81.137	-8.49
9	B4	-73.089	-9.42
10	C2	-67.383	-10.22
11	C3	-56.260	-12.24
12	C4	-45.926	-15.00
13	D1	-43.824	-15.72
14	D2	-36.395	-18.92
15	D3	-30.387	-22.67
16	E1	-29.581	-23.28
17	D4	-24.806	-27.77
18	E2	-24.567	-28.04
19	E3	-20.511	-33.58
20	E4	-16.744	-41.13
(*) Calculated with a tyre dynamic radius index of 870 mm (pneumatic tyred tractors only) (ISO 4251-1:1998)			

C - Number of revolutions of front wheels for one revolution of rear-wheels (For 4WD tractors only): 1.3247

1.4 Power take-off (PTO)

1.4.1 Main power take-off

C - Type (independent, semi-independent or not independent): Independent

C - Method of engagement (if necessary describe the type of clutch): Electro-hydraulically actuated multi-plate wet clutch operated by single hand switch

C - Number of shafts: One

C - Method of changing power take-off shaft ends and speeds: Reversible shaft; two (540/1000) or three speed lever optional (540/1000/1000E)

1.4.1.1	Power take-off proportional to engine speed		
	Power take-off at 540 min^{-1} (rev / min)		
C	- Location:	Rear of tractor; center plane	
C	- Diameter of power take-off shaft end (mm):	35	
C	- Number of splines: (Conformity to ISO 500:1991)	6; conforms to ISO 500 / 1991	
C	- Height above ground (mm):	750	
C	- Distance from the median plane of the tractor (mm):	0	
C	- Distance behind rear-wheel axis (mm):	687	
C	- PTO speed at rated engine speed (min^{-1} (rev/min)):	582	
C	- Engine speed at standard power take-off speed (min^{-1} (rev/min)):	1950	
C	- Ratio of rotation speeds (engine speed / p.t.o. speed):	3.611 : 1	
D	- Power restriction (kW):	None	
D	- Maximum torque transmissible (Nm):	None	
C	- Direction of rotation: (viewed from behind tractor)	Clockwise	
	Power take-off at 1000 min^{-1} (rev / min)		
C	- Location:	Rear of tractor, center plane	
C	- Diameter of power take-off shaft end (mm):	35	
C	- Number of splines: (Conformity to ISO 500:1991)	21; conforms to ISO 500 / 1991	
C	- Height above ground (mm):	750	
C	- Distance from the median plane of the tractor (mm):	0	
C	- Distance behind rear-wheel axis (mm):	687	
C	- PTO speed at rated engine speed (min^{-1} (rev/min)):	1077	
C	- Engine speed at standard power take-off speed (min^{-1} (rev/min)):	1950	
C	- Ratio of rotation speeds (engine speed / p.t.o. speed):	1.950 : 1	
D	- Power restriction (kW):	None	
D	- Maximum torque transmissible (Nm):	None	
C	- Direction of rotation: (viewed from behind tractor)	Clockwise	

	1.4.1.2	Power take-off proportional to ground speed	Not Available
	1.4.2	Optional power take-off	
C		- Give the same description as for the main PTO:	Not Available
	1.5	Hydraulic power lift	
C		- Make / Model / Type:	John Deere / N/A / Electro-hydraulic lower link sensing; variable mix of draft and position control; adjustable rate of drop
C		- Type of hydraulic system:	Closed center; pressure and flow compensated
C		- Type and number of cylinders (single or double acting):	Two external, single acting (90 mm or 100 mm)
C		- Type of linkage lock for transport:	Electro-hydraulic
D		- Relief valve pressure setting (tolerance) (MPa):	20.3 +/- 0.3
D		- Opening pressure of cylinder safety valve (if fitted) (MPa):	23.2
D		- Lift pump type:	Closed center, load sensing pressure-flow compensated axial piston pump with full flow charge pump
D		- Transmission between pump and engine:	Gear driven; transmission front housing
C		- Type and number of filters:	Synthetic spin on filter; one
C		- Site of oil reservoir:	Differential case housing
C		- Type, number, and location of tapping points:	ISO standard breakaway couplers / 3 standard with 4th optional and power beyond optional; rear of tractor, 5th and 6th optional mid-mount valves
D		- Maximum volume of oil available to external cylinders (dm^3):	50

1.6 Three point linkage




Figure 2.1
Lift Test – Linkage geometry




Figure 2.2
Lift Test – Linkage geometry

C	- Category: • *Conformity with categories 1, 2, 3, 4, 3N, or 4N of ISO 730-1:1994 + Cor.1:1995 and ISO 730-2:1979*	3 Specific Market Version Standard Lift
C	- Category adapter:	None

			Dimension or range	Settings used in test(s)
			mm	mm
C	Length of arms:	(A)	425	Same
C	Length of lower links:	(B)	1120	Same
	Distance of lift arm pivot point from rear wheel axis			
C	- horizontally:	(a)	230	Same
C	- vertically:	(b)	608	Same
C	Horizontal distance between the 2 lower link points:	(u)	529	Same
C	Horizontal distance between the 2 lift arm end points:	(v)	680	Same
C	Length of upper arm link:	(S)	from 630 to 810	760
	Distance of upper link pivot point from rear wheel axis			
C	- horizontally:	(c)	532/527/530	530
C	- vertically:	(d)	201/283/353	353
	Distance of lower link pivot point from rear wheel axis			
C	- horizontally:	(e)	180	Same
C	- vertically:	(f)	324	Same
C	Distance of lower link pivot points to lift rod pivot points on lower links:	(D)	688	Same
C	Length of lift rods:	(L)	From 910 to 1050	975
	Height of lower hitch points relative to the rear wheel axis			
C	- in low position:	(h)	530 - 780	675
C	- in high position:	(H)	33 - 244	120
C	Height above ground of lower hitch points when locked in transport position (*):		903 - 1114	1025
	(*) Assuring r = 870 Tyre dynamic radius index of ISO 4251-1:1998 (pneumatic tyred tractors only)			

Table 1.1.1

Dimensions of linkage geometry when connected to the standard frame

C	- Category:	3
	• *Conformity with categories 1, 2, 3, 4, 3N, or 4N of ISO 730-1:1994 + Cor.1:1995 and ISO 730-2:1979*	North American Version Standard Lift
C	- Category adapter:	None

			Dimension or range	Settings used in test(s)
			mm	mm
C	Length of arms:	(A)	425	Same
C	Length of lower links:	(B)	1023	Same
	Distance of lift arm pivot point from rear wheel axis			
C	- horizontally:	(a)	230	Same
C	- vertically:	(b)	608	Same
C	Horizontal distance between the 2 lower link points:	(u)	529	Same
C	Horizontal distance between the 2 lift arm end points:	(v)	680	Same
C	Length of upper arm link:	(S)	625 to 770	700
	Distance of upper link pivot point from rear wheel axis			
C	- horizontally:	(c)	523/520	523
C	- vertically:	(d)	190/120	190
	Distance of lower link pivot point from rear wheel axis			
C	- horizontally:	(e)	180	Same
C	- vertically:	(f)	324	Same
C	Distance of lower link pivot points to lift rod pivot points on lower links:	(D)	617	Same
C	Length of lift rods:	(L)	910 to 1050	940
	Height of lower hitch points relative to the rear wheel axis			
C	- in low position:	(h)	559 to 804	640
C	- in high position:	(H)	11 to 228	154
C	Height above ground of lower hitch points when locked in transport position (*):		881 to 1098	1028
	(*) Assuring r = 870 Tyre dynamic radius index of ISO 4251-1:1998 (pneumatic tyred tractors only)			

Table 1.1.2

Dimensions of linkage geometry when connected to the standard frame

- Category: 3
  - *Conformity with categories 1, 2, 3, 4, 3N, or 4N of ISO 730-1:1994 + Cor.1:1995 and ISO 730-2:1979* North American Version Optional High Lift
- Category adapter: 3/3N

		Dimension or range	Settings used in test(s)
		mm	mm
Length of arms:	(A)	425	Same
Length of lower links:	(B)	1024	Same
Distance of lift arm pivot point from rear wheel axis			
- horizontally:	(a)	230	Same
- vertically:	(b)	608	Same
Horizontal distance between the 2 lower link points:	(u)	529	Same
Horizontal distance between the 2 lift arm end points:	(v)	680	Same
Length of upper arm link:	(S)	660 to 825	670
Distance of upper link pivot point from rear wheel axis			
- horizontally:	(c)	523/520	523
- vertically:	(d)	190/120	190
Distance of lower link pivot point from rear wheel axis			
- horizontally:	(e)	180	Same
- vertically:	(f)	315	Same
Distance of lower link pivot points to lift rod pivot points on lower links:	(D)	688.5	Same
Length of lift rods:	(L)	910 to 1050	990
Height of lower hitch points relative to the rear wheel axis			
- in low position:	(h)	523 to 748	675
- in high position:	(H)	7 to 218	75
Height above ground of lower hitch points when locked in transport position (*):		912 to 1123	980
(*) Assuring r = 905 Tyre dynamic radius index of ISO 4251-1:1998 (pneumatic tyred tractors only)			

Table 1.1

Dimensions of linkage geometry when connected to the standard frame

	1.7	Swinging drawbar	
C		- Type:	Oscillating
		- Height above ground	
C		. Minimum (mm):	462; offset down
C		. Maximum (mm):	526; offset up
C		- Type of adjustment:	Offset drawbar
		- Distance of hitch point from rear wheel axis	
C		. Horizontally (mm):	936, 1036, 1086
		- Distance of hitch point from power take-off shaft end	
C		. Horizontally (mm):	249, 349, 399
C		. Vertically (mm):	289.4
C		- Lateral adjustment (center of clevis)	
C		. Left hand (mm):	200
C		. Right hand (mm):	200
		- Distance of pivot point from rear wheel axis	
C		. Horizontally (mm):	14
C		- Diameter of drawbar pinhole (mm):	33
D		- Maximum vertical permissible load (kN):	14 kN PTO Position 22.2 kN Short Position
	1.8	**Trailer hitch**	Not Available
	1.9	**Holed drawbar**	Not Available
	1.10	Steering	
D		- Make / Model / Type:	Danfoss / RE186401 / Hydrostatic
		- Method of operation	
D		. Pump(s):	Same as main hydraulic pump
D		. Rams(s):	Integrated symmetrical design
D		- Working pressure (MPa):	17.5
	1.11	**Brakes**	
	1.11.1	Service brake	
D		- Make / Model / Type:	Vickers / RE221206 / John Deere Oil immersed
C		- Method of operation:	Hydraulic, operated by two pedals which can be locked together
C		- Trailer braking take-off (hydraulic or air brakes):	Optional air or hydraulic (not installed)
	1.11.2	Parking brake	
C		- Type:	Transmission lock
C		- Method of operation:	Gear selector lever

1.12 Wheels

- Number

C . Front (driving / steering): Two; driving and steering

C . Rear (driving / steering): Two; Driving

C - Wheelbase (mm): MFWD - 2860

- Track width adjustment:

		Minimum mm	Maximum mm	Adjustment method
D	Front	1524	2235	Reversing wheels and offset lug rims
D	Rear	1524	2774	Rack and pinion axle; reversing wheels and offset lug rims

1.13 Protective structure

C - Make / Model / Type: John Deere / SG093 / Cab

C - Manufacturer's name and address: John Deere Waterloo Works Waterloo, Iowa, USA

- Protective device

C . Cab / frame / rollguard / other: Cab

C . Tiltable / not tiltable: Not tiltable

- OECD approval

C . approval number: 4/0 784

C . Date of approval: 31 July 2003

C . Nos. of minor modification certificates, if any: None

1.14 Seat(s)

1.14.1 Driver's seat

C - Make / Model / Type: Sears Manufacturing / Comfort Command / air cushion suspension

C - Seat and steering wheel reversible: Yes / No: No

C - Type of suspension: Air ride

C - Type of damping: Adjustable viscous damping

- Range of adjustment

C . Longitudinally (mm): 178

C . Vertically (mm): 172

C - Safety belt: Yes

. Type: 2 point, fully retractable

	1.14.2.	Optional driver's seat(s)	
	1.14.2.1	Option 1	
D		- Make / Model / Type	John Deere/ Sears Manufacturing/ John Deere Active Seat
D		- Type of suspension:	Air/Hydraulic
D		- Type of damping:	Active position control
		- Range of adjustment	
D		. Longitudinally (mm):	178
D		. Vertically (mm):	172; (87 mm adjustment range)
	1.14.2.2	Option 2	
D		- Make / Model / Type	John Deere/ Sears Manufacturing/ John Deere Personal Posture™
D		- Type of suspension:	Air Ride
D		- Type of damping:	Adjustable, viscous damping
		- Range of adjustment	
D		. Longitudinally (mm):	200
D		. Vertically (mm):	140
	1.14.3	Passenger seat	
C		- Location:	Optional Instruction seat located left of driver's seat
C		- Capacity (number)	One

1.15 Lighting

		Height above ground of centre	Size	Distance from outside edge of lights to median plane of tractor
		mm	mm	mm
C	Headlights			
C	Inner	1535	180 x 120	170
C	Outer	1535	160 x 115	330
C	Sidelights			
C	Midbody	2145	160 x 110	620
C	Rearlights			
C	Roof	2920	160 x 110	405
C	Fender	2140	160 x 110	843
C	Reflectors			
C	Front (Wrap around)	3010	82 x 240	770
C	Rear (Wrap around)	3020	82 x 240	770
C	Brake	1950	210 x 95	910
C	Extremity	2170	140 x 72	1792

2. TEST CONDITIONS

Separate tables may be added to report other test conditions or equipments.

2.1 Overall dimensions

	Length	Width		Height at top of:	
		minimum	maximum	protective structure	exhaust pipe
	mm	mm	mm	mm	mm
Ballasted	5664	2800	3656	3072	3090
Unballasted	5245	2800	3254	3072	3090

2.2 Ground clearance (unballasted tractor)

(mm): 355

- Clearance – limiting part: Hitch Sway Blocks

2.3 Tractor mass

- Mass (with or without frame / roll guard / cab / other:

	Unballasted		Ballasted	
	With driver	Without driver	With driver	Without driver
	kg	kg	kg	kg
Front	2803	2783	3152	3133
Rear	4749	4694	6019	5964
Total	7552	7477	9171	9097

Ballast Added	Number of Weights	Total Mass	Liquid
		kg	kg
Front (weights)	4	181	None
Front (weight support	1	71	None
Rear (weights)	2	185	None
Rear (weights)	2	443	None
Rear (duals)	2	739	None

2.4 Track specifications

Not Applicable

2.5 Tyres and track specifications

	Front	Rear
Tyres		
- dimensions:	Goodyear 380/85R30	Goodyear 480/80R42
- ply rating:	135 A8	151 A8
- type:	Radial	Radial
- maximum load (tyre manufacturer's) (kN):	21.37	33.83
- maximum load (tractor manufacturer's) (kN):	Same	Same
- inflation pressure (tyre manufacturer's) (kPa):	From 60 to 160	From 60 to 160
- dynamic radius index (mm):	665	870
Chosen track width (mm):		
- unballasted:	1842	1651
- ballasted (inner):	1842	1651
- ballasted (outer):	None	3019

2.6 Fuel

- Type: No. 2 diesel in conformity with national standard
- Density at 15° C: 0.841 g/cm^3

2.7 Oil and lubricants

2.7.1 Capacity and change interval

	Capacity	Oil Change	Filter change
	Dm^3	h	h
Engine	26	250 (500 with John Deere PLUS-50 and John Deere filter)	Same
Gear Box	108	1500	750
Front Axle	14.4	1500	Not applicable
Rear Axle	Common w/gearbox	1500	Common w/gearbox
Final Drive (front)	1.9	1500	Not Applicable
Final Drive (rear)	Common w/gearbox	1500	Common w/gearbox
Hydraulic System (*)	Common w/gearbox	1500	750
Other (steering, ___)	NA	NA	NA
(*) State if common with gear box and rear axle.			

2.7.2 Specifications (SAE, API, CCMC, ACEA, Mil.L, ISO)

	Recommended	Used during test
Engine oil		
. Type:	John Deere; Torq-Gard Supreme SAE 5W30: PLUS-50 SAE 15W40 or 0W40	John Deere; Torq-Gard Supreme SAE 15W40
. Viscosity:	12.5 - 16.3 cSt @ 100 C	12.5 - 16.3 cSt @ 100 C
. Classifications:	API CF-4; CH - 4; ACEA E2	Same
Transmission oils		
. Type:	John Deere HY-GARD; J20C SAE 10W-30	Same
. Viscosity:	58 cSt at 43 C	Same
. Classifications:	NA	NA
Hydraulic fluid		
. Type:	Same as transmission	Same
. Viscosity:		
. Classifications:		
Steering oil		
. Type:	Same as transmission	Same
. Viscosity:		
. Classifications:		

2.7.3 Grease

- Number of lubrication points: 19 (27 w/ TLS II)

3. COMPULSORY TESTS RESULTS

3.1 Main power take-off

- Date and location of tests: 30-Mar-04 Nebraska Tractor Test Laboratory, Lincoln, NE, USA
- Type of dynamometer bench: Eaton

	Speed			Fuel consumption			Specific
Power	Engine	PTO	Fan	Hourly		Specific	energy
kW	rev/min			kg/h	l/h	g/kWh	kW-h/l
3.1 MAXIMUM POWER - TWO HOUR TEST							
119.16	1650	846	1166	26.95	32.08	227	3.71
3.1.2 POWER AT RATED ENGINE SPEED							
105.81	2099	1076	1302	25.92	30.86	245	3.43
3.1.3 STANDARD POWER TAKE-OFF SPEED (1000 +/- 25 rev/min)							
112.29	1951	1000	1304	26.31	31.32	235	3.59
3.1.4 PART LOADS							
3.1.4.1 the torque corresponding to maximum power at rated engine speed							
105.81	2099	1076	1302	25.92	30.86	245	3.43
3.1.4.2 85% of torque obtained in 3.1.4.1							
92.40	2154	1104	1299	23.78	28.31	258	3.26
3.1.4.3 75% of torque defined in 3.1.4.2							
69.61	2161	1108	1320	19.70	23.45	283	2.97
3.1.4.4 50% of torque defined in 3.1.4.2							
46.70	2174	1115	1195	15.35	18.28	329	2.56
3.1.4.5 25% of torque defined in 3.1.4.2							
23.43	2184	1119	1137	11.28	13.42	482	1.75
3.1.4.6 unloaded							
0.80	2194	1125	1089	7.06	8.41	8860	0.09
3.1.5 PART LOADS AT STANDARD POWER TAKE-OFF SPEED (1000 +/- 25 rev/min)							
3.1.5.1 the torque corresponding to maximum power							
112.29	1951	1000	1304	26.31	31.32	235	3.59
3.1.5.2 85% of torque obtained in 3.1.5.1							
98.16	2005	1028	1184	23.68	28.14	241	3.49
3.1.5.3 75% of torque defined in 3.1.5.2							
73.99	2014	1032	1191	19.32	22.97	261	3.22
3.1.5.4 50% of torque defined in 3.1.5.2							
49.56	2032	1042	1201	14.97	17.79	302	2.79
3.1.5.5 25% of torque defined in 3.1.5.2							
24.91	2041	1046	1137	10.75	12.78	432	1.95
3.1.5.6 unloaded							
0.75	2051	1052	1106	6.26	7.44	8382	0.10

- No load maximum engine speed: 2194 rev/min
- Torque (equivalent crankshaft) at rated speed:
  - At rated engine speed 481 Nm
  - At 2-hour test 690 Nm
- Maximum torque (equivalent crankshaft): 757 Nm
  (engine speed: 1402 rev/min)

Mean atmospheric conditions:			
Dry bulb		24	°C
Pressure		98.8	kPa
Relative Humidity		48	%
Maximum temperatures:			
Coolant		98	°C
Engine oil		101	°C
Fuel		47	°C
Engine air intake		32	°C

3. COMPULSORY TESTS RESULTS (OPTIONAL PTO PART LOAD TEST)

3.1 Main power take-off

- Date and location of tests: 30-Mar-04 Nebraska Tractor Test Laboratory, Lincoln, NE, USA
- Type of dynamometer bench: Eaton

Power	Speed			Fuel consumption			Specific energy
				Hourly		Specific	
kW	Engine	PTO	Fan	kg/h	l/h	g/kWh	kW-h/l
3.1.6 PART LOADS AT DIFFERENT ENGINE SPEEDS							
3.1.6.1 maximum power at rated engine speed							
105.81	2099	1076	1302	25.92	30.86	245	3.43
3.1.6.2 80% of power obtained in 3.1.6.1 at max speed setting							
85.23	2157	1106	1107	22.32	26.53	262	3.21
3.1.6.3 80% of power obtained in 3.1.6.1 with governor control set to 90% of rated engine speed							
85.04	1892	970	1197	20.68	24.59	243	3.46
3.1.6.4 40% of power obtained in 3.1.6.1 with governor control set to 90% of rated engine speed							
42.69	1892	970	1100	13.06	15.53	306	2.75
3.1.6.5 60% of power obtained in 3.1.6.1 with governor control set to 60% of rated engine speed							
63.67	1265	648	989	14.83	17.63	233	3.61
3.1.6.6 40% of power obtained in 3.1.6.1 with governor control set to 60% of rated engine speed							
42.85	1265	649	967	11.02	13.10	257	3.27

3.2 HYDRAULIC POWER AND LIFTING FORCE

3.2.1 Hydraulic Power Test

Date of Test: 09-Apr-04 Location of Test-City-State: Tractor Test Lab, Lincoln, NE, USA
Tractor Model: JD 7720 Tapping point used for test: Remote hydraulic outlets

3.2.1.1 Hydraulic Fluid Characteristics

Found in: **2.7.2 Specifications**

3.2.1.2 Compulsory Report(Test Results):

	Pressure	Reservoir oil Temperature	Engine Speed	Flow Rate	Power
	MPa	°C	rev/min^{-1}	l/min	kW
Rated Engine Speed: (Manufactures Specification)			2100		
Maximum (sustained) pressure with relief valve open as measured at the coupler Pump stalled: Yes	19.66	67	2197		
Flow rate corresponding to a hydraulic pressure equivalent to 90 percent of the actual relief valve pressure setting and corresponding hydraulic power through two coupler pairs:	17.57	63	2178	114.2	33.4
Maximum available flow from one coupler pair:	4.26	64	2186	126.1	8.9
Maximum available power from one coupler pair:	14.57	66	2177	119.4	29.0
Maximum available flow from coupler pairs operating simultaneously (flow through two or more coupler pairs if required):	1.73	60	2193	126.8	3.7
Maximum power from coupler pairs operating simultaneously (flow through two or more coupler pairs if required):	17.22	62	2177	121.6	34.9

3.2 POWER LIFT TEST Category III, S.M. lower links with lifting cylinders (2) x 90 mm dia..
Date of test: 17 Feb 2004.

	Hitch points	Frame
Lower hitch points above ground - down position:	230 mm	246 mm
Vertical movement - without load:	795 mm	836 mm
with load:	748 mm	781 mm
Maximum corrected force exerted through full range:	55.2 kN	60.6 kN
Corresponding pressure:	18.5 MPa	18.5 MPa
Moment about rear axle:	71.8 kNm	115.8 kNm
Maximum mast tilt angle	--	4.6 deg

Lifting height relative to horizontal position of lower links.

mm	-347	-331	-297	-200	-97	3	100	200	301	401	450
Corrected lift forces											
At the Hitch point kN	55.2	--	58.2	62.8	66.4	69.1	71.3	72.7	74.2	76.1	--
at the frame kN	--	61.9	62.9	64.7	65.6	65.9	65.7	64.6	62.9	61.4	60.6
Corresponding pressure 18.5 Mpa											

Date of tests: 05,06-Apr-2004 | Fuel density: 0.841 kg/l

Type of tract Concrete | Test number: 1833

3.3.1 Maximum power in tested gears (unballasted, 4wd) | Tire pressure: 110 kPa, rear 117 kPa, fron | Drawbar Height 495 mm

Gear Number and range	Power	Drawbar pull	Speed	Engine speed	Slip of wheels and/or tracks	Fan speed	Fuel		Temperature			Atmospheric conditions		
							Specific fuel consumption	Specific energy	Fuel	Coolant	Oil	Temperature	Relative humidity	Pressure
	kW	kN	km/h	min^{-1}	%	min^{-1}	kg/kW.h	kW.h/l	°C	°C	°C	°C	%	kPa
*A3	62.99	72.59	3.12	2161	13.6	1092	0.330	2.55	40	83	85	12	77	97.5
*A4	78.61	73.13	3.87	2152	12.3	1080	0.314	2.68	39	84	86	9	69	97.5
B1	91.41	70.47	4.67	2095	9.4	1091	0.282	2.98	39	85	86	12	83	97.4
B2	99.59	68.04	5.27	1928	7.8	1047	0.264	3.19	42	86	89	14	73	97.5
B3	105.72	65.79	5.78	1745	6.6	1068	0.263	3.20	42	90	92	15	59	97.7
C1	106.86	63.35	6.07	1649	5.9	1050	0.253	3.33	41	89	91	14	54	97.7
B4	107.40	56.58	6.83	1646	4.5	1048	0.251	3.35	41	89	91	13	52	97.7
C2	107.49	52.08	7.43	1645	4.3	1060	0.252	3.34	41	89	91	16	55	97.7
C3	108.14	43.30	8.99	1645	3.2	1071	0.249	3.38	43	92	94	17	49	97.7
C4	105.64	34.18	11.13	1648	2.4	1146	0.256	3.29	42	92	95	18	49	97.7
D1	106.85	32.97	11.66	1646	2.3	1073	0.252	3.34	41	91	92	18	50	97.7
D2	104.53	26.78	14.05	1640	1.7	1128	0.258	3.26	43	94	96	18	50	97.7

* Note: Slip within operating procedures of testing station.

3.3.2 Fuel consumption

3.3.2.1		In selected gear at maximum power at rated engine speed.												
C3	94.06	29.17	11.61	2097	2.0	1182	0.274	3.07	42	92	96	17	49	97.7
3.3.2.1.1		75% of pull at maximum power at rated engine speed												
C3	72.90	21.87	12.00	2153	1.3	1149	0.306	2.75	39	86	84	21	49	97.6
3.3.2.1.2		50% of pull at maximum power at rated engine speed												
C3	49.33	14.61	12.16	2168	0.7	1168	0.374	2.25	41	84	88	21	49	97.5
3.3.2.1.3		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.1												
C4	73.17	21.88	12.04	1763	1.3		0.289	2.91	41	86	87	21	50	97.5
3.3.2.1.4		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.2												
C4	49.24	14.56	12.18	1772	0.7	1131	0.339	2.48	41	84	85	21	50	97.5
3.3.2.1.5		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.1												
D1	73.37	21.87	12.08	1687	1.3	1057	0.275	3.06	40	85	84	21	50	97.5
3.3.2.1.6		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.2												
D1	49.48	14.55	12.25	1700	0.7	1066	0.336	2.51	41	84	84	21	50	97.5
3.3.2.2		In selected gear nearest to 7.5 km/h at rated engine speed.												
B3	96.25	48.43	7.16	2095	3.7	1096	0.269	3.13	42	87	90	15	55	97.7
3.3.2.2.1		75% of pull at maximum power at rated engine speed												
B3	75.34	36.36	7.46	2157	2.5	1110	0.298	2.82	41	87	90	20	48	97.7
3.3.2.2.2		50% of pull at maximum power at rated engine speed												
B3	50.99	24.19	7.59	2171	1.5	1123	0.350	2.40	41	84	88	20	48	97.7
3.3.2.2.3		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.2.1												
C1	75.53	36.35	7.48	1959	2.5	1090	0.285	2.96	40	86	88	20	48	97.6
3.3.2.2.4		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.2.2												
C1	50.82	24.22	7.55	1958	1.5	1142	0.323	2.60	41	83	85	20	48	97.6
3.3.2.2.5		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.2.1												
C2	75.36	36.33	7.47	1624	2.5	1118	0.274	3.07	41	86	84	21	49	97.6
3.3.2.2.6		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.2.2												
C2	51.18	24.22	7.61	1638	1.5	1105	0.306	2.75	41	83	83	21	49	97.6

OECD Drawbar Data (SI)

Date of tests:	7,8,13-Apr-04					**Fuel density:**	0.841 kg/l							
Type of track:	Concrete					**Test number:**	1833							
4.1 Maximum power in tested gears (ballasted, front drive disengaged)						**Tire pressure:**	110 kPa, rear		117 kPa, front			**Drawbar Height**	521 mm	
Gear Number and range	**Power**	**Drawbar pull**	**Speed**	**Engine speed**	**Slip of wheels and/or tracks**	**Fan speed**	**Fuel**		**Temperature**			**Atmospheric conditions**		
							Specific fuel consumption	**Specific energy**	**Fuel**	**Coolant**	**Oil**	**Temperature**	**Relative humidity**	**Pressure**
	kW	kN	km/h	min^{-1}	%	min^{-1}	kg/kW.h	kW.h/l	°C	°C	°C	°C	%	kPa
*A4	82.64	76.46	3.89	2149	10.8	1097	0.309	2.72	35	84	85	8	66	97.4
B1	92.34	69.13	4.81	2112	6.6	1092	0.280	3.01	39	86	89	16	61	97.2
B2	94.62	57.61	5.91	2098	4.0	1127	0.275	3.06	41	88	92	18	58	97.2
B3	96.39	48.55	7.15	2098	3.0	1158	0.269	3.13	36	84	77	19	59	97.2
C1	95.41	43.34	7.93	2100	2.6	1171	0.273	3,08	41	88	92	21	57	97.1
B4	93.25	38.03	8.83	2098	2.3	1198	0.278	3.03	42	90	94	20	64	97.2
C2	94.16	35.35	9.59	2097	2.0	1238	0.276	3.05	43	91	95	22	54	97.1
C3	94.25	29.39	11.54	2097	1.6	1223	0.275	3.06	43	90	93	22	54	97.1
C4	90.45	23.02	14.14	2088	1.1	1275	0.291	2.89	44	92	96	23	55	97.1
* Note: Slip within operating limits of test station														
3.3.2 Fuel consumption														
3.3.2.1		In selected gear at maximum power at rated engine speed.												
B3	96.39	48.55	7.15	2098	3.0	1158	0.269	3.13	36	84	77	19	59	97.2
3.3.2.1.1		75% of pull at maximum power at rated engine speed												
B3	74.22	36.12	7.40	2154	2.2	1103	0.297	2.83	43	86	89	15	55	98.1
3.3.2.1.2		50% of pull at maximum power at rated engine speed												
B3	50.29	24.16	7.49	2165	1.5	1110	0.357	2.36	41	83	86	16	51	98.1
3.3.2.1.3		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.1												
C2	74.51	36.22	7.41	1622	2.2		0.277	3.04	40	85	83	16	52	98.1
3.3.2.1.4		Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.2												
C2	50.54	24.18	7.52	1636	1.5	1033	0.310	2.71	40	82	80	17	48	98.1

OECD Drawbar Data (SI)

Date of tests:	7,8,13-Apr-04					**Fuel density:**	0.841 kg/l							
Type of track:	Concrete					**Test number:**	1833							
4.2 Maximum power in tested gears (ballasted, 4wd)							**Tire pressure:**	110 kPa, rear		117 kPa, front		**Drawbar Height:**	521 mm	
Gear Number and range	**Power**	**Drawbar pull**	**Speed**	**Engine speed**	**Slip of wheels and/or tracks**	**Fan speed**	**Fuel**		**Temperature**			**Atmospheric conditions**		
							Specific fuel consumption	**Specific energy**	**Fuel**	**Coolant**	**Oil**	**Temperature**	**Relative humidity**	**Pressure**
	kW	kN	km/h	min^{-1}	%	min^{-1}	kg/kW.h	kW.h/l	°C	°C	°C	°C	%	kPa
*A3	83.38	91.65	3.28	2149	8.6	1109	0.296	2.84	33	83	80	6	63	97.4
A4	93.96	86.90	3.89	2053	7.2	1080	0.281	3.00	39	86	88	14	69	97.2
B1	102.37	84.48	4.36	1906	6.6	1079	0.264	3.19	40	87	90	17	57	97.2
B2	105.53	83.53	4.55	1649	6.5	1110	0.262	3.21	42	89	92	18	59	97.2
B3	108.56	69.99	5.58	1648	4.1	1129	0.254	3.31	42	90	92	19	60	97.2
C1	108.56	62.99	6.20	1649	3.5	1137	0.254	3.32	43	92	95	22	58	97.1
B4	108.08	56.19	6.92	1648	2.9	1173	0.256	3.29	42	91	94	21	61	97.1
C2	107.41	51.34	7.53	1647	2.6	1237	0.255	3.30	44	91	94	22	54	97.1
C3	107.69	42.68	9.08	1650	2.1	1244	0.255	3.30	44	92	95	23	55	97.1
C4	105.43	34.00	11.16	1645	1.5	1329	0.252	3.33	44	92	95	23	52	97.1
D1	106.15	32.59	11.73	1648	1.4	1157	0.253	3.32	45	94	95	23	52	97.1
D2	104.22	26.58	14.12	1641	1.0	1192	0.266	3.16	45	95	97	24	49	97.1

* Note: Within operating limits of test station

4.3 POWER LIFT TEST Category III, S.M. lower links with lifting cylinders (2) x 100 mm dia..
Date of test: 17 Feb 2004.

	Hitch points	Frame
Lower hitch points above ground - down position:	230 mm	236 mm
Vertical movement - without load:	795 mm	847 mm
with load:	748 mm	781 mm
Maximum corrected force exerted through full range:	69.6 kN	75.1 kN
Corresponding pressure:	18.5 MPa	18.5 MPa
Moment about rear axle:	90.5 kNm	143.3 kNm
Maximum mast tilt angle	--	3.7 deg

Lifting height relative to horizontal position of lower links.

mm	-347	-341	-298	-199	-99	3	101	202	302	401	440
Corrected lift forces											
At the Hitch point kN	69.6	--	72.9	78.5	82.5	86.0	88.5	90.8	92.6	94.6	--
at the frame kN	--	77.7	78.9	80.8	81.8	82.1	81.7	80.1	78.1	75.8	75.1

Corresponding pressure 18.5 Mpa

4.4 POWER LIFT TEST Category III, Quick attaching coupler and lifting cylinders (2) x 90 mm dia..
Date of test: 17 Feb 2004.

	Hitch points	Frame
Lower hitch points above ground - down position:	234 mm	169 mm
Vertical movement - without load:	794 mm	1077 mm
with load:	744 mm	971 mm
Maximum corrected force exerted through full range:	54.3 kN	45.0 kN
Corresponding pressure:	18.4 MPa	18.4 MPa
Moment about rear axle:	65.4 kNm	81.6 kNm
Maximum mast tilt angle	--	15.4 deg

Lifting height relative to horizontal position of lower links.

mm		-378	-313	-299	-199	-98	2	100	200	302	431	593
Corrected lift forces												
At the Hitch point	kN	--	54.3	55.1	60.0	63.6	67.0	68.8	70.6	72.5	74.8	--
at the frame	kN	47.3	47.9	50.7	–	52.3	52.8	52.4	51.1	–	48.1	45.0
Corresponding pressure	18.4 Mpa											

4.5 POWER LIFT TEST Category III, Quick attaching coupler and lifting cylinders (2) x 100 mm dia..
Date of test: 17 Feb 2004.

	Hitch points	Frame
Lower hitch points above ground - down position:	229 mm	219 mm
Vertical movement - without load:	750 mm	853 mm
with load:	686 mm	767 mm
Maximum corrected force exerted through full range:	75.2 kN	69.3 kN
Corresponding pressure:	18.5 MPa	18.5 MPa
Moment about rear axle:	97.2 kNm	131.8 kNm
Maximum mast tilt angle	--	6.7 deg

Lifting height relative to horizontal position of lower links.

mm	-358	-348	-302	-202	-102	-3	98	198	298	338	409
Corrected lift forces											
At the Hitch point kN	--	75.2	78.6	84.4	88.0	91.1	93.1	94.1	95.0	95.1	--
at the frame kN	80.4	–	81.0	81.9	81.4	80.2	78.2	74.7	–	71.3	69.3

Corresponding pressure 18.5 Mpa

4.6 Measurement of External Noise Level – John Deere 7720

-- Date of Test	March 31, 2004
-- Location of Test	Nebraska Tractor Test Laboratory
-- Sound Level Meter	Bruel and Kjaer 2236
-- Type of Track	Concrete Oval
-- Gear Number	20 (E4)
-- Speed Prior to Acceleration	31.3 km/h
-- Noise Level	85.5 dB(A)


4.7 Measurement of Noise Level at Operator's Ear*


-- Date of Test	March 31, 2004
-- Location of Test	Nebraska Tractor Test Laboratory
-- Sound Level Meter	Bruel and Kjaer 2236
-- Type of Track	Concrete Oval
-- Gear Number	7 (B3)
-- Drawbar Load	None
-- Noise at Operator Ear	68.8 dB(A) – front wheel drive engaged 68.8 dB(A) – front wheel drive disengaged


* Note: Nebraska tractor test station guidelines.

5. Repairs and Adjustments: None

6. Remarks: None


Power and Equivalent Crankshaft Torque
Power, kW
Equivalent Crankshaft Torque, Nm
Engine Speed, rev/min
Standard PTO Speed - 1000 rev/min
kW
kW, std PTO
kW, DLG
Nm
Nm, std PTO
Nm, DLG
125
100
75
50
25
0
800
640
480
320
160
0
900
1000
1100
1200
1300
1400
1500
1600
1700
1800
1900
2000
2100
2200
2300


Specific Fuel Consumption and Fuel Rate
SFC, g/kWh
Fuel Rate, kg/h
Engine Speed, rev/min
Standard PTO Speed
1000 rev/min
500
450
400
350
300
250
200
30.0
25.0
20.0
15.0
10.0
5.0
0.0
900
1000
1100
1200
1300
1400
1500
1600
1700
1800
1900
2000
2100
2200
2300
g/kWh
g/kWh, std PTO
g/kW-h, DLG
kg/h
kg/h, std PTO
kg/h, DLG


Power and Specific Fuel Consumption
SFC, g/kWh
500
450
400
350
300
250
200
0
25
50
75
100
125
Power, kW
g/kWh
g/kWh, std PTO
g/kW-h, DLG