Prüfstelle für Landmaschinen



REPORT on test in accordance with OECD STANDARD CODE 2 for the Official Testing of Agricultural Tractor Performance

OECD No. 2/2126
14th May 2004

Agricultural Tractor

John Deere 6420 NA AutoQuad (4WD) TIER2

Manufacturer

DEERE & COMPANY, Moline, Illinois, USA

This is a report on a tractor test in accordance with OECD STANDARD CODE for the Official Testing of Agricultural Tractor Performance (C(2002)17(FINAL) "Red Code", Code 2).

It does not contain an evaluation of the tractor on practical work.

Duration of tests: September till November 2003

DLG-Testing Station for Agricultural Machinery, Max-Eyth-Weg 1,
D-64823 Gross-Umstadt

This report has been approved by the OECD Co-Ordinating Centre (CEMAGREF, France) as being in accordance with the OECD STANDARD CODE.

Date of approval: 14th May 2004 OECD No. 2/2126

A new OECD-test on the agricultural tractor John Deere 6420 NA AutoQuad was necessary, because the engine setting has been changed in accordance to the exhaust emission standard TIER2, EPA.

Statement

The information opposite each item has been validated by the Testing Station. An item marked [C] indicates to the test report user that the information declared by the manufacturer has been checked; an item marked [D] indicates that the manufacturer's declaration has been endorsed.

All rights including the right of translation, reprint and photo-mechanical copying - also of excerpts - reserved by the editor.
Printed in Germany, August 2004
DLG-No. 339

TABLE OF CONTENTS

		Page
1	SPECIFICATIONS OF TRACTOR	4 to 17
2	TEST CONDITIONS	18 to 20
3	COMPULSORY TESTS	
3.1	Main power take-off	21 to 25
3.2	Hydraulic power and lifting force	26 and 27
3.3	Drawbar power and fuel consumption of unballasted tractor	28 and 29
4	ADDITIONAL TESTS	30
4.1	Measurement of noise at the driving position carried out in accordance with OECD CODE 5	30 and 31
5	REPAIRS	32
6	REMARKS	32

[C]	Tractor manufacturer's name and address:	DEERE & COMPANY, Moline, Illinois, USA
[C]	Location of tractor assembly:	JOHN DEERE Werke Mannheim, D-68163 Mannheim
[C]	Submitted for test by:	Manufacturer
[C]	Selected for test by:	Manufacturer with agreement by DLG
[D]	Place of running-in:	Mannheim and Gross-Umstadt
[D]	Duration of running-in:	Engine 20h, tractor 17h
[C]	Location of test:	DLG-Testing Station, D-64823 Gross-Umstadt

1 SPECIFICATIONS OF TRACTOR

1.1 Identification

1.1.1

[C]	- Make:	JOHN DEERE
[C]	- Model:	6420
[C]	- Type:	4WD, full frame design
1.1.2	Numbers	
[D]	- 1st serial No.:	316456 (1st September 2001)
[C]	- Serial No.:	387427
1.1.3	Other specifications:	
[C]	- Region version:	NA
[C]	- Transmission version:	AutoQuad, 40 km/h
[D]	- Engine version:	exhaust emission according to TIER2, EPA and guideline 2000/25/EG

1.2 Engine

[C]	Make/Model/Type:	JOHN DEERE / 4045HL271 (DD20212) / water-cooled 4-stroke Diesel-engine, direct injection, supercharged and intercooler, antivibration mounted
[C]	Serial No.:	807962

1.2.1	Cylinders	
[C]	Number/disposition:	4 / vertical in line
[D]	Bore/stroke:	106.5 mm / 127 mm
[D]	Capacity:	4525 cm^3
[D]	Compression ratio:	17 ± 0.5 : 1
[D]	Arrangement of valves:	Overhead valves, 2 per cylinder
[D]	Cylinder liners:	Wet
1.2.2	Supercharging	
[C]	- Make / Model / Type:	CZECH / K27 123 (RE518823) / exhaust driven supercharger with SAMSUNG water cooled intercooler (by low temperature section of water cooler)
[D]	- Pressure	Max. 90 kPa
1.2.3	Fuel system	
[C]	- Fuel feed system:	Electrical vane type fuel supply pump
	- Fuel filter	
[C]	Make/Model:	JOHN DEERE / -
[C]	Type :	2 replaceable paper element filter
[D]	- Capacity of fuel tank:	165 dm^3
	- Injection pump	
[C]	Make/Model:	STANADYNE / B3 DE2435-5780 (RE518167)
[C]	Type:	DE 10 distributor injection pump with timing device
[C]	Serial no.:	10506887
[C]	Manufacturer's production setting:	83 ± 3 mm^3/stroke at full load and rated speed;
[C]	Flow rate:	22.9 ± 0.8 dm^3/h at 2300 min^{-1} and full load
[C]	Timing:	electronically controlled
	- Injectors	
[D]	Make/Model:	STANADYNE / -
[D]	Type :	Multi hole
[D]	Injection pressure:	26.3 ± 0.25 MPa
1.2.4	Governor	
[D]	- Make/Model/Type:	STANADYNE / - / electronically driven all speed governor
[C]	- Governed range of engine speed:	850 ± 50 to 2460 ± 50 min^{-1}
[C]	- Rated engine speed:	2300 min^{-1}

1.2.5	Air cleaner	
	- Pre-cleaner	
[C]	Make/Model:	DONALDSON / 991220
[C]	Type:	Vacuum aspirated (cooling fan) cyclone type pre-cleaner integrated in front cover of main cleaner housing
[C]	Location of air intake:	Above water cooler, below bonnet
	- Main cleaner	
[C]	Make/Model:	DONALDSON / 991220
[C]	Type:	Dry paper element filter with additional safety cartridge
[C]	- Maintenance indicator:	Warning light on dashboard
1.2.6		
[D]	Lubrication system	Pressure lubrication with engine oil/cooling water heat exchanger in engine block
[D]	- Type of feed pump:	Gear pump
[C]	- Type of filter:	Full flow, replaceable cartridge
[C]	- Number of filters:	1
1.2.7		
[C]	Cooling system	Water cooling (high temperature section of water cooler)
[C]	- Type of coolant:	Water-anti-freeze mixture
[D]	- Type of pump:	Impeller pump
	- Specification of fan	
[C]	Number of fan blades:	9
[C]	Fan diameter:	600 mm
[D]	- Coolant capacity:	13.5 dm^3
[C]	- Type of temperature control:	Thermostat and by-pass circuit, BEHR viscous drive fan, belt driven; variable fan speed controlled by air flow temperature
[D]	- Superpressure system:	70 ± 20 kPa

1.2.8	Starting system	
[C]	- Make/Model/Type:	BOSCH EV / 12V / 2339402131 (RE506589) electrical, solenoid pre-engaged drive starter motor, gear reduction starter
[D]	- Starter motor power rating:	3 kW
[C]	- Cold starting aid:	Heating spiral in air intake manifold
[C]	- Safety device:	Forward / reverse lever in neutral position at engine shut off
1.2.9	Electrical system	
[D]	- Voltage:	12 V
	- Generator:	
[C]	Make/Model/Type:	BOSCH / 14 V / 70 - 115 A / 3-phase alternator
[C]	Power:	1.6 kW
[C]	- Battery:	1 lead acid battery, 12 V / 154 Ah (AL119622) at 20 hours rating
1.2.10	Exhaust system	
[C]	- Make/Model/Type:	EBERSPÄCHER / AL82411 / single-chamber absorption type, oval 175 mm x 275 mm / 215 mm long
[C]	- Location:	Under bonnet, vertical stack at right A-post of cab, mouth showing upward / forward
1.2.11		
[D]	Operating hours meter:	Electronic, counts real hours when engine is running

1.3 Transmission

1.3.1	Clutch	
[D]	- Make/Model/Type:	JOHN DEERE /- / wet multi-plate
[D]	- Number of plates:	4
[D]	- Diameter of plates:	225 mm
[C]	- Method of operation:	By pedal and reverse lever, hydraulically, by low pressure hydraulic circuit, operated by valve

1.3.2 Gear box

[C] - Make/Model/Type: JOHN DEERE / AutoQuad, 40 km/h / mechanical, 40 km/h version

[C] - Description: Speed change gear with 6 ranges (A, B, C, D, E, F; synchronized),
4 step power shift (1, 2, 3, 4), automatic power shift selectable,
power shifted reversing gear

		Forward	Reverse
[C]	No. of gears	4	4
[C]	No. of ranges	6	6
[C]	Total	24	24

2 levers, 2 buttons and 1 rocker switch for alternative power shifting, 1 rocker switch for automatic speed shifting when ECO- or Power-Mode is selected

[D] - Available options (not fitted): AutoQuad (36/36) 40 km/h with creeper gear; PowrQuad (16/16) 30 km/h without creeper gear; PowrQuad (28/28) 30 km/h with creeper gear

[D] - Lubrication: Forced-feed lubrication, oil cooler (ring cooler) at the rear end of engine block, (low temperature section of water cooler), 2 filters

1.3.3 Rear axle and final drives

[D] - Make/Model/Type: JOHN DEERE / - / bevel gear drive with bevel gear differential and planetary final drives

- Differential lock:

[D] Type: Wet multi-plate

[C] Engagement: Electro-hydraulically by foot switch

[C] Disengagement: By pedal of service brake

1.3.4 Front axle and final drives

[C] - Make/Model/Type: ZF/ APL2035/12G / swing axle, driving and steering; axle driven through wet multi plate clutch, shaft in median plane of tractor, bevel gear;
clutch electro-hydraulically operated by rocker switch (two positions: engaged / engaged by service brake operation);
planetary final drives

- Differential lock:

[D] Type: Limited slip multi-plate type

[C] Engagement: Automatic

[C] Disengagement: Automatic

1.3.5 Total ratios and travelling speeds

	Range	Gear	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed*) at rated engine speed of 2300 min^{-1} km/h
	Forward Speed			
[C]	A	1	450.59	1.58
[C]		2	374.30	1.90
[C]		3	312.56	2.27
[C]		4	255.15	2.79
[C]	B	1	184.57	3.85
[C]		2	153.32	4.64
[C]		3	128.03	5.55
[C]		4	104.52	6.80
[C]	C	1	113.21	6.28
[C]		2	94.04	7.56
[C]		3	78.53	9.05
[C]		4	64.10	11.09
[C]	D	1	68.99	10.31
[C]		2	57.31	12.41
[C]		3	47.85	14.86
[C]		4	39.06	18.20
[C]	E	1	42.45	16.75
[C]		2	35.27	20.16
[C]		3	29.45	24.15
[C]		4	24.04	29.58
[C]	F	1	31.45	22.61
[C]		2	26.12	27.22
[C]		3	21.81	32.60
[C]		4	17.81	39.93
	Reverse Speed			
[C]	A	1	431.67	1.65
[C]		2	358.58	1.98
[C]		3	299.43	2.37
[C]		4	244.43	2.91
[C]	B	1	176.82	4.02
[C]		2	146.89	4.84
[C]		3	122.65	5.80
[C]		4	100.13	7.10

[C]	C	1	108.45	6.56
[C]		2	90.09	7.89
[C]		3	75.23	9.45
[C]		4	61.41	11.58
[C]	D	1	66.09	10.76
[C]		2	54.90	12.95
[C]		3	45.84	15.51
[C]		4	37.42	19.00
[C]	E	1	40.67	17.48
[C]		2	33.78	21.05
[C]		3	28.21	25.20
[C]		4	23.03	30.87
[C]	F	1	30.13	23.60
[C]		2	25.03	28.41
[C]		3	20.90	34.02
[C]		4	17.06	41.68

*) Calculated with a dynamic radius index of 820 mm
(in conformity with ISO 4251-1:1998)

[D] - Number of revolutions of front wheels for one revolution of rear wheels: 1.3481

1.4 Power take-off

1.4.1 Main power take-off

[C]	- Type:	Independent
[C]	- Method of engagement:	Driven by wet multi-plate clutch with 197 mm dia, electro-hydraulically operated by rotary switch through control valve; response of valve automatically controlled
[C]	- Number of shafts:	1
[C]	- Method of changing power take-off shaft ends and speeds:	Reversible stub giving two different standard speeds

1.4.1.1 Power take-off proportional to engine speed, 540 min^{-1} or 1000 min^{-1} p.t.o.

[C] - Location: At rear of tractor

[C] - Diameter of p.t.o. shaft end: 35 mm

[C] - Number of splines: 6 (540 min^{-1}) in conformity with ISO 500:1991, type 1
21(1000 min^{-1}) in conformity with ISO 500:1991, type 2

[C] - Height above ground: 750 mm

[C] - Distance from the median plane of the tractor: 0 mm

[C] - Distance behind rear wheel axis: 530 mm

	P.t.o. type	P.t.o. transmission ratio	P.t.o. speed min^{-1}	Engine speed min^{-1}	Power restriction kW	Max. torque transmissible Nm
[D]	540	3.9685	540 580	2143 2300	not specified	
[D]	1000	2.2080	1000 1042	2208 2300	not specified	

[C] - Direction of rotation (viewed from behind tractor): Clockwise

1.4.1.2 Power take-off proportional to ground speed: None

1.4.2 Optional power take-off: Front p.t.o., independent, not fitted to tractor

1.5 Hydraulic power lift


[C]	- Make/Model/Type:	JOHN DEERE / - / desintegrated, electronically controlled hydraulic power lift, lower link sensing
[C]	- Type of hydraulic system:	Closed center, load sensing pressure and flow compensated system
[C]	- Type and number of cylinders:	2 external cylinders, single acting, 75 mm bore, 175 mm stroke,
[C]	- Type of linkage lock for transport:	Hydraulic, lock of valve lever
[D]	- Relief valve pressure setting:	19.2 to 20.7 MPa
[D]	- Opening pressure of cylinder safety valve:	23.5 MPa
	- Lift pump:	
[D]	- Make:	BRÜNINGHAUS HYDROMATIC
[D]	- Model:	A10VNO41
[D]	- Type:	41 cm^3 axial-piston pump with 100 dm^3/min delivery at rated speed; optional: 25 cm^3 axial-piston pump with 60 dm^3/min delivery at rated speed
[D]	- Transmission between pump and engine:	Gear driven by transmission
[D]	- Type and number of filters:	2 filters, 1 in feeding line of hydraulic pump, 1 on transmission housing
[C]	- Site of oil reservoir:	Transmission housing
[C]	- Type, number and location of tapping points:	3 double acting, quick-action coupler-pairs at rear of tractor
[D]	- Maximum volume of oil available to external cylinders:	Stationary 25 dm^3, driving 15 dm^3
[D]	- Oil cooler:	Engine cooling water / transmission-hydraulic oil heat exchanger at the rear end of engine block

1.6 Three-point linkage:

1.6.1 Three-point linkage at rear:

[C] - Category: 2, in conformity with ISO 730-1/1994 + Cor. 1:1995 with extendable lower links

[C] - Category adapter: None



Dimensions of rear implement linkage				Projected lengths in mm	
				Dimensions	Settings used in test-page 27
[D]	Rear tyres 18.4 - 38 Front tyres 16.9 - 24		(r) *) (r') *)	820 620	
[C]	Length of lift arms		(A)	305	
[C]	Length of lower links		(B)	945	
[C]	Distance of lift arm pivot points from rear wheel axis	horizontal vertical	(a) (b)	180 475	
[C]	Horizontal distance between the 2 lower link pivot points		(u)	480	
[C]	Horizontal distance between the 2 lift arm end points		(v)	535	
[C]	Length of upper link		(S)	from 550 to 730	665
[C]	Distance of upper link pivot point from rear wheel axis	horizontal vertical	(c) (d)	460 185	460 185
[C]	Distance of lower link pivot points from rear wheel axis	horizontal vertical	(e) (f)	135 225	
[C]	Distance of lower link pivot points from lift rod pivot points on lower links		(D)	505	
[C]	Length of lift rods		(L)	from 715 to 860	815

Heights (h,H,H') of lower link hitch point relative to rear wheel axis (situated 820 mm above ground); at different adjustments of L

These data are valid for unloaded power lift

[C]	Length of lift rods	(L)	815	715	860
[C]	Linkage distance of lift rods	(D)	505		
[C]	Lowest position	(h)	620	385	710
[C]	Highest position	(H)	60	220	-60
[C]	Transport position	(H')	60	220	-60

*) Assuming r resp. r' = tyre dynamic radius index (in conformity with ISO 4251-1:1998)

1.7	**Swinging drawbar**		
[C]	- Type:	Adjustable in height and length	
[C]	- Height above ground	Maximum: Minimum:	600 mm 530 mm
[C]	- Type of adjustment:	Turning the drawbar	
[C]	- Distance of hitch point from rear wheel axis	Horizontal:	780 / 880 / 930 / 1080 mm
[C]	- Distance of hitch point from p.t.o. shaft end	Vertical: Horizontal:	150 / 220 mm 250 / 350 / 400 / 550 mm
[C]	- Lateral adjustment (centre of clevis)	Right/left hand side: 190 / 210 / 225 / 260 mm	
[C]	- Distance of pivot point from rear-wheel axis, horizontally:		0 mm
[C]	- Diameter of drawbar pin hole:		33 mm
[C]	- Maximum permissible vertical load:		27 kN
1.8	**Trailer hitch**	None	
1.9	**Holed drawbar**	Optional: short bar, category 2, not fitted	
1.10	**Steering**		
[D]	- Make/Model/Type:	JOHN DEERE and DANFOSS/ - / hydrostatic steering, acting on front wheels	
	- Method of operation		
[D]	Pump:	Steering system connected to main hydraulic circuit	
[C]	Ram:	Integrated cylinder of symmetrical design, 224 mm stroke, 70 mm bore, 36 mm dia of piston rod	
[D]	- Working pressure:	18.5 MPa	

1.11 Brakes

1.11.1 Service brake

[D] - Make/Model/ Type: JOHN DEERE / - / muscle power braking system with hydraulic transmission with additional power fill, oil-immersed disc brake with 2 acting faces on each differential half shaft, disc 313 mm diameter

[C] - Method of operation: Pedal operated, acting on rear wheels, front axle drive is automatically engaged when braking

[C] -Trailer braking take-off: None

1.11.2 Parking brake

[C] - Type: Parking lock of transmission

[C] - Method of operation: Range gear lever in "P" position

1.12 Wheels

- Number

[C] Front: 2, driving and steering

[C] Rear: 2, driving

[C] - Wheelbase: 2400 mm

- Track width adjustment:

	Minimum	Maximum	Adjustment method
[D] Front	1516	2136	adjustable rims
[D] Rear	1604	2514	rack and pinion axle

1.13 Protective structure

[C] - Make/Model/Type: JOHN DEERE / SG068 / Cab

[C] - Manufacturer's name and address: DEERE & COMPANY, Moline, Illinois, USA

- Protective device

[C] Cab: Welded and screwed profile steel tube construction, mounted on silent blocks, for service (repair) with separate device tiltable to the side

[C] Tiltable / not tiltable: Not tiltable

- OECD approval

[C] Approval number: 4/0 694

[C] Date of approval: 11th October 2001

John Deere 6420 NA AutoQuad (4WD) TIER2 **DLG-Test No. 2003-304**

1.14 Seat

1.14.1	Driver's seat	Fitted to tractor
[C]	- Make/Model:	Grammer / MSG 95 AL / 731
[C]	- Type:	Air suspended upholstered seat with backrest and armrests
[C]	- Seat and steering wheel reversible:	No
[C]	- Type of suspension:	Pneumatic
[C]	- Type of damping:	Hydraulic
	- Range of adjustment	
[C]	Longitudinal:	195 mm
[C]	Vertical:	380 to 565 mm
[C]	- Safety belt:	Yes
1.14.2	Optional driver's seats	
[D]	- Make/Model/Type:	Grammer/MSG 95A; MSG 93; MSG 85 / mechanical suspension or pneumatic suspension
1.14.3	Passenger seat:	Optional, not fitted to tractor tested

1.15 Lighting

Electrical, 12 Volt, according to US legislation

		Height above ground of centre mm	Size mm	Distance from outside edge of lights to median plane of tractor mm
[C]	Headlights	1295	150 x 90	190
[C]	Side Lights	n.a.	n.a.	n.a.
[C]	Rearlights	1770	230 x 45	900
[C]	Reflectors	1730	160 x 25	865

2. TEST CONDITIONS

2.1 Overall dimensions

	Length mm	Width (track width as in 2.5) mm	Height at top of protective structure mm	Height at top of exhaust silencer pipe mm
Unballasted	4250	2250	2715	2710

2.2 Ground clearance 440 mm

- Clearance-limiting part: Bracket for sway blocks

2.3 Tractor mass Unballasted (with cab)

	Without driver kg	With driver kg
Front	1825	1850
Rear	3255	3305
Total	5080	5155

2.4 Track specifications Not applicable

2.5 Tyres and track widths specifications

	Front	Rear
Tyres:	GOODYEAR DynaTorque II	
- Dimensions	16.9 - 24	18.4 - 38
- Load index speed index	6 PR	8 PR
- Type	cross ply	cross ply
- Maximum load (tyre manufacturer's)	17.50 kN*)	27.25 kN*)
- Maximum load (tractor manufacturer's)	21.00 kN	32.50 kN
at travelling speed	30 km/h	30 km/h
at tyre inflation pressure	150 kPa	140 kPa
dynamic radius index	620 mm	820 mm
Chosen track width:	1840 mm	1830 mm

*) With other tyres higher load capacity possible

2.6 Fuel

- Type: ARAL-Diesel-fuel, in conformity with DIN 51601
- Density at 15°C: At p.t.o. tests 0.830 g/cm³
  at drawbar power tests 0.833 g/cm³

2.7 Oils and lubrication

2.7.1 Capacity and change interval

	Capacity dm³	Oil change h	Filter-change h
Engine	16	500	500
Gear box and rear axle	52	1500	750
Front axle	5	1500	-
Rear axle	in common with gearbox		
Final drives (front each)	0.8	1500	-
Final drives rear (each)	in common with gearbox		
Hydraulic system	in common with gearbox		
Steering	in common with gearbox		

2.7.2 Specifications:

	Recommended	Used during test
Engine oil: Used in engine		Fuchs Titan
Type	engine oil	engine oil
Viscosity	SAE 20W40, 15W40, 10W40, JD PLUS-50, JD TORQ-GARD SUPREME	SAE 15W40
Classification	API CG-4 or CF-4; ACEA - E2 or E3;	API CF-4
Transmission oil: Used in gear box, rear axle, hydraulic system and brake system	John Deere HY-GARD John Deere Low Viscosity HY-GARD, John Deere BIO-HY-GARD	John Deere HY-GARD
Type Viscosity Classification	transmission oil SAE 75 JDM J20C or J20D	transmission oil SAE 75 JDM J20C
Transmission oil: Used in front axle and front final drives	John Deere HY-GARD, John Deere BIO-HY-GARD or transmission oil	Fuchs
Type Viscosity Classification	transmission oil SAE 75 or SAE 80W90 JDM J20C	transmission oil SAE 80W90 JDM J20C

2.7.3 Grease Multi purpose grease GC-LB

- Number of lubrication points: 18

3 COMPULSORY TESTS

3.1 Main power take off performance

Date of tests: 2003-10-07
Location of tests: DLG-Testing Station Groß-Umstadt
Type of dynamometer: SCHENCK hydraulic dynamometer U1-40

Power kW	Speed Engine min^{-1}	Speed P.t.o. min^{-1}	Speed Fan min^{-1}	Fuel consumption hourly kg/h	Fuel consumption hourly dm³/h	Fuel consumption specific g/kWh	Specific energy kWh/dm³
Maximum power							
3.1.1 At 2-hour test							
78.8	2100	951	1402	20.37	24.54	258	3.21
3.1.2 At rated speed							
71.5	2301	1042	1418	19.26	23.20	269	3.08
3.1.3 At standard p.t.o. speed							
75.1	2208	1000	1401	19.59	23.60	261	3.18
3.1.4 Part loads, the governor hand lever in the position corresponding to maximum power at full load (curve a)							
3.1.4.1 the torque corresponding to maximum power at rated speed							
71.5	2301	1042	1418	19.26	23.20	269	3.08
3.1.4.2 85% of the torque obtained in 3.1.4.1							
62.4	2362	1070	1515	17.90	21.57	287	2.89
3.1.4.3 75% of the torque defined in 3.1.4.2							
47.4	2391	1083	1435	15.34	18.48	324	2.56
3.1.4.4 50% of the torque defined in 3.1.4.2							
32.0	2420	1096	1421	11.97	14.42	374	2.22
3.1.4.5 25% of the torque defined in 3.1.4.2							
16.3	2455	1112	1402	8.82	10.63	542	1.53
3.1.4.6 unloaded							
-	2459	1113	1360	5.51	6.64	-	-

Power kW	Speed Engine min^{-1}	Speed P.t.o. min^{-1}	Speed Fan min^{-1}	Fuel consumption hourly kg/h	Fuel consumption hourly dm^3/h	Fuel consumption specific g/kWh	Specific energy kWh/dm^3
3.1.5 Part loads, the governor hand lever in the position corresponding to standard p.t.o. speed at full load (curve b)							
3.1.5.1 the torque corresponding to maximum power							
75.1	2208	1000	1401	19.59	23.60	261	3.18
3.1.5.2 85% of the torque obtained in 3.1.5.1							
66.3	2276	1031	1409	18.16	21.88	274	3.03
3.1.5.3 75% of the torque defined in 3.1.5.2							
50.1	2294	1039	1410	15.35	18.49	306	2.71
3.1.5.4 50% of the torque defined in 3.1.5.2							
33.7	2314	1048	1381	12.09	14.57	359	2.31
3.1.5.5 25% of the torque defined in 3.1.5.2							
17.0	2338	1059	1319	8.59	10.35	505	1.64
3.1.5.6 unloaded							
-	2353	1065	1311	5.37	6.47	-	-

John Deere 6420 NA AutoQuad (4WD) TIER2 — DLG-Test No. 2003-304

OPTIONAL RESULTS

Power kW	Speed Engine min^{-1}	Speed P.t.o. min^{-1}	Speed Fan min^{-1}	Fuel consumption hourly kg/h	Fuel consumption hourly dm³/h	Fuel consumption specific g/kWh	Specific energy kWh/dm³
3.1.6 Part loads at different engine speeds							
3.1.6.1 maximum power at rated engine speed							
71.5	2301	1042	1418	19.26	23.20	269	3.08
3.1.6.2 80% of power obtained in 3.1.6.1 at max. speed setting							
57.2	2371	1074	1708	16.90	20.36	295	2.81
3.1.6.3 80% of power obtained in 3.1.6.1 with governor control set to 90% of rated engine speed							
57.4	2078	941	1592	15.32	18.46	267	3.11
3.1.6.4 40% of power obtained in 3.1.6.1 with governor control set to 90% of rated engine speed							
28.6	2073	939	1479	9.30	11.20	325	2.55
3.1.6.5 60% of power obtained in 3.1.6.1 with governor control set to 60% of rated engine speed							
43.0	1382	626	1376	11.04	13.30	257	3.23
3.1.6.6 40% of power obtained in 3.1.6.1 with governor control set to 60% of rated engine speed							
28.7	1380	625	1383	7.80	9.40	272	3.05


No load maximum engine speed:	2459 min^{-1}
Equivalent flywheel torque at rated engine speed:	287 Nm
Equivalent flywheel torque at 2-hour test:	358 Nm
at engine speed:	2100 min^{-1}
Maximum equivalent flywheel torque:	438 Nm
at engine speed:	1503 min^{-1}


Mean atmospheric conditions

temperature:	21 °C
pressure:	98.4 kPa
relative humidity:	43 %

Maximum temperatures

coolant:	78 °C
oil:	102 °C
fuel:	33 °C
air intake:	20 °C


p.t.o. test
M
P
B
be
John Deere 6420 NA AutoQuad TIER2
standard p.t.o. speed 1000 min-1
p.t.o. power P [kW]
equivalent torque M [Nm]
fuel consumption B [kg/h]
spec. fuel consumption be [g/kWh]
engine speed n [min-1]
100
90
80
70
60
50
40
30
20
10
0
500
450
400
350
300
250
200
150
100
50
0
20
15
10
5
0
360
320
280
240
200
800
1000
1200
1400
1600
1800
2000
2200
2400
2600


p.t.o. test
specific fuel consumption be [g/kWh]
640
600
560
520
480
440
400
360
320
280
240
200
0
20
40
60
80
100
p.t.o. power P [kW]
curve a
curve b
be
John Deere 6420 NA AutoQuad TIER2

3.2 HYDRAULIC POWER AND LIFTING FORCE

- Date of tests: 24th November 2003

3.2.1 Hydraulic power test

3.2.1.1 Hydraulic fluid data

- Hydraulic fluid type: Transmission oil
- Viscosity index (ISO 3448+Corr 1:1993): SAE 75
- Viscosity at 65°C: n.a.

3.2.1.2 Compulsory Reporting (Test Results):

	Pressure	Reservoir oil Temperature °C (65°C traget)		Engine speed	Flow rate	Power
		Min.	Max.			
	MPa	°C	°C	min^{-1}	l/min	kW
Rated Engine Speed *(Manufacturers Specification)*	-	-	-	2300	-	-
3.2.1.2.1 Maximum (sustained) pressure with relief valve open as measured at the coupler Pump stalled: No	20.3	65	65	2432	-	-
3.2.1.2.2 Flow rate corresponding to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting and corresponding hydraulic power	18.3	65		2430 [1] 2425 [2]	89.4 [1] 96.4 [2]	27.4 [1] 29.6 [2]
3.2.1.2.3 Maximum available flow and maximum power from one coupler pair	4.0 18.0	65		2425 2427	107.7 95.8	- 28.8
3.2.1.2.4 Maximum available flow and maximum power from coupler pairs operating simultaneously (flow through two or more coupler pairs if required)	2.3 18.5	65		2426 2425	109.0 96.2	- 29.7

- Tapping point used for test: At rear of tractor, [1] 1 double acting control valve
  [2] 2 double acting control valves parallel connection

3.2.2 Power lift test at rear power lift

	At the hitch points	On the frame
Height of lower hitch points above ground in down position	200 mm	
Vertical movement without lifting forces with lifting forces	685 mm 640 mm	890 mm 874 mm
Max. corrected force exerted through full range	29.70 kN	24.75 kN
Corresponding pressure	18.3 MPa	
Moment about rear axle	-	41.83 kNm
Max. tilt angle of mast from vertical		12°

Lifting heights relative to horizontal lower links												
mm	-485	-400	-395	-300	-200	-100	0	+100	+200	+245	+300	+390
Lifting forces at hitch points, corrected to 18.3 MPa												
kN			29.70	34.20	37.35	40.50	42.75	45.00	46.80	47.70		
Lifting forces at standard frame, corrected to 18.3 MPa												
kN	24.75	26.55		28.80	30.15	31.50	31.95	31.50	31.05		30.60	29.25

John Deere 6420 NA AutoQuad (4WD) TIER2 **DLG-Test No. 2003-304**

3.3 DRAWBAR POWER TEST (unballasted tractor)

Date of tests: 15th till 17th October 2003
Type of track: Concrete

	Height of drawbar above ground	Tyre inflation pressure	
		Front	Rear
Unballasted	500 mm	80 kPa	80 kPa

Gear number and range	Power	Drawbar pull	Speed	Engine speed	Slip of wheels	Fan speed	Specific fuel consumption	Specific energy	Temperature			Atmospheric conditions		
									Fuel	Coolant	Engine oil	Temperature	Relative humidity	Pressure
	kW	kN	km/h	min^{-1}	%	min^{-1}	g/kWh	kWh/dm^3	°C	°C	°C	°C	%	kPa

3.3.1 MAXIMUM POWER IN TESTED GEARS (unballasted tractor)

B3	55.4	41.12	4.85	2346	15.2	1302	350	2.37	43	81	103	13	43	101.2
C1	60.4	42.32	5.14	2192	15.0	1206	329	2.53	36	78	101	9	43	101.2
B4	61.6	41.48	5.35	2105	15.0	1350	334	2.49	43	81	103	12	43	101.2
C2	63.2	37.58	6.06	2096	13.2	1429	325	2.56	47	81	104	17	43	101.2
C3	64.5	30.86	7.53	2099	10.5	1468	318	2.62	47	82	105	17	43	101.2
D1	64.5	26.52	8.75	2106	8.5	1384	319	2.62	45	81	105	14	43	101.2
C4	63.3	24.07	9.48	2094	7.3	1269	324	2.57	42	81	104	11	43	101.2
D2	64.8	21.85	10.68	2089	6.2	1379	316	2.64	45	81	104	14	43	101.2
D3	66.7	18.45	13.02	2100	5.2	1211	305	2.73	36	80	103	6	43	101.2
E1	64.6	15.78	14.74	2095	4.5	1217	315	2.64	36	80	102	6	43	101.2

John Deere 6420 NA AutoQuad (4WD) TIER2 **DLG-Test No. 2003-304**

Gear number and range	Power	Drawbar pull	Speed	Engine speed	Slip of wheels	Fan speed	Specific fuel consumption	Specific energy	Temperature			Atmospheric conditions		
									Fuel	Coolant	Engine oil	Tempe-rature	Relative humidity	Pressure
	kW	kN	km/h	min^{-1}	%	min^{-1}	g/kWh	kWh/dm^3	°C	°C	°C	°C	%	kPa
	FUEL CONSUMPTION													
3.3.2.1	In selected gear, at maximum power at rated speed													
D3	58.8	14.68	14.43	2304	4.2	1295	333	2.50	42	81	102	14	55	101.5
3.3.2.1.1	75 % of pull at maximum power at rated speed													
D3	46.3	11.13	14.99	2370	3.2	1370	376	2.21	44	80	103	16	55	101.5
3.3.2.1.2	50 % of pull at maximum power at rated speed													
D3	31.7	7.42	15.36	2402	2.2	1386	466	1.78	43	79	102	16	55	101.5
3.3.2.1.3	Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.1													
E1	47.4	11.31	15.08	2115	3.4	1306	342	2.43	43	80	101	16	55	101.5
3.3.2.1.4	Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.2													
E1	30.8	7.20	15.38	2131	2.3	1318	416	2.00	42	78	100	16	55	101.5
3.3.2.2	In selected gear nearest to 7.50 km/h at rated speed													
C2	59.5	31.09	6.89	2300	10.0	1421	328	2.53	44	81	103	13	55	101.5
3.3.2.2.1	75 % of pull at maximum power at rated speed													
C2	47.6	23.34	7.34	2372	7.1	1425	360	2.31	42	80	104	14	55	101.5
3.3.2.2.2	50 % of pull at maximum power at rated speed													
C2	32.7	15.38	7.66	2408	4.4	1373	432	1.93	41	78	102	14	55	101.5
3.3.2.2.3	Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.1													
C3	47.5	23.34	7.34	1975	6.7	1251	310	2.68	41	79	100	14	55	101.5
3.3.2.2.4	Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.2													
C3	32.7	15.45	7.61	2000	4.3	1264	352	2.36	41	78	100	14	55	101.5

4 ADDITIONAL TESTS under the responsibility of the DLG Testing Station

4.1 Measurement of noise at the driving position carried out in accordance with OECD CODE 5

Results of sound level test - "Under load" procedure

Date of test: 7th and 11th November 2003
Type of track: Concrete
Type of sound level meter: BRÜEL & KJAER model 2233

Gear number and range	Drawbar pull	Engine speed	Measured travelling speed	Number of driving wheels	Sound level
	kN	min^{-1}	km/h		dB(A)
4.1.1 Test with the drawbar pull for which the tractor gives the maximum sound level (gear ratio giving the nearest nominal forward speed to 7.5 km/h and also in any speed settings with a sound level increase of at least 1 dB(A))					
4.1.1.1 All openings closed					
C 2	32.41	2308	6.95	4	74.0
C 2	32.89	2298	6.50	2	74.0
4.1.1.2 All openings open *)					
C 2	31.76	2302	6.85	4	82.5
E 1	12.60	2310	16.37	4	83.5
D 4	11.22	2306	18.03	4	83.5
C 2	32.90	2300	6.35	2	81.5
C 4	21.55	2317	10.18	2	82.5
D 2	17.52	2311	11.44	2	82.5
D 3	15.38	2304	13.96	2	82.5
E 1	13.99	2306	15.62	2	82.5
D 4	11.52	2320	17.49	2	83.0

*) Openings: 2 side windows, rear window

Gear number and range	Drawbar pull	Engine speed	Measured travelling speed	Number of driving wheels	Sound level
	kN	min^{-1}	km/h		dB(A)
4.1.2 Unloaded test in the gear ratio giving the forward speed nearest to 7.5 km/h					
4.1.2.1 All openings closed					
C 2	0	2457	8.06	4	72.0
C 2	0	2460	7.91	2	73.5
4.1.2.2. All openings open *)					
C 2	0	2457	8.06	4	80.0
C 2	0	2460	7.86	2	79.5
4.1.3 Unloaded test in the gear ratio giving the maximum forward speed					
4.1.3.1 All openings closed					
F 4	0	2460	40.0	2	75.0
4.1.3.2 All openings open *)					
F 4	0	2460	40.0	2	83.5

*) Openings: 2 side windows, rear window

5	**REPAIRS**	**None**
6	**REMARKS**	**None**

Head of Vehicle Technology

Test carried out by

Dipl.-Ing. (FH) Ottmar Degrell

Dipl.-Ing. (FH) Thomas Feuerstein

Date: 2nd August 2004

John Deere 6420 NA AutoQuad (4WD) TIER2 **DLG-Test No. 2003-304**

John Deere 6420 NA AutoQuad (4WD) TIER2 **DLG-Test No. 2003-304**



Deutsche Landwirtschafts-Gesellschaft e.V.
Prüfstelle für Landmaschinen
Max-Eyth-Weg 1, D-64823 Groß-Umstadt
Telefon: 0 60 78 / 96 35 0 Fax: 0 60 78 / 96 35 90
E-mail: Tech@DLG-Frankfurt.de, Internet: www.DLG.org/landtechnik