Testzentrum Technik und Betriebsmittel



REPORT on test in accordance with **OECD No. 2/2 238**
OECD STANDARD CODE 2 for the **20th April 2005**
Official Testing of Agricultural Tractor Performance

Agricultural Tractor

John Deere 6715 NA PowerReverser (4WD) TIER 2

Manufacturer

DEERE & COMPANY, Moline, Illinois, USA

This is a report on a tractor test in accordance with OECD STANDARD CODE for the Official Testing of Agricultural Tractor Performance (C(2002)17(FINAL), "Red Code", Code 2).

It does not contain an evaluation of the tractor on practical work.

Duration of tests: November 2004 till January 2005

DLG-Test Center Technology and Farm Inputs, Max-Eyth-Weg 1,
D-64823 Gross-Umstadt

This report has been approved by the OECD Co-Ordinating Centre (CEMAGREF, France) as being in accordance with the OECD STANDARD CODE.

Date of approval: 20th April 2005 OECD No.: 2/2 238

Statement

The information opposite each item has been validated by the Testing Station. An item marked [C] indicates to the test report user that the information declared by the manufacturer has been checked; an item marked [D] indicates that the manufacturer's declaration has been endorsed.

All rights including the right of translation, reprint and photo-mechanical copying - also of excerpts - reserved by the editor.
Printed in Germany, July 2005
DLG-No. 353

TABLE OF CONTENTS

		Page
1	SPECIFICATIONS OF TRACTOR	4 to 17
2	TEST CONDITIONS	18 to 20
3	COMPULSORY TESTS	
3.1	Main power take-off	21 to 25
3.2	Hydraulic power and lifting force	26 and 27
3.3	Drawbar power and fuel consumption of unballasted tractor	28 and 29
4	ADDITIONAL TESTS	30
4.1	Measurement of noise at the driving position carried out in accordance with OECD CODE 5	30 and 31
5	REPAIRS	32
6	REMARKS	32

[C]	Tractor manufacturer's name and address:	DEERE & COMPANY, Moline, Illinois, USA
[C]	Location of tractor assembly:	JOHN DEERE Werke Mannheim, D-68163 Mannheim
[C]	Submitted for test by:	Manufacturer
[C]	Selected for test by:	Manufacturer with agreement by DLG
[D]	Place of running-in:	Mannheim and Gross-Umstadt
[D]	Duration of running-in:	Engine 52 h, tractor 52 h
[C]	Location of test:	DLG-Test Centre Technology and Farm Inputs, D-64823 Gross-Umstadt

1 SPECIFICATIONS OF TRACTOR

1.1 Identification

1.1.1

[C]	- Make:	JOHN DEERE
[C]	- Model:	6715
[C]	- Type:	4WD, full frame design
1.1.2	Numbers	
[D]	- 1st serial No.:	316456 (1st September 2001)
[C]	- Serial No.:	424136
1.1.3	Other specifications:	
[C]	- Region version:	NA
[C]	- Transmission version:	Power Reverser, 30 km/h
[D]	- Engine version:	exhaust emission according to TIER 2, EPA and guideline 2000/25/EG

1.2 Engine

[C]	Make/Model/Type:	JOHN DEERE / 6068HL273 (DD20810) / water-cooled 4-stroke Diesel-engine, direct injection, supercharged and intercooler, antivibration mounted
[C]	Serial No.:	870911

1.2.1	Cylinders	
[C]	Number/disposition:	6 / vertical in line
[D]	Bore/stroke:	106.5 mm / 127 mm
[C]	Capacity:	6788 cm^3
[D]	Compression ratio:	16.9 ± 0.5 : 1
[D]	Arrangement of valves:	Overhead valves, 2 per cylinder
[D]	Cylinder liners:	Wet
1.2.2	Supercharging	
[C]	- Make / Model / Type:	BORG WARNER / G0604a218 (RE508657) / exhaust driven supercharger with SAMSUNG water cooled intercooler (by low temperature section of water cooler)
[D]	- Pressure	Max. 69 ± 1 kPa
1.2.3	Fuel system	
[C]	- Fuel feed system:	Electrical vane type fuel supply pump
	- Fuel filter	
[C]	Make/Model:	JOHN DEERE / -
[C]	Type :	2 replaceable paper element filter
[D]	- Capacity of fuel tank:	207 dm^3
	- Injection pump	
[C]	Make/Model:	STANADYNE / F4 DE2635-5807 (RE518164)
[C]	Type:	DE10; distributor injection pump with timing device
[C]	Serial no.:	10847689
[C]	Manufacturer's production setting:	63 ± 3 mm^3/stroke at full load and rated speed;
[C]	Flow rate:	26 ± 0.8 dm^3/h at 2300 min^{-1} and full load
[C]	Timing:	electronically controlled
	- Injectors	
[D]	Make/Model:	STANADYNE / 35107
[D]	Type :	Multi hole
[D]	Injection pressure:	26.3 ± 0.25 MPa

1.2.4	Governor	
[D]	- Make/Model/Type:	STANADYNE / - / electronically driven all speed governor
[C]	- Governed range of engine speed:	850 ± 50 to 2460 ± 50 min^{-1}
[C]	- Rated engine speed:	2300 min^{-1}
1.2.5	Air cleaner	
	- Pre-cleaner	
[D]	Make/Model:	DONALDSON / 991220
[C]	Type:	vacuum aspirated (cooling fan) cyclone type pre-cleaner integrated in front cover of main cleaner housing
[C]	Location of air intake:	Above water cooler, below bonnet
	- Main cleaner	
[D]	Make/Model:	DONALDSON / 991220
[C]	Type:	Dry paper element filter with additional safety cartridge
[C]	- Maintenance indicator:	Warning light on dashboard
1.2.6		
[D]	Lubrication system	Pressure lubrication with engine oil/cooling water heat exchanger in engine block
[D]	- Type of feed pump:	Gear pump
[C]	- Type of filter:	Full flow, replaceable cartridge
[C]	- Number of filters:	1
1.2.7	Cooling system	
[C]	Water cooling (high temperature section of water cooler)	
[C]	- Type of coolant:	Water-anti-freeze mixture
[D]	- Type of pump:	Impeller pump
	- Specification of fan	
[C]	Number of fan blades:	9
[C]	Fan diameter:	600 mm
[D]	- Coolant capacity:	15.5 dm^3

[C]	- Type of temperature control:	Thermostat and by-pass circuit, BEHR viscous drive fan, belt driven; variable fan speed controlled by air flow temperature
[D]	- Superpressure system:	70 ± 20 kPa
1.2.8	Starting system	
[C]	- Make/Model/Type:	BOSCH EV / 12V / 0 001 230 002 (RE506589) electrical, solenoid pre-engaged drive starter motor, gear reduction starter
[D]	- Starter motor power rating:	3 kW
[C]	- Cold starting aid:	Heating spiral in air intake manifold
[C]	- Safety device:	Forward / reverse lever in neutral position at engine shut off
1.2.9	Electrical system	
[D]	- Voltage:	12 V
	- Generator:	
[C]	Make/Model/Type:	BOSCH / 14 V / 90 A / 3-phase alternator
[C]	Power:	1.68 kW
[C]	- Battery:	1 lead acid battery, 12 V / 174 Ah at 20 hours rating
1.2.10	Exhaust system	
[C]	- Make/Model/Type:	ROTH / AL161217 / single-chamber absorption type, 300 mm dia / 280 mm long
[C]	- Location:	Under bonnet, vertical stack at right A-post of cab, mouth showing upward / forward
1.2.11		
[D]	Operating hours meter:	Electronic, counts real hours when engine is running

1.3 Transmission

1.3.1	Clutch	
[D]	- Make/Model/Type:	JOHN DEERE / - / wet multi-plate
[D]	- Number of plates:	4
[D]	- Diameter of plates:	225 mm
[C]	- Method of operation:	By pedal and reverse lever, mechanically, assisted by low pressure hydraulic circuit, operated by valve

1.3.2 Gear box

[C] - Make/Model/Type: JOHN DEERE / Power Reverser, 30 km/h / mechanical, 30 km/h version

[C] - Description: Speed change gear with 4 forward speeds and 4 reverse speeds (1, 2, 3, 4; synchronized), Range gear with 4 ranges (A, B, C, D; synchronized); power shifted reversing gear (power reverser)

		Forward	Reverse
[C]	No. of gears	4	4
[C]	No. of ranges	4	4
[C]	Total	16	16

3 levers

[D] - Available options (not fitted): SynchroPlus (12/4) 30 km/h, with or without creeper gear
PowrQuad (16/16) 30 km/h, with or without creeper gear

[D] - Lubrication: Forced-feed lubrication, oil cooler (ring cooler) at the rear end of engine block, (low temperature section of water cooler), 2 filters

1.3.3 Rear axle and final drives

[D] - Make/Model/Type: JOHN DEERE / - / bevel gear drive with bevel gear differential and planetary final drives

- Differential lock:

[D] Type: Wet multi-plate

[C] Engagement: Electro-hydraulically by foot switch

[C] Disengagement: By pedal of service brake

1.3.4 Front axle and final drives

[C] - Make/Model/Type: DANA 740/101 / AL 158 127 / swing axle, driving and steering; axle driven through wet multi plate clutch, shaft in median plane of tractor, bevel gear;
clutch electro-hydraulically operated by rocker switch (two positions: engaged / engaged by service brake operation); planetary final drives

- Differential lock:

[D] Type: Limited slip multi-plate type

[C] Engagement: Automatic

[C] Disengagement: Automatic

1.3.5 Total ratios and travelling speeds

	Range	Gear	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed*) at rated engine speed of 2300 min^{-1} km/h
	Forward Speed			
[C]	A	1	362.65	1.96
[C]		2	279.15	2.55
[C]		3	201.04	3.54
[C]		4	157.75	4.51
[C]	B	1	180.91	3.93
[C]		2	139.26	5.11
[C]		3	100.29	7.09
[C]		4	78.70	9.03
[C]	C	1	110.01	6.46
[C]		2	84.68	8.40
[C]		3	60.98	11.66
[C]		4	47.86	14.86
[C]	D	1	53.42	13.31
[C]		2	41.12	17.29
[C]		3	29.61	24.01
[C]		4	23.24	30.60
	Reverse Speed			
[C]	A	1	347.42	2.05
[C]		2	267.42	2.66
[C]		3	192.59	3.69
[C]		4	151.13	4.70
[C]	B	1	173.32	4.10
[C]		2	133.41	5.33
[C]		3	96.08	7.40
[C]		4	75.39	9.43
[C]	C	1	105.39	6.75
[C]		2	81.12	8.76
[C]		3	58.42	12.17
[C]		4	45.85	15.51
[C]	D	1	51.18	13.89
[C]		2	39.39	18.05
[C]		3	28.37	25.06
[C]		4	22.26	31.94

*) Calculated with a dynamic radius index of 820 mm (in conformity with ISO 4251-1:1998)

[D] - Number of revolutions of front wheels for one revolution of rear wheels: 1.3722

1.4 Power take-off

1.4.1 Main power take-off

[C]	- Type:	Independent
[C]	- Method of engagement:	Driven by wet multi-plate clutch with 197 mm dia, electro-hydraulically operated by rotary switch through control valve; response of valve automatically controlled
[C]	- Number of shafts:	1
[C]	- Method of changing power take-off shaft ends and speeds:	Reversible stub giving two different standard speeds

1.4.1.1 Power take-off proportional to engine speed, 540 min^{-1} or 1000 min^{-1} p.t.o.

[C]	- Location:	At rear of tractor
[C]	- Diameter of p.t.o. shaft end:	35 mm
[C]	- Number of splines:	6 (540 min^{-1})in conformity with ISO 500:1991, type 1 21 (1000 min^{-1}) in conformity with ISO 500:1991, type 2
[C]	- Height above ground:	750 mm
[C]	- Distance from the median plane of the tractor:	0 mm
[C]	- Distance behind rear wheel axis:	530 mm

	P.t.o. type	P.t.o. transmission ratio	P.t.o. speed min^{-1}	Engine speed min^{-1}	Power restriction kW	Max. torque transmissible Nm
[D]	540	3.9685	540 580	2143 2300	not specified	
[D]	1000	2.2082	1000 1042	2208 2300	not specified	


[C]	- Direction of rotation (viewed from behind tractor):	Clockwise
1.4.1.2	Power take-off proportional to ground speed:	None
1.4.2	Optional power take-off:	Front p.t.o., independent, not fitted to tractor
1.5	**Hydraulic power lift**	
[D]	- Make/Model/Type:	JOHN DEERE / - / desintegrated, electronically controlled hydraulic power lift, lower link sensing
[C]	- Type of hydraulic system:	Closed center, load sensing pressure and flow compensated system
[C]	- Type and number of cylinders:	2 external cylinders, single acting, 75 mm bore, 175 mm stroke,
[C]	- Type of linkage lock for transport:	Hydraulic, lock of valve lever
[D]	- Relief valve pressure setting:	19.2 to 20.7 MPa
[D]	- Opening pressure of cylinder safety valve:	no safety valve
	- Lift pump:	
[D]	Make:	HEMA Industries
[D]	Model:	-
[D]	Type:	28 cm^3 gear pump with 65 dm^3/min delivery at rated speed

[D]	- Transmission between pump and engine:	Gear driven by transmission
[C]	- Type and number of filters:	2 filters, 1 in feeding line of hydraulic pump, 1 on transmission housing
[C]	- Site of oil reservoir:	Transmission housing
[C]	- Type, number and location of tapping points:	2 double acting, quick-action couplers at rear of tractor
[D]	- Maximum volume of oil available to external cylinders:	Stationary 25 dm^3, driving 15 dm^3
[D]	- Oil cooler:	Engine cooling water / transmission-hydraulic oil heat exchanger at the rear end of engine block

1.6 Three-point linkage:

1.6.1 Three-point linkage at rear:

[C]	- Category:	2, in conformity with ISO 730-1/1994 + Cor. 1:1995 with extendable lower links
[C]	- Category adapter:	None



Dimensions of rear implement linkage				Projected lengths in mm	
				Dimensions	Settings used in test-page 27
[D]	Rear tyres 18.4 R 38 Front tyres 13.6 R 28		(r) *) (r') *)	820 610	
[C]	Length of lift arms		(A)	305	
[C]	Length of lower links		(B)	945	
[C]	Distance of lift arm pivot points from rear wheel axis	horizontal vertical	(a) (b)	180 475	
[C]	Horizontal distance between the 2 lower link pivot points		(u)	485	
[C]	Horizontal distance between the 2 lift arm end points		(v)	530	
[C]	Length of upper link		(S)	from 550 to 730	660
[C]	Distance of upper link pivot point from rear wheel axis	horizontal vertical	(c) (d)	460 185	460 185
[C]	Distance of lower link pivot points from rear wheel axis	horizontal vertical	(e) (f)	135 225	
[C]	Distance of lower link pivot points from lift rod pivot points on lower links		(D)	505	
[C]	Length of lift rods		(L)	from 715 to 860	815

Heights (h, H, H`) of lower link hitch points relative to rear wheel axis (situated 820 mm above ground), at different adjustements of L

These data are valid for unloaded power lift

[C]	Length of lift rods	(L)	715	860	815
[C]	Linkage distance of lift rods	(D)		505	
[C]	Lowest position	(h)	385	710	620
[C]	Highest position	(H)	220	-60	60
[C]	Transport position	(H')	220	-60	60

*) Assuming r resp. r' = tyre dynamic radius index (in conformity with ISO 4251-1:1998)

1.7	**Swinging drawbar**			
[C]	- Type:	Adjustable in height and length		
[C]	- Height above ground	Maximum: Minimum:		580 mm 510 mm
[C]	- Type of adjustment:	Turning the drawbar		
[C]	- Distance of hitch point from rear wheel axis	Horizontal:		780 / 880 / 930 / 1080 mm
[C]	- Distance of hitch point from p.t.o. shaft end	Vertical: Horizontal:		170 / 240 mm 250 / 350 / 400 / 550 mm
[C]	- Lateral adjustment (centre of clevis)	Right/left hand side:		190 / 210 / 225 / 260 mm
[C]	- Distance of pivot point from rear-wheel axis, horizontally:			0 mm
[C]	- Diameter of drawbar pin hole:			33 mm
[C]	- Maximum permissible vertical load:			27 kN
1.8	**Trailer hitch**	None		
1.9	**Holed drawbar**	None		
1.10	**Steering**			
[D]	- Make/Model/Type:	JOHN DEERE and SAUER-DANFOSS/ - / hydrostatic steering, acting on front wheels		
	- Method of operation			
[D]	Pump:	Steering system connected to main hydraulic circuit		
[C]	Ram:	Integrated cylinder of symmetrical design, 250 mm stroke, 75 mm bore, 42 mm dia of piston rod		
[D]	- Working pressure:	18.5 MPa		

1.11 Brakes

1.11.1 Service brake

[D] - Make/Model/ Type: JOHN DEERE / - / muscle power braking system with hydraulic transmission with additional power fill, oil-immersed disc brake with 2 acting faces on each differential half shaft, disc 313 mm dia

[C] - Method of operation: Pedal operated, acting on rear wheels, front axle drive is automatically engaged when braking

[C] -Trailer braking take-off: None

1.11.2 Parking brake

[C] - Type: Parking lock of transmission

[C] - Method of operation: Range gear lever in "P" position

1.12 Wheels

- Number

[C] Front: 2, driving and steering

[C] Rear: 2, driving

[C] - Wheelbase: 2650 mm

- Track width adjustment:

	Minimum mm	Maximum mm	Adjustment method
[D] Front	1516	2016	adjustable rims
[D] Rear	1516	1916	adjustable rims

1.13 Protective structure

[C] - Make/Model/Type: JOHN DEERE / SG070 / Cab

[C] - Manufacturer's name and address: DEERE & COMPANY, Moline, Illinois, USA

- Protective device

[C] Cab: Welded and screwed profile steel tube construction, mounted on silent blocks, for service (repair) with separate device tiltable to the side

[C] Tiltable / not tiltbale: Not tiltable

- OECD approval

[C] Approval number: 4/0 692/1

[C] Date of approval: 7th January 2005

1.14 Seat

1.14.1	Driver's seat	Fitted to tractor
[C]	- Make/Model:	Grammer / MSG 83/20
[C]	- Type:	mechanical suspended upholstered seat with backrest and armrests
[C]	- Seat and steering wheel reversible:	No
[C]	- Type of suspension:	Mechanical
[C]	- Type of damping:	Hydraulic
	- Range of adjustment	
[C]	Longitudinal:	200 mm
[C]	Vertical:	345 to 560 mm
[C]	- Safety belt:	Yes
1.14.2	Optional driver's seats	
[D]	- Make/Model/Type:	Grammer/MSG 95A; MSG 95AL; MSG 93; MSG 85 / mechanical suspension or pneumatic suspension
1.14.3	Passenger seat:	Optional, not fitted to tractor tested

1.15 Lighting

Electrical, 12 Volt, according to US legislation

		Height above ground of centre mm	Size mm	Distance from outside edge of lights to median plane of tractor mm
[C]	Headlights	1325	150 x 90	190
[C]	Sidelights	n.a.	n.a.	n.a.
[C]	Rearlights	1780	230 x 45	900
[C]	Reflectors	1740	160 x 25	865

2. TEST CONDITIONS

2.1 Overall dimensions

	Length mm	Width (track width as in 2.5) mm	Height at top of protective structure mm	Height at top of exhaust silencer pipe mm
Unballasted	4460	2250	2830	2795

2.2 Ground clearance 425 mm

- Clearance-limiting part: Bracket for sway blocks

2.3 Tractor mass Unballasted (with cab)

	Without driver kg	With driver kg
Front	1990	2015
Rear	2945	2995
Total	4935	5010

2.4 Track specifications Not applicable

2.5 Tyres and track widths specifications

	Front	Rear
Tyres:	Goodyear STR	Goodyear STR
- Dimensions	13.6 R 28	18.4 R 38
- Load index speed index	123 A 8	146 A 8
- Type	radial ply	radial ply
- Maximum load (tyre manufacturer's)	16.60 kN	32.20 kN
- Maximum load (tractor manufacturer's)	21.00 kN	32.50 kN
at travelling speed	30 km/h	30 km/h
at tyre inflation pressure	140 kPa	140 kPa
dynamic radius index	610 mm	820 mm
Chosen track width:	1820 mm	1812 mm

2.6 Fuel

- Type:	ARAL-Diesel-fuel, in conformity with DIN 51601	
- Density at 15°C:	At p.t.o. tests	0.8354 g/cm³
	at drawbar power tests	0.8379 g/cm³

2.7 Oils and lubrication

2.7.1 Capacity and change interval

	Capacity dm³	Oil change h	Filter-change h
Engine	20	500	500
Gear box and rear axle	52	1500	750
Front axle	8	1500	-
Rear axle	in common with gearbox		
Final drives (front each)	3	1500	-
Final drives rear (each)	in common with gearbox		
Hydraulic system	in common with gearbox		
Steering	in common with gearbox		

2.7.2 Specifications:

	Recommended	Used during test
Engine oil: Used in engine		Fuchs Titan
Type	engine oil	engine oil
Viscosity	SAE 20W40, 15W40, 10W40, JD PLUS-50, JD TORQ-GARD SUPREME	SAE 15W40
Classification	API CG-4 or CF-4; ACEA - E2 or E3;	API CF-4
Transmission oil: Used in gear box, rear axle, hydraulic system and brake system	John Deere HY-GARD John Deere BIO-HY-GARD	John Deere HY-GARD
Type Viscosity Classification	transmission oil SAE 75 JDM J20C or J20D	transmission oil SAE 75 JDM J20C
Transmission oil: Used in front axle and front final drives	John Deere HY-GARD, John Deere BIO-HY-GARD or transmission oil	Fuchs
Type Viscosity Classification	transmission oil SAE 80W90 JDM J20C	transmission oil SAE 80W90 JDM J20C

2.7.3 Grease Multi purpose grease GC-LB

- Number of lubrication points: 18

3 COMPULSORY TESTS

3.1 Main power take off performance

Date of tests: 2004-11-26
Location of tests: DLG-Testing Station Groß-Umstadt
Type of dynamometer: SCHENCK hydraulic dynamometer U1-40

Power	Speed Engine	Speed P.t.o.	Speed Fan	Fuel consumption hourly	Fuel consumption hourly	Fuel consumption specific	Specific energy
kW	min^{-1}	min^{-1}	min^{-1}	kg/h	dm^3/h	g/kWh	kWh/dm^3
Maximum power							
3.1.1 At 2-hour test							
88.8	2000	906	1333	21.84	26.14	246	3.40
3.1.2 At rated speed							
80.1	2300	1042	1310	21.75	26.04	272	3.08
3.1.3 At standard p.t.o. speed							
86.1	2208	1000	1294	22.61	27.06	263	3.18
3.1.4 Part loads, the governor hand lever in the position corresponding to maximum power at full load (curve a)							
3.1.4.1 the torque corresponding to maximum power at rated speed							
80.1	2300	1042	1310	21.75	26.04	272	3.08
3.1.4.2 85% of the torque obtained in 3.1.4.1							
70.0	2364	1071	1318	19.92	23.84	284	2.94
3.1.4.3 75% of the torque defined in 3.1.4.2							
53.3	2395	1085	1329	17.32	20.73	325	2.57
3.1.4.4 50% of the torque defined in 3.1.4.2							
36.1	2431	1101	1346	14.06	16.83	389	2.15
3.1.4.5 25% of the torque defined in 3.1.4.2							
18.2	2455	1112	1345	10.69	12.80	587	1.42
3.1.4.6 unloaded							
-	2460	1114	1346	7.82	9.36	-	-

Power kW	Speed Engine min^{-1}	Speed P.t.o. min^{-1}	Fan min^{-1}	Fuel consumption hourly kg/h	Fuel consumption hourly dm^3/h	Fuel consumption specific g/kWh	Specific energy kWh/dm^3
3.1.5 Part loads, the governor hand lever in the position corresponding to standard p.t.o. speed at full load (curve b)							
3.1.5.1 the torque corresponding to maximum power							
86.1	2208	1000	1294	22.61	27.06	263	3.18
3.1.5.2 85% of the torque obtained in 3.1.5.1							
76.1	2294	1039	1289	20.89	25.01	275	3.04
3.1.5.3 75% of the torque defined in 3.1.5.2							
57.6	2318	1050	1304	17.53	20.98	304	2.74
3.1.5.4 50% of the torque defined in 3.1.5.2							
38.7	2336	1058	1320	14.16	16.95	366	2.28
3.1.5.5 25% of the torque defined in 3.1.5.2							
19.6	2360	1069	1312	10.39	12.44	531	1.57
3.1.5.6 unloaded							
-	2372	1074	1319	7.32	8.77	-	-

OPTIONAL RESULTS

Power	Speed		Fan	Fuel consumption			Specific
	Engine	P.t.o.		hourly		specific	energy
kW	min^{-1}	min^{-1}	min^{-1}	kg/h	dm^3/h	g/kWh	kWh/dm^3

3.1.6 Part loads at different engine speeds

3.1.6.1 maximum power at rated engine speed

80.1	2300	1042	1310	21.75	26.04	272	3.08

3.1.6.2 80% of power obtained in 3.1.6.1 at max. speed setting

64.1	2380	1078	1284	18.96	22.70	296	2.82

3.1.6.3 80% of power obtained in 3.1.6.1
with governor control set to 90% of rated engine speed

64.2	2071	938	1208	17.35	20.77	270	3.09

3.1.6.4 40% of power obtained in 3.1.6.1
with governor control set to 90% of rated engine speed

32.0	2071	938	1192	11.02	13.19	344	2.43

3.1.6.5 60% of power obtained in 3.1.6.1
with governor control set to 60% of rated engine speed

48.2	1377	624	1100	12.11	14.50	252	3.32

3.1.6.6 40% of power obtained in 3.1.6.1
with governor control set to 60% of rated engine speed

32.0	1382	626	1102	9.00	10.77	281	2.97


No load maximum engine speed:	2460	min^{-1}
Equivalent flywheel torque at rated engine speed:	333	Nm
Equivalent flywheel torque at 2-hour test:	424	Nm
at engine speed:	2000	min^{-1}
Maximum equivalent flywheel torque:	461	Nm
at engine speed:	1600	min^{-1}


Mean atmospheric conditions

temperature:	19	°C
pressure:	100.5	kPa
relative humidity:	38	%

Maximum temperatures

coolant:	84	°C
oil:	104	°C
fuel:	46	°C
air intake:	19	°C


p.t.o. test
P
M
B
be
John Deere 6715 NA PowerReverser
standard p.t.o. speed 1000 min-1
p.t.o. power P [kW]
equivalent torque M [Nm]
fuel consumption B [kg/h]
spec. fuel consumption be [g/kWh]
engine speed n [min-1]
100
90
80
70
60
50
40
30
20
10
0
750
675
600
525
450
375
300
225
150
75
0
20
15
10
5
0
360
320
280
240
200
800
1000
1200
1400
1600
1800
2000
2200
2400
2600


p.t.o. test
specific fuel consumption be [g/kWh]
640
600
560
520
480
440
400
360
320
280
240
200
0
20
40
60
80
100
p.t.o. power P [kW]
be
curve a
curve b
John Deere 6715 NA PowerReverser

3.2 HYDRAULIC POWER AND LIFTING FORCE

- Date of tests: 17th January 2005

3.2.1 Hydraulic power test

3.2.1.1 Hydraulic fluid data

- Hydraulic fluid type: Transmission oil
- Viscosity index (ISO 3448+Corr 1:1993): SAE 75
- Viscosity at 65°C: n.a.

3.2.1.2 Compulsory Reporting (Test Results):

	Pressure	Reservoir oil Temperature °C (65°C target)		Engine speed	Flow rate	Power
		Min.	Max.			
	MPa	°C	°C	min^{-1}	l/min	kW
Rated Engine Speed *(Manufacturers Specification)*	-	-	-	2300	-	-
3.2.1.2.1 Maximum (sustained) pressure with relief valve open as measured at the coupler Pump stalled: No	19.2 [1)] 19.3 [2)]	61 [1)] 64 [2)]	61 [1)] 64 [2)]	2449 [1)] 2451 [2)]	-	-
3.2.1.2.2 Flow rate corresponding to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting and corresponding hydraulic power	17.3 [1)] 17.4 [2)]	63 [1)] 63 [2)]		2451 [1)] 2451 [2)]	48.3 [1)] 60.6 [2)]	13.8 [1)] 17.6 [2)]
3.2.1.2.3 Maximum available flow and maximum power from one coupler pair	1.9 16.0	60 61		2460 2453	70.7 62.5	- 16.7
3.2.1.2.4 Maximum available flow and maximum power from coupler pairs operating simultaneously (flow through two or more coupler pairs if required)	2.0 17.2	60 63		2458 2453	73.7 63.2	- 18.1

- Tapping point used for test: At rear of tractor.

[1)] 1 double acting control valve
[2)] 2 double acting control valves parallel connection

3.2.2 Power lift test at rear power lift

	At the hitch points	On the frame
Height of lower hitch points above ground in down position	200 mm	
Vertical movement without lifting forces	685 mm	889 mm
with lifting forces	656 mm	828 mm
Max. corrected force exerted through full range	26.50 kN	24.15 kN
Corresponding pressure	17.3 MPa	
Moment about rear axle	28.60 kNm	40.80 kNm
Max. tilt angle of mast from vertical	-	12 °

Lifting heights relative to horizontal lower links											
mm	-474	-395	-300	-200	-100	0	+100	+200	+261	+300	+354
Lifting forces at hitch points, corrected to 17.3 MPa											
kN		26.50	32.15	35.95	38.80	41.15	43.50	45.10	43.40		
Lifting forces at standard frame, corrected to 17.3 MPa											
kN	24.15	26.35	28.05	28.95	29.80	29.60	29.80	29.50		28.65	27.80

John Deere 6715 NA PowerReverser (4WD) **DLG-Test No. 2004-392**

3.3 DRAWBAR POWER TEST (unballasted tractor)

Date of tests: 1st and 2nd December 2004
Type of track: Concrete

	Height of drawbar above ground	Tyre inflation pressure Front	Rear
Unballasted	475 mm	80 kPa	80 kPa

Gear number and range	Power	Drawbar pull	Speed	Engine speed	Slip of wheels	Fan speed	Specific fuel consumption	Specific energy	Temperature Fuel	Coolant	Engine oil	Atmospheric conditions Tempe-rature	Relative humidity	Pressure
	kW	kN	km/h	min^{-1}	%	min^{-1}	g/kWh	kWh/dm^3	°C	°C	°C	°C	%	kPa

3.3.1 MAXIMUM POWER IN TESTED GEARS (unballasted tractor)

A4	54.0	49.34	3.94	2369	15.0	1222	371	2.26	30	71	105	5	100	98.9
B2	61.0	49.92	4.40	2340	15.1	1246	355	2.36	33	74	108	5	100	98.9
C1	72.6	52.29	5.00	1995	10.8	1287	301	2.79	36	74	106	5	100	98.8
B3	74.6	47.71	5.63	2001	8.6	1188	292	2.87	35	75	106	5	100	98.9
C2	76.7	39.88	6.93	1996	5.8	1347	286	2.93	38	75	106	5	100	98.8
B4	77.8	37.68	7.44	2001	5.3	1181	280	3.00	35	75	106	5	100	98.9
C3	77.3	28.46	9.77	2002	3.5	1336	283	2.96	38	76	106	5	100	98.8
D1	77.1	24.64	11.27	2001	2.9	1266	283	2.96	37	76	105	5	100	98.8
C4	77.3	22.07	12.61	2009	2.9	1349	285	2.94	37	75	105	5	100	98.8
D2	76.3	18.71	14.68	1999	2.2	1304	288	2.91	36	74	105	5	100	98.8

John Deere 6715 NA PowerReverser (4WD) **DLG-Test No. 2004-392**

Gear number and range	Power	Drawbar pull	Speed	Engine speed	Slip of wheels	Fan speed	Specific fuel consumption	Specific energy	Temperature			Atmospheric conditions		
									Fuel	Coolant	Engine oil	Tempe-rature	Relative humidity	Pressure
	kW	kN	km/h	min^{-1}	%	min^{-1}	g/kWh	kWh/dm^3	°C	°C	°C	°C	%	kPa
	FUEL CONSUMPTION													
3.3.2.1	In selected gear. at maximum power at rated speed													
B4	70.3	29.06	8.71	2301	3.6	1282	308	2.72	32	73	105	5	100	99.1
3.3.2.1.1	75 % of pull at maximum power at rated speed													
B4	54.7	21.63	9.11	2384	2.6	1360	344	2.43	32	72	106	5	100	99.1
3.3.2.1.2	50 % of pull at maximum power at rated speed													
B4	36.7	14.21	9.29	2412	1.7	1372	421	1.99	31	71	105	5	100	99.1
3.3.2.1.3	Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.1													
C3	55.0	21.67	9.14	1851	2.7	1210	295	2.84	31	71	105	5	100	99.1
3.3.2.1.4	Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.2													
C3	36.8	14.25	9.30	1869	1.7	1204	341	2.46	30	69	102	5	100	99.1
3.3.2.2	In selected gear nearest to 7.50 km/h at rated speed													
B3	68.6	36.52	6.76	2301	4.7	1292	316	2.65	31	72	107	5	100	99.1
3.3.2.2.1	75 % of pull at maximum power at rated speed													
B3	53.7	27.26	7.09	2384	3.2	1355	351	2.38	31	71	106	5	100	99.1
3.3.2.2.2	50 % of pull at maximum power at rated speed													
B3	36.4	18.06	7.26	2413	2.4	1370	424	1.97	29	69	105	5	100	99.1
3.3.2.2.3	Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.1													
C2	53.6	27.31	7.07	2014	3.6	1215	306	2.74	31	71	103	5	100	99.1
3.3.2.2.4	Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.2													
C2	36.6	18.12	7.28	2040	2.2	1224	359	2.33	31	69	101	5	100	99.1

ADDITIONAL TESTS under the responsibility of the DLG Testing Station

Not covered by the approval!

4.1 Measurement of noise at the driving position carried out in accordance with OECD CODE 5

Results of sound level test - "Under load" procedure

Date of test: 29th November 2004
Type of track: Concrete
Type of sound level meter: NORSONIC 118

Gear number and range	Drawbar pull	Engine speed	Measured travelling speed	Number of driving wheels	Sound level
	kN	min^{-1}	km/h		dB(A)
4.1.1	Test with the drawbar pull for which the tractor gives the maximum sound level (gear ratio giving the nearest nominal forward speed to 7.5 km/h and also in any speed settings with a sound level increase of at least 1 dB(A))				
4.1.1.1	All openings closed				
B3	35.45	2302	6.77	4	69.5
C3	21.03	2309	11.40	4	70.5
D1	18.33	2305	13.04	4	70.5
C4	16.47	2303	14.56	4	70.5
D2	13.77	2297	16.95	4	71.0
B3	36.07	2304	6.31	2	69.0
B1	38.20	2348	3.49	2	70.0
A4	38.09	2323	4.00	2	70.5
C3	21.50	2303	11.18	2	70.0
D1	18.51	2307	12.87	2	70.5
C4	16.40	2314	14.43	2	70.5
4.1.1.2	All openings open*)				
B3	34.68	2301	6.79	4	80.5
B3	36.39	2301	6.39	2	79.5

*) Openings: 2 side windows. rear window

Gear number and range	Drawbar pull	Engine speed	Measured travelling speed	Number of driving wheels	Sound level
	kN	min^{-1}	km/h		dB(A)
4.1.2 Unloaded test in the gear ratio giving the forward speed nearest to 7.5 km/h					
4.1.2.1 All openings closed					
B3	0	2460	7.56	4	70.0
B3	0	2460	7.52	2	69.5
4.1.2.2. All openings open *)					
B3	0	2460	7.56	4	80.0
B3	0	2460	7.52	2	80.0
4.1.3 Unloaded test in the gear ratio giving the maximum forward speed					
4.1.3.1 All openings closed					
D 4	0	2460	32.19	2	72.0
4.1.3.2 All openings open *)					
D 4	0	2460	32.19	2	81.0

*) Openings: 2 side windows. rear window

5	**REPAIRS**	**None**
6	**REMARKS**	**None**

Head of Vehicle Technology

Test carried out by

Dipl.-Ing. (FH) Ottmar Degrell

Dipl.-Ing (FH) Thomas Feuerstein

Date: 13th June 200

John Deere 6715 NA PowerReverser (4WD) **DLG-Test No. 2004-392**



Deutsche Landwirtschafts-Gesellschaft e.V.
Testzentrum Technik und Betriebsmittel
Max-Eyth-Weg 1, D-64823 Groß-Umstadt
Telefon: 0 60 78 / 96 35 0 Fax: 0 60 78 / 96 35 90
E-mail: Tech@DLG.org, Internet: www.DLG.org/landtechnik