OECD APPROVAL NO. 2/2 048
CODE 2
DATE OF APPROVAL: 20 February 2003

NEBRASKA TRACTOR TEST LABORATORY
DEPARTMENT OF BIOLOGICAL SYSTEMS ENGINEERING
INSTITUTE OF AGRICULTURE AND NATURAL RESOURCES
UNIVERSITY OF NEBRASKA - EAST CAMPUS
LINCOLN, NEBRASKA 68583-0832, USA

REPORT ON TEST IN ACCORDANCE WITH OECD STANDARD CODE 2 FOR THE OFFICIAL TESTING OF AGRICULTURAL TRACTORS



JOHN DEERE 9120
Powershift
Articulated 4 Wheel Drive with Dual Wheels

MANUFACTURED BY:	**John Deere Tractor Works** **3500 East Donald Street** **P.O. Box 270** **Waterloo, Iowa 50704-0270**
NEBRASKA TEST NO.	**1810**
TEST DATES:	**September 23 – September 27, 2002**

TABLE OF CONTENTS

Page

1. **SPECIFICATIONS** 1

2. **TEST CONDITIONS** 15

3. **COMPULSORY TESTS**
   - **3.1** Main Power Take-Off Performance 18
   - **3.2** Hydraulic Power and Lifting Forces 19
   - **3.3** Drawbar Performance 21

4. **OPTIONAL TESTS**
   - **4.1** Drawbar Power (Unballasted – 2100 rev/min) 22
   - **4.2** Measurement of External Noise Level 23
   - **4.3** Measurement of Noise Level at Operator's Ear 23

5. **REPAIRS** 23

6. **REMARKS** 23

7. **PTO PERFORMANCE CURVES** 24

This test report provides the results of the tests conducted in accordance with the OECD Standard Test Code for the Official Testing of Agricultural Tractor Performance - C(87)53 Final, Code 2.

This report has been approved by the OECD Coordinating Centre in Paris on 20 February 2003 for the John Deere 9120 Powershift, articulated four-wheel drive tractor with OECD Number 2/2 048.

No reproduction of this report or any part of it can be made without prior approval by the Nebraska Tractor Test Laboratory, Lincoln, Nebraska USA.

Dr. Leonard L. Bashford, Director
Nebraska Tractor Test Laboratory and
Chair, Nebraska Tractor Test Board

David L. Morgan, Assistant Director
Nebraska Tractor Test Laboratory

Brent T. Sampson, Test Engineer
Nebraska Tractor Test Laboratory

Date: MAR 2 1 2003

SPECIMEN TEST REPORT

Note: Units shown below, which appear in ISO 1000:1992, shall be stated and followed by national units in parentheses, if necessary.

- Tractor manufacturer's name and address:	John Deere Tractor Works 3500 East Donald St. P.O. Box 270 Waterloo, IA 50704-0270
- Location of tractor assembly:	Same
- Submitted for test by:	The Manufacturer
- Selected for test by:	The Manufacturer in agreement with the Nebraska Tractor Test Laboratory
- Place of running-in:	John Deere Product Engineering Center, Waterloo, Iowa
- Duration of running-in:	115 hours
- Location of test:	Nebraska Tractor Test Laboratory, Lincoln, Nebraska U.S.A.

1. SPECIFICATIONS OF TRACTOR

1.1 Identification

1.1.1 Make of the tractor:	John Deere
- Model:	9120
- Type:	Articulated frame, four-wheel drive
- Number of driving wheels:	4; 8; 12
1.1.2 *Numbers*	
- 1st Serial N :	CONFIDENTIAL
- Serial N :	RW9120P002038
1.1.3 *Other specifications:*	
- Transmission type	Powershift

1.2 Engine

- Make:	John Deere
- Model:	6081HRW30
- Type:	4-stroke diesel; direct injection; turbocharged; air-to-air aftercooled
- Serial N:	RG6081H209014
1.2.1 *Cylinders*	
- Number/disposition:	6, in-line, vertical
- Bore/stroke:	115.8 mm/ 128.5 mm
- Capacity:	8134 cm^3
- Compression ratio:	15.7:1
- Arrangement of valves:	Overhead
- Cylinder liners (wet or dry):	Wet; replaceable

1.2.2 *Supercharging*

- Make:	Borg Warner
- Model:	RE508197
- Type:	Exhaust Driven
- Pressure:	190 kPa at rated engine speed and full load

1.2.3 *Fuel system*

-Fuel feed system:	Transfer pump with HPCR system
-Type of fuel filter(s):	Fuel Filter/ Water Separator
-Make:	RACOR
-Model:	RE507284
-Capacity of fuel tank:	1026 dm^3
-Type of injection pump:	HPCR; electronic
-Make:	Denso
-Model:	RE501640
-Serial N:	NA
-Manufacturer's production setting of injection pump	
· Flow rate (rated engine speed and full load):	54.5 ± 2 liter/hr
· Timing:	Variable
-Type of injectors:	HPCR Injection
-Make:	Denso
-Model:	RE501010
-Injection pressure:	120 Mpa
-Type of carburetor:	NA
-Make:	NA
-Model:	NA

1.2.4 *Governor*

- Make:	John Deere
- Model:	Focus
- Type:	Electronic Control
- Governed range of engine speed	900 rpm to 2240 rpm
- Rated engine speed:	2100 min^{-1}(rev/min)

1.2.5 *Air cleaner*

-Pre-cleaner	
· Make:	Donaldson
· Model:	RE63932
· Type:	Strato-tube pre-cleaner with aspirator
·Location of air intake:	Top of Air Stack, right front corner of cab
-Main cleaner	
· Make:	Donaldson
·Model:	RE63931

· Type:	Pleated Paper
·Location of air intake (in case of no pre cleaner):	Right Front
-Maintenance indicator:	Dash mounted warning light and audible signal

1.2.6 *Lubrication system*

- Type of feed pump:	Full pressure; positive displacement
- Type of filter(s):	Full flow
- Number of filters:	One; top load
- Oil Cooler:	Heat exchanger with engine coolant

1.2.7 *Cooling system*

- Type of coolant:	Liquid
- Type of pump:	Centrifugal, Gear-driven
- Specification of fan or blower	Belt driven; suction type; variable speed
· Number of fan blades:	8
· Fan diameter:	711 mm
- Coolant capacity:	52 dm^3
- Type of temperature control:	2 thermostats and variable speed fan
- Superpressure system:	69 ± 5 kPa

1.2.8 *Starting system*

- Make:	Delco-Remy
- Model:	RE61547
- Type:	Solenoid engaged
- Starter motor power rating:	6.9 kW
- Cold starting aid:	Ether spray in intake manifold
- Safety device:	Electrical lockout on gearshift lever

1.2.9 *Electrical system*

- Voltage:	12 V DC; neg ground
- Generator	
· Make:	Nippondenso
· Model	RE46608
· Type:	Belt-driven
· Power:	1.9 kW
- Battery of accumulators	
· Number:	Two; 12-volt batteries in parallel
· Rating	925 cold crank amp/battery, 175 Ah/battery at 20h rating

1.2.10 *Exhaust system*

- Make:	Nelson (muffler)
- Model:	RE71295
- Type:	Expansion Chamber
- Location:	Vertical muffler, right front corner of cab

1.3 Transmission

1.3.1 *Clutch (travel and power take-off/travel alone)*

- Make:	John Deere
- Model:	Multiple Plate
- Type:	Oil Cooled
- Number of plates:	7
- Diameter of plates:	279 mm
- Method of operation:	Hydraulic, pedal actuated

1.3.2 *Gear box*

- Make:	John Deere
- Model:	Full Powershift
- Type:	Mechanical
- Description:	Countershaft design consisting of 8 multi-disk hydraulically cooled clutches and multi-disk hydraulically cooled planetary brake.

	Forward	Reverse
Number of gears	18	6
Number of ranges/groups	NA	NA
Total of arrangements	18	6

Available Options

- Make: John Deere
- Model: 24 spd PowrSync
- Type: Mechanical
- Description: Countershaft design consisting of one 3-speed gearbox with 4 synchronized ranges and one two-speed planetary gearset with multiple wet discs.

	Forward	Reverse
Number of gears	3	1
Number of ranges/groups	4/2 (Lo & Hi)	3/2 (Lo & Hi)
Total of arrangements	24	6

- Make: John Deere
- Model: 12-speed Syncro
- Type: Mechanical
- Description: Countershaft design consisting of one 3-speed gearbox with 4 synchronized ranges.

	Forward	Reverse
Number of gears	3	1
Number of ranges/groups	4	3
Total of arrangements	12	3

1.3.3 *Rear axle and final drives*

- Make: John Deere
- Model: NA
- Type: Spiral bevel gear and pinion, differential and inboard planetary reduction

- Differential lock
  - Type: Electro/Hydraulic
  - Method of engagement: Foot operated switch
  - Method of disengagement: Self-disengaging w/ brake operation;

1.3.4 *Front axle and final drives*

- Make: John Deere
- Model: NA
- Type: Spiral bevel gear and pinion, differential and inboard planetary reduction

- Differential lock
  - Type: Limited slip
  - Method of engagement: Self-engaging
  - Method of disengagement: Self-disengaging

1.3.5 *Total ratios and traveling speeds*

Gear No.	Number of engine revolutions for one revolution of the driving wheels	Nominal traveling speed (*) at rated engine speed of 2100 min-1 (rev/min) km/h
1	192.5600	3.92
2	156.4343	4.83
3	141.2714	5.35
4	126.5228	5.98
5	114.7985	6.59
6	102.7842	7.36
7	92.8414	8.15
8	83.1471	9.09
9	75.4414	10.02
10	67.5700	11.19
11	61.0242	12.39
12	55.2242	13.69
13	49.5900	15.24
14	44.8671	16.85
15	36.2914	20.83
16	29.4971	25.63
17	23.8628	31.69
18	19.3885	39.00
1R	192.5600	3.92
2R	141.2714	5.35
3R	126.5228	5.98
4R	92.8414	8.15
5R	83.1471	9.09
6R	61.0242	12.39
	*Tire Rolling Radius	955 mm

- Number of revolutions of front wheels for one revolution of rear-wheels: 1.000

1.4 Power take-off (Optional; Installed on tested machine)

1.4.1 *Main power take-off*

-Type (independent, semi-independent or not independent):	Independent
-Method of engagement (if necessary describe the type of clutch):	Electro-Hydraulically actuated multi-plate wet clutch operated by single hand control switch
-Number of shafts:	One, 1000RPM only
-Method of changing power take-off shaft ends and speeds:	None

1.4.1.1 Power take-off proportional to engine speed

Power take-off at 1000 min^{-1} (rev/min)

- Location:	Rear of tractor, center plane
- Diameter of power take-off shaft end:	44.5 mm
- Number of splines:	20; in conformity with ISO 500:1991
- Height above ground:	817 mm
- Distance from the median plane of the tractor:	0 mm
- Distance behind rear-wheel axis:	760 mm
- PTO speed at rated engine speed (2100 rev/min):	1108 min^{-1} (rev/min)
- Engine speed at standard power take-off speed:	1895 min^{-1} (rev/min)
- Ratio of rotation speeds (engine speed/p.t.o. speed):	1.895:1
- Power restriction:	Maximum power available
- Maximum torque transmissible:	Maximum torque available
- Direction of rotation (viewed from behind tractor):	Clockwise

1.4.1.2 Power take-off proportional to ground speed — Not Available

1.5 Hydraulic power lift

- Make:	John Deere
- Model:	NA
- Type:	Electro-Hydraulic lower link sensing; variable mix of draft and position control; adjustable rate of drop
-Type of hydraulic system:	Closed center, pressure and flow compensated
-Type and number of cylinders (single or double-acting):	2 external/ single acting Category III: Two; 90 x 276
-Type of linkage lock for transport:	Electro-hydraulic
-Relief valve pressure setting (tolerance):	20.20 ± 0.40 Mpa
-Opening pressure of cylinder safety valve (if fitted):	23.25 ± 0.50 Mpa
-Lift pump type:	Axial piston, variable pressure and flow; Pressure and flow compensated
-Transmission between pump and engine:	Direct drive from transmission
-Type and number of filters:	Spin-on canister/ one
-Site of oil reservoir:	Under hood; engine compartment
-Type, number and location of tapping points:	4 pairs of ISO standard couplings at rear of tractor; 5th coupler optional. Additional inlet/outlet pair for externally controlled implements
-Maximum volume of oil available to external cylinders:	31.81 dm^3

1.6 Three point linkage




Figure 2.1
Lift test - Linkage Geometry




Figure 2.2
Lift test - Linkage Geometry

1.6.1 Three point linkage (Optional – not fitted on the tested tractor)

- Category: 3, in conformity with ISO 730-1:1994 +Cor. 1:1995 and ISO 730-2:1979.
- Category adapter: -Quick attaching coupler

		Dimension or range	Settings used in test
		mm	mm
Lift category:		3	3
Rear Tire – Radius Index:	(r)	955	905
Front Tire – Radius Index:	(r')	955	905
Length of lift arms:	(A)	472	same
Length of lower links:	(B)	1117	same
Distance of lift arm pivot point from rear-wheel axis:			
- horizontally	(a)	244	same
- vertically	(b)	620	same
Horizontal distance between the 2 lower link points:	(u)	640	same
Horizontal distance between the 2 lift arm end points:	(v)	750	same
Length of upper link:	(S)	705 to 825	781
Distance of upper link pivot point from rear wheel axis:			
- horizontally	(c)	577	same
- vertically	(d)	288	same
Distance of lower link pivot point from rear wheel axis:			
- horizontally	(e)	288	same
- vertically	(f)	350	same
Distance of lower link pivot points to lift rod pivot points on lower links:	(D)	731	same
Length of lift rods:	(L)	1030 to 1150	1121
Height of lower hitch points relative to the rear-wheel axis:			
- in low position	(h)	521 to 724	676
- in high position	(H)	89 to 284	118
Height above ground of lower hitch points when locked in transport position (*)		1005 to 1201	1022
(*) Assuming r = 905 mm tyre dynamic radius index (pneumatic tyred tractors only)			

1.7 Swinging drawbar

-Type:	Oscillating
-Height above ground	
· Maximum:	489 mm
· Minimum:	464 mm
-Type of adjustment:	Invert drawbar; removable clevis
-Distance of hitch point from rear-wheel axis, horizontally:	1268 mm
-Distance of hitch point from power take-off shaft end	
· Vertically:	300 mm
· Horizontally:	508 mm
-Lateral adjustment (centre of clevis)	
· Right hand	200 mm
· Left hand	200 mm
-Distance of pivot point from rear-wheel axis, horizontally:	585 mm
-Diameter of drawbar pin hole:	52.5 mm
-Maximum vertical permissible load:	20 kN

1.8 Trailer hitch

Not available

1.9 Holed drawbar

Not available

1.10 Steering

- Make: Eaton
- Model: RE61112
- Type: Hydrostatic
- Method of operation: Steering wheel
  - Pump(s): Same as main hydraulic pump
  - Ram(s): Two external; double acting
- Working pressure: 18.4 ± 0.4 Mpa

1.11 Brakes

1.11.1 *Service brake*

- Make: Vickers-John Deere
- Model: RE175393
- Type: Load sensing power with manual backup
- Method of operation: Hydraulic oil immersed disc operated by one pedal
- Trailer braking take-off (hydraulic or air brake): Not available

1.11.2 *Parking brake*

- Type: PST--Spring applied, Hydraulic release; MST—Transmission Lock
- Method of operation: Gear selector lever

1.12 Wheels

- Number
  - Front: 2; 4; 6 driving and steering
  - Rear: 2; 4; 6 driving and steering
- Wheelbase: 3500 mm

- Track width adjustment:

	Minimum	Maximum	Adjustment
	mm	mm	method
Inner wheels	1690	2060	Rack axle, reversing wheels and offset rims
Outer wheels	3240	3615	Same as inner wheels

1.13 Protective structure

- Make:	John Deere
- Model:	SG-079
- Type:	Sound-Gard body
- Manufacturer's name and address:	John Deere Tractor Works Waterloo, Iowa, USA
- Protective device	
· Cab/frame/ rollguard/ other:	Cab
· Tiltable/not tiltable:	Not tiltable
- OECD approval	
· Approval number:	4/0 717
· Date of approval:	4 April 2002
· Nos. of minor modification certificates, if any:	None

1.14 Seat

1.14.1 *Driver's seat*

- Make:	John Deere
- Model:	Comfort Command
- Type:	Air Cushion Suspension
- Seat and steering wheel reversible: Yes/No	No
- Type of suspension:	Air
- Type of damping:	Adjustable, viscous damping
- Range of adjustment	
· Longitudinally:	178 mm
· Vertically	172 mm
- Safety belt Yes/No	Yes

1.14.2 *Optional driver's seat(s)*

- Make:	John Deere
- Model:	John Deere Active Seat ™
- Type of suspension:	Air/Hydraulic
- Type of damping:	Active Position Control
- Range of adjustment	
· Longitudinally:	178 mm
· Vertically:	172 mm travel; 92 mm adjustment range

1.14.3 *Instructional seat*

- Location:	Optional Instructional Seat located left of drivers seat
- Capacity (number):	One

1.15 Lighting

	Height above ground of centre	Size	Distance from outside edge of lights to median plane of tractor
	mm	mm	mm
Headlights			
Outside	2185	135 x 90	445
Inside	2185	155 x 115	270
Center	2185	130 x 85	65
Sidelights			
Front	3480	160 x 110	955
Rear	3480	160 x 110	955
Rear lights			
Outside	2050	160 x 110	980
Inside	2050	160 x 110	785
Hazard Lights			
Roof Front	3380	82 x 240(*)	715
Roof Rear	3340	82 x 240(*)	715
Extremity Lights		110 dia	
Tail lights	1855	210 x 95	900

(*) Wrap-around lights

2. TEST CONDITIONS

Separate tables may be added to report other test conditions or equipments.

2.1 Overall dimensions

	Length	Width		Height at top of	
		minimum	maximum	protective structure	exhaust pipe
	mm	mm	mm	mm	mm
Unballasted	7315	3860	4235	3530	3896
Ballasted	NA	NA	NA	NA	NA

2.2 Ground clearance (unballasted tractor): 315 mm

- Clearance-limiting part: Drawbar rear support

2.3 Tractor mass

Mass (with cab, full fuel tank):

	Without driver	With driver
	kg	kg
Unballasted		
Front	9145	9190
Rear	6905	6935
Total	16050	16125

2.5 Tyres and track width specifications

		Front	Rear
Tyres:		Goodyear	Goodyear
- dimensions		620/70R46	620/70R46
- load index		162	162
- type		Radial DT – 820	Radial DT - 820
- maximum load (tyre manufacturer's)		4750 kg/tire	4750 kg/tire
- maximum load (tractor manufacturer's)		4750 kg/tire	4750 kg/tire
- inflation pressure (tyre manufacturer's)		160 kPa	160 kPa
- dynamic radius index		955 mm	955 mm
Chosen track width with dual wheels:	inner	1990 mm	1990 mm
	outer	3565 mm	3565 mm

2.6 Fuel

-Type: No. 2 diesel in conformity with national standard

- Density at 15°C: 0.842 g/cm^3

2.7 Oils and lubricants

2.7.1 *Capacity and change interval*

	Capacity	Oil change	Filter change
	dm^3	h	h
Engine	26.5	250 (375 with John Deere PLUS-50 oil and John Deere filter)	250
Transmission with front axle and rear axle	174 (PST) 134 (12/24spd)	1500	750
Hydraulic system combined and steering system	102	1500	750

2.7.2 *Specifications (SAE, API, CCMC, ACEA, Mil.L, ISO)*

	Recommended	Used during test
Engine oil · Type: · Viscosity: · Classification:	 John Deere; Torq-Gard Supreme, PLUS-50 SAE 15W40 or 10W-40 12.5 - 16.3 cSt @ 100 C API CF-4; CH-4; ACEA E2	 SAE 15W40
Transmission oils · Type: · **Viscosity:** · Classification:	 John Deere HY-GARD; J20C SAE 10W-30 **58 cSt at 43 C** NA	 same
Hydraulic fluid	Same as Transmission	same
Steering oil	Same as Transmission	same
Grease	John Deere Moly High Temperature EP Grease	same

2.7.3 *Grease*

- Number of lubrication points: 20

3. COMPULSORY TESTS RESULTS

3.1 Main power take-off

- Date and location of tests: 23-Sep-02 Nebraska Tractor Test Laboratory, Lincoln, NE, USA
- Type of dynamometer bench: Eaton


	Speed		Fuel consumption			Specific energy
Power	Engine	PTO	Hourly		Specific	
kW	rev/min		kg/h	l/h	g/kWh	kW-h/l
3.1 MAXIMUM POWER - TWO HOUR TEST						
196.10	1900	1003	45.93	54.58	234	3.59
3.1.2 POWER AT RATED ENGINE SPEED						
182.37	2100	1109	46.36	55.09	254	3.31
3.1.3 STANDARD POWER TAKE-OFF SPEED (1000 +/- 25 rev/min)						
196.10	1900	1003	45.93	54.58	234	3.59
3.1.4 PART LOADS						
3.1.4.1 the torque corresponding to maximum power at rated engine speed						
182.37	2100	1109	46.36	55.09	254	3.31
3.1.4.2 85% of torque obtained in 3.1.4.1						
159.07	2159	1140	42.46	50.45	267	3.15
3.1.4.3 75% of torque defined in 3.1.4.2						
120.13	2177	1150	34.84	41.40	290	2.90
3.1.4.4 50% of torque defined in 3.1.4.2						
79.95	2199	1161	27.76	32.99	347	2.42
3.1.4.5 25% of torque defined in 3.1.4.2						
40.77	2220	1172	20.00	23.77	491	1.72
3.1.4.6 unloaded						
0.84	2238	1182	11.84	14.07	14109	0.06
3.1.5 PART LOADS AT STANDARD POWER TAKE-OFF SPEED (1000 +/- 25 rev/min)						
3.1.5.1 the torque corresponding to maximum power						
196.10	1900	1003	45.93	54.58	234	3.59
3.1.5.2 85% of torque obtained in 3.1.5.1						
171.43	1955	1032	41.10	48.83	240	3.51
3.1.5.3 75% of torque defined in 3.1.5.2						
130.32	1980	1046	33.20	39.45	255	3.30
3.1.5.4 50% of torque defined in 3.1.5.2						
87.79	2001	1057	25.85	30.72	294	2.86
3.1.5.5 25% of torque defined in 3.1.5.2						
44.35	2022	1068	17.42	20.70	393	2.14
3.1.5.6 unloaded						
0.77	2045	1080	10.07	11.97	13134	0.06

- No load maximum engine speed: 2238 rev/min
- Torque (equivalent crankshaft) at rated speed:
  - At rated engine speed 829 Nm
  - At 2-hour test 986 Nm
- Maximum torque (equivalent crankshaft): 1185 Nm
  (engine speed: 1400 rev/min)

Mean atmospheric conditions:		
Dry bulb	24	°C
Pressure	98.3	kPa
Relative Humidity	58	%
Maximum temperatures:		
Coolant	101	°C
Engine oil	119	°C
Fuel	53	°C
Engine air intake	44	°C

3.2.1 Hydraulic Power (two inlets, two outlets)

Date of Test:	27-Sep-02	JOHN DEERE 9120	
Location of Test-City-State:		Tractor Test Lab, Lincoln, NE, USA	
Tapping point used for test:		Remote hydraulic outlets	
I.	Sustained pressure with pump stalled:		
	20.20 MPa		
	2930 psig		
II.	Pump delivery rate at minimum pressure at rated engine speed:		
	183.2 l/min		
	48.4 gpm		
III.	Flow rate, pressure, power:		
	90% of relief valve setting		
	96.1 l/min	18.25 MPa	29.3 kW
	25.4 gpm	*2647 psig*	*39.2 hp*
	Maximum hydraulic power:		
	167.7 l/min	14.83 MPa	41.5 kW
	44.3 gpm	*2151 psig*	*55.6 hp*
IV.	Hydraulic fluid temperature at flow meter:		
	74 °C		
	166 °F		
	This hydraulic system does not use an accumulator. Opening and closing pressures of the unloading valve could not be measured.		



3.2.2 POWER LIFT TEST Category III, Quick attach linkage, 90 mm cylinders
Date of test: 23 June 1997. Test conducted on John Deere 9400 which is technically equivalent.

	Hitch points	Frame
Lower hitch points above ground - down position:	229 mm	231 mm
Vertical movement - without load:	793 mm	861 mm
with load:	774 mm	841 mm
Maximum corrected force exerted through full range:	62.2 kN	58.3 kN
Corresponding pressure:	18.3 MPa	18.3 MPa
Moment about rear axle:	97.6 kNm	127.0 kNm
Maximum mast tilt angle	--	6.7 degrees

Lifting height relative to horizontal position of lower links.

mm	-318	-300	-201	-99	0	99	201	300	401	455	526
Corrected lift forces											
At the Hitch point kN	63.6	62.2	64.6	66.6	68.6	70.2	71.5	72.6	73.6	73.7	--
at the frame kN	63.8	63.0	63.3	63.9	63.9	63.6	62.9	61.6	--	59.8	58.3
Corresponding pressure 18.3 MPa											

OECD Drawbar Data (SI)

Date of tests: 25,26-Sep-02							**Fuel density:** 0.842 kg/l							
Type of track: Concrete							**Test number:** 1810							
3.3.1 Maximum power in tested gears (unballasted, 4wd)							**Tire pressure:** 48 kPa, rear			76 kPa, front		**Drawbar Height:** 521 mm		
Gear	**Gear Designation**	**Power**	**Drawbar pull**	**Speed**	**Engine speed**	**Slip**	**Fuel**		**Temperature**			**Atmospheric conditions**		
							SFC	**SFE**	**Fuel**	**Coolant**	**Oil**	**Temperature**	**Relative humidity**	**Pressure**
		kW	**kN**	**km/h**	**rev/min**	**%**	**kg/kW.h**	**kW.h/l**	**°C**	**°C**	**°C**	**°C**	**%**	**kPa**
*1	1	156.94	156.62	3.61	2109	10	0.295	2.85	52	82	111	12	88	97.6
2	2	169.83	148.96	4.10	1901	8	0.269	3.13	53	84	111	12	88	97.6
3	3	171.68	134.74	4.59	1901	7	0.265	3.17	54	93	117	25	40	97.7
4	4	175.07	120.65	5.22	1900	5	0.260	3.23	53	93	117	24	43	97.8
5	5	176.35	109.22	5.81	1906	4	0.259	3.25	56	93	118	29	34	97.7
6	6	175.78	96.64	6.55	1900	3	0.259	3.24	52	85	111	18	54	98.4
7	7	177.03	87.37	7.29	1904	3	0.258	3.27	53	88	114	15	54	98.5
8	8	176.46	77.96	8.15	1899	2	0.258	3.26	53	88	113	17	52	98.5
9	9	174.42	69.68	9.01	1901	2	0.262	3.21	53	86	114	13	57	98.5
10	10	173.44	62.00	10.07	1898	2	0.263	3.20	53	90	115	20	44	98.2
11	11	172.93	55.54	11.21	1903	2	0.263	3.20	52	90	114	21	45	98.1
12	12	173.47	50.38	12.40	1902	2	0.264	3.19	52	90	114	22	46	98.1
13	13	167.69	43.69	13.82	1899	2	0.272	3.09	51	90	114	23	44	98.1
* Note: Pull limited to avoid excessive bouncing														
3.3.2 Fuel consumption														
3.3.2.1			In selected gear at maximum power at rated engine speed.											
7	7	168.54	75.30	8.06	2098	3	0.274	3.07	53	94	118	27	37	97.7
3.3.2.1.1			75% of pull at maximum power at rated engine speed											
7	7	131.20	56.39	8.38	2168	2	0.295	2.86	53	87	110	29	32	97.6
3.3.2.1.2			50% of pull at maximum power at rated engine speed											
7	7	89.11	37.59	8.53	2193	1	0.336	2.50	51	84	109	29	32	97.5
3.3.2.1.3			Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.1											
8	8	131.42	56.38	8.39	1943	2	0.271	3.11	54	88	111	29	32	97.6
3.3.2.1.4			Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.2											
8	8	89.09	37.59	8.53	1963	1	0.306	2.75	51	82	108	29	32	97.5
3.3.2.1.5			Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.1											
9	9	131.08	56.37	8.37	1759	2	0.263	3.20	54	88	111	30	30	97.6
3.3.2.1.6			Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.1.2											
9	9	89.00	37.63	8.52	1778	1	0.290	2.90	50	81	106	29	32	97.5
3.3.2.2			In selected gear nearest to 7.5 km/h at rated engine speed.											
6	6	166.07	82.35	7.26	2099	3	0.277	3.04	53	94	118	27	39	97.7
3.3.2.2.1			75% of pull at maximum power at rated engine speed											
6	6	129.89	61.88	7.56	2168	2	0.297	2.83	53	88	111	29	34	97.7
3.3.2.2.2			50% of pull at maximum power at rated engine speed											
6	6	88.23	41.26	7.70	2193	1	0.339	2.48	53	82	107	30	30	97.6
3.3.2.2.3			Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.2.1											
7	7	130.07	61.87	7.57	1961	2	0.273	3.09	54	87	111	29	34	97.6
3.3.2.2.4			Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.2.2											
7	7	88.23	41.24	7.70	1981	1	0.308	2.73	52	81	106	30	30	97.5
3.3.2.2.5			Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.2.1											
8	8	130.30	61.84	7.59	1760	2	0.261	3.23	53	87	109	29	32	97.6
3.3.2.2.6			Higher gear at reduced engine speed, same pull and travel speed as 3.3.2.2.2											
8	8	88.45	41.27	7.72	1778	1	0.287	2.93	51	81	105	30	30	97.5

4.1 Drawbar Power (unballasted - 2100 rev/min)

OECD Drawbar Data (SI)

Date of tests: 25,26-Sep-02							**Fuel density:**	0.842 kg/l						
Type of track: Concrete							**Test number:**	1810						
4.1.1 Maximum power in tested gears (unballasted, 4wd)							**Tire pressure:**	48 kPa, rear		76 kPa, front		**Drawbar Height:**	521 mm	
Gear	**Gear Designation**	**Power**	**Drawbar pull**	**Speed**	**Engine speed**	**Slip**	**Fuel**		**Temperature**			**Atmospheric conditions**		
							SFC	**SFE**	**Fuel**	**Coolant**	**Oil**	**Temperature**	**Relative humidity**	**Pressure**
		kW	**kN**	**km/h**	**rev/min**	**%**	**kg/kW.h**	**kW.h/l**	**°C**	**°C**	**°C**	**°C**	**%**	**kPa**
*1	1	156.78	156.50	3.61	2109	10	0.295	2.85	52	82	111	12	88	97.6
2	2	163.06	126.65	4.63	2097	5	0.283	2.97	53	89	114	24	43	97.7
3	3	168.29	116.77	5.19	2101	5	0.274	3.07	52	89	114	24	43	97.8
4	4	167.98	103.76	5.83	2098	4	0.276	3.05	55	93	117	28	33	97.7
5	5	167.70	93.31	6.47	2099	3	0.273	3.08	53	94	116	26	38	97.7
6	6	166.07	82.35	7.26	2099	3	0.277	3.04	53	94	118	27	39	97.7
7	7	168.54	75.30	8.06	2098	3	0.274	3.07	53	94	118	27	37	97.7
8	8	165.76	66.10	9.03	2098	2	0.276	3.05	53	92	116	23	48	97.8
9	9	163.90	59.18	9.97	2096	2	0.280	3.01	52	88	114	19	47	98.2
10	10	161.21	51.95	11.17	2098	2	0.284	2.97	51	89	114	20	44	98.2
11	11	160.81	46.72	12.39	2099	2	0.284	2.96	51	89	113	21	46	98.1
12	12	160.65	42.21	13.70	2097	1	0.284	2.96	53	89	113	22	44	98.1

*** Note:** Pull limited to avoid excessive bouncing

4.2 Measurement of External Noise Level – John Deere 9120

-- Date of Test	September 26, 2002
-- Location of Test	Nebraska Tractor Test Laboratory
-- Sound Level Meter	Bruel and Kjaer 2236
-- Type of Track	Concrete Oval
-- Gear Number	18
-- Speed Prior to Acceleration	30.1 km/h
-- Noise Level	88.2 dB(A)

4.3 Measurement of Noise Level at Operator's Ear*


-- Date of Test	September 26, 2002
-- Location of Test	Nebraska Tractor Test Laboratory
-- Sound Level Meter	Bruel and Kjaer 2236
-- Type of Track	Concrete Oval
-- Gear Number	6
-- Drawbar Load	None
-- Noise at Operator Ear	74.7 dB(A)


* Note: Nebraska tractor test station guidelines.

5. Repairs and Adjustments: None

6. Remarks: None

John Deere 9120




Specific Fuel Consumption and Fuel Rate
SFC, g/kWh
Fuel Rate, kg/h
Engine Speed, rev/min
Standard PTO Speed - 1000 rev / min
g/kWh
g/kWh, std PTO
kg/h
kg/h, std PTO
500
450
400
350
300
250
200
60
50
40
30
20
10
0
900
1000
1100
1200
1300
1400
1500
1600
1700
1800
1900
2000
2100
2200
2300

John Deere 9120

