Report on test in accordance with OECD STANDARD CODE

OECD No. **1213/1**

Agricultural Tractor
LANDINI
R 6060 (2WD)

Type denomination

TL 39 N/K



OECD No. **1213/2**

Agricultural Tractor
MASSEY-FERGUSON
363 (2WD)

Type denomination

TL 39 N/V



Manufacturer

Massey-Ferguson S.p.A., Landini Division
I-42042 Fabbrico (R.E.) Italy

Deutsche Landwirtschafts-Gesellschaft e.V.
Zimmerweg 16 · D-6000 Frankfurt a. M. 1
Telefon: (069) 71 68-0 · Telex: 04 131 85 dlg-d

This is a report on a tractor test in accordance with OECD STANDARD CODE for the Official Testing of Agricultural Tractor Performance (C(87)53(Final), Code I).

It does not contain an evaluation of the tractor on practical work.

Duration of tests: October 1988 till February 1989
DLG-Testing Station for Agricultural Machinery, Max-Eyth-Weg 1,
D-6114 Groß-Umstadt

This report has been approved by the OECD Co-Ordinating Centre (CEMAGREF, France) as being in accordance with the OECD STANDARD CODE.

Date of approval: 23 rd August 1989
OECD No. 1213/1 for LANDINI R 6060 (2WD)
OECD No. 1213/2 for MASSEY-FERGUSON 363 (2WD)

The tractors LANDINI R 6060 (2WD) and
MASSEY-FERGUSON 363 (2WD)
are technically identical in all main respects except colour and denominations.

The tractor LANDINI 6060, serial no. 5371V52132 had been tested in 2 variants: As model DT 6060 (4WD) and as model R 6060 (2WD).

Model DT 6060 was converted into model R 6060 by dismantling the front axle drive and by exchange of front axle and steering.

In this report all performance characteristics are given corresponding to the International System of Units.

The reference to the former used Technical System of Units is given by the following relations:

Forces	1 kN	=	1000 N	=	102 kp
Powers			1 kW	=	1,36 PS
Pressures	1 MPa	=	10 bar	=	10,2 kp/cm²
	100 kPa	=	1000 mbar	=	750,10 mm Hg

All rights including the right of translation, reprint and photo-mechanical copying — also of excerpts — reserved by the editor.

Printed in the Federal Republic of Germany
September 1989; DLG-No. 253

PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82

TABLE OF CONTENTS

		Page
SPECIFICATION OF TRACTOR		4 to 14
TEST CONDITIONS		14 to 16
COMPULSORY TESTS		
1	Main power take-off performance	17 to 20
2	Hydraulic power and lifting force	21
3	Drawbar power	22 and 23
4	Turning area and turning circle	24
5	Position of centre of gravity	24
6	Braking	25
7	External noise level	26
APPENDIX		
	Measurements of noise in the protective structure (according to CODE V), carried out under the responsibility of the testing station	26
OPTIONAL TESTS		
8	Engine performance	27 to 30

PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82

Tractor manufacturer:	MASSEY-FERGUSON S.p.A. I-42042 Fabbrico (R.E.), Italy
Location of tractor assembly:	I-42042 Fabbrico
Submitted for test by:	Manufacturer
Selected by:	Manufacturer with agreement by DLG
Place of running-in:	Fabbrico and Groß-Umstadt
Duration of running-in:	Engine and tractor appr. 18 hours

SPECIFICATION OF TRACTOR

Tractor

Make:	LANDINI respectively MASSEY-FERGUSON
Trade name:	R 6060 respectively 363
Type denomination:	TL39N/K respectively TL39N/V
Type:	Wheel tractor, unit construction, rear wheel driven
Serial No.:	5371V52132
Start of series:	5370V52009 (see note on page 2)

Engine

Make:	PERKINS
Model:	T 3.152.4
Type:	Watercooled 4-stroke Diesel-engine, direct injection, turbo charged
Serial No.:	CN 31198U815253P
Cylinders:	3, in line, bore 91,5 mm, stroke 127 mm, displacement 2505 cm³, compression ratio 15,5:1; replaceable wet cylinder liners
Valves:	Overhead

Supercharging

Make:	SCHWITZER
Model/type:	S2A 2674A152, exhaust driven
Max.pressure:	55 kPa

Fuel system:	PERKINS fuel supply pump; CAV distributor injection pump DPA 3238F471/DSA649, serial no. 31626LEG; manufacturer's production setting 61±2 mm³/stroke at rated engine speed and full load; with automatic injection timing device; injection timing 17+3° before TDC static, additional 8° automatic; CAV multihole-injection nozzles PN2645k603, injection pressure 21,0 MPa, CAV fuel filter with replaceable paper element; capacity of fuel tank 86 dm³
Governor:	CAV centrifugal variable speed governor, governed range of engine speed 750 to 2530 rev/min, rated engine speed 2250 rev/min;
Air cleaner:	FISPA oil bath air filter, cyclone pre-cleaner; no maintenance indicator; air intake in front of engine, below bonnet
Lubrication system:	Forced feed with gear pump; strainer in sump, PERKINS oil filter in full flow, replaceable filter
Cooling system:	Water cooling with impeller pump, overpressure relief valve set to 70 kPa, thermostat with by-pass; fan with 4 blades with 394 mm dia, water capacity 10,5 dm³
Starting system:	Electrical; LUCAS solenoid pre engaged-drive starter motor 2,5 kW; depressed pedal of clutch as safety device; ISKRA flame plug in intake manifold
Electrical equipment:	12 Volt, negative earth; LUCAS 3-phase alternator 12 V 500 W; 1 lead acid battery, Ah at 20 hours rating, test current for low temperature 420 A

Exhaust silencer:	ANSA, DGM SA 1269, expansion type silencer, vertical, 130 x 100 mm oval, 660 mm long; on the left, beside the engine bonnet, mouth showing upwards, 2320 mm above ground

Transmission

Clutch:	LUK dry dual-disc clutch; pedal operated travel drive, disc 280 mm dia, organic lining, hand lever operated p.t.o. drive, disc 280 mm dia, organic lining
Gear box:	MASSEY-FERGUSON synchronized speed change gear with 4 gears, collar shifted range gear with 3 forward ranges (L, M and H) and 1 reverse range (R); total 12 forward and 4 reverse speeds, 2 gear shift levers; two further gear box models on request available: 1. gear arrangement as described above, additional range gear with 3 ranges, in 3 varaiants: Standard range combined with a) creeper and underdrive range, or b) creeper and overdrive range, or c) underdrive and overdrive range; in each case total: 36 forward and 12 reverse speeds 2. change gear with 4 gears, range gear with 3 forward ranges, reversing gear (acting on 4x3 forward speeds), combined in 3 variants with a) creeper range, or b) underdrive range, or c) overdrive range; in each case total: 24 forward and 12 reverse speeds
Rear axle and final drives:	MASSEY-FERGUSON bevel gear drive, bevel gear differential with pedal operated lock, self disengaging; spur gear final drives
Front axle:	MASSEY-FERGUSON not driven, telescopically adjustable
Lubrication:	Gear box, rear axle and hydraulic system have oil in common, see pages 15 and 16

PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82

Total ratios and speeds

Range	Gear	Total ratio engine : driving wheel	Nominal travelling speed *) at rated engine speed 2250 rev/min km/h
L	1	331,81	1,78
	2	211,09	2,79
	3	167,15	3,53
	4	113,28	5,20
M	1	138,90	4,24
	2	88,36	6,67
	3	69,97	8,43
	4	47,42	12,43
H	1	56,31	10,47
	2	35,82	16,46
	3	28,37	20,78
	4	19,22	30,66
R	1	124,32	4,74
	2	79,09	7,45
	3	62,63	9,41
	4	42,44	13,89

*) calculated with the radius index 695 mm (ISO 4251/1-1984)

Power take-off

Main p.t.o.: Shiftable by hand lever (collar shifting) to independent or ground speed p.t.o. and by second hand lever to 540 or 1000 rev/min;
p.t.o. speed indicator lamps

1 p.t.o. shaft at rear of tractor, in tractor's median plane;
height above ground 685 mm, horizontal distance to rear wheels centre line 265 mm;
35 mm dia, 6 splines, in conformity with ISO 500/1979, type 1, when using 540 rev/min speed

Power take-off proportional to engine speed
(independent p.t.o.): Driven by second plate of dry dual-disc clutch; sense of rotation clockwise (viewed to tractor's rear)

P.t.o. type	P.t.o. speed rev/min	Engine speed rev/min	Ratio engine : p.t.o.	Power restriction kW
540	540	1944	3,6000	-
	625	2250		
1000	1000	1917	1,9167	-
	1174	2250		

Power take-off proportional to ground speed:
Driven by rear axle drive, sense of rotation clockwise (at forward movement, viewed to tractor's rear)

P.t.o. type	Travel distance per p.t.o. revolution m	Number of p.t.o. revolutions per rear wheel revolution
540	0,4754	9,1852
1000	0,2531	17,2522


Power lift


MASSEY-FERGUSON
hydraulic power lift, unit construction;
draft and position control, both infinitely mixable, floating position, lowering throttle (non-adjustable);
adjustable raise control, top link sensing;
open centre system
1 single acting lifting cylinder,
100 mm bore, 127 mm stroke;
cylinder safety valve set to 19,0 MPa

no linkage lock for transport;
SUNDSTRAND/TUROLLA gear type pump TFA/211 S,
gear driven by engine;
delivery 36 l/min at rated engine speed, relief valve pressure setting 17,0+0,5 MPa;
1 hydraulic oil filter within suction line;
hydraulic oil circuit in common with gear box lubrication, reservoir within gear box;

MASSEY-FERGUSON control valve,
1 double acting OMC additional control valve, 2 oil couplings ar rear of tractor;
maximum volume of oil available to external cylinders 5 dm³

Three-point linkage — category 2 acc. to ISO 730/I-1977





PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82

Dimensions of rear implement linkage (projected lengths in mm, underlined dimensions are valid for power lift measurements p.21)

Rear tyres 16.9 R 30	radius index	(r)	695
Front tyres 7.50 - 18	static radius	(r')	403
Length of lift arms		(A)	272
Length of lower links		(B)	855
Distance of lift arm pivot points from rear wheel centre	horizontal	(a)	12
	vertical	(b)	310
Horizontal distance between lower link pivot points		(u)	390
Horizontal distance between lift arm end points		(v)	525
Length of upper link		(S)	590 to 790, 680
Distance of upper link pivot point from rear wheel centre	horizontal	(c)	254
	vertical	(d)	256 or 301
Distance of lower link pivot point from rear wheel centre	horizontal	(e)	80
	vertical	(f)	138
Distance of lower link pivot points from lift rod pivot points on lower links		(D)	455
Length of lift rods		(L)	545 tp 665. 610

Height of lower link hitch points relative to rear wheels' centre line (situated 695 mm above ground), these data are valid for unloaded power lift:

Length of lift rods	(L)	610	545	665
Linkage distance of lift rods	(D)	455		
Lowest position	(h)	495	337	630
Highest position	(H)	178	295	80
Transport position	(H')	178	295	80

Pull attachment

Swinging drawbar:	Optionally available (not fitted on tested tractor)
Trailer hitch:	LANDINI , DGM GA 725 C-87 6t V1.5; non-automatical, height adjustable;
	hole diameter 28 mm
	hitch point 480, 575, 705 or 800 mm above ground
	behind rear wheel axis
	horizontal 395 mm
	distance from p.t.o. shaft end
	vertical, above 20 or 115 mm
	below 110 or 205 mm
	horizontal 130 mm
	maximum permissible vertical load 15 kN
Holed drawbar:	Long bar; length 1500 mm, thickness 30 mm, width 80 mm, length between joint balls 770 mm; 7 holes between joint balls with 80 mm distance each, 2 holes outside the joint balls on either side with 120 mm distance each, holes' diameter 22 mm and 24 mm alternately; at each end of the bar 1 hole with 32 mm dia;
	height above ground minimum 125 mm
	maximum 1050 mm
	holes' centre line behind p.t.o. shaft end 710 mm
	(lower links in horizontal position)
Towing hitch:	At front of tractor,
	height above ground 710 mm

Steering	MASSEY-FERGUSON and DANFOSS, model ORBITROL OSPC 80, hydrostatic steering; separate oil circuit fed by SUNDSTRAND/ TUROLLA gear type pump TFA/211 S directly driven by front end of crankshaft; delivery 24,8 l/min at rated engine speed, working pressure 12,0 MPa; 1 double acting differential ram, bore 45 mm, stroke 165 mm, piston rod 20 mm dia, acting on track rod of front axle; oil filter incorporated in steering oil tank
Brakes	
Service brake:	SIRMAC, 7 x 5,5 inches pedal operated muscle power brake with mechanical transmission, acting on rear axle of tractor; wet disc brakes on the differential half shafts with 4 lining discs each with 178 mm dia
Parking brake:	Mechanically actuated by hand lever with ratchet, acting on the discs of service brake
Steering brake:	Divided pedals of service brake, for normal use locked together
Trailer braking take-off:	None
Wheels	
Steering wheels:	At front, 2 pneumatics 7.50 - 18 rims 5.50 Fx18
Driving wheels:	At rear, 2 pneumatics 16.9 R 30, rims W14x30
Wheelbase:	2126 mm
Track widths:	At front 1420 to 1920 mm, in steps of 100 mm each, variable by extending telescopic half shafts at rear 1300 to 2000 mm in steps of 100 mm each, variable by adjustable gauge bowl wheels

Permissible tyre combinations:

Tyre sizes			
at front		at rear	
7.50 - 18	6 ply	8.3/8 - 44 12.4 R 36 16.9 R 30 137	6 ply 6 ply A8
7.50 - 16	6 ply	9.5 R 36 12.4 R 32 14.9 R 28 128 14.9 R 30 129 16.9 R 28 136 420/70 R 28 133	6 ply 6 ply A8 A8 A8 A8

Protective structure: LANDINI TS 19/2, MASSEY-FERGUSON TS 20/2, 4 post frame, OECD-tested, approval-no. CSS 081/14 for LANDINI R 6060 (TL39N/K) CSS 081/34 for MASSEY-FERGUSON 363 (TL39N/V)

Driver's seat: GRAMMER, DS 44/1H; upholstered seat with back rest, adjustable suspension and hydraulic shock absorber; driver's platform 830 mm above ground, 1 step, 555 mm above ground; range of adjustment of unloaded seat: longitudinal 200 mm vertical 510 to 570 mm (stepless) above platform

Running-time meter: Electronic, counts real operating hours, when engine speed rises above 800 rev/min, otherwise is off

PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82

Lighting — Electrical 12 Volt, in accordance with Italian legislation

	Size mm	Height above ground of centre mm	Distance from outside edge of lights to median plane of tractor mm
Head lights	130 dia	1105	245
Side lights	110x30	1445	790
Rear lights	70x50	1504	600
Reflectors			
1st pair	45x50	1504	645
2nd pair	80 dia	590	400

TEST CONDITIONS

Overall dimensions

Length:	3540 mm without ballast, 3810 mm with ballast
Width:	1925 mm without ballast, 1925 mm with ballast
Height:	2370 mm to top of protective structure 2320 mm to exhaust pipe's mouth
Ground clearance:	490 mm below bracket of trailer hitch

Tractor mass

			without driver kg	with driver kg
Without ballast:	Mass	front	850	860
		rear	1550	1620
		total	2400	2480
With ballast:	Mass	front	1170	1180
		rear	2195	2265
		total	3365	3445

Ballast

Front:	8 weights, total	288 kg
Rear:	2 weights per wheel, total	240 kg
	water in the tyres	437 kg

Tyres and track widths specifications

	Front	Rear
Tyres:	MICHELIN	MICHELIN BIB'X
dimensions	7.50 - 18	16.9 R 30
type	cross-ply	radial
ply rating/load index	6/-	-/137A8
maximum load	810 kg (30 km/h)	2300 kg
inflation pressure	230 kPa	160 kPa
radius index	403 mm (static)	695 mm
Chosen track width:	1420 mm	1500 mm
Technically permissible axle load:	1180 kg	3400 kg
Technically permissible total weight:	3450 kg	

Oils and lubrication

Capacity and change interval:

	Capacity dm³	Oil change h	Filter change h
engine	6,7	250	250
gear box including rear axle and hydraulic system	33,0	1000	250 *)
final drives at rear	2x2,2		-
steering system	2,3		500 *)

*) only filter cleaning

PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82

Specifications

	Recommended	Used during test
Engine oil:		
type	engine oil	MF SUPER UNIVERSALOIL
viscosity		
winter	SAE 10W, 20W or 10W/30	SAE 15W/40
summer	SAE 20W or 20W/30	
tropics	SAE 30, 20W/40 or 20W/50	
for all conditions	SAE 15W/40	
classification	API - CC	API - CC
Transmission oils:		
Gearbox, rear axle hydraulic system		
type	super tractor oil universal	MF SUPER UNIVERSALOIL
viscosity	SAE 15W/40	SAE 15W/40
classification	API - CD/API -GL4	API - CD/API - GL4
Final drives at rear		
type	gear oil	MOBILUBE GX85W/90-A
viscosity	SAE 85W/90	SAE 85W/90
classification	API - GL4	API - GL4
Steering oil:		
Steering system		
type	automatic transmission fluid	MOBIL ATF 200
viscosity	-	
classification	Type A, SUFFIX A	

Grease: Multi purpose grease
number of lubrication points 15

Fuel

type: ARAL Diesel-fuel in conformity with DIN 51601
density: at 15°C at engine test 0,838 g/cm³
at p.t.o. test 0,822 g/cm³
at drawbar power test 0,837 g/cm³

REPAIRS None

REMARKS None

PRÜFUNGS-ABTEILUNG
Landini R 6060

Test No. 88-82

COMPULSORY TESTS

1. MAIN POWER TAKE OFF PERFORMANCE (540 rev/min)

Date of tests: 21st October 1988
Location of tests: DLG-Testing Station Groß-Umstadt
Type of dynamometer: SCHENCK hydraulic dynamometer U1-40

Power kW	Speed Engine rev/min	Speed P.t.o. rev/min	Fuel consumption hourly l/h	Fuel consumption hourly kg/h	Fuel consumption specific g/kWh	Specific energy kWh/l
Maximum power						
1.1 At 2-hour test						
40,5	2250	625	12,30	10,11	250	3,29
1.2 At rated speed						
40,5	2250	625	12,30	10,11	250	3,29
1.3 At standard p.t.o. speed						
37,5	1944	540	10,83	8,90	238	3,46
1.4 Part loads, the governor hand lever in the position corresponding to maximum power at full load (curve a)						
1.4.1 the torque corresponding to maximum power at rated speed						
40,5	2250	625	12,30	10,11	250	3,29
1.4.2 85% of the torque obtained in 1.4.1						
35,2	2297	638	10,96	9,01	256	3,21
1.4.3 75% of the torque defined in 1.4.2						
26,9	2340	650	9,16	7,53	280	2,93
1.4.4 50% of the torque defined in 1.4.2						
18,6	2432	676	7,49	6,16	331	2,48
1.4.5 25% of the torque defined in 1.4.2						
9,5	2480	689	5,51	4,53	478	1,72
1.4.6 unloaded						
-	2527	702	3,55	2,92	-	-

PRÜFUNGS-ABTEILUNG
Landini R 6060

Test No. 88-82

Power kW	Speed Engine rev/min	Speed P.t.o. rev/min	Fuel consumption hourly l/h	Fuel consumption hourly kg/h	Fuel consumption specific g/kWh	Specific energy kWh/l
1.5 Part loads, the governor hand lever in the position corresponding to the standard p.t.o. speed at full load (curve b)						
1.5.1 the torque corresponding to maximum power						
37,5	1944	540	10,83	8,90	238	3,46
1.5.2 85% of the torque obtained in 1.5.1						
32,6	1993	554	9,67	7,95	243	3,38
1.5.3 75% of the torque defined in 1.5.2						
25,2	2050	570	7,99	6,57	261	3,15
1.5.4 50% of the torque defined in 1.5.2						
17,6	2143	595	6,51	5,35	305	2,70
1.5.5 25% of the torque defined in 1.5.2						
8,9	2175	604	4,45	3,65	410	2,00
1.5.6 unloaded						
-	2210	614	2,88	2,37	-	-

No load maximum engine speed: 2527 rev/min
Equivalent flywheel torque at rated engine speed: 172 Nm
Maximum equivalent flywheel torque: 199 Nm at 1453 rev/min of the engine

Mean atmospheric conditions

temperature	19 °C
pressure	101 kPa
rel. humidity	56 %


Maximum temperatures

coolant	84 °C
oil	106 °C
fuel	18 °C
air intake	20 °C

PRÜFUNGS-ABTEILUNG


Landini R 6060

Test-No.88-82



PRÜFUNGS-ABTEILUNG
Landini R 6060

Test-No.88-82



PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82

2 HYDRAULIC POWER AND LIFTING FORCE

Date of tests: 31st January 1989

2.1 Hydraulic power test

Sustained pressure with relief valve open **17,4 MPa**
Pump delivery rate at minimum pressure **37,6 l/min**

	Hydraulic power kW	Flow rate l/min	Pressure MPa	Oil temperature °C
At 90% of the actual relief valve setting	7,9	30,2	15,7	39 +)
At max. power	9,0	35,9	15,1	39 +)

Tapping point used for test: At rear of tractor
+) Oil temperature in suction line of hydraulic pump more than 65°C

2.2 Power lift test

	At the hitch point	On the frame
Height of lower hitch points above ground in down position	200 mm	200 mm
Vertical movement without lifting force	673 mm	800 mm
Vertical movement with lifting force	645 mm	740 mm
Max. corrected force exerted through full range	14,6 kN	13,5 kN
Corresponding pressure	15,1 MPa	15,1 MPa
Moment about rear axle	-	20,9 kNm
Max. tilt angle of mast from vertical	-	9,5°

Lifting heights relative to horizontal lower links

mm	-407	-400	-357	-300	-200	-100	0	+100	+200	+288	+300	+333

Lifting forces at hitch points, corrected to 15,1 MPa

kN			14,6	16,0	17,5	18,8	19,7	20,3	20,5	21,2		

Lifting forces at standard frame, corrected to 15,1 MPa

kN	13,5	13,7		15,2	15,6	16,0	16,2	16,0	15,6		14,7	14,5

PRÜFUNGS-ABTEILUNG
LANDINI R 6060

3 DRAWBAR PERFORMANCE

Date of tests: 28th November till 6th December 1988
Type of track: Concrete

Gear	Driving speed km/h	Power kW	Drawbar pull kN	Engine speed rev/min	Slip of wheels %
3.1 Maximum power in tested gears (unballasted tractor) height of drawbar above ground 600 mm					
1 M	3,65	23,9	23,61	2304	15,1
4 L	4,43	29,0	23,58	2279	15,1
2 M	6,03	33,9	20,21	2246	8,5
3 M	7,85	34,2	15,68	2246	5,8
1 H	9,90	34,7	12,62	2250	4,2
4 M	11,81	33,2	10,12	2246	3,4
3.2 Maximum power in tested gears (ballasted tractor) height of drawbar above ground 620 mm					
1 L	1,63	14,2	31,43	2441	15,1
2 L	2,46	21,4	31,38	2336	14,9
3 L	3,02	26,4	31,44	2279	14,9
1 M	3,59	31,4	31,44	2261	15,0
4 L	4,78	33,2	24,99	2254	7,4
2 M	6,25	35,0	20,18	2250	5,2
3 M	8,03	34,6	15,51	2250	3,7
1 H	10,03	34,5	12,39	2246	2,8
3.3.1 Five-hour-test at 75% of pull at maximum power in 2 M gear *)					
2 M	6,73	25,9	13,88	2304	3,0
3.3.2 Five-hour-test at pull corresponding to 15% wheel slip in test 3.2 *)					
2 L	2,32	25,10	38,96	2279	-

Total oil consumption during ten hours duration of tests 3.3.1 and 3.3.2 : 14 g/h

*) The tests 3.3.1 and 3.3.2 were carried out with the model DT 6060

PRÜFUNGS-ABTEILUNG

Test No. 88-82

Tyre size front: 7.50 - 18
rear: 16.9 R 30

Specific fuel consumption g/kWh	Specific energy kWh/l	Temperatures Fuel °C	Coolant °C	Engine-oil °C	Atmospheric conditions Tempe-rature °C	Relative humidity %	Pressure kPa
tyre inflation pressure:125 kPa at front and 80 kPa at rear							
347	2,42	27	81	89	4	77	98,9
337	2,49	29	82	92	4	72	98,8
301	2,78	30	85	99	4	76	98,9
297	2,81	30	86	100	4	78	98,9
294	2,85	31	85	101	5	74	98,9
307	2,72	31	86	100	5	77	98,9
tyre inflation pressure: 125 kPa at front and 80 kPa at rear							
443	1,89	24	83	95	3	94	100,5
361	2,32	24	84	92	3	95	100,5
341	2,46	30	84	94	3	99	100,4
324	2,59	30	83	97	3	99	100,4
305	2,74	30	84	100	3	99	100,4
291	2,88	31	84	101	3	99	100,4
293	2,85	30	85	100	4	100	100,4
294	2,85	31	85	101	4	98	100,4
326	2,57	26	80	94	7	94	100,0
-	-	31	80	95	12	80	100,6

Test 3.3.2 was carried out with additional ballast of 552 kg, relative to the weight of ballasted model DT 6060 (4WD), the figures not quoted are therefore irrelevant

PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82

4 TURNING AREA AND TURNING CIRCLE

Wheel equipment front: 7.50 - 18
rear: 16.9 R 30

Track of wheels front: 1420 mm
rear: 1500 mm

	With brakes		Without brakes	
	left-hand m	right-hand m	left-hand m	right-hand m
Radius of turning area	3,57	3,58	4,00	4,02
Radius of turning circle	3,43	3,44	3,86	3,88

5 LOCATION OF CENTRE OF GRAVITY

Height above ground	817 mm
Distance forward from rear axle centre	739 mm
Distance from tractor's median plane, to the left	2 mm

PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82


6 BRAKING

Date of tests: 1st and 2nd December 1988

	Tractor mass (with driver) front kg	rear kg	total kg	Speed before application of brakes km/h
Without ballast	860	1620	2480	32,8
With ballast	1180	2265	3445	32,5

6.1 Cold service braking device test

6.2 Fade test



No significant deviation of tractor from original course and no abnormal vibrations

Brakes-heating: Actuating of brake for 1 km with pedal force corresponding to 1 m/s²

6.3 Parking braking device test

	Ballasted tractor on 18% - slope up	down
Braking device control force N	160	160

PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82

7 MEASUREMENT OF EXTERNAL NOISE LEVEL

Date of test: 16th December 1988
Type of track: Concrete
Type of sound level meter: BRÜEL & KJAER model 2233

Results of test

Gear: 4 H
Travelling speed before acceleration: 24,6 km/h
Sound level: 87,0 dB(A)

APPENDIX

MEASUREMENT OF NOISE IN THE PROTECTIVE STRUCTURE

with 4-post frame LANDINI TS 19/2

Date of test: 6th December 1988
Type of track: Concrete
Type of sound level meter: BRÜEL & KJAER model 2233

Gear	Drawbar pull kN	Travelling speed km/h	Sound level dB(A)
1 L	23,15	1,54	92,0
2 L	23,68	2,41	92,5
3 L	23,54	3,03	94,0
1 M	23,61	3,64	95,0
4 L	23,38	4,40	95,5
2 M	20,17	6,02	95,0
2 M +)	light load	7,41	91,0
3 M	15,51	7,86	95,0
1 H	12,48	9,89	94,5
4 M	10,00	11,82	94,5
2 H	7,24	15,71	94,5
4 H *)	light load	32,80	93,0

+) The 2 M gear corresponds to the nominal travelling speed nearest to 7,5 km/h

*) Front wheel drive disengaged

PRÜFUNGS-ABTEILUNG
Landini R 6060

Test No. 88-82

OPTIONAL TEST

8. ENGINE PERFORMANCE

Date of tests: 17th October 1988
Location of tests: DLG-Testing-Station Groß-Umstadt
Type of dynamometer: SCHENCK eddy-current-dynamometer W 150


Power kW	Engine speed rev/min	Fuel consumption hourly l/h	Fuel consumption hourly kg/h	Fuel consumption specific g/kWh	Specific energy kWh/l
Maximum power					
8.1 At 2-hour test					
44,0	2250	12,57	10,34	235	3,50
8.2 At rated engine speed					
44,0	2250	12,57	10,34	235	3,50
8.3 At standard p.t.o. speed (540 rev/min)					
40,0	1944	11,06	9,09	227	3,62
8.4 Part loads					
8.4.1 the torque corresponding to maximum power at rated speed					
44,0	2250	12,57	10,34	235	3,50
8.4.2 85% of the torque obtained in 8.4.1					
38,3	2307	11,05	9,08	237	3,47
8.4.3 75% of the torque obtained in 8.4.2					
29,2	2341	9,06	7,44	255	3,22
8.4.4 50% of the torque obtained in 8.4.2					
20,3	2447	7,25	5,96	293	2,81
8.4.5 25% of the torque obtained in 8.4.2					
10,3	2491	5,06	4,16	403	2,04
8.4.6 unloaded					
-	2533	2,98	2,45	-	-

Optimum fuel consumption: 217 g/kWh at 19,4 kW and 1238 rev/min
No load maximum engine speed: 2533 rev/min
Torque at rated engine speed: 187 Nm
Maximum torque: 210 Nm at 1451 rev/min of the engine

Mean atmospheric conditions	temperature	20 °C
	pressure	100 kPa
	relative humidity	60 %
Maximum temperatures	coolant	85 °C
	oil	106 °C
	fuel	20 °C
	engine air intake	21 °C


PRÜFUNGS-ABTEILUNG
Landini R 6060

Test-No.88-82




PRÜFUNGS-ABTEILUNG
Landini R 6060

Test-No.88-82



PRÜFUNGS-ABTEILUNG
LANDINI R 6060

Test No. 88-82



Published
with the support of the Federal Minister for Food, Agriculture and Forestry

Deutsche Landwirtschafts-Gesellschaft e.V. (DLG)
Fachbereich Landtechnik — Prüfungsabteilung —
Zimmerweg 16 (DLG-Haus)
D-6000 Frankfurt am Main 1