Report on test in accordance with OECD STANDARD CODE

OECD No. **1212/1**

Agricultural Tractor
LANDINI
DT 6860 (4WD)

Type denomination

TL 21 DT/K



OECD No. **1212/2**

Agricultural Tractor
MASSEY-FERGUSON
373-4 (4WD)

Type denomination

TL 21 DT/V



Manufacturer

Massey-Ferguson S.p.A., Landini Division
I-42042 Fabbrico (R.E.) Italy

Deutsche Landwirtschafts-Gesellschaft e.V.
Zimmerweg 16 · D-6000 Frankfurt a. M. 1
Telefon: (069) 71 68-0 · Telex: 04 131 85 dlg-d

This is a report on a tractor test in accordance with OECD STANDARD CODE for the Official Testing of Agricultural Tractor Performance (C(87)53(Final), Code I).

It does not contain an evaluation of the tractor on practical work.

Duration of tests: May till September 1988
DLG-Testing Station for Agricultural Machinery, Max-Eyth-Weg 1,
D-6114 Groß-Umstadt

This report has been approved by the OECD Co-Ordinating Centre (CEMAGREF, France) as being in accordance with the OECD STANDARD CODE.

Date of approval: 23 rd August 1989
OECD No. 1212/1 for LANDINI DT 6860 (4WD)
OECD No. 1212/2 for MASSEY-FERGUSON 373-4 (4WD)

The tractors LANDINI DT 6860 and
MASSEY-FERGUSON 373-4
are technically identical in all main respects except colour and denominations.

In this report all performance characteristics are given corresponding to the International System of Units.

The reference to the former used Technical System of Units is given by the following relations:

Forces	1 kN	=	1000 N	=	102 kp
Powers			1 kW	=	1,36 PS
Pressures	1 MPa	=	10 bar	=	10,2 kp/cm²
	100 kPa	=	1000 mbar	=	750,10 mm Hg

All rights including the right of translation, reprint and photo-mechanical copying — also of excerpts — reserved by the editor.

Printed in the Federal Republic of Germany
September 1989; DLG-No. 252

PRÜFUNGS-ABTEILUNG
LANDINI DT 6860

Test No. 88-83

TABLE OF CONTENTS

		Page
SPECIFICATION OF TRACTOR		4 to 14
TEST CONDITIONS		14 to 16
COMPULSORY TESTS		
1	Main power take-off performance	17 to 20
2	Hydraulic power and lifting force	21
3	Drawbar power	22 and 23
4	Turning area and turning circle	24
5	Position of centre of gravity	24
6	Braking	25
7	External noise level	26
APPENDIX		
	Measurements of noise in the protective structure (according to CODE V), carried out under the responsibility of the testing station	26
OPTIONAL TESTS		
8	Engine performance	27 to 30

PRÜFUNGS-ABTEILUNG
LANDINI DT 6860

Test No. 88-83

Tractor manufacturer:	MASSEY-FERGUSON S.p.A. I-42042 Fabbrico (R.E.), Italy
Location of tractor assembly:	I-42042 Fabbrico
Submitted for test by:	Manufacturer
Selected by:	Manufacturer with agreement by DLG
Place of running-in:	Fabbrico and Groß-Umstadt
Duration of running-in:	Engine and tractor appr. 25 hours

SPECIFICATION OF TRACTOR

Tractor

Make:	LANDINI respectively MASSEY-FERGUSON
Trade name:	DT 6860 respectively 373-4
Type denomination:	TL 21 DT/K resp. TL 21 DT/V
Type:	Wheel tractor, unit construction, four-wheel driven
Serial No.:	5373 V 51260
Start of series:	5373 V 51001

Engine

Make:	PERKINS
Model:	4.236
Type:	Watercooled 4-stroke Diesel-engine, direct injection, naturally aspirated
Serial No.:	LD 31202 U 204215 P
Cylinders:	4, in line, bore 98,5 mm, stroke 127 mm, displacement 3871 cm³, compression ratio 16,0+1:1; replaceable wet cylinder liners
Valves:	Overhead

Fuel system:	PERKINS fuel supply pump; CAV distributor injection pump DPA 3241 F490, serial no. 22117 LEG; manufacturer's production setting 55±1,5 mm³/stroke at rated engine speed and full load; injection timing 23°±2° before TDC, without automatic injection timing device, CAV multihole-injection nozzles PN 2646842, injection pressure 17,0 MPa, CAV fuel filter with replaceable paper element; capacity of fuel tank 86 dm³
Governor:	CAV centrifugal variable speed governor, governed range of engine speed 750 to 2340 rev/min, rated engine speed 2200 rev/min;
Air cleaner:	FISPA oil bath air filter, cyclone pre-cleaner; no maintenance indicator; air intake in front of engine, below bonnet
Lubrication system:	Forced feed with gear pump; strainer in sump, PERKINS oil filter in full flow, replaceable filter
Cooling system:	Water cooling with impeller pump, overpressure relief valve set to 70 kPa, thermostat with by-pass; fan with 6 blades with 410 mm dia, water capacity 15 dm³
Starting system:	Electrical; LUCAS solenoid pre engaged-drive starter motor 2,5 kW; depressed pedal of clutch as safety device; ISKRA flame plug in intake manifold
Electrical equipment:	12 Volt, negative earth; LUCAS 3-phase alternator 12 V 500 W; 1 lead acid battery, 95 Ah at 20 hours rating, test current for low temperature 510 A

Exhaust silencer:	ANSA, DGM SA 1269, expansion type silencer, vertical, 130 x 100 mm oval, 660 mm long; on the left, beside the engine bonnet, mouth showing upwards, 2305 mm above ground

Transmission

Clutch:	LUK, model A2.028.074.08, dry dual-disc clutch; pedal operated travel drive, disc 280 mm dia, organic lining; hand lever operated p.t.o. drive, disc 280 mm dia, organic lining
Gear box:	MASSEY-FERGUSON synchronized speed change gear with 4 gears, collar shifted range gear with 3 forward ranges (L, M and H) and 1 reverse range (R); total 12 forward and 4 reverse speeds, 2 gear shift levers; two further gear box models on request available: 1. gear arrangement as described above, additional range gear with 3 ranges, in 3 variants: Standard range combined with a) creeper and underdrive range, or b) creeper and overdrive range, or c) underdrive and overdrive range; in each case total: 36 forward and 12 reverse speeds 2. change gear with 4 gears, range gear with 3 forward ranges, reversing gear (acting on 4x3 forward speeds), combined in 3 variants with a) creeper range, or b) underdrive range, or c) overdrive range; in each case total: 24 forward and 12 reverse speeds
Rear axle and final drives:	MASSEY-FERGUSON bevel gear drive, bevel gear differential with pedal operated lock, self disengaging; spur gear final drives
Front axle and final drives:	MASSEY-FERGUSON, driven by jointless central propeller shaft, hand lever operated, collar shifted; bevel gear drive, planetary final drives, No-spin differential optionally available
Lubrication:	Gear box, rear axle and hydraulic system have oil in common, see pages 15 and 16

Total ratios and speeds

Range	Gear	Total ratio engine : driving wheel	Nominal travelling speed *) at rated engine speed of 2200 rev/min km/h
L	1	331,81	1,74
	2	211,09	2,73
	3	167,15	3,45
	4	113,28	5,09
M	1	138,90	4,15
	2	88,36	6,52
	3	69,97	8,24
	4	47,42	12,16
H	1	56,31	10,24
	2	35,82	16,09
	3	28,37	20,32
	4	19,22	29,99
R	1	124,32	4,64
	2	79,09	7,29
	3	62,63	9,20
	4	42,44	13,58

*) calculated with the radius index 695 mm (ISO 4251/1-1984)

Number of revolutions of front wheels for one revolution of rear wheels: 1,3632

Power take-off

Main p.t.o.: Shiftable by hand lever (collar shifting) to independent or ground speed p.t.o. and by second hand lever to 540 or 1000 rev/min;
p.t.o. speed indicator lamps

1 p.t.o. shaft at rear of tractor, in tractor's median plane;
height above ground 680 mm,
horizontal distance to rear wheels centre line 265 mm;
35 mm dia, 6 splines, in conformity with ISO 500/1979, type 1, when using 540 rev/min speed

Power take-off proportional to engine speed
(independent p.t.o.): Driven by second plate of dry dual-disc clutch; sense of rotation clockwise (viewed to tractor's rear)

P.t.o. type	P.t.o. speed rev/min	Engine speed rev/min	Ratio engine : p.t.o.	Power restriction kW
540	540	1944	3,6000	-
	611	2200		
1000	1000	1917	1,9167	-
	1148	2200		

Power take-off proportional to ground speed:
Driven by rear axle drive, sense of rotation clockwise (at forward movement, viewed to tractor's rear)

P.t.o. type	Travel distance per p.t.o. revolution m	Number of p.t.o. revolutions per rear wheel revolution
540	0,4754	9,1852
1000	0,2531	17,2522

Power lift

MASSEY-FERGUSON
hydraulic power lift, unit construction;
draft and position control, both infinitely mixable, floating position, lowering throttle (non-adjustable);
adjustable raise control, top link sensing;
open centre system
1 single acting lifting cylinder,
100 mm bore, 127 mm stroke;
cylinder safety valve set to 19,0 MPa


PRÜFUNGS-ABTEILUNG
LANDINI DT 6860


Test No. 88-83

no linkage lock for transport;
SUNDSTRAND/TUROLLA gear type pump TFA/211 S,
gear driven by engine;
delivery 37 l/min at rated engine speed, relief valve pressure setting 17,0+0,5 MPa;
1 hydraulic oil filter within suction line;
hydraulic oil circuit in common with gear box lubrication, reservoir within gear box;

MASSEY-FERGUSON control valve,
1 double acting OMC additional control valve, 2 oil couplings ar rear of tractor;
maximum volume of oil available to external cylinders 5 dm³

Three-point linkage — category 2 acc. to ISO 730/I-1977





PRÜFUNGS-ABTEILUNG
LANDINI DT 6860

Test No. 88-83

Dimensions of rear implement linkage (projected lengths in mm, underlined dimensions are valid for power lift measurements p.21)

Rear tyres (16.9 R 30)	radius index	(r)	695
Front tyres (12.4 R 24)	radius index	(r')	540
Length of lift arms		(A)	272
Length of lower links		(B)	855
Distance of lift arm pivot points from rear wheel centre	horizontal	(a)	12
	vertical	(b)	310
Horizontal distance between lower link pivot points		(u)	390
Horizontal distance between lift arm end points		(v)	525
Length of upper link		(S)	590 to 790, 680
Distance of upper link pivot point from rear wheel centre	horizontal	(c)	254
	vertical	(d)	256 or 301
Distance of lower link pivot point from rear wheel centre	horizontal	(e)	80
	vertical	(f)	138
Distance of lower link pivot points from lift rod pivot points on lower links		(D)	455
Length of lift rods		(L)	545 to 665, 606

Height of lower link hitch points relative to rear wheels' centre line (situated 695 mm above ground), these data are valid for unloaded power lift:

Length of lift rods	(L)	606	545	665
Linkage distance of lift rods	(D)	455		
Lowest position	(h)	495	338	635
Highest position	(H)	217	316	102
Transport position	(H')	217	316	102

Pull attachment

Swinging drawbar:	Optionally available (not fitted on tested tractor)
Trailer hitch:	LANDINI DGM GA 725 C-87 6t V1,5, non-automatical, height adjustable; hole diameter 28 mm, hitch point above ground 475, 570, 700 or 795 mm, behind rear wheel axis horizontal 395 mm distance from p.t.o. shaft end vertical, above 20 or 115 mm below 110 or 205 mm, horizontal 130 mm, maximum permissible vertical load 1500 kg
Holed drawbar:	Long bar; length 1500 mm, thickness 30 mm, width 80 mm, length between joint balls 770 mm; 7 holes between joint balls with 80 mm distance each, 2 holes outside the joint balls on either side with 120 mm distance each, holes' diameter 22 mm and 24 mm alternately; at each end of the bar 1 hole with 32 mm dia; height above ground minimum 120 mm, maximum 1071 mm; holes' centre line behind p.t.o. shaft end 710 mm (lower links in horizontal position)
Towing hitch:	At front of tractor, height above ground 735 mm

Steering	MASSEY-FERGUSON and DANFOSS, model ORBITROL OSPC 100,, hydrostatic steering; separate oil circuit fed by SUNDSTRAND/ TUROLLA gear type pump TFA/211 S, directly driven by front end of crankshaft; delivery 24 l/min at rated engine speed, working pressure 15,0 MPa; 1 double acting ram (symmetrical design), bore 57 mm, stroke 234 mm, piston rod 32 mm dia, acting on steering levers of front axle; oil filter incorporated in steering oil tank
Brakes	
Service brake:	SIRMAC, 7 x 5,5 inches pedal operated muscle power brake with mechanical transmission, acting on rear axle of tractor; wet disc brakes on the differential half shafts with 4 lining discs each with 178 mm dia
Parking brake:	Mechanically actuated by hand lever with ratchet, acting on the discs of service brake
Steering brake:	Divided pedals of service brake, for normal use locked together
Trailer braking take-off:	None
Wheels	
Steering wheels:	At front, 2 pneumatics 12.4 R 24 rims W10x24
Driving wheels:	At front and at rear, rear wheels: 2 pneumatics 16.9 R 30 rims W14x30
Wheelbase:	2225 mm
Track widths:	At front 1413, 1501, 1601, 1689, 1517, 1605, 1705 or 1793 mm, variable by adjustable gauge bowl wheels, at rear 1400 to 2000 mm, variable by adjustable gauge bowl wheels in steps of 100 mm each

PRÜFUNGS-ABTEILUNG
LANDINI DT 6860

Test No. 88-83

Permissible tyre combinations:

Tyre sizes at front		at rear	
9.5 - 28	6 ply	8.3 - 44 9.5 - 44	6 ply 8 ply
11.2 R 24	114 A8	14.9 R 30 12.4 - R 36 16.9 R 28	129 A8 6 ply 136 A8
12.4 R 20	116 A8	14.9 R 28 420/70 R28	128 A8 133 A8
12.4 R 24	119 A8	16.9 R 30	6 ply
13.6 R 24	121 A8	13.6 R 38	128 A8

Protective structure: LANDINI TS 19/2 - MASSEY-FERGUSON TS 20/2, 4-post frame, OECD tested, approval-no. CSS 081/9 for LANDINI DT 6860 (TL21DT/K), CSS 081/29 for MASSEY-FERGUSON 373-4 (TL21DT/V)

Driver's seat: GRAMMER, DS 44/1H; upholstered seat with back rest, adjustable suspension and hydraulic shock absorber; driver's platform 835 mm above ground, 1 step, 560 mm above ground; range of adjustment of unloaded seat: longitudinal 200 mm vertical 510 to 570 mm (stepless) above platform

Running-time meter: Electronic, counts real operating hours, when engine speed rises above 800 rev/min

PRÜFUNGS-ABTEILUNG
LANDINI DT 6860

Test No. 88-83

Lighting — Electrical 12 Volt, in accordance with Italian legislation

	Size mm	Height above ground of centre mm	Distance from outside edge of lights to median plane of tractor mm
Head lights	130 dia	1125	241
Side lights	110x30	1450	788
Rear lights	70x50	1505	606
Reflectors			
1st pair	50x45	1505	646
2nd pair	80 dia	590	400

TEST CONDITIONS

Overall dimensions

Length:	3770 mm without ballast, 3925 mm with ballast
Width:	1915 mm with and without ballast
Height:	2375 mm to top of protective structure 2305 mm to exhaust pipe's mouth
Ground clearance:	415 mm below front axle

Tractor mass

			without driver kg	with driver kg
Without ballast:	Mass	front	1205	1210
		rear	1545	1650
		total	2750	2860
With ballast:	Mass	front	1665	1670
		rear	2235	2320
		total	3900	3990

Ballast

Front:	8 weights, total	288 kg
	water in the tyres	152 kg
Rear:	2 weights per wheel, total	240 kg
	water in the tyres	470 kg

Tyres and track widths specifications

	Front	Rear
Tyres:	MICHELIN BIB' X	MICHELIN BIB' X
dimensions	12.4 R 24	16.9 R 30
type	radial	radial
ply rating/load index	-/119 A8	-/137 A8
maximum load	1360 kg	2300 kg
inflation pressure	160 kPa	160 kPa
radius index	540 mm	695 mm
Chosen track width:	1501 mm	1500 mm
Technically permissible axle load:	1700 kg	3400 kg
Technically permissible total weight:		4000 kg

Oils and lubrication

Capacity and change interval:

	Capacity dm³	Oil change h	Filter change h
engine	7,0	250	250
gear box including rear axle and hydraulic system	33,0		250 *)
front axle	5,8		-
final drives at front	2 x 1,4	1000	-
final drives at rear	2 x 2,2		-
steering system	2,3		500 *)

*) only filter cleaning

PRÜFUNGS-ABTEILUNG
LANDINI DT 6860 Test No. 88-83

Specifications

	Recommended	Used during test
Engine oil:		
type	engine oil	MF SUPER UNIVERSALOIL
viscosity		
winter	SAE 10W, 20W or 10W/30	SAE 15W/40
summer	SAE 20W or 20W/30	
tropics	SAE 30, 20W/40 or 20W/50	
for all conditions	SAE 15W/40	
classification	API - CC	API - CC
Transmission oils:		
Gearbox, rear axle hydraulic system		
type	super tractor oil universal	MF SUPER UNIVERSALOIL
viscosity	SAE 15W/40	SAE 15W/40
classification	API - CD/API -GL4	API - CD/API - GL4
Final drives at front and at rear, front axle		
type	gear oil	MOBILUBE GX85W/90-A
viscosity	SAE 85W/90	SAE 85W/90
classification	API - GL4	API - GL4
Steering oil:		
Steering system		
type	automatic transmission fluid	MOBIL ATF 200
viscosity	-	
classification	Type A, SUFFIX A	

Grease: Multi purpose grease
number of lubrication points 13

Fuel

type: ARAL Diesel-fuel in conformity with DIN 51601
density: at 15°C at engine test 0,835 g/cm³
at p.t.o. test 0,819 g/cm³
at drawbar power test 0,821 g/cm³

REPAIRS None

REMARKS None

PRÜFUNGS-ABTEILUNG
Landini DT 6860

Test No. 88-83

COMPULSORY TESTS

1. MAIN POWER TAKE OFF PERFORMANCE (1000 rev/min)

Date of tests: 14th June 1988
Location of tests: DLG-Testing Station Groß-Umstadt
Type of dynamometer: SCHENCK hydraulic dynamometer U1-40

Power kW	Speed engine rev/min	Speed P.t.o. rev/min	Fuel consumption hourly l/h	Fuel consumption hourly kg/h	Fuel consumption specific g/kWh	Specific energy kWh/l
Maximum power						
1.1 At 2-hour test						
42,7	2200	1148	14,72	12,06	283	2,90
1.2 At rated speed						
42,7	2200	1148	14,72	12,06	283	2,90
1.3 At standard p.t.o. speed						
41,2	1917	1000	13,08	10,71	260	3,15
1.4 Part loads, the governor hand lever in the position corresponding to maximum power at full load (curve a)						
1.4.1 the torque corresponding to maximum power at rated speed						
42,7	2200	1148	14,72	12,06	283	2,90
1.4.2 85% of the torque obtained in 1.4.1						
37,6	2280	1189	13,96	11,44	304	2,69
1.4.3 75% of the torque defined in 1.4.2						
28,6	2310	1205	11,39	9,33	327	2,51
1.4.4 50% of the torque defined in 1.4.2						
19,1	2312	1206	8,77	7,19	377	2,17
1.4.5 25% of the torque defined in 1.4.2						
9,6	2321	1211	6,87	5,62	584	1,40
1.4.6 unloaded						
-	2331	1216	4,94	4,05	-	-

PRÜFUNGS-ABTEILUNG
Landini DT 6860

Test No. 88-83

Power kW	Speed engine rev/min	Speed P.t.o. rev/min	Fuel consumption hourly l/h	Fuel consumption hourly kg/h	Fuel consumption specific g/kWh	Specific energy kWh/l
1.5 Part loads, the governor hand lever in the position corresponding to the standard p.t.o. speed at full load (curve b)						
1.5.1 the torque corresponding to maximum power						
41,2	1917	1000	13,08	10,71	260	3,15
1.5.2 85% of the torque obtained in 1.5.1						
35,4	1936	1010	11,32	9,27	262	3,13
1.5.3 75% of the torque defined in 1.5.2						
27,2	1984	1035	9,49	7,77	286	2,87
1.5.4 50% of the torque defined in 1.5.2						
18,5	2026	1057	7,45	6,10	329	2,49
1.5.5 25% of the torque defined in 1.5.2						
9,4	2055	1072	5,87	4,80	512	1,60
1.5.6 unloaded						
-	2085	1088	3,83	3,14	-	-

No load maximum engine speed: 2331 rev/m
Equivalent flywheel torque at rated engine speed: 185 Nm
Maximum equivalent flywheel torque: 239 Nm at 1199 rev/min of the engine

Mean atmospheric conditions


temperature	24 °C
pressure	100 kPa
rel. humidity	40 %

Maximum temperatures

coolant	82 °C
oil	104 °C
fuel	25 °C
air intake	26 °C


PRÜFUNGS-ABTEILUNG
Landini DT 6860

Test-No.88-83



PRÜFUNGS-ABTEILUNG
Landini DT 6860

Test-No.88-83



PRÜFUNGS-ABTEILUNG
LANDINI DT 6860

Test No. 88-83

2 HYDRAULIC POWER AND LIFTING FORCE

Date of tests: 17th August 1988

2.1 Hydraulic power test

Sustained pressure with relief valve open 16,7 MPa
Pump delivery rate at minimum pressure 38,4 l/min

	Hydraulic power kW	Flow rate l/min	Pressure MPa	Oil temperature °C
At 90% of the actual relief valve setting	6,7	26,7	15,0	38 *)
At max. power	8,9	37,7	14,1	38 *)

Tapping point used for test: At rear of tractor

*) Oil temperature in suction line of hydraulic pump more than 60°C

2.2 Power lift test

	At the hitch points	On the frame
Height of lower hitch points above ground in down position	200 mm	200 mm
Vertical movement without lifting forces	712 mm	785 mm
Vertical movement with lifting forces	677 mm	729 mm
Max. corrected force exerted through full range	12,9 kN	13,0 kN
Corresponding pressure	14,1 MPa	14,1 MPa
Moment about rear axle	-	20,1 kNm
Max. tilt angle of mast from vertical	-	7,5°

Lifting heights relative to horizontal lower links

mm	-389	-357	-300	-200	-100	0	+100	+200	+300	+320	+340

Lifting forces at hitch points, corrected to 14,1 MPa

kN		12,9	14,2	16,1	17,4	18,3	18,9	19,3	19,8	19,9	

Lifting forces at standard frame, corrected to 14,1 MPa

kN	13,0		14,3	15,4	16,0	16,2	16,2	15,8	15,3		15,2

3 DRAWBAR PERFORMANCE

Date of tests: 27th June till 5th July 1988
Type of track: Concrete

Gear	Driving speed km/h	Power kW	Drawbar pull kN	Engine speed rev/min	Slip of wheels %
3.1 Maximum power in tested gears (unballasted tractor) height of drawbar above ground 480 mm					
3 L	3,08	24,9	29,16	2269	15,0
1 M	3,69	30,0	29,31	2258	14,9
4 L	4,60	33,8	26,43	2200	11,2
2 M	6,13	34,2	20,09	2198	7,6
3 M	7,89	34,4	15,69	2200	5,7
1 H	9,92	34,3	12,45	2198	4,5
4 M	11,90	33,0	9,99	2197	3,5
3.2 Maximum power in tested gears (ballasted tractor) height of drawbar above ground 475 mm					
1 L	1,57	17,0	39,01	2287	15,0
2 L	2,44	26,6	39,22	2267	15,1
3 L	3,00	32,5	39,00	2210	14,9
1 M	3,82	34,2	32,22	2200	9,4
4 L	4,81	34,0	25,48	2198	6,9
2 M	6,27	34,7	19,92	2198	5,2
3 M	8,03	33,4	14,96	2198	3,8
3.3.1 Five-hour-test at 75% of pull at maximum power in 3 M gear					
3 M	8,37	26,0	11,20	2267	2,8
3.3.2 Five-hour-test at pull corresponding to 15% wheel slip in test 3.2					
2 L	2,27	24,7	39,21	2266	-

Total oil consumption during ten hours duration of tests 3.3.1 and 3.3.2 : 41 g/h

PRÜFUNGS-ABTEILUNG

Test No. 88-83

Tyre size front: 12.4 R 24
rear: 16.9 R 30

Specific fuel consumption g/kWh	Specific energy kWh/l	Temperatures Fuel °C	Coolant °C	Engine-oil °C	Atmospheric conditions Tempe-rature °C	Relative humidity %	Pressure kPa
tyre inflation pressure: 60 kPa at front, 80 kPa at rear							
397	2,07	28	80	89	19	84	99,4
368	2,23	26	79	93	18	87	99,4
354	2,32	28	81	91	19	76	99,4
349	2,35	28	80	90	22	81	99,4
348	2,36	29	79	88	22	73	99,4
349	2,35	30	80	91	23	75	99,4
362	2,27	30	80	90	23	72	99,4
tyre inflation pressure: 60 kPa at front, 80 kPa at rear							
455	1,80	28	80	89	22	90	98,5
389	2,11	28	79	89	23	87	98,5
366	2,24	28	80	88	23	86	98,5
350	2,34	30	81	90	23	86	98,4
352	2,33	30	80	91	24	78	98,3
345	2,38	30	81	90	24	84	98,4
358	2,29	29	80	87	23	87	98,3
394	2,08	31	81	95	23	68	98,9
-	-	31	81	98	23	70	98,9

Test 3.3.2 was carried out with additional ballast of 505 kg, the figures not quoted are therefore irrelevant

PRÜFUNGS-ABTEILUNG

LANDINI DT 6860 Test No. 88-83

4 TURNING AREA AND TURNING CIRCLE (front wheel drive disengaged)

Wheel equipment front: 12.4 R 24
rear: 16.9 R 30

Track of wheels front: 1501 mm
rear: 1500 mm

	With brakes		Without brakes	
	left-hand m	right-hand m	left-hand m	right-hand m
Radius of turning area	4,09	4,06	4,70	4,73
Radius of turning circle	3,84	3,80	4,45	4,47

5 LOCATION OF CENTRE OF GRAVITY

Height above ground	815 mm
Distance forward from rear axle centre	949 mm
Distance from tractor's median plane, to the left	1 mm

PRÜFUNGS-ABTEILUNG
LANDINI DT 6860

Test No. 88-83


6 BRAKING (Front wheel drive disengaged)

Date of tests: 29th and 30th June 1988

	Tractor mass (with driver) front kg	rear kg	total kg	Speed before application of brakes km/h
Without ballast	1210	1630	2840	31,5
With ballast	1670	2320	3990	31,2

6.1 Cold service braking device test

6.2 Fade test



No significant deviation of tractor from original course and no abnormal vibrations

Brakes-heating: Actuating of brake for 1 km with pedal force corresponding to 1 m/s²

6.3 Parking braking device test

	Ballasted tractor on 18% - slope	
	up	down
Braking device control force N	190	190

PRÜFUNGS-ABTEILUNG
LANDINI DT 6860

Test No. 88-83

7 MEASUREMENT OF EXTERNAL NOISE LEVEL

Date of test: 28th June 1988
Type of track: Concrete
Type of sound level meter: BRÜEL & KJAER model 2233

Results of test

Gear: 4 H (Front wheel drive disengaged)
Travelling speed before acceleration: 23,2 km/h
Sound level: 87,5 dB(A)

APPENDIX

MEASUREMENT OF NOISE IN THE PROTECTIVE STRUCTURE

with 4-post frame LANDINI TS 19/2

Date of test: 27th June 1988
Type of track: Concrete
Type of sound level meter: BRÜEL & KJAER model 2233

Gear	Drawbar pull kN	Travelling speed km/h	Sound level dB(A)
1 L	24,30	1,55	94,0
2 L	24,07	2,44	95,0
3 L	24,50	3,01	96,0
1 M	24,29	3,68	95,0
4 L	23,41	4,79	97,0
2 M	19,89	6,09	96,5
3 M +)	15,30	7,86	97,0
3 M +)	light load	8,86	93,0
1 H	12,24	9,90	97,0
4 M	9,74	11,88	97,5
2 H	6,99	15,88	97,5
4 H *)	light load	30,99	95,0

+) The 3 M gear corresponds to the nominal travelling speed nearest to 7,5 km/h

*) Front wheel drive disengaged

PRÜFUNGS-ABTEILUNG
Landini DT 6860

Test No. 88-83

OPTIONAL TEST

8. ENGINE PERFORMANCE

Date of tests: 27th May 1988
Location of tests: DLG-Testing-Station Groß-Umstadt
Type of dynamometer: SCHENCK eddy-current-dynamometer W 150


Power kW	Engine speed rev/min	Fuel consumption hourly l/h	Fuel consumption hourly kg/h	Fuel consumption specific g/kWh	Specific energy kWh/l
Maximum power					
8.1 At 2-hour test					
46,0	2200	14,48	12,10	263	3,18
8.2 At rated engine speed					
46,0	2200	14,48	12,10	263	3,18
8.3 At standard p.t.o. speed (1000 rev/min)					
43,8	1917	12,90	10,78	246	3,40
8.4 Part loads					
8.4.1 the torque corresponding to maximum power at rated speed					
46,0	2200	14,48	12,10	263	3,18
8.4.2 85% of the torque obtained in 8.4.1					
40,3	2265	13,23	11,05	275	3,04
8.4.3 75% of the torque obtained in 8.4.2					
30,7	2303	10,62	8,88	289	2,89
8.4.4 50% of the torque obtained in 8.4.2					
20,5	2307	8,28	6,92	337	2,48
8.4.5 25% of the torque obtained in 8.4.2					
10,3	2326	6,36	5,31	514	1,62
8.4.6 unloaded					
-	2339	5,05	4,22	-	-

Optimum fuel consumption: 228 g/kWh at 25.3 kW and 1210 rev/min
No load maximum engine speed: 2339 rev/min
Torque at rated engine speed: 199 Nm
Maximum torque: 246 Nm at 1201 rev/min of the engine

Mean atmospheric conditions	temperature	24 °C
	pressure	100 kPa
	relative humidity	42 %
Maximum temperatures	coolant	82 °C
	oil	105 °C
	fuel	25 °C
	engine air intake	24 °C


PRÜFUNGS-ABTEILUNG
Landini DT 6860

Test-No.88-83




PRÜFUNGS-ABTEILUNG
Landini DT 6860

Test-No.88-83



PRÜFUNGS-ABTEILUNG
LANDINI DT 6860

Test No.88-83



Published
with the support of the Federal Minister for Food, Agriculture and Forestry

Deutsche Landwirtschafts-Gesellschaft e.V. (DLG)
Fachbereich Landtechnik — Prüfungsabteilung —
Zimmerweg 16 (DLG-Haus)
D-6000 Frankfurt am Main 1