



SILSOE RESEARCH INSTITUTE

Wrest Park, Silsoe,

Bedford MK45 4HS

Report No: OECD/7133/0196

OECD Approval No: 1703 Restricted Code

Approval Date: 13 November 1997

**Report on test in accordance with the OECD STANDARD CODE II (RESTRICTED CODE) for
the Official Testing of Agricultural and Forestry Tractors**

New Holland 8260/M115 Four-Wheel Drive Tractor with 23-speed Hi-lo Transmission (30 Km/h)



Manufactured by:

New Holland UK Ltd
Basildon
Essex
United Kingdom

Submitted for test by:

The manufacturer

Report No:

779

Date:

February 1997

TABLE OF CONTENTS

I.	SPECIFICATION OF TRACTOR	1
II.	TEST CONDITIONS	15
III.	TEST RESULTS	18
A.	Compulsory tests	
1	Main power take-off (1000 rev/min)	18
2	Hydraulic power and lifting force	20
3	Drawbar power and fuel consumption test (unballasted tractor, four-wheel drive)	22
B.	Supplementary tests	
2	I .Power lift test (To manufacturers lift rod setting)	23
3	Drawbar power and fuel consumption test (unballasted tractor, two-wheel drive)	24
	Repairs and adjustments during tests	25
	Remarks	25
Annex 1	Main power take-off curves (1000 rev/min)	26

Tractor manufacturer's name and address: New Holland UK Ltd
Basildon, Essex, United Kingdom

Location of tractor assembly: Basildon, Essex

Submitted for test by: The manufacturer

Selected for test by: The manufacturer

Place of running in: Basildon, Essex

Duration of running in: 130 hours

Location of test: Silsoe Research Institute
Wrest Park, Silsoe, United Kingdom

I. SPECIFICATION OF TRACTOR

TRACTOR

Make: New Holland
Model: 8260/M115
Type: Four wheel drive, unit construction
Serial No: BX00072
1st Serial No: 003485B

ENGINE

Make: New Holland
Model: 675/TD
Type: 4 stroke, naturally aspirated, direct injection diesel
Serial No: TD473323

Cylinders

Number/disposition: 6 vertical In-line
Bore/stroke: 111.8 mm/127.0 mm
Capacity: 7480 cm³
Compression ratio: 17.5 :1
Arrangement of valves: Overhead
Cylinder liners: None, monobloc construction

Supercharging

Make: None fitted

Fuel system

Fuel feed system:	Wabco series 6000 or Purolator 'Facet' electric lift pump
Make, type and model of fuel filter:	Plastic strainer in tank and one disposable canister filter with sediment bowl and water separator plus secondary disposable canister filter between tank and injection pump
Capacity of fuel tank:	325 litres
Make, type and model of injection pump:	Bosch, 'VE' Rotary, 0 460 426 233
Serial No:	662 748329
Manufacturer's production setting of injection pump:	
Flow rate:	66.4-70.6 mm ³ per stroke at 1100 rev/min pump speed and full load
Timing:	Delivery starts 6° before T.D.C
Make, type and model of injectors:	Bosch, multihole, 0 432 191 641 nozzle
Injection pressure:	270-278 bar

Governor

Make:	Bosch
Model:	None
Type:	Mechanical incorporated in fuel injection pump
Governed range of engine speed:	700 rev/min to 2420 rev/min
Rated engine speed:	2200 rev/min

Air cleaner

Pre-cleaner:	None
Make:	Locker Air Maze or Donaldson
Type:	3 stage dry paper element with replaceable cartridge (Exhaust Aspirated - optional)
Model:	None
Location of air intake:	Under engine hood in front and above radiator
Maintenance indicator:	Warning light on instrument panel

Lubrication system

Type of feed pump:	Forced feed from eccentric rotor pump
Type of filter:	Metal mesh strainer in sump on suction line and full flow disposable canister on pressure line to engine
Number:	1

Cooling system

Type of coolant:	Water and antifreeze (50% solution)
Type of pump:	Belt driven centrifugal impeller
Specification of fan:	Thermal controlled with viscous clutch
Number of fan blades:	5
Fan diameter:	510 mm
Coolant capacity:	25.5 litres
Type of temperature control:	Thermostat with full flow bypass
System pressure:	100 kPa

Starting system

Make:	Bosch JF
Model:	JF
Type:	Electrical, positive engagement, solenoid operated
Starter motor power rating:	3.1/3.6 kW
Cold starting aid:	CAV Thermostart - Type 357-33
Safety device:	Starting operable when all gear levers are in neutral

Electrical system

Voltage:	12 V
Generator:	Alternator
Make:	Magneti Marcelli
Model:	MME A 127
Type:	Belt driven
Power:	70/100 amps at 6000 rev/min
Batteries:	2 CEAC lead acid, mounted on front support
Rating:	70/95 AH at 20 hours rating

Exhaust system

Make:	Alcom
Model:	None
Type:	Underhood horizontal silencer with vertical stack pipe
Location:	Left-hand side of engine, under bonnet
Height of outlet above ground:	2982 mm

TRANSMISSION TO WHEELS

Main clutch

Make:	New Holland
Model:	None
Type:	Wet multiplate in gearbox for travel only
Number of plates:	7
Diameter of plates:	160 mm
Method of operation:	Mechanical/electro-hydraulic with pedal override

Gear box

Make:	New Holland
Model:	Dual command (Hi-lo)
Operation:	4 gears fully synchronised plus 3 ranges with synchromesh on upper 2 ranges, with an additional Hi/lo function on forward gears, operated by two levers on right-hand console. Forward and reverse actuated by a steering column mounted shuttle lever.
Number of gears:	23 forward, 12 reverse (30 km/h)
Available options:	46 x 24 with creep (30 km/h), 24 x 12 (40 km/h) 48 x 24 with creep (40 km/h)

Rear axle final drives

Make: New Holland

Model: None

Type: Crown wheel and pinion with differential and inboard epicyclic reduction gear final drive

Differential lock:

Type: Mechanical

Method of engagement: Electro-hydraulic actuation in response to signal from switch on right-hand control panel

Method of disengagement: Via panel switch or in response to electrical signal from brakes on application

Front axle and final drives

Make: New Holland

Model: None

Type: Crown wheel and pinion with differential and outboard epicyclic reduction gear final drives

Drive engagement:

Type: Multiplate clutch - located within the gearbox

Method of operation: Electro-hydraulic actuation in response to signal from switch on the RH control panel

Differential lock:

Type: Mechanical

Method of engagement: Electro-hydraulic actuation in response to signal from switch on right-hand control panel

Method of disengagement: Via panel switch or in response to electrical signal from brakes on application

Total ratios and travelling speeds

Gear	Ratio	Group No	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed at rated engine speed:* 2200 rev/min km/h
Forward				
1	L	A	478.02	1.42
1	H	A	396.84	1.72
2	L	A	331.37	2.05
2	H	A	275.10	2.47
3	L	A	230.32	2.95
3	H	A	191.21	3.56
4	L	A	160.72	4.23
4	H	A	133.42	5.10
1	L	B	166.33	4.09
1	H	B	138.09	4.93
2	L	B	115.31	5.90
2	H	B	95.73	7.10
3	L	B	80.14	8.49
3	H	B	66.53	10.22
4	L	B	55.91	12.16
4	H	B	46.43	14.65
1	L	C	68.02	10.00
1	H	C	56.47	12.04
2	L	C	47.15	14.42
2	H	C	39.15	17.37
3	L	C	32.77	20.75
3	H	C	27.21	25.00
4	L	C	22.87	29.74
1		A	489.13	1.39
2		A	339.08	2.01
3		A	235.68	2.89
4		A	164.45	4.14
1		B	170.20	4.00
2		B	117.99	5.76
3		B	82.01	8.29
4		B	57.22	11.89
1		C	69.60	9.77
2		C	48.25	14.10
3		C	33.54	20.28
4		C	23.40	29.06

A = Low range B = Medium range C = High range

(*) Calculated with a tyre dynamic radius index of 820 mm (ISO 4251/1-1992)

Number of revolutions of front wheels for one revolution of rear wheels: 1.340

POWER TAKE-OFF

Main power take-off

Type:	Independent
Method of engagement:	Electro - hydraulically operated multi-plate clutch in response to a signal from switch on the right-hand control panel
Number of shafts:	1 interchangeable shaft, 6 or 21 spline to ISO.500/1991
Method of changing power take-off speeds:	
Two speed	Shiftable, 540 or 1000 rev/min by lever on right-hand console

Clutch

Make:	New Holland
Model:	None
Type:	Multiplate, wet
Number of plates:	6
Diameter of plates:	140.0 mm

Two/three speed shiftable power take-off proportional to engine speed and with changeable shafts

	540 rev/min	750 rev/min	1000 rev/min
540/750/1000 rev/min			
Location:	Rear of tractor	Rear of tractor	Rear of tractor
Diameter of power take-off shaft:	34.9 mm	34.9 mm	34.9 mm
Number of splines:	6 or 21	6 or 21	6 or 21
Height above ground:	803 mm	803 mm	803 mm
Distance from the median plane of the tractor:	Central	Central	Central
Distance behind rear wheel axis:	602 mm	602 mm	602 mm
Pto speed at rated engine speed:	603	769	1038
Engine speed at standard power take-off speed:	1971	2145	2121
Ratio of rotation speeds:	3.65	2.86	2.12
Power restriction and maximum torque:	None	None	None
Direction of rotation (viewed from behind tractor):	Clockwise	Clockwise	Clockwise

Power take-off proportional to ground speed

Travelling distance for one revolution of power take-off shaft	.355 m	.263 m	.194 m
Number of power take-off shaft revolutions for one revolution of rear driving wheels	15.4	19.6	26.5

POWER LIFT - standardPump - standard

Make:	New Holland
Model:	None
Type:	Electro-hydraulic with solenoid valves, open centre for lift and drop
Type and number of cylinders:	1 single acting inside transmission housing plus the option of single acting, externally mounted assistor ram (1 fitted for test)
Type of linkage lock for transport:	Hydraulic
Relief valve pressure setting:	18.7 - 193 MPa
Opening pressure of cylinder safety valve:	19.3 MPa
Lift pump type:	Gear
Transmission between pump and engine:	Gear driven from pto shaft, independent of main and pto clutches
Type and number of filters:	2 disposable canister filters
Site of oil reservoir:	Rear axle housing
Type, number and position of tapping points:	1, 2, 3 or 4 remote couplers at rear of tractor
Maximum volume of oil available to external cylinders:	18 - 20 litres

THREE-POINT LINKAGE

Category:


2 to ISO standard 730-1:1994

Category adaptor:

None

Controls:

Electronic draught/position control link.
(Optional - draught or position control)
Lower link sensing



LIFT TEST
Linkage geometry

Table 2.1

Dimensions of linkage when attached to the standard frame (ISO 730/3-1994 CAT 2)

			Dimensions or range	Settings used in main test	Settings used in optional test
Length of lift arms		(A)	230	230	230
Length of lower links		(B)	974	974	974
Distance of lift arm pivot point from rear wheel centre line:	horizontally:	(a)	156	156	156
	vertically:	(b)	362.5	362.5	362.5
Horizontal distance between the two lower link points:		(u)	544	544	544
Horizontal distance between the two lift arm end points:		(v)	560	560	560
Length of upper link:		(S)	652-942	754	768
Distance of upper link pivot point from rear wheel centre line:	horizontally:	(c)	430-455	455	430
	vertically:	(d)	208-275	208	275
Distance of lower link pivot point from rear wheel centre line:	horizontally:	(e)	220	220	220
	vertically:	(f)	250	250	250
Distance of lower link points to lift rod pivot points on lower link centre line:	horizontally:	(D)	435-504	435	504
	vertically:	(E)	on centre line	on centre line	on centre line
Length of lift rods:		(L)	635-780	740	780
ISO mast height			610	610	610
Height of lower hitch points (*) relative to the rear wheel centre line, situated 820 mm above the ground level:					
- in low position		(h)	250-744	625	599
- in high position		(H)	41-328	70	75
Height of lower hitch points when locked in transport position (*)			Any height within lift range (hydraulic transport lock)		

* Assuming r = tyre dynamic radius index of 820 mm ISO 4251/1-1992

SWINGING DRAWBAR

Type:	Clevis			
Height above ground, unballasted maximum:	545 mm			
minimum:	443 mm			
Type of adjustment:	Inverting drawbar			
Distance of hitch point from rear-wheel axis, horizontally:	845 mm	960 mm	1010 mm	
Distance of hitch point from power take-off shaft ends:				
Vertically:	258 mm	360 mm		
Horizontally:	243 mm	358 mm	408 mm	
Lateral adjustment from the (centre of clevis):				
Right-hand	172 mm	208 mm	220 mm	
Left-hand	172 mm	208 mm	220 mm	
Distance of pivot point from rear axles horizontally:	300 mm			
Width of clevis:	68 mm			
Diameter of pin hole:	33 mm			
Maximum vertical permissible load - Clevis uppermost:	910 kg	1065 kg	1630 kg	
Clevis underneath:	910 kg	1065 kg	1135 kg	

Trailer Hitch

Type: None fitted

Linkage Drawbar

Type: None fitted

Front Towing Hitch

Type None fitted

STEERING

Make:	New Holland
Model:	None
Type:	Hydrostatic
Method of operation:	
Pump:	New Holland
Motor:	Danfoss OSPC-160-OR
Ram:	2, a balanced single acting cylinder operating each steering arm
Filter:	Integral with hydraulic power lift system
Working pressure:	166 - 178 bar

BRAKES

Service brake

Make:	New Holland
Model:	None
Type:	Oil-immersed single plate disc
Method of operation:	Hydraulic, independent on rear wheels (On (4WD) models. When the service brakes are actuated the front wheel drive is automatically engaged providing 4-wheel braking)
Trailer braking take-off:	Hydraulic connector fitted to ISO 5676-1983

Parking brake

Make:	New Holland
Type:	Fully independent three plate disc operating on bevel pinion shaft
Method of operation:	Hand lever with ratchet

WHEELS

Number: 4

Front: 2 steering and driving

Rear: 2 driving

Wheelbase: 2723 mm

Track settings

	Minimum mm	Maximum mm	Adjustment method
Front	1551	2269	Reversing wheels and offset lug rims
Rear	1630	2232	Reversing wheels and offset lug rims

PROTECTIVE STRUCTURE

Make:	New Holland
Model:	New Holland SLTV 1
Type:	Cab safety frame
Manufacturer's name and address:	New Holland UK Ltd, Basildon
Protective device:	
Rollguard:	Safety cab
Tiltable/Not tiltable:	Non-tiltable
OECD approval number:	CSD-1398/1-12, 28 September 1994
New Holland M115	CSD 1398/9
New Holland 8260	CSD 1398/3

Original test and minor modification certificates under the responsibility of S.H. STATENS
HUSDYRBRUGSFORSOG BYGHOLM, DENMARK

DRIVERS SEAT

Make/Model/Type:	Grammar DS85H1/90A
Type of suspension:	Low frequency, parallelogram suspension spring
Type of damping:	Double acting, hydraulic
Range of adjustment:	
Longitudinal:	± 75 mm
Vertical:	± 30 mm

Passenger seat (optional)

Make:	New Holland
Type:	Soft plastic moulding, half folding, on LH side of inner fender. EEC approved to Directive 76/763/EEC-e110725

LIGHTING

In accordance with EEC Directive 78/933/EEC

Unrestricted beam angle of headlight in plan view: 140°

	Height above ground to centre mm	Size mm	Distance from outside edge to median plane of tractor mm
Headlight	1380	150 x 90	200
Sidelights	1840	105 x 30	870
Rear lights	1827	50 x 50	847
Axle reflectors	792	100 x 35	570
Cab reflectors	1827	50 x 50	847

II TEST CONDITIONS

Overall dimensions

Length mm	Width		Height at top of	
	Minimum mm	Maximum mm	Protective structure mm	Exhaust pipe mm
4658	2135	2771	2824	2982

Ground clearance (unballasted tractor) 360 mm

Clearance-limiting part: Drawbar clevis in lowest position

Tractor mass (with safety cab)

	Unballasted		Ballasted	
	Without driver kg	With driver kg	Without driver kg	With driver kg
Front	2032	2037	--	--
Rear	2997	3067	--	--
Total	5029	5104	--	--

Tyres and track width specification

	Front	Rear
Tyres dimensions ply rating type	14.9 R 28 128A8 Radial	18.4 R 38 146A8 Radial
Maximum load (tyre manufacturer's), kg 30 km/h (40 km/h)	1925 (1800)	3210 (3000)
Maximum load (tractor manufacturer's), kg	1925 (1800)	3210 (3000)
Inflation pressure (tyre manufacturer's), Bar	1.6	1.6
Dynamic radius index	640	820
Chosen track width (manufacturer's nominal)	1757	1830

Oils and lubrication

Capacity and change interval

	Capacity litre	Oil change hours	Filter change hours
Engine	19.0	300	300
Front axle differential	9.0	1200	None
Final drive (front) - per side	1.7	1200	None
Rear axle Dual command + CCLS	73	1200	300
Gearbox } Hydraulic system } Final drives (rear) } Steering }	Integral with rear axle		
Brakes	0.5	Top-up	None

Fuels and lubricants used in tests

Fuel

Type: Diesel oil to Class D, 1.5 to 5.5 cSt
Specific gravity: 0.8390 g/cm³ at 15°C

<u>Oils</u>	<u>NH spec</u>	<u>Recommended</u>	<u>Used during test</u>
Engine oil			
Type:	NH 324B	SAE 10W/30	As recommended
Viscosity:		11.5 cSt at 100°C	
Classification:		API CF-4	
Transmission oils			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Rear final drives			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Front differential and final drives			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Hydraulic brakes			
Type:	NH 610A	No equivalent	As recommended
Viscosity:		6 cSt at 100°C	
Classification:		No equivalent	
Hydraulic fluid			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Steering oil			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Grease points			
Recommended grease:	NH 720A	Lithium based	As recommended
Number of lubrication points:	14		

III. TEST RESULTS

A. COMPULSORY TESTS

1. MAIN POWER TAKE-OFF (1000)

Date and location of tests:

21 January 1997
Silsoe Research Institute,
Wrest Park, Silsoe, Bedford

Type of dynamometer:

Eddy Current, Borghi and Saveri

Power kW	Speed		Fuel consumption			Specific energy kWh/l
	Engine rev/min	P.T.O. rev/min	Hourly kg/h	l/h	Specific g/kWh	
1.1 MAXIMUM POWER - TWO HOUR TEST						
81.4	2090	986	21.39	25.50	263	3.19
1.2 POWER AT RATED ENGINE SPEED						
80.3	2200	1038	21.90	26.10	273	3.08
1.3 STANDARD POWER TAKE-OFF SPEED (1000 ± 25 rev/min)						
81.1	2121	1000	21.46	25.58	265	3.17
1.4 PART LOADS						
1.4.1 The torque corresponding to maximum power at rated engine speed						
80.3	2200	1038	21.90	26.10	273	3.08
1.4.2 85% of the torque defined in 1.4.1						
71.1	2289	1080	19.78	23.58	278	3.02
1.4.3 75% of the torque defined in 1.4.2						
54.2	2324	1096	16.31	19.44	301	2.79
1.4.4 50% of the torque defined in 1.4.2						
36.3	2340	1104	12.83	15.29	353	2.37
1.4.5 25% of the torque defined in 1.4.2						
18.3	2358	1112	9.74	11.61	531	1.58
1.4.6 Unloaded						
0	2383	1124	6.66	7.94	--	--

Power kW	Speed		Fuel consumption			Specific energy kWh/l
	Engine rev/min	P.T.O. rev/min	Hourly kg/h	l/h	Specific g/kWh	
1.5	PART LOADS AT STANDARD POWER TAKE-OFF SPEEDS (1000 ± 25 rev/min)					
1.5.1	The torque corresponding to maximum power					
81.1	2121	1000	21.46	25.58	265	3.17
1.5.2	85% of the torque obtained in 1.5.1					
71.7	2203	1039	19.10	22.77	267	3.15
1.5.3	75% of the torque obtained in 1.5.2					
54.7	2239	1056	15.94	19.00	292	2.88
1.5.4	50% of the torque obtained in 1.5.2					
36.6	2255	1064	12.49	14.89	341	2.46
1.5.5	25% of the torque obtained in 1.5.2					
18.5	2278	1074	9.21	10.98	497	1.69
1.5.6	Unloaded					
0	2294	1082	6.14	7.31	--	--

No load, maximum engine speed: 2383 rev/min

Torque (equivalent crankshaft) at maximum power: 372.0 Nm

Torque (equivalent crankshaft) at rated speed: 348.7 Nm

Maximum torque (equivalent crankshaft): 460.0 Nm
(engine speed 1400 rev/min)

Mean atmospheric conditions:

- Temperature 25°C
- Pressure 1030 m bar
- Relative humidity 27%

Maximum temperatures:

- Coolant 84°C
- Engine oil 106°C
- Fuel 54°C
- Engine air intake 33°C

2. HYDRAULIC POWER AND LIFTING FORCE

Date of tests: 17 January 1997

2.1 Hydraulic power test

Sustained pressure with relief valve open: 20.2 MPa

Pump delivery rate at minimum pressure: 99.4 l/min

	Flow rate l/min	Pressure MPa	Power kW
Flow rate corresponding to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting and corresponding hydraulic power	70.6	18.2	21.41
Flow rate and hydraulic pressure corresponding to maximum hydraulic power	93.6	17.0	26.52

Tapping point used for test:

Auxiliary service connection

Temperature of hydraulic fluid if different from $65 \pm 5^{\circ}\text{C}$

-- $^{\circ}\text{C}$

Opening pressure of the unloading valve:

-- MPa

Closing pressure of the unloading valve:

-- MPa

2.2 Power lift test - (To ISO 730-1:1990)

	At the hitch point	On the frame
Height of lower hitch points above ground in down position	193 mm	193 mm
Vertical movement	732 mm	892 mm
Maximum corrected force exerted through full range	32.1 kN	30.0 kN
Corresponding pressure of hydraulic fluid	18.2 MPa	18.2 MPa
Moment about rear-wheel axis	38.3 kNm	54.1 kNm
Maximum tilt angle of mast from vertical	—	12 degrees

Linkage settings for test - see Table 2.1 and Figure 2.1

Lifting heights relative to the horizontal plane including the lower link pivot points											
mm	-432	-377	-300	-200	-100	0	100	200	300	355	460
Lifting forces (the values measured are corrected to correspond to a hydraulic pressure equivalent to 90% of the actual relief valve pressure delivered by the hydraulic system)											
at the hitch points kN	--	32.1	38.5	43.8	47.2	49.6	51.4	52.5	54.0	54.8	—
Corresponding pressure: 18.2 MPa											
at the frame kN	30.0	32.9	36.1	39.3	40.5	40.9	40.7	40.0	39.0	38.7	37.5
Corresponding pressure: 18.2 MPa											

3. DRAWBAR POWER AND FUEL CONSUMPTION TEST (UNBALLASTED TRACTOR), 4 WHEEL DRIVE

Date and Location of tests: 6 February 1997
 Silsoe Research Institute
 Wrest Park
 Silsoe
 Bedford MK45 4HS

Tyre inflation pressure
 (kPa)

Type of track: Concrete

Height of drawbar above ground	Front	Rear
400 mm	117	103

Gear and Range	Power	Drawbar Pull	Speed	Engine Speed	Slip of wheels or track	Spec Fuel cons	Spec energy	Temperature			Atmospheric conditions		
								Fuel	Coolant	Eng oil	Temp	Rel Humidity	Pressure
	kW	kN	km/h	rev/min	%	g/kWh	kWh/l	Deg C	Deg C	Deg C	Deg C	%	kPa
3.1 MAXIMUM POWER IN TESTED GEARS													
3LA*	37.5	50.2	2.69	2326	15.4	440	1.91	47	83	100	11	65	101.4
3HA*	45.8	50.3	3.28	2311	15.0	396	2.12	51	83	99	11	63	101.4
1LB	51.9	48.8	3.82	2302	12.7	366	2.30	51	83	99	11	66	101.
4LA	55.0	49.0	4.04	2296	10.7	354	2.37	50	83	99	11	65	101.5
1HB	62.5	48.3	4.66	2258	10.1	348	2.41	49	83	100	11	66	101.5
4HA	63.4	47.1	4.84	2245	9.1	345	2.43	47	84	99	11	69	101.5
2LB	67.8	43.6	5.60	2201	7.2	307	2.74	49	84	100	11	65	101.6
2HB	67.3	37.3	6.49	2090	6.0	323	2.59	45	84	101	10	74	101.6
3LB	68.5	31.4	7.84	2092	5.0	314	2.67	49	83	101	10	74	101.6
1LC	68.8	26.6	9.31	2091	4.3	312	2.69	48	84	103	10	72	101.7
3HB	66.9	25.3	9.52	2089	4.1	319	2.63	49	84	103	10	71	101.7
1HC	67.0	21.3	11.30	2093	3.5	322	2.61	48	84	101	11	67	101.6
4LB	66.7	21.0	11.42	2092	3.5	320	2.62	48	84	102	11	68	101.6
2LC	67.5	17.9	13.58	2090	3.0	316	2.65	48	84	102	11	68	101.6
4HB	65.5	17.0	13.86	2097	2.9	330	2.54	49	84	102	11	68	101.6
3.2 FUEL CONSUMPTION													
1LC	68.0	24.9	9.82	2203	4.2	323	2.59	49	84	104	10	73	101.7
3.2.1.1 75% of pull at maximum power at rated speed													
1LC	53.8	18.7	10.36	2302	3.2	342	2.45	49	83	102	11	68	101.6
3.2.1.2 50% of pull at maximum power at rated speed													
1LC	36.6	12.5	10.59	2333	2.2	409	2.05	50	82	102	11	68	101.6
3.2.1.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.1.1													
1HC	53.8	18.7	10.33	1908	3.3	315	2.66	46	82	96	11	67	101.5
3.2.1.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.1.2													
1HC	36.7	12.5	10.56	1933	2.3	375	2.24	46	81	96	11	67	101.5
3.2.2 In selected gear nearest to 7.5 km/h, at maximum power at rated engine speed													
2HB	66.6	34.9	6.87	2201	5.6	332	2.53	46	84	102	10	74	101.6
3.2.2.1 75% of pull at maximum power at rated speed													
2HB	53.1	26.2	7.29	2302	4.1	349	2.41	50	83	101	11	66	101.6
3.2.2.2 50% of pull at maximum power at rated speed													
2HB	36.2	17.5	7.47	2332	2.9	411	2.04	50	82	101	11	65	101.6
3.2.2.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.2.1													
3LB	53.0	26.3	7.26	1922	4.3	314	2.68	48	82	97	11	67	101.5
3.2.2.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.2.2													
3LB	36.1	17.5	7.45	1951	3.1	367	2.29	48	81	97	11	67	101.5

* Maximum power limited by wheelslip

2.2 Power lift test - (To manufacturers lift rod setting)

	At the hitch point	On the frame
Height of lower hitch points above ground in down position	220 mm	220 mm
Vertical movement	661 mm	716 mm
Maximum corrected force exerted through full range	39.4 kN	40.8 kN
Corresponding pressure of hydraulic fluid	18.2 MPa	18.2 MPa
Moment about rear-wheel axis	47.0 kNm	73.6 kNm
Maximum tilt angle of mast from vertical	—	6 degrees

Linkage settings for test – see Table 2.1 and Figure 2.1

Lifting heights relative to the horizontal plane including the lower link pivot points											
mm	-353	-350	-300	-200	-100	0	100	200	250	311	363
Lifting forces (the values measured are corrected to correspond to a hydraulic pressure equivalent to 90% of the actual relief valve pressure delivered by the hydraulic system)											
at the hitch points kN	--	39.4	42.7	49.7	53.9	56.3	57.7	58.4	58.8	59.1	--
Corresponding pressure: 18.2 MPa											
at the frame kN	40.8	40.8	43.5	48.0	50.0	50.4	49.7	48.1	47.2	46.1	45.4
Corresponding pressure: 18.2 MPa											

3. DRAWBAR POWER AND FUEL CONSUMPTION TEST (UNBALLASTED TRACTOR), 2 WHEEL DRIVE

Date and Location of tests: 14 February 1997
 Silsoe Research Institute
 Wrest Park
 Silsoe
 Bedford MK45 4HS

Tyre inflation pressure
 (kPa)

Type of track: Concrete

Height of drawbar above ground	Front	Rear
515 mm	117	103

Gear and Range	Power	Drawbar Pull	Speed	Engine Speed	Slip of wheels or track	Spec Fuel cons	Spec energy	Temperature			Atmospheric conditions		
								Fuel	Coolant	Eng oil	Temp	Rel Humidity	Pressure
	kW	kN	km/h	rev/min	%	g/kWh	kWh/l	Deg C	Deg C	Deg C	Deg C	%	kPa
3.1 MAXIMUM POWER IN TESTED GEARS													
3HA*	32.8	36.8	3.24	2331	14.7	576	1.46	49	82	98	7	57	99.4
1LB*	38.2	37.0	3.72	2327	15.0	493	1.70	52	82	99	7	57	99.4
4LA	39.7	36.0	3.96	2327	11.9	500	1.68	50	82	99	7	56	99.4
1HB	46.1	36.1	4.59	2314	11.6	429	1.95	51	83	100	7	58	99.4
4HA	47.3	35.4	4.80	2312	10.7	415	2.02	48	82	100	7	49	99.4
2LB	54.4	35.5	5.52	2298	10.9	376	2.23	49	83	101	6	59	99.4
2HB	63.7	35.5	6.46	2227	10.5	355	2.36	49	82	103	6	59	99.4
3LB	67.6	32.4	7.52	2088	7.1	323	2.60	48	83	104	7	58	99.4
1LC	69.7	27.8	9.03	2093	5.6	313	2.68	46	83	104	8	58	99.5
3HB	67.8	26.4	9.23	2086	5.0	322	2.61	45	83	104	7	58	99.5
1HC	68.6	22.5	11.00	2090	4.2	320	2.62	45	83	104	8	58	99.5
4LB	68.1	22.0	11.13	2093	4.1	322	2.61	43	83	103	7	62	99.5
2LC	68.5	18.6	13.27	2093	3.6	318	2.64	43	83	103	5	69	99.5
4HB	66.7	17.8	13.48	2090	3.5	327	2.57	42	83	102	5	70	99.5
3.2 FUEL CONSUMPTION													
3.2.1 in selected gear, at maximum power at rated speed													
1LC	69.1	26.1	9.54	2205	5.2	321	2.62	46	84	105	8	56	99.5
3.2.1.1 75% of pull at maximum power at rated speed													
1LC	55.1	19.6	10.11	2303	3.8	345	2.43	46	83	104	8	54	99.5
3.2.1.2 50% of pull at maximum power at rated speed													
1LC	37.5	13.0	10.35	2334	2.7	421	1.99	48	82	103	7	56	99.5
3.2.1.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.1.1													
1HC	54.8	19.5	10.10	1913	4.0	320	2.62	45	82	100	7	50	99.4
3.2.1.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.1.2													
1HC	37.3	13.0	10.34	1936	2.8	394	2.13	45	81	99	7	50	99.4

* Maximum power limited by wheelslip
 Gear nearest 7.5 km/h is also slip gear

REPAIRS AND ADJUSTMENTS DURING TESTS: None

REMARKS: None

Test carried out by: S J Devonshire

Signed:



P C Seward

Officer in charge of tests

Signed:



P C Seward
Head of Test Engineering Group

for the Director



Date:

13/11/97

ANNEX 1 MAIN POWER TAKE-OFF CURVES



P.T.O. POWER TEST - NEW HOLLAND M115 FOUR-WHEEL DRIVE (1000 rev/min)

Governor set for maximum power at rated speed
Governor set for maximum power at pto speed
Power take-off speed (1000 rev/min)



P.T.O. POWER TEST - NEW HOLLAND M115 FOUR-WHEEL DRIVE (1000 rev/min)

Governor set for maximum power at rated speed □
 Governor set for maximum power at pto speed ■
 Power take-off speed (1000 rev/min) |




P.T.O. POWER TEST - NEW HOLLAND M115 FOUR-WHEEL DRIVE (1000 rev/min)

Governor set for maximum power at rated speed



Governor set for maximum power at pto speed



1. *Staphylococcus aureus* (Staphylococcus aureus)

2. *Staphylococcus aureus* (Staphylococcus aureus)

3. *Staphylococcus aureus* (Staphylococcus aureus)

4. *Staphylococcus aureus* (Staphylococcus aureus)

5. *Staphylococcus aureus* (Staphylococcus aureus)

6. *Staphylococcus aureus* (Staphylococcus aureus)

7. *Staphylococcus aureus* (Staphylococcus aureus)

8. *Staphylococcus aureus* (Staphylococcus aureus)

9. *Staphylococcus aureus* (Staphylococcus aureus)

10. *Staphylococcus aureus* (Staphylococcus aureus)

11. *Staphylococcus aureus* (Staphylococcus aureus)

12. *Staphylococcus aureus* (Staphylococcus aureus)

13. *Staphylococcus aureus* (Staphylococcus aureus)

14. *Staphylococcus aureus* (Staphylococcus aureus)

