T.C
TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI
TEST MERKEZİ MÜDÜRLÜĞÜ

TEST REPORT

REPORT NUMBER:1379/2245 TGK.8

OECD APPROVAL NO: 2/2 174
DATE OF APPROVAL : 11/10/2004

Report on test in accordance with the OECD Standard Code 2 for the Official Testing of Agricultural Tractors Performance

CODE 2
(Restricted code)



NEW HOLLAND TD80D – 2 WD
(12+12 speeds-30 km/h)

CASE IH JX80 – 2 WD
(CASE IH JX75 for North America)
(12+12 speeds-30 km/h)

Tested Equipment
TRACTOR
Make : NEWHOLLAND
Model : TD80D
Type : 2WD

Applicant
Name: Türk Traktör ve Ziraat Mak.A.Ş.
Adress: Güvercin yolu 111-112 06560 Gazi/ANKARA
Tel: +90 312 2110190(Pbx)

This test report may be copied only in full, partial copying is allowed only with written permission from TAMTEST.

MAY - 2004
ANKARA

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

TABLE OF CONTENTS

1. SPECIFICATIONS OF TRACTOR ..... 3 to 17

2. TEST CONDITIONS ..... 18 to 19

3. COMPULSORY TEST RESULTS
3.1 Main power take-off ..... 20 to 24

3.2 Hydraulic power and lifting force ..... 25 to 26

3.3 Drawbar power and fuel consumption (unballasted tractor) ..... 26 to 27

4. OPTIONAL TEST RESULT 27

5. REPAIRS 27

6. REMARKS 27

This is a report on a tractor tested in accordance with OECD standard code for the official Testing of Agricultural Tractor Performance, it doesn't contain an evaluation of the tractor on field activities.

UNITS

Forces	1 kN	= 1000 N	= 102 kp
Powers	1 kW	= 1.36 HP	
Pressures	1 MPa	= 10 bar	= 10.2 kp/cm^2
	100 kPa	= 1000 mbar	= 750.1 mmHg

New Holland TD 80 D (2WD) and Case IH JX 80 (2WD) tractors have same specification but they have different colour, bonnet, rim colour, grill, headlights, grill support and model (trade name).
All tests were carried out on New Holland TD 80 D.

Note:
[C] data declared by the manufacturer and controlled by the station
[D] data declared by the manufacturer

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

[C]	Tractor Manufacturer's name and address	:TÜRK TRAKTÖR ve ZIRAAT MAKINALARI A.Ş. Güvercin yolu 111-112 Gazi/ANKARA Tel:+90 312 211 01 90
[D]	Location of tractor assembly	:TÜRK TRAKTÖR ve ZIRAAT MAKINALARI A.Ş.
[D]	Submitted for test by	:TÜRK TRAKTÖR ve ZIRAAT MAKINALARI A.Ş.
[C]	Selected for test by	: TÜRK TRAKTÖR ve ZIRAAT MAKINALARI A.Ş. with agreement of the Testing Station
[C]	Place of running – in	:DAEMTC (The Directorate of Agricultural Equipment and Machinery Testing Centre)
[C]	Duration of running-in	: 10 hours
[C]	Location of test	:DAEMTC, Ankara

1. SPECIFICATIONS OF TRACTOR

1.1 IDENTIFICATION

1.1.1.	Make of the tractor	: NEW HOLLAND
[C]	Model (trade name)	: TD 80 D
[C]	Type	: 2 WD
1.1.2.	Serial No	
[D]	First Serial No or Prototype	: Not announced
[C]	Serial No	: HFD018111
1.1.3.	Other Specifications;	
[D]	Model (s) for other countries	: sold as CASE IH JX 75 in North America
[C]	Transmission Type or Gears x Ranges	: Mechanical, full synchromesh, 12 forward 12 reverse
[C]	Speed version	: 30 km/h
[C]	Manufacturer identification or Technical type number	: D3S2AA

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

1.2 ENGINE

[C]	Make, Model and Type	:IVECO, 8045.05 R, water cooled, direct injection, 4 cycles, diesel engine
[C]	Serial No.	: *639-998366*
1.2.1	**Cylinders**	
[C]	Number/disposition	: 4, vertical in line
[D]	Bore/stroke	: (104 /115) mm
[D]	Capacity	: 3908 cm^3
[D]	Compression rate	: (18±0.5) /1
[D]	Arrangement of valves	: Overhead
[D]	Cylinder liners	: Dry
1.2.2	**Supercharging**	: None
1.2.3	**Fuel System**	
[C]	Fuel feed system	: With double diaphragm, mechanical
[C]	Make, type and model of fuel filter (s)	: New Holland, replaceable paper element cartridge
[D]	Capacity of fuel tank	: 90 dm^3
[C,D]	Make, model and type of injection pump	: BOSCH, L985 , rotative (or BOSCH VE 4/12 F1250 LV 15604)
[C]	Serial no	: 556748

Manufacturer's production setting of injection pump

[C]	Flow rate*	: (14.64 -15.95) dm^3/h at rated engine speed and full load
[D]	Timing	: 4°± 0.5° before T.D.C
[D]	Make,type and model of injectors	: BOSCH, DLLA 132 S,multipoints injected
[D]	Injection pressure	: (26.0 ±1.2) MPa

*not any setting by the manufacturer because of atmospheric pressure

1.2.4 Governor

[C]	Make, model and type	: BOSCH, mechanical, in corporated in the fuel pump
[C]	Governed range of engine speed:	(650 – 2750) rev/min
[C]	Rated engine speed	: 2500 rev/min

1.2.5 Air cleaner

Pre-cleaner

[C]	Make, model and type	: New Holland, 1930536 11C, paper filter
[C]	Location of air intake	: In front of radiator, under bonnet

Main cleaner

[C]	Make, model and type	: CNH, 1930537
[C]	Maintenance indicator	: Warning light on the dashboard

1.2.6 Lubrication system

[D]	Type of feed pump	: Gear type
[D]	Type of filter(s)	: One is metal mesh strainer, the other is replaceable paper cartridge
[C]	Number of filters	: 2

1.2.7 Cooling system

[C]	Type of coolant	: Water
[D]	Type of pump	: Centrifugal, belt driven
	Specification of fan	
[C]	Number of fan blades	: 4
[C]	Fan diameter	: 392 mm
[D]	Coolant capacity	: 14 dm^3
[C]	Type of temperature control	: Thermostat and thermometer indicating temperature level on dashboard
[D]	Superpressure system	: 70 kPa

1.2.8 Starting system

[C]	Make, model and type	: BOSCH, 6 033 ACO 218, solenoid engaged
[D]	Starter motor power rating	: 3.5 kW
[C]	Cold starting aid	: Flame glow plug and additional fuel system in injection pump
[C]	Safety device	: Clutch safety switch

1.2.9 Electrical system

[C]	Voltage	: 12 V
	Generator	
[C]	Make,model and type	: MAGNETTI MARELLI, RTT 119 AC, alternator
[D]	Power	: 1.0 kW
	Battery of accumulators	
[C]	Number	: 1
[D]	Rating	: 120 Ah at 20 h

1.2.10 Exhaust system

[C,D]	Make, model and type	: BİLEN 5093950, (or ALCOM 5172649) under the bonnet, with expansion chamber
[C]	Location	: On left hand side of engine, vertical (or on left hand side of engine ,horizontal)

1.3 TRANSMISSION

1.3.1 Clutch (travel and power take-off)

[D]	Make, model and type	:VALEO, dual clutch, dry, cerametallic material
[D]	Number of plates	: 2
[D]	Diameter of plates	: 280 mm
[C]	Method of operation	: Mechanical; pedal operated for main clutch and hand lever for PTO clutch

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

1.3.2 Gear box

[D] Make, model and type : CNH, mechanical, full syncromesh

Description :

		Forward	Reverse
[C]	Number of gears	4	4
[C]	Number of ranges/groups	3/-	3/-
[C]	Total of arrangements	12	12

Available options :

[D] 12x4

[D] 20x12 with creeper

1.3.3 Rear axle and final drives

[D] Make, model and type : CNH, with reducter

Differantial lock

[D] Type : Mechanical

[C] Method of engagement : Pedal operated

[C] Method of disengagement : Self disengaged or steering movement

1.3.4 Front axle

[D] Make, model and type : NEW HOLLAND, telescopic, adjustable U type

[C] **1.3.5 Total ratios & travelling speed (tested tractor)**

Gear no	Group or range	Number of engine revolutions for one revolution of the driving wheels		Nominal travelling speed (*) at rated engine speed of 2500 rev/min km/h	
		Forward	Reverse	Forward	Reverse
1	I Slow	396.236	404.257	1.77	1.74
2		257.172	262.378	2.73	2.68
3		189.113	192.941	3.71	3.64
4		132.015	134.688	5.32	5.21
1	II Normal	169.648	173.082	4.14	4.06
2		110.108	112.337	6.38	6.25
3		80.968	82.607	8.67	8.50
4		56.522	57.666	12.42	12.18
1	III Fast	72.060	73.518	9.74	9.55
2		46.769	47.716	15.01	14.72
3		34.392	35.088	20.42	20.01
4		24.008	24.494	29.25	28.67

* Calculated with a tyre dynamic index of 745 mm (ISO 4251/1-1998)

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

[D] 1.3.6 Total ratios & travelling speed (Optional)

Gear no	Group or range	Number of engine revolutions for one revolution of the driving wheels		Nominal travelling speed (*) at rated engine speed of 2500 rev/min km/h	
		Forward	Reverse	Forward	Reverse
1	I Slow	396.236	-	1.77	-
2		257.172	-	2.73	-
3		189.113	-	3.71	-
4		132.015	-	5.32	-
1	II Normal	169.648	191.776	4.14	3.66
2		110.108	124.470	6.38	5.64
3		80.968	91.529	8.67	7.67
4		56.522	63.894	12.42	10.99
1	III Fast	72.060	-	9.74	-
2		46.769	-	15.01	-
3		34.392	-	20.42	-
4		24.008	-	29.25	-

*Calculated with a tyre dynamic index of 745 mm 4251/1-1998)

[D] 1.3.7 Total ratios & travelling speed (Optional)

Gear no	Group or range	Number of engine revolutions for one revolution of the driving wheels		Nominal travelling speed (*) at rated engine speed of 2500 rev/min km/h	
		Forward	Reverse	Forward	Reverse
1	I Creeper	2188.611	-	0.32	-
2		1420.492	-	0.49	-
3		1044.564	-	0.67	-
4		729.186	-	0.96	-
1	II Creeper	937.050	-	0.75	-
2		608.181	-	1.15	-
3		447.228	-	1.57	-
4		312.200	-	2.25	-
1	I Slow	396.236	417.090	1.77	1.68
2		257.172	270.708	2.73	2.59
3		189.113	199.066	3.71	3.53
4		132.015	138.963	5.32	5.05
1	II Normal	169.648	178.576	4.14	3.93
2		110.108	115.903	6.38	6.06
3		80.968	85.230	8.67	8.24
4		56.522	59.497	12.42	11.80
1	III Fast	72.060	75.852	9.74	9.26
2		46.769	49.231	15.01	14.26
3		34.392	36.202	20.42	19.40
4		24.008	25.272	29.25	27.78

*Calculated with a tyre dynamic index of 745 mm ISO 4251/1-1998)

1.4 POWER TAKE-OFF

1.4.1 Main power take-off

[C]	Type	: Independent
[C]	Method of engagement	: Mechanical, by hand lever
[C]	Number of shafts	: 1
[D]	Method of changing power take-off shaft ends and speeds	:Hand lever and changing PTO shaft

1.4.1.1 Power take-off proportional to engine speed

540 rev/min

[C]	Location	: At rear of tractor
[C]	Diameter of power take-off shaft end	: 34.9 mm
[C]	Number of splines	: 6, in conformity with ISO 500:1991
[C]	Height above ground	: 735 mm
[C]	Distance from the median plane of the tractor	: 0 mm
[C]	Distance behind rear-wheel axis	: 305 mm
[C]	P.T.O speed at rated engine speed	: 614 rev/min
[C]	Engine speed at standard power take-off speed	: 2200 rev/min
[C]	Ratio of rotation speeds (engine speed/p.t.o speed)	: 4.074/1
[D]	Power restriction and maximum torque	: None
[D]	Maximum torque transmissible	: None
[C]	Direction of rotation (viewed from behind tractor)	: Clockwise

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

750 rev/min

[D]	Location	: At rear of tractor
[D]	Diameter of power take-off shaft end	: 34.9 mm
[D]	Number of splines	:6,not in conformity with ISO 500:1991
[D]	Height above ground	: 735 mm
[D]	Distance from the median plane of the tractor	: 0 mm
[D]	Distance behind rear-wheel axis	: 305 mm
[D]	P.T.O speed at rated engine speed	: 787 rev/min
[D]	Engine speed at standard power take-off speed	: 2382 rev/min
[D]	Ratio of rotation speeds (engine speed/p.t.o speed)	: 3.176/1
[D]	Power restriction and maximum torque	: None
[D]	Maximum torque transmissible	: None
[D]	Direction of rotation (viewed from behind tractor)	: Clockwise

1000 rev/min (not fitted on tested tractor)

[C]	Location	: At rear of tractor
[C]	Diameter of power take-off shaft end	: 34.9 mm
[C]	Number of splines	: 21
[C]	Height above ground	: 735mm
[C]	Distance from the median plane of the tractor	: 0 mm
[C]	Distance behind rear-wheel axis	: 305 mm
[C]	P.T.O speed at rated engine speed	: 1050 rev/min
[C]	Engine speed at standard power take-off speed	: 2381 rev/min

[C]	Ratio of rotation speeds (engine speed/p.t.o speed)	: 2.381/1
[D]	Power restriction and maximum torque	: None
[D]	Maximum torque transmissible	: None
[C]	Direction of rotation (viewed from behind tractor)	: Clockwise

1.4.1.2 Power take-off proportional to ground speed (rear)

		540	750	[D]1000*
[C]	Travelling distance for 1 revolution of take-off shaft	: 0.526 m	0.411 m	0.308 m
[C]	Number of power take-off shaft revolutions for one revolution of (rear) driving wheels	: 8.9	11.4	15.2
[C]	Direction of ratation with forward gear engaged (viewed from behind tractor)	: Clockwise		

* Not fitted on tested tractor

1.4.2 Optional power take-off : None


1.5 HYDRAULIC POWER LIFT


[C]	Make, model and type	: NEW HOLLAND, Lift-O-matic, draft and float controlled
[C]	Type of hydraulic system	: Open center system
[C]	Type and number of cylinders	: 1, single acting
[C]	Type of linkage lock for transport	: Hydraulic
[D]	Relief valve pressure setting	: (19.4-19.9) MPa
[D]	Opening pressure of cylinder safety valve	: (23.4 - 24.5) MPa
[D]	Lift pump type	: Gear
[D]	Transmission between pump and engine	: Mechanical
[C]	Type and number of filters	: 1, replaceable cartridge element
[C]	Site of oil reservoir	: Gear box and rear axle
[C]	Type, number and location of tapping points	: At rear of tractor, 4, double acting
[C]	Maximum volume of oil available to external cylinders	: None

1.6 Three- point linkage

[C]	Category	: I and II, ISO 730-1:1994 + Corrigendum 1:1995
[C]	Category adapter	: Yes

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr





TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

TABLE 2.1. Dimensions of linkage geometry (when connected to the standard frame)

		Dimension or range (mm)	Settings used in test (mm)
[C] Length of lift arms	(A)	255	255
[C] Length of lower links	(B)	970	970
Distance of lift arm pivot point from rear wheel axis			
- [C] Horizontally	(a)	-16	-16
- [C] Vertically	(b)	295	295
[C] Horizontal distance between the two lower link points	(u)	510	510
[C] Horizontal distance between the two lift arm end points	(v)	505	505
[C] Length of upper link	(S)	from710 to1060	840
Distance of upper link pivot point from rear wheel axis			
- [C] horizontally	(c)	180/195	195
- [C] vertically	(d)	200/250	200
Distance of lower link pivot point from rear wheel axis			
- [C] horizontally	(e)	57	57
- [C] vertically	(f)	205	205
[C] Distance of lower link pivot points to lift rod pivot points on lower links	(D)	470/540	470
[C] Length of lift rods	(L)	from 520 to 690	645
Height of lower hitch points relative to the rear wheel axis			
- [C] in low position	(h)	from 185 to 640	545
- [C] in high position	(H)	from 140 to 450	215
[C] Height above ground of lower hitch points when locked in transport position (*)		Any height within lift range	

[C] (*)Assuming r = 745 mm tire dynamic radius index of ISO 4251/1-1998

Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

1.7 SWINGING DRAWBAR

[C]	Type	: Clevis
	Height above ground;	
[C]	Maximum	: 485 mm
[C]	Minimum	: 375 mm
[C]	Type of adjustment	: Reversing
[C]	Distance of hitch point from rear – wheel axis horizontally	: 785 mm
[C]	Distance of hitch point from p.t.o shaft ends	
	Vertically	: 240/350 mm
	Horizontally	: 480 mm
	Lateral adjustment (center of clevis)	
[C]	Right-hand	: -
[C]	Left-hand	: -
[C]	Distance of pivot point from rear-wheel axis horizontally	: 137 mm
[C]	Diameter drawbar pin hole	: 29 mm
[D]	Maximum vertical permissible load	: None

1.8 TRAILER HITCH

[C]	Type	: Coupling
[C]	Hole diameter	: 29 mm
[C]	Height above ground	: 1035 mm
[C]	Distance of hitch point from rear – wheel axis, horizontally	: 540 mm
	Distance of hitch point from PTO shaft end	
[C]	Vertically	: 300 mm
[C]	Horizontally	: 235 mm
[D]	Maximum vertical permissible load	: None

1.9 HOLED DRAWBAR : None

1.10 STEERING

[D] Make, model and type : Ognibene, STA ON 100, hydrostatic

Method of operation

[D] Pump(s) : Gear pump

[D] Ram(s) : 1, Double acting, actuated on front axle

[D] Working pressure : 10.0 MPa

1.11 BRAKES

1.11.1 Service brake

[D] Make, model and type : NEWHOLLAND, mechanical, oil immersed disc

[C] Method of operation : Mechanical, pedal operated

[C] Trailer braking take-off : None

1.11.2 Parking brake

[C] Type :Mechanical, in common with servise brake

[C] Method of operation :By hand lever operated

1.12. WHEELS

Number

[C] Front : 2/steering

[C] Rear : 2/driving

[C] Wheelbase : 2295 mm

Track width adjustment

		Minumum mm	Maximum mm	Adjustment method
[D]	Front	1375	1775	extending of front axle
[D]	Rear	1515	2015	reversing wheels and off-set lug rims

1.13 PROTECTIVE STRUCTURE

[C]	Make, model and type	: NEW HOLLAND, TD-KÇ-2, (CNH GR6)
[C]	Manufacturer's name and address	: Türk Traktör Ziraat Mak. A.Ş. Güvercin yolu No:111-112 Gazi/ANKARA
	Protective device	
[C]	Cab / frame / roll guard / other	: Roll-bar
[C]	Tiltable / not tiltable	: Tiltable
	OECD approval	
[C]	Approval number	: 4/0 761/1
[C]	Date of approval	: 10/05/2004

[D] Nos. of minor modification of certificates, if any: None

1.14 SEAT

1.14.1 Driver's seat

[C]	Make, model and type	: PILOT, 2001/SM 80 X, vinylex covered
[C]	Seat and steering wheel reversible	: No
[C]	Type of suspension	: Mechanical, with spring
[C]	Type of damping	: Hydraulic, with amortisor
	Range of adjustment	
[C]	Longitudinally	:150 mm
[C]	Vertically	: 65 mm
[C]	Safety belt	: None

1.14.2. Optional driver's seat(s)

1.14.2.1

[D] Make, model and type : PİLOT, T 300, vinylex covered

[D] Type of suspension : Mechanical, with spring

[D] Type of damping : Hydraulic, amortisor

Range of adjustment

[D] Longitudinally :150 mm

[D] Vertically : 65 mm

1.14.2.2

[D] Make, model and type : PILOT, T 300 A, vinylex covered

[D] Type of suspension : Mechanical, with spring

[D] Type of damping : Hydraulic, with amortisor

Range of adjustment

[D] Longitudinally :150 mm

[D] Vertically : 65 mm

1.14.3 Passenger seat : None

1.15 LIGHTING

		Height above ground of center mm	Size mm	Distance from outside edge of lights to median plane of tractor mm
[C]	Headlights	1295	145x90	196
[C]	Sidelights	1665	75x70	765
[C]	Rearlights	1665	75x70	655
[C]	Reflectors I	1665	75x35	690
[C]	Reflectors II	665	105x55	558

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

2. TEST CONDITIONS

2.1 OVERALL DIMENSIONS (unballasted tractor)

Length mm	Width		Height at top of	
	minimum mm	maximum mm	Protective structure mm	exhaust pipe mm
3765	1944	2444	2670	2505

2.2 GROUND CLEARANCE (unballasted tractor)

Clearance – limiting part :300 mm (bottom point of swinging drawbar)

2.3 TRACTOR MASS (with roll-bar)

	Unballasted	
	Without driver kg	with driver kg
Front	1117	1145
Rear	2018	2070
Total	3135	3215

2.4 TRACK SPECIFICATION: Not applicable

2.5 TYRES AND TRACK WIDTH SPECIFICATIONS

	Front	Rear
Tyres :	GOOD YEAR	GOOD YEAR
Dimensions	9.00-16	16.9R34
Ply rating	10	139 A8
Type	Diagonal	Radyal
Maximum load (tyre manufacturer's)	12.21 kN	23.82 kN
Maximum load (tractor manufacturer's)	12.21 kN	23.82 kN
Inflation pressure (tyre manufacturer's)	390 kPa	170 kPa
Dynamic radius index	415 mm	745 mm
Chosen track width	1497 mm	1516 mm

2.6 FUEL

Type : Diesel oil, in conformity with national standard, TS 3082

Density at 15 °C : 0.835 g/cm^3

2.7 OILS AND LUBRICATION

2.7.1 Capacity and change interval

	Capacity dm^3	Oil change h	Filter Change h
Engine	11.7	200	400
Gear box*	46	1600	400
Final drive (rear) *			
Hydraulic system *			
Steering	1.8	-	800

* Common with gear box

2.7.2 Specifications

	Recommended	Used during test
Engine oil Type Viscocity Classification	BP TERRAC DIESEL 20W/50 DM/12	Same
Hydraulic Fluid Type Viscocity Classification	BP TERRAC TRACTAN 8 Fluid 8 DT/14	Same
Transmission oils Type Viscocity Classification	BP TERRAC TRACTAN 8 Fluid 8 DT/14	Same
Steering Type Viscocity Classification	BP TERRAC TRACTAN 8 Fluid 8 DT/14	Same

2.7.3 Grease : MOBILUX EP2

Number of lubrication points : 9

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

3. COMPULSORY TEST RESULTS

3.1 MAIN POWER TAKE-OFF

Date and location of tests : 28/05/2004, D.A.E.M.T.C,Ankara

Type of dynamometer bench : AEG, Electrical

Power	Speed		Fuel consumption			Specific energy
	Engine	PTO	Hourly		Specific	
kW	rev/min		kg/h	l/h	g/kWh	kWh/ l
3.1.1. MAXIMUM POWER- TWO HOUR TEST						
47.9	2500	614	13.13	15.72	274	3.05
3.1.2. Power at rated engine speed						
47.9	2500	614	13.13	15.72	274	3.05
3.1.3. Standard Power Take-off speed (540 ± 10 rev/min)						
47.3	2200	540	12.14	14.54	257	3.25
3.1.4. PART LOADS						
3.1.4.1.The torque corresponding to maximum power at rated engine speed						
47.9	2500	614	13.13	15.72	274	3.05
3.1.4.2. 85% of torque obtained in 3.1.4.1.						
42.1	2584	634	11.67	13.98	277	3.01
3.1.4.3. 75% of torque defined in 3.1.4.2.						
32.1	2624	644	9.60	11.50	300	2.79
3.1.4.4. 50% of torque defined in 3.1.4.2.						
21.7	2664	654	7.76	9.29	357	2.34
3.1.4.5. 25% of torque defined in 3.1.4.2.						
11.1	2724	669	5.26	6.30	474	1.76
3.1.4.6. No load						
0	2750	675	3.82	4.58	-	-

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

Power	Speed		Fuel consumption			Specific energy
	Engine	PTO	Hourly		Specific	
kW	rev/min		kg/h	l/h	g/kWh	kWh/ l
3.1.5.PART LOADS AT STANDARD POWER TAKE-OFF SPEED (540 ±10 rev/min)						
3.1.5.1. The torque corresponding to maximum power						
47.3	2200	540	12.14	14.54	257	3.25
3.1.5.2. 85% of torque obtained in 3.1.5.1.						
42.8	2340	574	11.22	13.44	262	3.18
3.1.5.3. 75% of torque defined in 3.1.5.2.						
32.9	2397	588	9.13	10.93	278	3.01
3.1.5.4. 50% of torque defined in 3.1.5.2.						
22.4	2453	602	7.07	8.47	315	2.65
3.1.5.5. 25% of torque defined in 3.1.5.2.						
11.6	2528	621	4.96	5.94	429	1.95
3.1.5.6. No load						
0	2563	629	3.30	3.95	-	-

Maximum engine speed at no load : 2750 rev/min


Torque at maximum power(equivalent crankshaft)
At rated engine speed :183.16 Nm
At 2-hour test :183.16 Nm
Maximum torque :250.47 Nm (1300 rev/min engine speed)


Mean atmospheric conditions
Temperature : 27 °C
Pressure : 92.1 kPa
Relative humidity : 42%

Maximum temperatures (°C)
Cooling water : 89
Engine oil : 109
Fuel : 36
Engine air intake : 36

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr


PTO POWER






TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr


PTO POWER





TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

PTO POWER



TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

3.2 HYDRAULIC POWER AND LIFTING FORCE

Date of tests :02/06/2004 and 09/06/2004

3.2.1 Hydraulic power test

3.2.1.1 Hydrolic fluid data

Hydrolic fluid type : TERRAC TRACTAN 8
Viscosity index, ISO 3448 + Cor. 1:1993 : 95
Viscosity at 65 °C : Not declared

3.2.1.2 Compulsory Reporting (Test results) *

	Pressure(4)	Reservoir oil Temperature°C (65 °C target)		Engine speed	Flow rate	Power
	MPa	Min	Max	rev/min	L/min	kW
Rated Engine Speed (Manufacturer Specification)	-	-	-	2500	-	-
3.2.1.2.1 Maximum (sustained) pressure with relief valve open as measured at the coupler Pump stalled: No	(2) 17.5	60	70	2709	-	-
	17.5	60	69	2705	-	-
3.2.1.2.2 Flow rate corresponding to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting and corresponding hydraulic power	(2) 15.8	(3) 67		2717	29.9	7.9
	15.8	67		2709	32.1	8.4
3.2.1.2.3 Maximum avaible flow and maximum power from one coupler pair (1)	(2) 12.0	(3) 64		2734	53.7	10.7
	12.0	66		2726	54.8	11.0
3.2.1.2.4 Maksimum flow rate at minimum pressure	(2) 2.0	(3) 60		2750	57.6	-
	2.0	60		2750	57.8	-
Number of pair of coupler used	1					
	2					

Note1:Calculated maximum power is based on only the coupler outlet pressure (pressure near coupler where oil is exiting from tractor) and does take not into account the return coupler pressure.
Note 2:Record pressure as measured at the outlet coupler (pressure near coupler where oil is exiting from tractor).
Note 3:Average test temperature.
Note 4: See ISO 789-10:1996 for the specific location of the pressure measurements and other referenced terms.

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

3.2.2 Power lift test

Linkage settings for test: see 12-13 pages

		At the hitch point	On the frame
Height of lower hitch point above ground in down position	mm	200	200
Vertical movement With lifting force Without lifting force	 mm mm	 730 760	 975 1020
Maximum corrected force exerted through full range	kN	20.0	14.4
Corresponding pressure of hydraulic fluid	MPa	15.8	15.8
Moment about rear wheel axis	kNm	20.54	23.57
Maximum tilt angle of mast from vertical	Degrees	-	18°

Lifting heights relative to the horizontal lower links											
mm	-415	-330	-200	-100	0	+100	+200	+300	+400	+500	+560
Lifting forces at the hitch point: Corresponding pressure:15.8 MPa											
kN*	-	20.0	22.3	23.0	23.5	23.7	23.9	24.3	23.6	-	-
Lifting forces at the frame: Corresponding pressure: 15.8 MPa											
kN*	16.9	17.0	17.6	17.6	17.6	17.5	17.0	16.7	16.4	16.2	14.4

*The values of force measured shall be corrected to correspond to a hydraulic pressure equivalent to 90 % of the actual relief valve pressure setting of the hydraulic lift system.

3.3 DRAWBAR POWER AND FUEL CONSUMPTION (unballasted tractor)

Date of tests :16/06/2004

Type of track : Concrete

Height of drawbar above ground	Tyre inflation pressure	
	Front	Rear
375 mm	390 kPa	170 kPa

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

Gear and range	Power	Drawbar pull	Speed	Engine speed	Slip of wheel	Specific fuel consump.	Specific energy	Temperature			Atmospheric conditions		
no	kW	kN	km/h	rev/min	%	g/ kWh	kWh / l	Fuel °C	Coolant °C	Engine Oil °C	Temperature °C	Relative humidity %	Pressure kPa
3.3.1. MAXIMUM POWER IN TESTED GEARS (Unballasted tractor)													
I-1	9.4	20.44	1.66	2704	15.0	664	1.26	39	76	105	24	44	91.2
I-2	14.5	20.68	2.53	2675	15.0	515	1.62	39	76	105	24	44	91.2
I-3	19.4	20.90	3.34	2602	15.0	468	1.78	39	76	105	24	44	91.2
II-1	21.6	20.93	3.72	2597	15.0	456	1.83	39	76	105	24	44	91.2
I-4	27.1	20.78	4.69	2549	15.0	435	1.92	39	76	105	24	44	91.2
II-2	32.2	20.56	5.63	2534	14.3	400	2.08	37	80	109	25	41	91.2
II-3	35.5	16.23	7.88	2500	10.6	367	2.28	37	80	109	25	41	91.2
III-1	36.6	14.56	9.06	2500	8.6	360	2.32	37	82	111	25	39	91.2
II-4	34.7	10.52	11.88	2505	6.1	378	2.21	37	82	111	25	39	91.2
III-2	33.5	8.25	14.60	2505	4.6	385	2.17	37	82	111	25	39	91.2
3.3.2.FUEL CONSUMPTION													
3.3.2.1. In selected gear, at maximum power at rated speed													
III-1	36.6	14.56	9.06	2500	8.6	360	2.32	40	76	101	27	27	90.8
3.3.2.1.1. 75 % of pull at maximum power at rated speed													
III-1	28.5	10.92	9.39	2532	6.4	424	1.97	40	76	101	22	27	90.8
3.3.2.1.2. 50 % of pull at maximum power at rated speed													
III-1	19.9	7.28	9.85	2582	3.7	492	1.70	40	76	101	27	27	90.8
3.3.2.1.3. Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.1.													
II-4	28.5	10.92	9.39	1986	6.4	370	2.26	40	76	101	27	27	90.8
3.3.2.1.4. Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.2.													
II-4	19.9	7.28	9.82	2016	3.6	418	2.00	40	76	101	27	27	90.8
3.3.2.2. in selected gear nearest to 7.5 km/h at rated speed													
II-3	35.5	16.23	7.88	2500	10.6	363	2.30	40	78	105	28	27	90.8
3.3.2.2.1. 75 % of pull at maximum power at rated speed													
II-3	28.2	12.17	8.33	2534	6.8	423	1.98	40	78	105	28	27	90.8
3.3.2.2.2. 50 % of pull at maximum power at rated speed													
II-3	19.9	8.12	8.81	2606	4.2	467	1.79	40	78	105	28	27	90.8
3.3.2.2.3. Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.1.													
III-1	28.3	12.20	8.34	2255	6.7	363	2.30	40	78	105	28	27	90.8
3.3.2.2.4. Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.2.													
III-1	19.7	8.12	8.75	2304	4.2	409	2.04	40	78	105	28	27	90.8

4.OPTIONAL TESTS : None

5. REPAIRS : None

6. REMARKS : Atmospheric pressure 90.8 kPa, 91.2 kPa and 92.1 kPa less than 96.6 kPa fixed in the OECD code.

TARIM VE KÖYİŞLERİ BAKANLIĞI
TARIM ALET VE MAKİNALARI TEST MERKEZİ MÜDÜRLÜĞÜ
Tel : 0 (312) 315 65 74- 315 56 85 Fax : 0 (312) 315 04 66
Web Sitesi : www.tamtest.gov.tr e-mail : info@tamtest.gov.tr

REPORT NUMBER:1379/2245-TGK.8

TEST COMMISSION

Bekir ILBAK
Agricultural Engineer

Duran DOGANGUZEL
Agricultural Engineer

Kerim EKMEKCI
Departmant Chief

Hüseyin YAŞAR
Chairman of Test Commission

This test report has been prepared and undersigned as 28 pages

Aşır NADAR
Assistant Director

Signatures that belong to members of test commission above have been approved **05/08/2004**

Dr. Hamdi TAŞBAŞ
Director