SILSOE RESEARCH INSTITUTE

OECD Report

Report No: OECD/6424/2002
OECD Approval No: 2/2142
Approval Date: 9 July 2004

CODE 2

Tests in accordance with the OECD RESTRICTED STANDARD CODE for the Official Testing of Agricultural and Forestry Tractors

New Holland MEC7CG1 (TM175) Four-Wheel Drive Tractor with 19-speed Full Power Shift Transmission (50 km/h)



Manufactured by: CNH UK Limited
Basildon
Essex SS14 3AD
United Kingdom

Reference No: 828

Date: April 2004

File: 6424/2002

Rev: 19 July 2004

ENGINEERING for Life

OECD/6424/2002

TABLE OF CONTENTS

1.	SPECIFICATIONS OF TRACTOR		1
2.	TEST CONDITIONS		16
3.	COMPULSORY TEST RESULTS		18
	Compulsory tests		
	1	Main power take-off (1000 rev/min)	18
		Main power take-off boosted power (1000 rev/min)	19
		Main power take-off curves (1000 rev/min)	20
	2	Hydraulic power and lifting force	23
	3	Drawbar power and fuel consumption test (unballasted tractor, four-wheel drive)	24
		Drawbar power and fuel consumption test (unballasted tractor, four-wheel drive with front axle disengaged)	25
4.	Optional tests		26
5.	Repairs and adjustments during tests		26
6.	Remarks		26
7.	Appendix 1 Additional tests		27

Statement

The information opposite each item has been validated by the Testing Station. An item marked [C] indicates to the test report user that the information declared by the manufacturer has been checked; an item marked [D] indicates that the manufacturer's declaration has been endorsed.

[C]	Tractor manufacturer's name and address:	CNH UK Limited Basildon, Essex, SS14 3AD United Kingdom
[C]	Location of tractor assembly:	Basildon, Essex
[D]	Submitted for test by:	The manufacturer
[C]	Selected for test by:	The manufacturer with the agreement of the testing station
[D]	Place of running in:	Basildon. Essex
[D]	Duration of running in:	93 hours
[C]	Location of test:	Silsoe Research Institute Wrest Park, Silsoe, MK45 4HS United Kingdom

1. SPECIFICATIONS OF TRACTOR

1.1 Identification

1.1.1

[C]	Make of tractor:	New Holland
[C]	Model (trade name):	TM 175
[C]	Type:	Four- wheel drive, unit construction

1.1.2 *Numbers*

[D]	1st Serial No or prototype:	ACM186090
[C]	Serial No:	170920B

1.1.3 *Other specifications (if applicable)*

[D]	Model(s) for other countries:	None
[C]	Transmission type or gears x ranges:	19-Speed Full Power Shift
[C]	Speed version:	30/40/50 km/h
[C]	Manufacturer identification or Technical type number:	MEC7CG1

1.2 Engine

[C]	Make:	CNH
[C]	Model:	675TA/FB
[C]	Type:	4 stroke turbocharged direct injection and after cooled diesel, electronically controlled
[C]	Serial No:	926099

1.2.1 *Cylinders*

[C]	Number/disposition:	6 vertical in-line
[D]	Bore/stroke:	111.8mm/127.0mm
[D]	Capacity:	7480 cm^3
[D]	Compression ratio:	17.5 : 1
[D]	Arrangement of valves:	Overhead
[D]	Cylinder liners:	None, monobloc construction

1.2.2	*Supercharging*	
[D]	Make/Model:	Borg Warner/K27
[C]	Type:	Exhaust driven
[D]	Pressure:	0.144 MPa at rated speed/load
1.2.3	*Fuel system*	
[D]	Fuel feed system:	Stanadyne electronic lift pump
[C]	Make, type and model of fuel filter:	One disposable canister filter with sediment bowl and water separator plus plastic strainer in tank
[D]	Capacity of fuel tank:	389 dm^3
[C]	Make, type and model of injection pump:	Bosch, VP Rotary Electronic, 0 470 006 001
[C]	Serial No:	87802531
	Manufacturer's production setting of injection pump	
[C]	Flow rate (rated engine speed and full load):	110 mm^3 ±3% per stroke at 2200 min^{-1} (rev/min) 42.25 - 44.87dm^3/h
[D]	Timing:	T.D.C
[D]	Make, type and model of injectors:	Bosch, differential needle, DSLA 143 PV 338 5300
[D]	Injection pressure:	27.0-28.2 MPa
1.2.4	*Governor*	
[C]	Make:	Bosch
[D]	Model:	None
[C]	Type:	Electronically controlled
[C]	Governed range of engine speed:	895 to 2405 min^{-1} (rev/min)
[C]	Rated engine speed:	2200 min^{-1} (rev/min)
1.2.5	*Air cleaner*	
[C]	Pre-cleaner	
[C]	Type:	Spin tube
[C]	Location:	Air cleaner canister inlet
	Main cleaner	
	Make:	Locker Filtration
[C]	Type:	3 stage dry paper element with replaceable cartridge Exhaust Aspirated
[D]	Model:	None
[C]	Location of air intake:	Under engine bonnet on front and above radiator.
[C]	Maintenance indicator:	Warning light on instrument

1.2.6 *Lubrication system*

[D]	Type of feed pump:	Forced feed from eccentric rotor pump
[D]	Type of filter:	Metal mesh strainer in sump on suction line and full flow disposable canister on pressure line to engine
[C]	Number:	1

1.2.7 *Cooling system*

[C]	Type of coolant:	Water and antifreeze (50% solution)
[D]	Type of pump:	Belt driven centrifugal impeller
	Specification of fan	
[C]	Number of fan blades:	7
[C]	Fan diameter:	550 mm
[D]	Coolant capacity:	26 dm^3
[D]	Type of temperature control:	Thermostat with full flow bypass
[D]	System pressure:	100 kPa

1.2.8 *Starting system*

[D]	Make:	Bosch JF / Iskra
[D]	Model:	JF
[C]	Type:	Electrical, positive engagement, solenoid operated
[D]	Starter motor power rating:	3.1/3.6 kW 3.0 kW (Reduction geared)
[D]	Cold starting aid:	Lucas – Type 357-33
[C]	Safety device:	Starting inoperable unless shuttle lever in neutral, clutch pedal depressed and seat presence switch is activated

1.2.9 *Electrical system*

[C]	Voltage:	12 V
	Generator:	Alternator
[C]	Make:	Magneti Marrelli / Denso
[C]	Model:	MME / A 127
[C]	Type:	Belt driven
[C]	Power:	100/120 amps at 6000 min^{-1} (rev/min)
	Batteries	
[C]	Number:	1 Exide lead acid, mounted on RHS fuel tank
[D]	Rating:	176 Ah at 20 hours

1.2.10 *Exhaust system*

[C]	Make:	COR.TUBI
[D]	Model:	None
[C]	Type:	Under bonnet horizontal silencer with vertical stack pipe
[C]	Location:	Rear left hand side above engine, under bonnet
[C]	Height of outlet above ground:	3175 mm

1.3 Transmission

1.3.1 *Clutch (Travel alone)*

[D]	Make:	CNH
[D]	Model:	None
[D]	Type:	Wet multiplate in gearbox, for travel only
[D]	Number of plates:	12
[D]	Diameter of plates:	150 mm
[C]	Method of operation:	Electro-hydraulic with pedal override

1.3.2 *Gear box*

[D]	Make:	CNH
[C]	Model:	Power command (full power shift)
[C]	Description:	Electro/Hydraulic, 19 forward and 6 reverse powershift speeds,selected by 2 buttons on an adjustable lever mounted on the RH console Forward/reverse is actuated by a steering column mounted shuttle lever.

		Forward	Reverse
[C]	Number of gears	19	6
[C]	Number of ranges/groups	1	1
[C]	Total of arrangements	19	6

Available options:

17 x 6 with creep (30 km/h)
18 x 6 with creep (40 km/h)
19 x 6 with creep (50 km/h)

1.3.3 *Rear axle and final drivers*

[D]	Make:	CNH
[D]	Model:	None
[D]	Type:	Crown wheel pinion with differential and inboard epicyclic reduction gear final drive
	Differential lock:	
[D]	Type:	Multi-plate clutch
[C]	Method of engagement:	Electro-hydraulic actuation in response to signal from switch on right-hand control panel
[C]	Method of disengagement:	Via panel switch or in response to signal from brakes on application, or steering movement, or axle lift

1.3.4 *Front axle and final drives*

[D]	Make:	CNH
[D]	Model:	None
[D]	Type:	Crown wheel and pinion with differential and outboard epicyclic reduction gear final drives
	Drive engagement:	
[D]	Type:	Multi-plate clutch – located within the gearbox
[C]	Method of operation:	Electro-hydraulic actuation in response to signal from switch on right-hand control panel
	Differential lock:	
[D]	Type:	multi-plate clutch
[C]	Method of engagement:	Electro-hydraulic actuation in response to signal from switch on right-hand control panel
[C]	Method of disengagement:	Via panel switch or in response to signal from brakes on application, or steering movement, or axle lift

1.3.5 *Total ratios and travelling speeds*

	Gear	Group or range	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed at rated engine speed:* 2200 rev/min km/h
	Forward			
[C]	1		396.08	1.90
[C]	2		329.38	2.28
[C]	3		274.21	2.74
[C]	4		228.03	3.29
[C]	5		189.58	3.96
[C]	6		157.65	4.76
[C]	7		136.44	5.50
[C]	8		113.47	6.62
[C]	9		94.46	7.95
[C]	10		78.55	9.56
[C]	11		65.31	11.49
[C]	12		54.31	13.82
[C]	13		47.25	15.87
[C]	14		39.29	19.10
[C]	15		32.71	22.95
[C]	16		27.20	27.60
[C]	17		22.62	33.19
[C]	18		18.81	39.91
[C]	19		16.39	45.80
	Reverse			
[C]	1		178.88	4.20
[C]	2		148.75	5.05
[C]	3		123.84	6.06
[C]	4		102.98	7.29
[C]	5		85.62	8.77
[C]	6		71.20	10.54

Range selection: None

(*) Calculated with a tyre dynamic radius index of 905 mm (Not in conformity with ISO 4251/1-1998)

[C] Number of revolutions of front wheels for one revolution of rear wheels: 1.343

1.4 Power take-off

1.4.1 *Main power take-off*

[C]	Type:	Independent
[C]	Method of engagement:	Electro – hydraulic operated multi-plate clutch in response to a signal from switch on the right – hand control panel
[C]	Number of shafts:	1 interchangeable shaft, 6 or 21 splines to ISO 500/1991
[C]	Method of changing power take-off speeds:	Two speed shiftable, 540E or 1000 min^{-1} (rev/min) by lever on right-hand console
	Clutch	
[D]	Make:	CNH
[D]	Model:	None
[D]	Type:	Multiplate, wet
[D]	Number of plates:	8
[D]	Diameter of plates:	140.0 mm

1.4.1.1 Power take-off proportional to engine speed

Power take-off at 540E min^{-1} (rev/min)

[C]	Location:	Rear of tractor
[C]	Diameter of power take-off shaft:	34.9 mm
[C]	Number of splines:	6 in conformity with ISO 500/1991 (available option 21)
[C]	Height above ground:	875 mm
[C]	Distance from the median plane of the tractor:	Central
[C]	Distance behind rear wheel axis:	637 mm
[C]	PTO speed at rated engine speed:	757 min^{-1} (rev/min)
[C]	Engine speed at standard power take-off speed:	1569 min^{-1} (rev/min)
[C]	Ratio of rotation speeds:	2.90
[D]	Power restriction:	None
[D]	Maximum torque transmissible:	None
[C]	Direction of rotation (viewed from behind tractor):	Clockwise

Power take-off at 1000 min^{-1} (rev/min)

[C]	Location:	Rear of tractor
[C]	Diameter of power take-off shaft:	34.9 mm
[C]	Number of splines:	21 in conformity with ISO 500/1991 (available option 6)
[C]	Height above ground:	875 mm
[C]	Distance from the median plane of the tractor:	Central
[C]	Distance behind rear wheel axis:	637 mm
[C]	PTO speed at rated engine speed:	1021 min^{-1} (rev/min)
[C]	Engine speed at standard power take-off speed:	2154 min^{-1} (rev/min)
[C]	Ratio of rotation speeds:	2.154
[D]	Power restriction	None
[D]	Maximum torque transmissible:	None
[C]	Direction of rotation (viewed from behind tractor):	Clockwise


1.4.1.2 Power take-off proportional to ground speed — Not applicable

1.5 Hydraulic power lift

[C]	Make:	CNH
[D]	Model:	None
[D]	Type:	Electro-hydraulic closed centre load sensing
[C]	Type and number of cylinders:	2 single acting, externally mounted
[C]	Type of linkage lock for transport:	Hydraulic
[D]	Pump maximum pressure / Relief valve pressure setting:	20.5 – 21.5 MPa
[D]	Opening pressure of cylinder safety valve:	22.0 – 23.0 MPa
[D]	Lift pump type:	Variable displacement piston pump
[D]	Transmission between pump and engine:	Gear driven from PTO shaft, independent of main and PTO clutches
[C]	Type and number filters:	1 disposable canister filter and 1 element filter
[C]	Site of oil reservoir:	Rear axle housing
[C]	Type, number and location of tapping points:	4 or 5 remote couplers at rear of tractor (4 Remote valves fitted on test tractor)
[D]	Maximum volume of oil available to external cylinders:	28 litres max under normal conditions (flat fields) 40 litres max when operating stationary on level ground

1.6 Three-point linkage

[C]	Category:	2 in conformity with ISO 730-1:1994 + Cor.1:1995
[C]	Category adapter:	None
[C]	Controls:	Electronic draught/ position control, lower link sensing



LIFT TEST
Linkage geometry

Fig 2.1

Table 2.1
Dimensions of linkage when attached to the standard frame (ISO 730-1-1994 CAT 2)

				Dimensions or ranges	Settings used in tests		
					3.2.2	7.1	7.2
				mm	mm	mm	mm
[C]	Length of lift arms:		(A)	450	450	450	450
[C]	Length of lower links:		(B)	974	974	974	974
[C]	Distance of lift arm pivot point from rear wheel centre line:	horizontally: vertically:	(a) (b)	92 372	92 372	92 372	92 372
[C]	Horizontal distance between the two lower link points:		(u)	644	644	644	644
[C]	Horizontal distance between the two lift arm end points:		(v)	560	560	560	560
[C]	Length of upper link:		(S)	690 – 915	740	790	790
[C]	Distance of upper link pivot point from rear wheel centre line:	horizontally: vertically:	(c) (d)	440 – 500 217 – 277	500 217	440 277	440 277
[C]	Distance of lower link pivot point from rear wheel centre line:	horizontally: vertically:	(e) (f)	250 270	250 270	250 270	250 270
[C]	Distance of lower link points to lift rod pivot points on lower link centre line:		(D)	612– 682	612	682	682
[C]	Length of lift rods:		(L)	870 – 990	978	990	990/945
	Height of lower hitch points (*) Relative to the rear wheel centre line, situated 905 mm above the ground level:						
[C]	- in low position		(h)	422 – 720	705	635	635/550
[C]	- in high position		(H)	75 – 260	80	100	83/163
[C]	Height of lower hitch points when locked in transport position (*)			Any height within lift range (hydraulic transport lock)			

*Assuming r = tyre dynamic radius index of 905 mm

1.7 Swinging drawbar
(Incorporated in automatic pick-up hitch with hook and clevis on drawbar and selected by reversing)

[C]	Type:		Clevis		Hook
[C]	Height above ground:	Unballasted Maximum:	538 mm		530 mm
		Minimum:	488 mm		
[C]	Type of adjustment:		Inverting drawbar		
[C]	Distance of hitch point from rear-wheel axis, horizontally:		897 mm	997 mm 1047 mm	656 mm
[C]	Distance of hitch point from power take-off shaft end:				
		Vertically:	337 mm	387 mm	345 mm
		Horizontally:	260 mm	360 mm 410 mm	19 mm
[C]	Lateral adjustment (centre of clevis):				
		Right-hand:	220 mm	235 mm	None
		Left-hand:	220 mm	235 mm	None
[C]	Distance of pivot point from rear axles	horizontally:	455 mm	605 mm	----
[C]	Width of clevis:		70 mm		
[C]	Diameter of drawbar pin hole:		33 mm		
[D]	Maximum vertical permissible load:	Clevis uppermost:	2400 kg		3000 kg
		Clevis underneath:	2180 kg		3000 kg

1.8 Trailer hitch None fitted

1.9 Holed drawbar

Type: None fitted

1.10 Steering

[D]	Make:	CNH
[D]	Model:	None
[D]	Type:	Hydrostatic
	Method of operation	
[C]	Pump:	Bosch Rexroth
[C]	Motor:	Sauer Danfoss OSPQ 125-250 (Dynamic)
[C]	Ram:	2, balanced system with double acting cylinders one operating each steering arm
[D]	Filter:	Integral with hydraulic power lift system
[D]	Working pressure:	17 MPa

1.11 Brakes

1.11.1 *Service brake*

[D]	Make:	CNH
[D]	Model:	None
[D]	Type:	Oil-immersed two plate disc
[C]	Method of operation:	Hydraulic boosted, independent on rear wheels (On 4 WD models. When the service brakes are activated the front wheel drive is automatically engaged providing 4-wheel braking)
[C]	Trailer braking take-off:	Hydraulic connector fitted to ISO 5676-1983

1.11.2 *Parking brake*

[D]	Type:	Fully independent six plate disc operating on bevel pinion shaft
[C]	Method of operation:	Hand lever with ratchet

1.12 Wheels

Number

[C] Front: 2 driving/steering

[C] Rear: 2 driving

[C] Wheelbase: 2818 mm

Track width adjustment:

		Minimum mm	Maximum mm	Adjustment method
[C]	Front*	1538/1560	2238/2260	Reversing wheels and offset lug rims
[C]	Rear	1530	2230	Reversing wheels and offset lug rims/ Optional bar axle fitted

*55° steering angle available only on 1860 mm and larger track settings

1.13 Protective structure

[C] Make: CNH

[C] Model: SLTV 10

[C] Type: Cab safety frame - suspended

[C] Manufacturer's name and address: CNH UK Ltd
Cranes Farm Road
Basildon
Essex
SS14 3AD

Protective device

[C] Cab/frame/rollguard/ other: Cab

[C] Tiltable/Not tiltable: Not tiltable

OECD approval

[C] Approval number: 4/0699

[C] Date of approval: 19 October 2001

Nos. minor modification certificates, if any: 2

The certificates for minor modifications established by and under the responsibility of the Danish Institute of Agricultural Sciences, Bygholm, Denmark

1.14 Seat

1.14.1 *Driver's seat*

[C]	Make/model/Type:	Sears SST 1503 EEC approved to 78/764/EEC – e11-1294
[C]	Seat and steering wheel reversible:	No
[C]	Type of suspension:	Low frequency, parallelogram suspension air spring
[C]	Type of damping:	Double acting, hydraulic
	Range of adjustment	
[C]	Longitudinal:	± 100 mm
[C]	Vertical:	± 68 mm
[C]	Safety belt:	Yes

1.14.2 *Optional driver's seat(s)*

1.14.3 *Passenger seat*

[C]	Make:	CNH (instructional seat)
[C]	Location:	Soft plastic moulding, folding, on left hand side of inner fender.
[C]	Type:	EEC approved to76/763/EEC – e11 1383
[C]	Capacity (numbers):	1

1.15 Lighting

		Height above ground to centre	Size	Distance from outside edge of lights to medium plane of tractor
		mm	mm	mm
[C]	Headlights	1430	150 x 90	200
[C]	Sidelights	2035	105 x 30	870
[C]	Rear lights	2025	50 x 50	845
[C]	Rear fender reflectors	2025	50 x 50	845
[C]	Rear axle reflectors	875	100 x 35	640

2 TEST CONDITIONS

2.1 Overall dimensions

	length	Width		Height at top of	
		minimum	maximum	Protective structure	Exhaust pipe
	mm	mm	mm	mm	mm
Unballasted	4865	2495	2495	3050	3175

2.2 Ground clearance (unballasted tractor) 385 mm

Clearance-limiting part: Drawbar clevis in lowest position

2.3 Tractor mass

Mass (with or without frame/roll guard/cab/other): With cab

	Unballasted	
	Without driver	With driver
	kg	kg
Front	2601	2608
Rear	4564	4632
Total	7165	7240

2.4 Track specifications Not applicable

2.5 Tyres and track width specification

	Front	Rear
Tyres Dimensions ply rating type	 540/65 R 30 143A8 Radial	 650/65 R 42 158A8 Radial
Maximum load (tyre manufacturer's) 30/40/50 km/h	28.6/26.7/24.3 kN	44.6/40.5/37.9 kN
Maximum load (tractor manufacturer's) 30/40/50	28.6/26.7/24.3 kN	44.6/40.5/37.9 kN
Inflation pressure (tyre manufacturer's)	160 kPa	160 kPa
Dynamic radius index	695 mm	905 mm
Chosen track width (manufacturer's nominal)	1825 mm	1815 mm

2.6 Fuel

Type: Diesel oil to Class D, 1.5 to 5.5 cSt.

Density at 15° C: 0.8413 g/cm^3

2.7 Oils and lubrication

2.7.1 *Capacity and change interval*

	Capacity	Oil change	Filter change
	dm^3	h	h
Engine	19.0	300	300
Front axle differential	9.0	1200	None
Front axle hub (each)	1.7	1200	None
Gearbox	100.0	1200	1200
Rear axle Hydraulic system Final drives (rear) Steering	Integral with gearbox		
Brakes	0.5	Top-up	None

2.7.2 *Specifications (SAE, APL, CCMC, ACEA, MILL, ISO)*

	NH spec	Recommended	Used during test
Engine oil Type: Viscosity Classification:	NH 324H	SAE 10W/30 11.5 cSt at 100° C API CH – 4	As recommended
Transmission oils Type: Viscosity Classification:	NH 410B	SAE 10W/30 9 cSt at 100° C API GL – 4	As recommended
Rear final drives Type: Viscosity: Classification:	NH 410B	SAE 10W/30 9 cSt at 100° C API GL – 4	As recommended
Front differential and final drives Type: Viscosity: Classification:	NH 410B	SAE 10W/30 9 cSt at 100° C API GL – 4	As recommended
Hydraulic brakes Type: Viscosity: Classification:	NH 610A	No equivalent 6 cSt at 100° C No equivalent	As recommended
Hydraulic fluid Type: Viscosity: Classification:	NH 410B	SAE 10W/30 9 cSt at 100° C API GL – 4	As recommended
Steering oil Type: Viscosity: Classification:	NH 410B	SAE 10W/30 9 cSt at 100° C API GL – 4	As recommended

2.7.3 *Grease*

Type:	NH 720A	Lithium Based	As recommended

Number of lubrication points: 14

3. COMPULSORY TESTS RESULTS

3.1 Main power take-off

Date and location of tests: 4 and 9 September 2003
Silsoe Research Institute
Wrest Park, Silsoe, Bedford

· Type of dynamometer bench: Eddy Current, Borghi and Saveri

Power	Speed		Fuel consumption			Specific Energy
	Engine	P.T.O.	Hourly		Specific	
kW	min^{-1} (rev/min)		kg/h	l/h	g/kWh	kWh/l
3.1.1 MAXIMUM POWER – TWO-HOUR TEST						
119.9	1799	835	28.75	34.18	240	3.51
3.1.2 POWER AT RATED ENGINE SPEED						
112.8	2200	1021	30.22	35.93	268	3.14
3.1.3 STANDARD POWER TAKE-OFF SPEED [1000 ± 25 min^{-1} (rev/min)]						
115.0	2154	1000	30.06	35.73	261	3.22
3.1.4 PART LOADS 3.1.4.1 the torque corresponding to maximum power at rated engine speed						
112.8	2200	1021	30.22	35.93	268	3.14
3.1.4.2 85% of torque obtained in 3.1.4.1						
98.9	2270	1054	27.24	32.38	275	3.06
3.1.4.3 75% of torque defined in 3.1.4.2						
75.0	2294	1065	22.20	26.39	296	2.84
3.1.4.4 50% of torque defined in 3.1.4.2						
50.5	2317	1076	17.41	20.70	345	2.44
3.1.4.5 25% of torque defined in 3.1.4.2						
25.5	2339	1086	12.55	14.92	492	1.71
3.1.4.6 unloaded						
0	2361	1096	6.33	7.52	-	-
3.1.5 PART LOADS AT STANDARD POWER TAKE-OFF SPEED [1000± 25 min^{-1} (rev/min)] 3.1.5.1 the torque corresponding to maximum power						
115.0	2154	1000	30.06	35.73	261	3.22
3.1.5.2 85% of torque obtained in 3.1.5.1						
100.5	2213	1027	27.45	32.63	273	3.08
3.1.5.3 75% of torque obtained in 3.1.5.2						
76.0	2233	1037	22.24	26.43	293	2.88
3.1.5.4 50% of torque obtained in 3.1.5.2						
51.2	2253	1046	17.20	20.44	336	2.50
3.1.5.5 25% of torque obtained in 3.1.5.2						
25.7	2269	1053	12.17	14.47	474	1.78
3.1.5.6 unloaded						
0	2289	1063	7.60	9.04	-	-

* In the PTO test fan speed was not measured because we do not have the facility to do so at present

No load maximum engine speed: 2361 min^{-1} (rev/min)

Torque (equivalent crankshaft) at maximum power

At rated engine speed: 489.6 Nm

At 2-hour test: 636.5 Nm

Maximum torque (equivalent crankshaft): 694.3 Nm
(engine speed:1500 min^{-1} (rev/min)

Mean atmospheric conditions:	
Temperature	25 °C
Pressure	102.5 kPa
Relative humidity	38 %
Maximum temperatures:	
Coolant	96 °C
Engine oil	123 °C
Fuel	64 °C
Engine air intake	29 °C

Boosted power take-off

Power	Speed		Fuel consumption			Specific Energy
	Engine	P.T.O.	Hourly		Specific	
kW	min^{-1} (rev/min)		kg/h	l/h	g/kWh	kWh/l
3.1.1 MAXIMUM POWER – TWO-HOUR TEST						
145.9	1969	914	36.88	43.84	253	3.33
3.1.2 POWER AT RATED ENGINE SPEED						
138.9	2198	1021	35.50	42.19	256	3.29
3.1.3 STANDARD POWER TAKE-OFF SPEED [1000 ± 25 min^{-1} (rev/min)]						
142.2	2153	1000	36.07	42.87	254	3.32
3.1.4 PART LOADS 3.1.4.1 the torque corresponding to maximum power at rated engine speed						
138.9	2198	1021	35.50	42.19	256	3.29
3.1.4.2 85% of torque obtained in 3.1.4.1						
120.6	2245	1042	32.19	38.26	267	3.15
3.1.4.3 75% of torque defined in 3.1.4.2						
91.8	2281	1059	25.62	30.45	279	3.02
3.1.4.4 50% of torque defined in 3.1.4.2						
62.0	2308	1072	19.52	23.20	315	2.67
3.1.4.5 25% of torque defined in 3.1.4.2						
31.4	2335	1084	13.52	16.07	430	1.96
3.1.4.6 unloaded						
0	2362	1096	7.72	9.18	-	-
3.1.5 PART LOADS AT STANDARD POWER TAKE-OFF SPEED [1000± 25 min^{-1} (rev/min)] 3.1.5.1 the torque corresponding to maximum power						
142.2	2153	1000	36.07	42.87	254	3.32
3.1.5.2 85% of torque obtained in 3.1.5.1						
123.3	2197	1020	32.24	38.32	261	3.22
3.1.5.3 75% of torque obtained in 3.1.5.2						
93.6	2223	1032	25.86	30.74	276	3.05
3.1.5.4 50% of torque obtained in 3.1.5.2						
63.1	2247	1043	19.53	23.22	310	2.72
3.1.5.5 25% of torque obtained in 3.1.5.2						
31.9	2271	1054	13.08	15.54	410	2.05
3.1.5.6 unloaded						
0	2293	1065	6.75	8.03	-	-

* In the PTO test fan speed was not measured because we do not have the facility to do so at present

No load maximum engine speed: 2362 min^{-1} (rev/min)

Torque (equivalent crankshaft) at maximum power

At rated engine speed: 603.5 Nm

At 2-hour test: 707.6 Nm


Maximum torque (equivalent crankshaft): 792.7 Nm
(engine speed:1600 min^{-1} (rev/min)

Mean atmospheric conditions:	
Temperature	24 °C
Pressure	101.1 kPa
Relative humidity	35 %
Maximum temperatures:	
Coolant	96 °C
Engine oil	125 °C
Fuel	62 °C
Engine air intake	27 °C


■ Main power take-off curve


▲ Boosted power take-off curve

Power take-off curves





Power take-off curves





Power take-off curves





3.2 Hydraulic power and lifting force

Date of tests: 14 and 22 April 2004

3.2.1 *Hydraulic power test*

3.2.1.1 Hydraulic fluid data

Hydraulic fluid type: See Specification

3.2.1.2 Compulsory Reporting (Test Results):

	Pressure	Reservoir oil Temperature °C (65 °C target)		Engine Speed	Flow rate	Power
	MPa	Min.	Max.	Rev/min	l/min	kW
Rated Engine Speed				2200		
3.2.1.2.1 Maximum (sustained) pressure with relief valve open as measured at the coupler Pump stalled: Yes	21.5	65	69	2361		
3.2.1.2.2 Flow rate corresponding to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting and corresponding hydraulic power	19.4	66		2345	75.9	24.54
3.2.1.2.3 Maximum available flow and maximum power from one coupler pair:	17.5	65		2330	101.9	29.72
3.2.1.2.4 Maximum available flow and maximum power from coupler pairs operating simultaneously (flow through two or more coupler pairs if required):	19.0	67		2335	102.1	32.33

Tapping point used for test: Remote/Auxiliary service connection

Temperature of hydraulic fluid if different from 65 ± 5°C ---°C

Opening pressure of the unloading valve: Not applicable

Closing pressure of the unloading valve: Not applicable

3.2.2*Power lift test – (To ISO 730-1:1994)*

Linkage settings for test – see Table 2.1 and Figures 2.1 and 2.2.

	At the hitch point	on the frame
Height of lower hitch points above ground in down position	200 mm	200 mm
Vertical movement	785 mm	903 mm
Maximum corrected force exerted through full range	62.7 kN	50.3 kN
Corresponding pressure of hydraulic fluid	19.4 MPa	19.4 MPa
Moment about rear-wheel axis	76.7 kNm	92.2 kNm
Maximum tilt angle of mast from vertical	----	10 degrees

Lifting heights relative to the horizontal plane including the lower link pivot points											
mm	-475	-435	-310	-215	-135	0	+78	+175	+300	+350	+428
Lifting forces (the values of force measured shall be corrected to correspond to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting of the hydraulic lift system):											
at the hitch points kN	--	62.7	62.9	64.9	66.2	68.6	69.8	71.0	72.1	71.8	--
Corresponding pressure:19.4 MPa											
at the frame kN	60.7	--	59.7	59.4	59.3	59.4	57.6	55.7	52.5	--	50.3
Corresponding pressure:19.4 MPa											

3.3 Drawbar power test (unballasted tractor)

(Four-Wheel Drive)

Date and Location of tests: 2 and 8 March 2004
Silsoe Research Institute
Wrest Park
Silsoe
Bedford MK45 4HS

Type of track: Concrete

	Height of drawbar above ground	Tyre inflation pressure	
		Front	Rear
	mm	kPa	kPa
Unballasted	435	85	85

Gear and range	Power	Drawbar pull	Speed	Engine speed	Slip of wheels or track	Specific fuel cons	Specific Energy	Temperature			Atmospheric conditions		
								Fuel	Coolant	Engine oil	Temp	Relative humidity	Pressure
	kW	kN	km/h	min^{-1}	%	g/kWh	kWh/l	°C	°C	°C	°C	%	kPa
3.3.1 MAXIMUM POWER IN TESTED GEARS													
1	35.9	73.2	1.77	2316	13.4	474	1.77	61	90	117	8	45	103.0
2	43.1	73.1	2.12	2309	13.2	436	1.93	62	90	117	10	37	102.9
3	50.9	71.9	2.55	2299	12.7	417	2.02	58	95	117	10	36	102.7
4	61.6	71.7	3.09	2289	11.5	378	2.23	58	95	115	9	38	102.9
5	73.1	70.7	3.72	2273	11.0	364	2.31	58	95	120	10	39	102.7
6	84.2	69.5	4.36	2201	10.3	348	2.42	57	95	120	9	39	102.7
7	94.5	67.2	5.06	2172	8.8	320	2.63	61	96	122	9	42	102.7
8	98.8	62.5	5.69	1990	6.9	295	2.85	63	96	120	9	41	102.9
9	103.0	59.3	6.25	1807	6.3	274	3.07	58	94	119	9	43	102.7
10	101.1	47.4	7.68	1805	4.2	279	3.02	58	96	116	7	41	102.9
11	103.7	40.5	9.21	1800	4.1	283	2.97	58	95	122	9	41	102.7
12	99.5	32.2	11.12	1792	3.4	283	2.97	62	92	116	9	41	102.7
13	102.7	28.6	12.95	1812	3.1	284	2.96	64	96	122	9	43	102.7
3.3.2 FUEL CONSUMPTION													
3.3.2.1 In selected gear, at maximum power at rated speed													
11	92.0	29.1	11.37	2199	3.1	325	2.59	59	95	120	9	42	102.7
3.3.2.1.1 75% of pull at maximum power at rated speed													
11	71.6	21.8	11.80	2266	2.4	367	2.29	65	96	123	9	44	102.6
3.3.2.1.2 50% of pull at maximum power at rated speed													
11	48.2	14.5	12.00	2291	1.8	473	1.78	66	96	123	9	41	102.6
3.3.2.1.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.1													
12	71.3	21.8	11.80	1886	2.5	322	2.61	66	90	120	9	41	102.6
3.3.2.1.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.2													
12	48.6	14.5	12.01	1906	1.9	370	2.27	66	90	119	9	43	102.6
3.3.2.2 In selected gear nearest to 7.5 km/h, at maximum power at rated engine speed													
9	92.2	42.7	7.77	2202	4.4	328	2.57	57	93	119	8	44	102.9
3.3.2.2.1 75% of pull at maximum power at rated speed													
9	72.2	32.0	8.12	2278	3.4	371	2.27	59	94	120	8	45	102.9
102.93.3.2.2.2 50% of pull at maximum power at rated speed													
9	49.3	21.4	8.28	2301	2.4	418	2.01	61	96	120	8	41	102.9
3.3.2.2.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.1													
10	72.5	32.0	8.15	1901	3.4	305	2.76	65	94	120	9	42	102.6
3.3.2.2.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.2													
10	49.5	21.4	8.32	1921	2.5	354	2.38	65	95	119	9	43	102.6

3.3.1 *Drawbar power test (unballasted tractor)*

(Four-Wheel Drive disengaged)

	Height of drawbar above ground	Tyre inflation pressure	
		Front	Rear
	mm	kPa	kPa
Unballasted	475	85	85

Gear and range	Power	Drawbar pull	Speed	Engine speed	Slip of wheels or track	Specific fuel cons	Specific Energy	Temperature			Atmospheric conditions		
								Fuel	Coolant	Engine oil	Temp	Relative humidity	Pressure
	kW	kN	km/h	min^{-1}	%	g/kWh	kWh/l	°C	°C	°C	°C	%	kPa
3.3.1 MAXIMUM POWER IN TESTED GEARS													
1	28.3	57.5	1.77	2327	12.9	513	1.64	57	93	116	9	53	102.9
2	33.7	57.0	2.13	2321	12.8	463	1.82	55	90	116	9	57	102.9
3	40.1	56.1	2.57	2312	12.0	465	1.81	57	90	118	8	59	102.9
4	48.1	55.4	3.13	2302	10.6	431	1.95	58	96	119	8	60	102.9
5	57.2	55.0	3.75	2293	10.6	385	2.19	57	92	119	8	61	102.9
6	68.5	54.8	4.50	2278	10.3	371	2.27	59	98	121	8	61	102.9
7	78.9	54.5	5.22	2272	9.6	327	2.57	59	95	121	9	61	102.9
8	91.2	53.8	6.10	2198	9.2	319	2.64	60	97	122	9	60	102.9
9	102.4	52.3	7.05	2077	7.6	302	2.78	55	95	120	9	58	102.9
10	103.3	46.2	8.05	1936	5.8	284	2.96	54	97	120	9	58	102.9
11	103.8	40.8	9.15	1815	5.0	286	2.94	55	95	122	9	58	102.9
12	100.8	32.7	11.10	1809	4.0	290	2.90	55	96	123	9	58	102.9
13	103.0	29.1	12.74	1800	3.5	283	2.97	61	94	123	8	61	102.9
3.3.3 FUEL CONSUMPTION													
3.3.2.1 In selected gear, at maximum power at rated speed													
11	93.4	29.9	11.24	2197	3.7	329	2.56	60	97	124	9	59	102.9
3.3.2.1.1 75% of pull at maximum power at rated speed													
11	73.0	22.4	11.74	2279	2.9	344	2.44	54	97	124	9	60	102.9
3.3.2.1.2 50% of pull at maximum power at rated speed													
11	49.7	15.0	11.95	2300	2.3	434	1.94	54	90	123	9	58	102.9
3.3.2.1.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.1													
12	73.3	22.4	11.76	1896	2.9	318	2.65	55	95	122	9	58	102.9
3.3.2.1.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.2													
12	49.7	14.9	11.98	1917	2.2	360	2.34	55	94	121	9	58	102.9
3.3.2.2 In selected gear nearest to 7.5 km/h, at maximum power at rated engine speed													
9	93.3	44.0	7.64	2200	5.5	329	2.55	61	93	123	9	61	102.9
3.3.2.2.1 75% of pull at maximum power at rated speed													
9	73.8	33.0	8.04	2281	4.1	338	2.49	59	98	123	9	60	102.9
3.3.2.2.2 50% of pull at maximum power at rated speed													
9	50.2	22.0	8.22	2304	2.9	395	2.13	58	89	122	9	61	102.9
3.3.2.2.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.1													
10	73.8	32.9	8.06	1901	4.0	316	2.67	55	94	119	9	59	102.9
3.3.2.2.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.2													
10	50.5	22.0	8.24	1921	2.8	354	2.38	55	95	119	9	59	102.9

* In the drawbar test(s) fan speed was not measured because we do not have the facility to do so at present

4. OPTIONAL TESTS RESULTS None

5. REPAIRS AND ADJUSTMENTS DURING TESTS: None

REMARKS: Boosted Power Take-Off (P.T.O.) Operation

This vehicle is equipped with an electronically – controlled engine Power Management™ system that monitors and boosts engine power output in certain circumstances, as engine load increases. This is achieved by electronically changing the characteristics of the engine power-speed curve.

The engine Power Management function ("boosted" power level) becomes active in higher transmission gears (16th and above), for road transport applications. The system is also activated once power transfer through the rear P.T.O. exceeds a pre-set level (and forward speed exceed 0.5 km/h), for mobile P.T.O. – driven implement applications.

An over-ride system is provided to enable P.T.O. operation at the "boosted" power level whilst the vehicle is stationary, for test purposes. The results of such a P.T.O. power output test are presented in this report.

The test results for this report were obtained from a test carried out on a Case IH MXM175 which is identical to the New Holland TM175 in all practical aspects relating to the tests.

Test carried out I S J Devonshire

Signed: 

Officer in charge

J P Evans
Senior Test Engineer
Field Machinery Centre

Date: **23/08/04**

7. APPENDIX 1 ADDITIONAL TESTS

7.1 *Power lift test – (To Manufacturers lift rod setting)*

"Not covered by the approval"

Linkage settings for test – see Table 2.1 and Figures 2.1 and 2.2.

	At the hitch point	on the frame
Height of lower hitch points above ground in down position	270 mm	270 mm
Vertical movement	735 mm	783 mm
Maximum corrected force exerted through full range	69.1 kN	57.3 kN
Corresponding pressure of hydraulic fluid	19.4 MPa	19.4 MPa
Moment about rear-wheel axis	84.6 kNm	105.1 kNm
Maximum tilt angle of mast from vertical	----	5 degrees

Lifting heights relative to the horizontal plane including the lower link pivot points											
mm	- 375	- 365	- 235	- 110	0	+ 65	+ 150	+ 228	+ 290	+ 370	+ 408
Lifting forces (the values of force measured shall be corrected to correspond to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting of the hydraulic lift system):											
at the hitch points kN	–	69.1	69.7	72.2	73.6	74.7	75.2	75.8	76.1	74.4	–
Corresponding pressure: 19.4 MPa											
at the frame kN	69.0	–	67.9	67.9	67.9	66.6	65.5	63.5	61.6	–	57.3
Corresponding pressure: 19.4 MPa											

7.2 *Power lift test – (To SAE J283)*

Linkage settings for test – see Table 2.1

* Lift rods readjusted to 945 mm to allow for lift force to be measured throughout the total lift range

Lifting heights relative to the horizontal plane including the lower link pivot points											
mm	- 365	- 280	- 175	- 50	0	+ 125	+ 213	+ 285	+ 353	---	---
*mm	---	- 280	- 175	- 50	0	+ 125	+ 213	+ 285	+ 353	+ 395	+ 433
SAE J283											
kN	82.1	82.1	80.8	77.6	76.4	72.9	70.1	65.8	62.2	—	—
*kN	—	80.5	80.5	79.0	78.5	74.0	72.3	69.3	65.9	62.8	60.9
Corresponding pressure: 18.5 MPa											

TEST RESULTS (OECD Code 5)

"Not covered by the approval"

Make and type of sound level meter: Bruel and Kjaer 2260

Type of test track: Concrete

Date of tests: 15 April 2004

Four wheel drive engaged Windows closed

Gear	Test Condition	Measured travelling speed km/h	Sound level dB(A)
9	Light Load	8.5	76

Four wheel drive engaged Windows open

Gear	Test Condition	Measured travelling speed km/h	Sound level dB(A)
9	Light Load	8.5	83

Four wheel drive dis-engaged Windows closed

Gear	Test Condition	Measured travelling speed km/h	Sound level dB(A)
9	Light Load	8.5	76

Four wheel drive dis-engaged Windows open

Gear	Test Condition	Measured travelling speed km/h	Sound level dB(A)
9	Light Load	8.5	83