



SILSOE RESEARCH INSTITUTE
Wrest Park, Silsoe,
Bedford MK45 4HS

Report No: OECD/7132/0196
OECD Approval No: 1723 Restricted Code
Approval Date: 23 December 1997

**Report on test in accordance with the OECD STANDARD CODE II (RESTRICTED CODE) for
the Official Testing of Agricultural and Forestry Tractors**

New Holland 8160/M100 Four-Wheel Drive Tractor with 18-speed Semi Power Shift Transmission (40 km/h)



Manufactured by: New Holland UK Ltd
Basildon
Essex
United Kingdom

Submitted for test by: The manufacturer

Report No: 789

Date: September 1997

TABLE OF CONTENTS

I.	SPECIFICATION OF TRACTOR	1
II.	TEST CONDITIONS	15
III.	TEST RESULTS	18
A.	Compulsory tests	
1	Main power take-off (1000 rev/min)	18
2	Hydraulic power and lifting force	20
3	Drawbar power and fuel consumption test (unballasted tractor, four-wheel drive)	22
B.	Supplementary tests	
2	I .Power lift test (To manufacturers lift rod setting)	23
3	Drawbar power and fuel consumption test (unballasted tractor, two-wheel drive)	24
	Repairs and adjustments during tests	25
	Remarks	25
Annex 1	Main power take-off curves (1000 rev/min)	26

Tractor manufacturer's name and address: New Holland UK Ltd
Basildon, Essex, United Kingdom

Location of tractor assembly: Basildon, Essex

Submitted for test by: The manufacturer

Selected for test by: The manufacturer

Place of running in: Basildon, Essex

Duration of running in: 140 hours

Location of test: Silsoe Research Institute
Wrest Park, Silsoe, United Kingdom

I. SPECIFICATION OF TRACTOR

TRACTOR

Make: New Holland
Model: 8160/M100
Type: Four wheel drive, unit construction
Serial No: BX00085
1st Serial No: 003794B

ENGINE

Make: New Holland
Model: 675/TC
Type: 4 stroke, naturally aspirated, direct injection diesel
Serial No: TC529437

Cylinders

Number/disposition: 6 vertical In-line
Bore/stroke: 111.8 mm/127.0 mm
Capacity: 7480 cm³
Compression ratio: 17.5 :1
Arrangement of valves: Overhead
Cylinder liners: None, monobloc construction

Supercharging

Make: None fitted

Fuel system

Fuel feed system: Wabco series 6000 or Purolator 'Facet' electric lift pump

Make, type and model of fuel filter: Plastic strainer in tank and one disposable canister filter with sediment bowl and water separator plus secondary disposable canister filter between tank and injection pump

Capacity of fuel tank: 325 litres

Make, type and model of injection pump: Bosch, 'VE' Rotary, 0 460 426 238

Serial No: 471565425

Manufacturer's production setting of injection pump:

Flow rate: 61.6-65.4 mm³ per stroke at 1100 rev/min pump speed and full load

Timing: Delivery starts 6° before T.D.C

Make, type and model of injectors: Bosch, multihole, 0 432 191 650 nozzle

Injection pressure: 270-278 bar

Governor

Make: Bosch

Model: None

Type: Mechanical incorporated in fuel injection pump

Governed range of engine speed: 700 rev/min to 2420 rev/min

Rated engine speed: 2200 rev/min

Air cleaner

Pre-cleaner: None

Make: Locker Air Maze or Donaldson

Type: 3 stage dry paper element with replaceable cartridge (Exhaust Aspirated - optional)

Model: None

Location of air intake: Under engine hood in front and above radiator

Maintenance indicator: Warning light on instrument panel

Lubrication system

Type of feed pump: Forced feed from eccentric rotor pump

Type of filter: Metal mesh strainer in sump on suction line and full flow disposable canister on pressure line to engine

Number: 1

Cooling system

Type of coolant: Water and antifreeze (50% solution)

Type of pump: Belt driven centrifugal impeller

Specification of fan: Thermal controlled with viscous clutch

Number of fan blades: 5

Fan diameter: 510 mm

Coolant capacity: 25.5 litres

Type of temperature control: Thermostat with full flow bypass

System pressure: 100 kPa

Starting system

Make: Bosch JF

Model: JF

Type: Electrical, positive engagement, solenoid operated

Starter motor power rating: 3.1/3.6 kW

Cold starting aid: CAV Thermostart - Type 357-33

Safety device: Starting operable when all gear levers are in neutral

Electrical system

Voltage: 12 V

Generator: Alternator

Make: Magneti Marelli

Model: MME A 127

Type: Belt driven

Power: 70/100 amps at 6000 rev/min

Batteries: 2 CEAC lead acid, mounted on front support

Rating: 70/95 AH at 20 hours rating

Exhaust system

Make: Alcom
Model: None
Type: Underhood horizontal silencer with vertical stack pipe
Location: Left-hand side of engine, under bonnet
Height of outlet above ground: 2982 mm

TRANSMISSION TO WHEELS

Main clutch

Make: New Holland
Model: None
Type: Wet multiplate in gearbox, for travel only
Number of plates: 7
Diameter of plates: 160 mm
Method of operation: Mechanical/electro-hydraulic with pedal overide

Gear box

Make: New Holland
Model: Range command (semi power shift)
Type: Electro/Hydraulic, syncromesh (range) operation. 6 powershift speeds with 3 ranges selected by 3 buttons on an adjustable lever mounted on the right-hand console. Forward/reverse is actuated by a steering column mounted shuttle lever.
Number of gears: 18 forward, 6 reverse (40 km/h)
Available options: 31 x 12 with creep (40 km/h)
17 x 6 (30 km/h) 30 x 12 with creep (30 km/h)

Rear axle final drives

Make: New Holland

Model: None

Type: Crown wheel and pinion with differential and inboard epicyclic reduction gear final drive

Differential lock:

Type: Mechanical

Method of engagement: Electro-hydraulic actuation in response to signal from switch on right-hand control panel

Method of disengagement: Via panel switch or in response to electrical signal from brakes on application

Front axle and final drives

Make: New Holland

Model: None

Type: Crown wheel and pinion with differential and outboard epicyclic reduction gear final drives

Drive engagement:

Type: Multiplate clutch - located within the gearbox

Method of operation: Electro-hydraulic actuation in response to signal from switch on the RH control panel

Differential lock:

Type: Mechanical

Method of engagement: Electro-hydraulic actuation in response to signal from switch on right-hand control panel

Method of disengagement: Via panel switch or in response to electrical signal from brakes on application

Total ratios and travelling speeds

Gear	Group No	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed at rated engine speed: 2200 rev/min km/h
Forward			
1	A	306.92	2.22
2	A	255.32	2.67
3	A	212.48	3.20
4	A	176.70	3.85
5	A	146.90	4.63
6	A	122.16	5.57
1	B	132.14	5.15
2	B	109.90	6.19
3	B	91.48	7.43
4	B	76.08	8.94
5	B	63.25	10.75
6	B	52.60	12.93
1	C	46.58	14.60
2	C	38.74	17.56
3	C	32.25	21.09
4	C	26.82	25.36
5	C	22.30	30.50
6	C	18.54	36.68
Reverse			
1	R	157.31	4.32
2	R	130.82	5.20
3	R	108.91	6.25
4	R	90.57	7.51
5	R	75.30	9.03
6	R	62.62	10.86

A = Low range B = Medium range C = High range

(*) Calculated with a tyre dynamic radius index of 820 mm (ISO 4251/1-1992)

Number of revolutions of front wheels for one revolution of rear wheels: 1.324

POWER TAKE-OFF

Main power take-off

Type:	Independent
Method of engagement:	Electro - hydraulically operated multi-plate clutch in response to a signal from switch on the right-hand control panel
Number of shafts:	1 interchangeable shaft, 6 or 21 spline to ISO.500/1991
Method of changing power take-off speeds:	
Two speed	Shiftable, 540 or 1000 rev/min by lever on right-hand console

Clutch

Make:	New Holland
Model:	None
Type:	Multiplate, wet
Number of plates:	6
Diameter of plates:	140.0 mm

Two/three speed shiftable power take-off proportional to engine speed and with changeable shafts

540/750/1000 rev/min	540 rev/min	1000 rev/min	1000 rev/min
Location:	Rear of tractor	Rear of tractor	Rear of tractor
Diameter of power take-off shaft:	34.9 mm	34.9 mm	34.9 mm
Number of splines:	6 or 21	6 or 21	6 or 21
Height above ground:	803 mm	803 mm	803 mm
Distance from the median plane of the tractor:	Central	Central	Central
Distance behind rear wheel axis:	602 mm	602 mm	602 mm
Pto speed at rated engine speed:	603	769	1038
Engine speed at standard power take-off speed:	1971	2145	2121
Ratio of rotation speeds:	3.65	2.86	2.12
Power restriction and maximum torque:	None	None	None
Direction of rotation (viewed from behind tractor):	Clockwise	Clockwise	Clockwise
<u>Power take-off proportional to ground speed</u>			
Travelling distance for one revolution of power take-off shaft	.355 m	.263 m	.194 m
Number of power take-off shaft revolutions for one revolution of rear driving wheels	15.4	19.6	26.5

POWER LIFT - standard

Pump - standard


Make:	New Holland
Model:	None
Type:	Electro-hydraulic with solenoid valves, open centre for lift and drop
Type and number of cylinders:	1 single acting inside transmission housing plus the option of single acting, externally mounted assister ram (1 fitted for test)
Type of linkage lock for transport:	Hydraulic
Relief valve pressure setting:	18.7 - 193 MPa
Opening pressure of cylinder safety valve:	19.3 MPa
Lift pump type:	Gear
Transmission between pump and engine:	Gear driven from pto shaft, independent of main and pto clutches
Type and number of filters:	2 disposable canister filters
Site of oil reservoir:	Rear axle housing
Type, number and position of tapping points:	1, 2, 3 or 4 remote couplers at rear of tractor
Maximum volume of oil available to external cylinders:	18 - 20 litres

THREE-POINT LINKAGE

Category: 2 to ISO standard 730-1:1994

Category adaptor: None

Controls: Electronic draught/position control link.
(Optional - draught or position control)
Lower link sensing



LIFT TEST
Linkage geometry

Table 2.1

Dimensions of linkage when attached to the standard frame (ISO 730/3-1994 CAT 2)

			Dimensions or range	Settings used in main test	Settings used in optional test
Length of lift arms		(A)	230	230	230
Length of lower links		(B)	974	974	974
Distance of lift arm pivot point from rear wheel centre line:	horizontally: vertically:	(a) (b)	156 362.5	156 362.5	156 362.5
Horizontal distance between the two lower link points:		(u)	544	544	544
Horizontal distance between the two lift arm end points:		(v)	560	560	560
Length of upper link:		(S)	652-942	754	968
Distance of upper link pivot point from rear wheel centre line:	horizontally: vertically:	(c) (d)	430-455 208-275	455 208	430 275
Distance of lower link pivot point from rear wheel centre line:	horizontally: vertically:	(e) (f)	220 250	220 250	220 250
Distance of lower link points to lift rod pivot points on lower link centre line:	horizontally: vertically:	(D) (E)	435-504 on centre line	435 on centre line	504 on centre line
Length of lift rods:		(L)	635-780 610	740 610	780 610
ISO mast height					
Height of lower hitch points (*) relative to the rear wheel centre line, situated 820 mm above the ground level:		(h)	250-744	625	599
- in low position		(H)	41-328	70	75
- in high position					
Height of lower hitch points when locked in transport position (*)				Any height within lift range (hydraulic transport lock)	

* Assuming r = tyre dynamic radius index of 820 mm ISO 4251/1-1992

SWINGING DRAWBAR

Drawbar

Pick up hitch

(Incorporated in automatic pick-up hitch with hook on opposite end and selectable by reversing drawbar)

Type:	Clevis	Hook
Height above ground, unballasted maximum:	487 mm	475 mm
minimum:	435 mm	-
Type of adjustment:	Inverting drawbar	None
Distance of hitch point from rear-wheel axis, horizontally:	850 mm 950 mm 1000 mm	602 mm
Distance of hitch point from power take-off shaft ends:		
Vertically:	316 mm	328 mm
Horizontally:	248 mm 348 mm 398 mm	0 mm
Lateral adjustment (centre of clevis):		
Right-hand	235 mm	260 mm
Left-hand	235 mm	260 mm
Distance of pivot point from rear axles horizontally:	345 mm	400 mm
Width of clevis:	64 mm	-
Diameter of drawbar pin hole:	33 mm	
Maximum vertical permissible load - Clevis uppermost:	2400 kg	3000 kg
Clevis underneath:	2180 kg	-

Trailer Hitch

Type:	None fitted
-------	-------------

Linkage Drawbar

Type:	None fitted
-------	-------------

Front Towing Hitch

Type	None fitted
------	-------------

STEERING

Make:	New Holland
Model:	None
Type:	Hydrostatic
Method of operation:	
Pump:	New Holland
Motor:	Danfoss OSPC-160-OR
Ram:	2, a balanced single acting cylinder operating each steering arm
Filter:	Integral with hydraulic power lift system
Working pressure:	166 - 178 bar

BRAKES

Service brake

Make:	New Holland
Model:	None
Type:	Oil-immersed single plate disc
Method of operation:	Hydraulic, independent on rear wheels (On (4WD) models. When the service brakes are actuated the front wheel drive is automatically engaged providing 4-wheel braking)
Trailer braking take-off:	Hydraulic connector fitted to ISO 5676-1983

Parking brake

Make:	New Holland
Type:	Fully independent three plate disc operating on bevel pinion shaft
Method of operation:	Hand lever with ratchet

WHEELS

Number: 4

Front: 2 steering and driving

Rear: 2 driving

Wheelbase: 2723 mm

Track settings

	Minimum mm	Maximum mm	Adjustment method
Front	1551	2268	Reversing wheels and offset lug rims
Rear	1630	2232	Reversing wheels and offset lug rims

PROTECTIVE STRUCTURE

Make: New Holland

Model: New Holland SLTV 1

Type: Cab safety frame

Manufacturer's name and address: New Holland UK Ltd, Basildon

Protective device:

Rollguard: Safety cab

Tiltable/Not tiltable: Non tiltable

OECD approval number: CSD-1398/1-12, 28 September 1994

New Holland M100 CSD 1398/11

New Holland 8160 CSD 1398/5

Original test and minor modification certificates under the responsibility of S.H. STATENS HUSDYRBRUGGSFORSOG BYGHOLM, DENMARK

DRIVERS SEAT

Make/Model/Type: Grammar DS85H/90A

Type of suspension: Parallelogram suspension spring

Type of damping: Double acting, hydraulic

Range of adjustment:

Longitudinal: ± 75 mm

Vertical: ± 30 mm

Passenger seat

Make: New Holland

Type: Soft plastic moulding, half folding, on LH side of inner fender. EEC approved to Directive 76/763/EEC-e110725

LIGHTING

In accordance with EEC Directive 78/933/EEC

Unrestricted beam angle of headlight in plan view: 140°

	Height above ground to centre mm	Size mm	Distance from outside edge to median plane of tractor mm
Headlight	1379	150 x 90	200
Sidelights	1847	105 x 30	870
Rear lights	1822	50 x 50	843
Axle reflectors	780	100 x 35	570
Cab reflectors	1822	50 x 50	843

II TEST CONDITIONS

Overall dimensions

Length mm	Width		Height at top of	
	Minimum mm	Maximum mm	Protective structure mm	Exhaust pipe mm
4658	2135	2771	2826	2982

Ground clearance (unballasted tractor) 365 mm

Clearance-limiting part: Drawbar clevis in lowest position

Tractor mass (safety cab)

	Unballasted		Ballasted	
	Without driver kg	With driver kg	Without driver kg	With driver kg
Front	2039	2050	--	--
Rear	3100	3164	--	--
Total	5139	5214	--	--

Tyres and track width specification

	Front	Rear
Tyres		
dimensions	14.9 R 28	18.4 R 38
ply rating	128A8	146A8
type	Radial	Radial
Maximum load (tyre manufacturer's), kg 30 km/h (40 km/h)	1925 (1800)	3210 (3000)
Maximum load (tractor manufacturer's), kg	1925 (1800)	3210 (3000)
Inflation pressure (tyre manufacturer's), Bar	1.6	1.6
Dynamic radius index	640	820
Chosen track width (manufacturer's nominal)	1720	1830

Oils and lubrication

Capacity and change interval

	Capacity litre	Oil change hours	Filter change hours
Engine	19.0	300	300
Front axle differential	9.0	1200	None
Final drive (front) - per side	1.7	1200	None
Rear axle Range command + CCLS	90	1200	300
Gearbox }			
Hydraulic system }			
Final drives (rear) }			
Steering }			
Brakes	0.5	Top-up	None

Fuels and lubricants used in tests

Fuel

Type: Diesel oil to Class D, 1.5 to 5.5 cSt.

Specific gravity: 0.8390 g/cm² at 15°C

<u>Oils</u>	<u>NH spec</u>	<u>Recommended</u>	<u>Used during test</u>
Engine oil			
Type:	NH 324B	SAE 10W/30	As recommended
Viscosity:		11.5 cSt at 100°C	
Classification:		API CF-4	
Transmission oils			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Rear final drives			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Front differential and final drives			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Hydraulic brakes			
Type:	NH 610A	No equivalent	As recommended
Viscosity:		6 cSt at 100°C	
Classification:		No equivalent	
Hydraulic fluid			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Steering oil			
Type:	NH 410B	SAE 10W/30	As recommended
Viscosity:		9 cSt at 100°C	
Classification:		API GL-4	
Grease points			
Recommended grease:	NH 720A	Lithium based	As recommended
Number of lubrication points:	14		

III. TEST RESULTS

A. COMPULSORY TESTS

1. MAIN POWER TAKE-OFF (1000)

Date and location of tests:

18 August 1997
Silsoe Research Institute,
Wrest Park, Silsoe, Bedford

Type of dynamometer:

Eddy Current, Borghi and Saveri

Power kW	Speed		Fuel consumption		Specific energy kWh/l	
	Engine rev/min	P.T.O. rev/min	Hourly kg/h	l/h		
1.1 MAXIMUM POWER - TWO HOUR TEST						
70.1	1893	893	17.10	20.39	244	3.44
1.2 POWER AT RATED ENGINE SPEED						
66.9	2201	1038	17.76	21.17	265	3.16
1.3 STANDARD POWER TAKE-OFF SPEED (1000 ± 25 rev/min)						
68.5	2120	1000	17.61	20.99	257	3.26
1.4 PART LOADS						
1.4.1 The torque corresponding to maximum power at rated engine speed						
66.9	2201	1038	17.76	21.17	265	3.16
1.4.2 85% of the torque defined in 1.4.1						
58.5	2269	1070	16.33	19.46	279	3.01
1.4.3 75% of the torque defined in 1.4.2						
44.7	2310	1090	13.72	16.35	307	2.73
1.4.4 50% of the torque defined in 1.4.2						
30.2	2338	1103	11.27	13.43	373	2.25
1.4.5 25% of the torque defined in 1.4.2						
15.4	2363	1115	8.84	10.53	575	1.46
1.4.6 Unloaded						
0	2389	1127	6.37	7.59	--	--

Power kW	Speed		Fuel consumption		Specific energy kWh/l	
	Engine rev/min	P.T.O. rev/min	Hourly kg/h	l/h		
1.5 PART LOADS AT STANDARD POWER TAKE-OFF SPEEDS (1000 ± 25 rev/min)						
1.5.1 The torque corresponding to maximum power						
68.5	2120	1000	17.61	20.99	257	
59.8	2174	1025	16.09	19.18	269	
46.0	2225	1049	13.57	16.17	295	
6.17						
1.5.4 50% of the torque obtained in 1.5.2						
31.3	2266	1069	11.05	13.17	353	
15.9	2294	1082	8.46	10.08	532	
1.5.6 Unloaded						
0	2321	1095	6.08	7.25	--	

No load, maximum engine speed: 2389 rev/min

Torque (equivalent crankshaft) at maximum power: 353.8 Nm

Torque (equivalent crankshaft) at rated speed: 290.4 Nm

Maximum torque (equivalent crankshaft): 389.8 Nm
(engine speed 1437 rev/min)

Mean atmospheric conditions:

- Temperature 27°C
- Pressure 1020 m bar
- Relative humidity 45%

Maximum temperatures:

- Coolant 86°C
- Engine oil 108°C
- Fuel 58°C
- Engine air intake 28°C

2. HYDRAULIC POWER AND LIFTING FORCE

Date of tests: 12 September 1997

2.1 Hydraulic power test

Sustained pressure with relief valve open: 19.7 MPa

Pump delivery rate at minimum pressure: 94.0 l/min

	Flow rate l/min	Pressure MPa	Power kW
Flow rate corresponding to a hydraulic pressure equivalent to 90% of the actual relief valve pressure setting and corresponding hydraulic power	76.0	17.7	22.42
Flow rate and hydraulic pressure corresponding to maximum hydraulic power	90.6	17.0	25.67

Tapping point used for test: Auxiliary service connection

Temperature of hydraulic fluid if different from $65 \pm 5^\circ\text{C}$ -- $^\circ\text{C}$

Opening pressure of the unloading valve: -- MPa

Closing pressure of the unloading valve: -- MPa

2.2 Power lift test - (To ISO 730-1:1990)

	At the hitch point	On the frame
Height of lower hitch points above ground in down position	193 mm	193 mm
Vertical movement	732 mm	892 mm
Maximum corrected force exerted through full range	32.1 kN	30.0 kN
Corresponding pressure of hydraulic fluid	17.7 MPa	17.7 MPa
Moment about rear-wheel axis	37.2 kNm	52.7 kNm
Maximum tilt angle of mast from vertical	—	12 degrees

Linkage settings for test - see Table 2.1 and Figure 2.1

Lifting heights relative to the horizontal plane including the lower link pivot points												
mm	-432	-377	-300	-200	-100	0	100	200	300	355	460	
Lifting forces (the values measured are corrected to correspond to a hydraulic pressure equivalent to 90% of the actual relief valve pressure delivered by the hydraulic system)												
at the hitch points kN	—	31.2	37.4	42.6	45.9	48.2	50.1	51.1	52.5	53.3	—	—
Corresponding pressure:											17.7 MPa	
at the frame kN	29.2	31.8	35.3	38.1	39.4	39.8	39.6	39.1	38.2	37.6	36.5	—
Corresponding pressure:											17.7 MPa	

3. DRAWBAR POWER AND FUEL CONSUMPTION TEST (UNBALLASTED TRACTOR), 4 WHEEL DRIVE

Date and location of tests: 15 September 1997
Silsoe Research Institute
Wrest Park
Silsoe

Tyre inflation press. (kPa)

Type of track: Concrete

Height of drawbar above ground			Front	Rear
400 mm			117	103

Gear and Range	Power	Drawbar Pull	Speed	Engine Speed	Slip of wheels or track	Spec fuel cons	Spec energy	Temperature			Atmospheric conditions		
								Fuel	Coolant	Eng oil	Temp	Rel Humidity	Pressure
3.1 MAXIMUM POWER IN TESTED GEARS													
1A*	27.1	48.2	2.02	2314	15.0	451	1.86	57	83	102	20	44	101.4
2A*	31.9	48.2	2.39	2296	15.4	407	2.06	57	83	104	20	45	101.4
3A	38.5	47.2	2.94	2279	12.6	391	2.15	57	84	104	20	45	101.4
4A	46.5	47.5	3.52	2251	11.8	359	2.34	55	84	106	20	46	101.5
5A	52.9	45.8	4.16	2158	9.8	325	2.58	55	83	105	18	50	101.6
1B	55.4	43.6	4.58	2101	8.3	311	2.70	52	83	103	18	51	101.6
6A	54.4	42.8	4.57	1932	7.9	313	2.68	55	85	104	18	55	101.6
2B	57.8	41.5	5.01	1894	7.2	292	2.88	54	84	103	16	59	101.6
3B	57.8	33.9	6.13	1891	5.4	293	2.86	52	86	104	17	57	101.6
4B	56.2	27.1	7.47	1893	4.3	301	2.79	52	85	104	14	66	101.6
5B	56.5	22.4	9.07	1898	3.6	300	2.80	49	85	102	16	57	101.6
6B	54.6	18.0	10.95	1892	3.1	309	2.71	48	85	103	16	56	101.6
1C	56.6	16.4	12.41	1896	2.8	305	2.75	51	85	104	16	57	101.6
2C	54.8	13.2	14.95	1891	2.2	309	2.72	50	84	103	16	60	101.6
3.2 FUEL CONSUMPTION													
3.2.1 In selected gear, at maximum power at rated speed													
2B	54.5	32.9	5.96	2202	5.2	324	2.59	52	84	105	17	55	101.6
3.2.1.1 75% of pull at maximum power at rated speed													
2B	43.0	24.7	6.25	2282	3.9	349	2.41	54	84	105	17	56	101.6
3.2.1.2 50% of pull at maximum power at rated speed													
2B	29.5	16.5	6.45	2324	2.7	413	2.03	55	83	105	17	56	101.6
3.2.1.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.1.1													
3B	42.9	24.7	6.26	1903	4.1	311	2.70	52	83	98	20	43	101.4
3.2.1.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.1.2													
3B	29.6	16.5	6.46	1940	2.9	364	2.31	56	82	99	20	43	101.5
3.2.2 In selected gear nearest to 7.5 km/h, at maximum power at rated engine speed													
3B	54.1	26.9	7.23	2203	4.2	325	2.58	52	83	100	14	68	101.6
3.2.2.1 75% of pull at maximum power at rated speed													
3B	42.4	20.2	7.57	2283	3.3	369	2.27	52	84	105	14	67	101.6
3.2.2.2 50% of pull at maximum power at rated speed													
3B	29.1	13.5	7.76	2320	2.4	437	1.92	50	83	104	14	68	101.6
3.2.2.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.2.1													
4B	42.4	20.2	7.56	1898	3.4	319	2.63	58	83	104	20	46	101.5
3.2.2.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.2.2													
4B	29.0	13.5	7.75	1927	2.4	381	2.20	57	82	103	20	45	101.5

*Maximum power limited by wheelslip

TEST RESULTS

B. SUPPLEMENTARY TESTS

2. Power lift tests

1. Power lift test - (To manufacturers lift rod setting)

	At the hitch point	On the frame
Height of lower hitch points above ground in down position	220 mm	220 mm
Vertical movement	661 mm	716 mm
Maximum corrected force exerted through full range	39.4 kN	40.8 kN
Corresponding pressure of hydraulic fluid	17.7 Mpa	17.7 MPa
Moment about rear-wheel axis	45.7 kNm	71.6 kNm
Maximum tilt angle of mast from vertical	—	6 degrees

Linkage settings for test - see Table 2.1 and Figure 2.1

3. DRAWBAR POWER AND FUEL CONSUMPTION TEST (UNBALLASTED TRACTOR), 2 WHEEL DRIVE

Date and location of tests: 16 September 1997
Silsøe Research Institute
Wrest Park
Silsøe

Type of track: Concrete

Height of drawbar above ground

Tyre inflation press
(kPa)

Front

Rea

460 mm

117

103

Gear and Range	Power	Drawbar Pull	Speed	Engine Speed	Slip of wheels or track	Spec fuel cons	Spec energy	Temperature						
								Fuel	Coolant	Eng oil	Temp	Rel Humidity	Press	
	kW	kN	km/h	rev/min	%	g/kwh	kWh/l	Deg.C	Deg.C	Deg.C	Deg.C	%		kPa
3.1 MAXIMUM POWER IN TESTED GEARS														
2A*	23.2	34.7	2.40	2328	14.9	491	1.71	61	83	104	23	34	100	
3A*	27.7	35.0	2.85	2322	15.0	440	1.91	58	84	102	23	35	100	
4A	32.5	33.5	3.49	2291	13.0	387	2.17	59	83	104	22	39	101	
5A	38.9	33.4	4.19	2274	12.6	388	2.16	60	83	104	22	40	101	
1B	43.2	33.0	4.71	2264	11.2	363	2.31	57	84	106	20	50	101	
6A	46.1	32.9	5.04	2233	11.0	370	2.27	56	85	107	19	52	101	
2B	51.1	33.0	5.57	2206	10.5	341	2.46	57	84	106	19	53	101	
3B	54.5	30.1	6.51	2082	7.7	319	2.63	52	85	106	16	71	101	
4B	55.2	27.6	7.20	1893	6.5	307	2.73	53	85	105	16	72	101	
5B	56.1	22.9	8.80	1896	5.2	304	2.76	52	86	103	19	58	101	
6B	54.1	18.2	10.70	1895	4.1	313	2.68	54	85	105	17	68	101	
1C	56.4	16.7	12.13	1897	3.9	303	2.77	55	85	105	17	68	101	
2C	55.1	13.5	14.66	1896	3.2	305	2.75	55	85	105	18	65	101	
3.2 FUEL CONSUMPTION														
3.2.1	In selected gear, at maximum power at rated speed													
1C	53.1	13.5	14.12	2196	3.3	334	2.51	54	85	105	18	66	101	
3.2.1.1 75% of pull at maximum power at rated speed														
1C	41.8	10.2	14.77	2283	2.6	380	2.21	53	85	106	18	66	101	
3.2.1.2 50% of pull at maximum power at rated speed														
1C	28.7	6.8	15.10	2318	2.0	473	1.78	54	84	106	18	66	101	
3.2.1.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.1.1														
2C	41.9	10.2	14.71	1895	2.9	343	2.44	59	84	103	22	36	101	
3.2.1.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.1.2														
2C	28.4	6.80	15.05	1924	2.2	393	2.14	57	82	102	22	37	101	
3.2.2 In selected gear nearest to 7.5 km/h, at maximum power at rated engine speed														
3B	52.8	27.2	7.00	2202	6.2	336	2.49	52	84	100	16	72	101	
3.2.2.1 75% of pull at maximum power at rated speed														
3B	41.8	20.4	7.36	2278	4.5	372	2.26	52	84	104	16	72	101	
3.2.2.2 50% of pull at maximum power at rated speed														
3B	28.7	13.6	7.59	2316	3.2	452	1.86	54	83	103	16	72	101	
3.2.2.3 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.2.1														
4B	41.8	20.5	7.34	1895	4.9	316	2.66	55	84	100	22	37	100	
3.2.2.4 Next higher gear at reduced engine speed; same pull and travelling speed as in 3.2.2.2														
4B	28.5	13.5	7.57	1927	3.5	376	2.23	57	82	101	22	37	100	

* Maximum power limited by wheelslip

REPAIRS AND ADJUSTMENTS DURING TESTS: None

REMARKS: None

Test carried out by: S J Devonshire



Signed: Officer in charge of tests

P C Seward



Signed: for the Director



P C Seward
Head of Test Engineering Group

Date: 23/12/97

ANNEX 1 MAIN POWER TAKE-OFF CURVES

P.T.O. POWER TEST - NEW HOLLAND M100 FOUR-WHEEL DRIVE (1000 rev/min)

Governor set for maximum power at rated speed
Governor set for maximum power at pto speed
Power take-off speed (1000 rev/min)



P.T.O. POWER TEST - NEW HOLLAND M100 FOUR-WHEEL DRIVE (1000 rev/min)



Governor set for maximum power at rated speed



Governor set for maximum power at pto speed



Power take-off speed (1000 rev/min)



P.T.O. POWER TEST - NEW HOLLAND M100 FOUR-WHEEL DRIVE (1000 rev/min)

Governor set for maximum power at rated speed

Governor set for maximum power at pto speed

