COTTEC

CHINA
OFFICIAL TRACTOR
TEST AND
EVALUATION CENTRE

Address:
Luoyang Tractor Research Institute
Luoyang, Henan, China 471039
Tel: 86 379 62690001
Fax:86 379 62690002

OECD TEST REPORT OF YTO-304 AGRICULTURAL TRACTOR (CODE 2)

Report on test in accordance with the OECD standard code for the official testing of agricultural and forestry tractor performance



OECD Approval
No.: 2/2 397
Date:Feb.19,2008

Tested Tractor	Submitted for test by
Make: YTO Model: YTO-304 Type: 4WD Speed version: 30 km/h	Name: China YTO Group Co., Ltd Address: Luoyang, Henan, China Tel: 86 379 64960764 Fax: 86 379 64969800

This report includes 23 pages and may only be duplicated as a whole

TABLE OF CONTENTS

1. SPECIFICATIONS OF TRACTOR

1.1 Identification....3
1.2 Engine....3
1.3 Transmission....5
1.4 Power take-off....6
1.5 Hydraulic power lift....7
1.6 Three point linkage....8
1.7 Swinging drawbar....10
1.8 Trailer hitch....10
1.9 Holed drawbar:....10
1.10 Steering....10
1.11 Brakes....10
1.12 Wheels....10
1.13 Protective structure....11
1.14 Seat....11
1.15 Lighting....11

2. TEST CONDITIONS

2.1 Overall dimensions....12
2.2 Ground Clearance(unballasted tractor)....12
2.3 Tractor mass....12
2.4 Ballast....12
2.5 Track specifications....12
2.6 Tyres and track width specifications....12
2.7 Fuel....12
2.8 Oils and lubricants....13

3. COMPULSORY TESTS

3.1 Main power take-off performance....13
3.2 Hydraulic power and lifting force....14
3.3 Drawbar performance....16

4. OPTIONAL TESTS

4.1 Drawbar performance....17
4.2 Low temperature starting....17
4.3 Turning area and turning circle....18
4.4 Location of centre of gravity....18
4.5 Braking....18
4.6 Measurement of external noise level....19

5. REPAIRS....19

6. REMARKS....19

ANNEX Ⅰ Main power take-off test curves 1....21

ANNEX Ⅱ Main power take-off test curves 2....22

ANNEXⅢ Main power take-off test curves 3....23

	Note: Units shown below, which appear in ISO 1000:1992; Amdl:1998, shall be stated and followed by national units in parenthesis	
C[1]	Tractor manufacturer's name and address:	China YTO (Yituo） Group Co., Ltd, Luoyang, Henan, China
D[1]	-Location of tractor assembly:	The manufacturer
D	-Submitted for test by:	The manufacturer
C	-Selected for test by:	The manufacturer with the agreement of the COTTEC
D	-Place of running-in:	COTTEC, Luoyang, Henan, China
D	-Duration of running-in:	49.5 hours
C	-Location of test:	COTTEC, Luoyang, Henan, China
	1. SPECIFICATIONS OF TRACTOR	
	1.1 Identification	
	1.1.1 Denomination	
C	- Make of the tractor:	YTO
C	-Model (trade name):	YTO -304
C	-Type:	4WD
	1.1.2 Numbers	
D	-1st Serial No or prototype:	0707465
C	- Serial No.:	0707465
	1.1.3 Other Specifications	
D	- Models for other countries:	东方红-304
C	-Transmission type or gears x ranges:	Mechanical
C	-Speed version:	30 km / h
D	- Manufacturer identification or Technical type number: None	
	1.2 Engine	
C	-Make:	Dongfanghong
C	-Model:	YTR2105T51SA
C	-Type:	4-stroke,water cooling ,Vertical, direct injection
C	-Serial No.:	X709710
	1.2.1 Cylinders	
C	-Number:	2
C	-Disposition:	Vertical, in line
D	-Bore/Stroke:	105 mm /120 mm
D	-Capacity:	2078 cm^3
D	-Compression ratio:	17.0
D	-Arrangement of valves:	Overhead, in line
D	-Cylinder liners:	Wet
	1.2.2 Supercharging	None

1. An item marked "C" indicates to the test report user that the information declared by the manufacturer has been checked; an item marked "D" that the manufacturer's declaration has been endorsed.

	1.2.3 Fuel system	
C	-Fuel feed system:	Forced feed type
C	-Make of fuel filter:	Luoyang tractor research Co.,Ltd
C	-Model of fuel filter:	CX0708
C	-Type of fuel filter:	Paper cartridge, replaceable
D	-Capacity of fuel tank:	38 dm^3
C	-Make of injection pump:	WUXI WEIFU HIGH-TECH CO.,Ltd
C	-Model/type of injection pump:	BHF2IW085024, cylinder plunger
C	-Serial No :	60376523
	-Manufacturer's production setting of injection pump:	
C	. Flow rate (at rated engine speed and full load):	8.0 ± 0.5 dm^3 /h
D	.Timing:	$20^0 \pm 1^0$ before T.D.C.
D	-Make of injectors:	Own make
D	-Model/type of injectors:	PB86J,Multi-hole
D	-Injection pressure:	20 MPa
C	-Make/Mode/Type of carburettor:	None
	1.2.4 Governor	
C	- Make:	WUXI WEIFU HIGH-TECH CO.,Ltd
C	-Model/type:	T152, Mechanical, centrifugal
C	-Governed range of engine speed:	700～2500 rev/min
C	-Rated engine speed:	2300 rev/min
	1.2.5 Air cleaner	
	-Pre-cleaner	
C	.Make:	Linhai Jiannan
C	.Model/type:	395，cyclone type, integrated with main cleaner
C	.Location of air intake:	Left-hand side of engine, vertical
C	.Maintenance indicator:	None
	-Main cleaner	
C	.Make:	Linhai Jiannan
C	.Model/type:	395, oil bath
C	.Location of air intake:	Left-hand side of engine, vertical
C	.Maintenance indicator:	None
	1.2.6 Lubrication system	
D	-Type of feed pump:	Roter
C	-Type of filters:	J0810B, paper cartridge, replaceable
C	-Number of filters:	1
	1.2.7 Cooling system	
C	-Type of coolant:	Water
D	-Type of pump:	Centrifugal, belt driven
	-Specification of fan or blower:	
C	.Number of fan blades:	7
C	.Fan diameter:	380 mm
D	-Coolant capacity:	12 dm^3
C	-Type of temperature control:	Thermostat
D	-Super pressure system:	None

	1.2.8 Starting system	
C	-Make:	Ningbo Huatai
C	-Model/Type:	QD143, solenoid engaged
D	-Starter motor power rating:	2.5 kW
C	-Cold starting aid:	None
C	-Safety device:	Forward and reverse lever in neutral position
	1.2.9 Electrical system	
C	-Voltage:	12 V (Negative earth)
	-Generator:	
C	.Make:	Ningbo Huatai
C	.Model/Type:	JF131, altermator, belt driven
D	.Power	0.35 kW
	-Battery of accumulators:	
C	.Number:	1
D	.Rating:	120 Ah at 20 hours rating
	1.2.10 Exhaust system	
C	-Make:	Yi Chuan JuXing
C	-Model/Type:	YT2100,expansion type, silencer
C	-Location:	Right-hand side of the engine, vertical
	1.3 Transmission	
	1.3.1 Clutch (Travel and PTO)	
D	-Make:	Weifang Baocheng
D	-Model/Type:	Dry, dual (for travel and PTO)
D	-Number of plates:	1
D	-Diameter of plates:	254 mm
C	-Method of operation:	Mechanically actuated by pedal
	1.3.2 Gear box	
D	-Make:	Own make
D	-Model/Type:	YT (2+1)×4, mechanical
	-Description:	8 forward speed gear,4 reverse speed gear, main gear is constant-mesh cylindrical gear, auxiliary gear is constant-mesh cylindrical gear, engaging sleeve gear shifting

		Forward	Reverse
C	Number of groups /ranges	2	1
C	Number of gears	4	4
C	Total of arrangements	8	4

D	-Available options	None

	1.3.3 Rear axle and final drives	
D	-Make:	Own make
D	**-Model/Type:**	Helical gear type differential and single stage epicyclic gear type final drives
	-Differential lock	
D	.Type:	Mechanical, two planet gear
C	.Method of engagement:	Mechanically actuated by pedal
C	.Method of disengagement:	Mechanically actuated by pedal
	1.3.4 Front axle and final drives	
D	-Make:	Own make
D	**-Model/Type:**	Helical gear type differential and full closed bevel gear type final drives
	-Differential lock:	None

1.3.5 Total ratios and travelling speeds

		Gear No	Group or range	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed(*) at rated engine speed of 2300 rev/min **km/h**
C		1	L	206.164	2.17
C		2		142.138	3.14
C		3		91.301	4.89
C		4		67.566	6.61
C		1	H	47.982	9.31
C		2		33.081	13.50
C		3		21.249	21.01
C		4		15.726	28.40
C		1	R	138.936	3.21
C		2		95.788	4.66
C		3		61.529	7.26
C		4		45.534	9.81
		(*) Calculated with the dynamic radius index of 515 mm (ISO 4251-1:2005)			

C	-Number of revolutions of front wheels for one revolution of rear-wheels:	1.471
	1.4 Power take-off	
	1.4.1 Main power take-off	
C	-Type:	Semi-independent
C	-Method of engagement:	By hand lever
C	-Number of shafts:	1
C	-Method of changing power take-off shaft ends and speeds:	By hand lever

	1.4.1.1 Power take-off proportional to engine speed	
	Power take-off at 540 rev/min	
C	-Location:	At rear of the tractor
C	-Diameter of power take-off shaft end:	35 mm
C	-Number of splines:	6, in conformity with ISO 500-1:2005, ISO 500-2:2004, ISO 500-3:2004
C	-Height above ground:	500 mm
C	-Distance from the median plane of the tractor:	0 mm
C	-Distance behind rear wheel axis:	440 mm
C	-PTO speed at rated engine speed:	627 rev/min
C	-Engine speed at standard power take-off speeds	1980 rev/min
C	-Ratio of rotation speeds (engine speed/PTO speed):	3.667
D	-Power restriction:	24.0 kW
D	-Maximum torque transmissible:	480 Nm
C	-Direction of rotation (viewed from behind tractor):	Clockwise
	Power take-off at 1000 rev/min:	
C	-Location:	At rear of the tractor
C	-Diameter of power take-off shaft end:	35 mm
C	-Number of splines:	6, in conformity with ISO 500-1:2005, ISO 500-2:2004, ISO 500-3:2004
C	-Height above ground:	500 mm
C	-Distance from the median plane of the tractor:	0 mm
C	-Distance behind rear wheel axis:	440 mm
C	-PTO speed at rated engine speed:	1200 rev/min
C	-Engine speed at standard power take-off speeds	1917 rev/min
C	-Ratio of rotation speeds (engine speed / PTO speed):	1.917
D	-Power restriction:	24.0 kW
D	-Maximum torque transmissible:	250 Nm
C	-Direction of rotation (viewed from behind tractor):	Clockwise
	1.4.1.2 Power take-off proportional to ground speed	None
	1.4.2 Optional power take-off:	None
	1.5 Hydraulic power lift	
C	-Make:	ShanDong HongYu
C	-Model:	300
C	-Type:	Hydraulic, three hitch point
C	-Type of hydraulic system:	Open centre system
C	-Type and number of cylinders:	Single acting,1
C	-Type of linkage lock for transport:	Hydraulic
D	-Relief valve pressure setting:	16±0.5 MPa
D	-Opening pressure of cylinder safety valve :	18±0.5 MPa


D	-Lift pump type:	Gear pump
D	-Transmission between pump and engine:	Driven by engine cam shaft
C	-Type and number of filters:	Cartridge type, 1
C	-Site of oil reservoir:	Transmission housing
C	-Type, number and location of tapping points:	Coupler pairs quick shift adaptor, At rear of tractor
D	-Maximum volume of oil available to external cylinders:	8 dm^3


1.6 Three point linkage

C	-Category	1 ,in conformity with ISO730-1:1994+Cor.1:1995
C	-Category Adapter:	None

Table 1.1
Dimensions of linkage geometry
when connected to the standard frame

				Dimension or range	Setting used in test	
				mm	mm	
C		Length of lift arms :	(A)	235	235	
C		Length of lower links :	(B)	720	720	
		Distance of lift arm pivot point from rear wheel axis:				
C		-Horizontally	(a)	143	143	
C		-Vertically	(b)	339	339	
C		Horizontal distance between the 2 lower link points:	(u)	425	425	
C		Horizontal distance between the 2 lift arms end points:	(v)	500	500	
C		Length of upper link:	(S)	From 500 to 720	537	
		Distance of upper link pivot point from rear wheel axis:				
C		-Horizontally:	(c)	361	361	
C		-Vertically	(d)	160,190,220,250	250	
		Distance of lower link pivot point from rear wheel axis:				
C		-Horizontally:	(e)	203	203	
C		-Vertically	(f)	160	160	
C		Distance of lower link pivot point to lift rod pivot points on lwer links:	(D)	340	340	
C		Length of lift rods:	(L)	From 475 to 590	515	
		Height of lower hitch points relative to the rear wheel axis:				
C		-in low position	(h)	From 260 to 555	330	
C		-in high position	(H)	From 142 to 340	282	
C		Height above ground of lower hitch points when locked in transport position (*):		Any height at lift range	Any height at lift range	
		(*)Assuming r = 515 mm rear tyre dynamic radius index of ISO 4251-1:2005				





Figures 1.1 Lift test-linkage geometry

	1.7 Swinging drawbar:	None
C	-Type:	None
	-Height above ground	
C	.Maximum	None
C	.Minimum	None
C	-Type of adjustment:	None
C	-Distance of hitch point from rear wheel axis, horizontally:	None
	-Distance of hitch point from power take-off shaft end:	
C	.Vertically:	None
C	.Horizontally:	None
	-Lateral adjustment (centre of clevis)	
C	.Right hand:	None
C	.Left hand:	None
C	-Distance of pivot point from rear wheel axis, horizontally:	None
C	-Diameter of drawbar pinhole:	None
D	-Maximum vertical permissible load:	None
	1.8 Trailer hitch	
C	-Type:	Fixed
C	-Hole diameter :	34 mm
C	-Height above ground:	539 mm
C	-Distance of hitch point from rear wheel axis, horizontally:	700 mm
	-Distance of hitch point from power take-off shaft end:	
C	.Vertically:	49 mm
C	.Horizontally:	260 mm
D	-Maximum vertical permissible load:	12.0 kN
	1.9 Holed drawbar:	None
	1.10 Steering	
D	-Make:	Jining Like
D	-Model/Type:	BZZI-E80C,Hydrostatic steering system
	-Method of operation	
D	.Pump:	HLCB-D16/12 Gear pump
D	.Ram:	Double acting ram actuating directly on front axle
D	-Working pressure:	16 MPa
	1.11 Brakes	
	1.11.1 Service brake	
D	-Make:	Own make
D	-Model/Type:	304,Oil –immersed multi-plate discs, mechanical
C	-Method of operation:	by pedals
C	-Trailer braking take-off:	None
	1.11.2 Parking brake	
C	-Type:	Mechanical
C	-Method of operation:	Hand lever with ratchet
	1.12 Wheels	
	-Number	
C	.Front:	2, steering & driving
C	.Rear:	2, driving

C	-Wheelbase:			1782 mm	
	-Track width adjustment:				
			Minimum mm	Maximum mm	Adjustment method
D		Front	1250	1250	None
D		Rear	1200	1600	Reversing wheels and off-set lug rims
	1.13 Protective structure				
C	-Make:				Own make
C	-Model:				MD400.46.001
C	-Type:				Rear roll bar
C	-Manufacture's name and address:				Own make
	-Protective device:				
C	-Cab/frame / roll guard / other:				Rear roll bar
C	-Tiltable / not tiltable:				Tiltable
	-OECD approval				
C	.Approval number:				4/0 947
C	.Date of approval:				June 19,2006
C	.Nos. of minor modification certificates, if any:				None
	1.14 Seat				
	1.14.1 Driver's seat				
C	-Make:				YC (Yacheng)
C	-Model:				616
C	-Type:				Adjustable suspension
C	-Seat and steering wheel reversible:				No
C	-Type of suspension:				Mechanical
C	-Type of damping:				Spring
	-Range of adjustment:				
C	.Longitudinal:				140 mm
C	.Vertical:				None
C	-Safety belt:				None
	1.14.2 Optional driver's seat (s):				None
	1.14.3 Passenger seat:				None
	1.15 Lighting				

		Height above ground of center mm	Size mm	Distance from outside edge of lights to median plane of tractor mm
C	Head lights	1000	110×120	270
C	Front direction lights	1065	80×70	270
C	Rear direction lights	1230	80×55	645
C	Stop lights	1230	80×55	565
	Work lights	1390	Φ130	625

2 TEST CONDITIONS

2.1 Overall dimensions

	Length	Width		Height at top of	
		Minimum	Maximum	Protective Structure	Exhaust Silencer
	mm	mm	mm	mm	mm
Ballasted	3600	1500	1880	2360	1948
Unballasted	3395	1500	1850	2363	1951

2.2 Ground Clearance (unballasted tractor)

-Clearance limiting part: Under the front axle 252 mm

2.3 Tractor mass

-Mass(with rear roll bar and full fuel tank):

	Unballasted		Ballasted	
	Without driver kg	With driver kg	Without driver kg	With driver kg
Front	820	830	927	937
Rear	1020	1085	1151	1216
Total	1840	1915	2078	2153

2.4 Ballast

	Weights		Water kg
	Number	Total mass kg	
Front	4	76	—
Rear	4	162	—
Optional	—	—	—

2.5 Track specifications: None

2.6 Tyres and track width specifications

	Front	Rear
Tyres:		
.dimensions	6.50-16	11.2-24
.ply rating	6	8
.type	Cross ply	Cross ply
.maximum load (tyre manufacturer's)	6.5 kN	9.5 kN
.maximum load (tractor manufacturer's)	6.5 kN	9.5 kN
.inflation pressure (tyre manufacturer's)	80～120 kPa	80～120 kPa
.dynamic radius index	350 mm	515 mm
Chosen track width	1250 mm	1300 mm

2.7 Fuel

-Type: Standard diesel fuel in conformity with GB 10327 (China standard)

-Density at 15 ℃ 0.8523 g/cm^3

2.8 Oils and lubricants

2.8.1 Capacity and change interval

	Capacity dm^3	Oil change h	Filter change h
Engine	7.1	250	250
Gear box, rear axle and final drives	20	500	—
hydraulic system	12	500	500
Front axle and final drives	7.0	500	—
Steering	0.8	500	—

2.8.2 Specifications (SAE, API, CCMC, ACEA, Mil.L, ISO)

	Recommended	Used during test
Engine oil .Type: .Viscosity: .Classification:	SAE 10W/30 11.4 cSt at 100 ℃ API-CD	Same as recommended
Transmission oil, Hydraulic fluid, Steering oil, rear axle and final drives oil, Front axle and final drives oil .Type: .Viscosity: .Classification:	SAE 80W/90 9.3 cSt at 100 ℃ API GL-4	Same as recommended

2.8.3 Grease

-Number of lubrication points: 9

3 COMPULSORY TESTS RESULTS

3.1 Main power take-off

-Date and location of tests: Sep.12, 2007, COTTEC

-Type of dynamometer: LPA-Bedienpult 250 Elec. dynamometer

Power	Speed			Fuel consumption			Specific energy
	Engine	P.T.O	Fan	Hourly		Specific	
kW	rev/min			kg/h	l/h	g/kWh	kWh/l
3.1.1 MAXIMUM POWER-ONE-HOUR TEST							
20.23	2300	1200	2800	6.940	8.14	343.1	2.48
3.1.2 POWER AT RATED ENGINE SPEED							
20.23	2300	1200	2800	6.940	8.14	343.1	2.48
3.1.3 STANDARD POWER TAKE-OFF SPEED (1000±25 or 540±10 rev/min)							
19.58	1917	1000	2334	5.837	6.85	298.1	2.86
3.1.4 PART LOADS 3.1.4.1 The torque corresponding to maximum power at the rated engine speed							
20.23	2300	1200	2800	6.940	8.14	343.1	2.48
3.1.4.2 85% of torque obtained in 3.1.4.1							
18.22	2435	1270	2964	6.165	7.23	338.3	2.52
3.1.4.3 75% of torque obtained in 3.1.4.2							
13.78	2450	1278	2983	5.087	5.97	369.0	2.31
3.1.4.4 50% of torque obtained in 3.1.4.2							
9.16	2467	1287	3003	4.170	4.89	455.1	1.87
3.1.4.5 25% of torque obtained in 3.1.4.2							
4.61	2481	1294	3020	3.305	3.88	717.3	1.19
3.1.4.6 Unloaded							
2.17	2484	1296	3024	2.935	3.44	—	—

Power	Speed			Fuel consumption			Specific energy
	Engine	P.T.O	Fan	Hourly		Specific	
kW	rev/min			kg/h	l/h	g/kWh	kWh/l
3.1.5 PART LOADS AT STANDARD POWER TAKE-OFF (1000±25 or 540±10 rev/min)							
3.1.5.1 The torque corresponding to maximum power							
19.58	1917	1000	2334	5.837	6.85	298.1	2.86
3.1.5.2 85% of torque obtained in 3.1.5.1							
17.68	2036	1062	2479	5.496	6.45	310.8	2.74
3.1.5.3 75% of torque obtained in 3.1.5.2							
13.46	2070	1080	2520	4.265	5.00	317.0	2.69
3.1.5.4 50% of torque obtained in 3.1.5.2							
9.15	2093	1092	2548	3.422	4.02	374.2	2.28
3.1.5.5 25% of torque obtained in 3.1.5.2							
4.60	2105	1098	2563	2.663	3.12	579.0	1.47
3.1.5.6 Unloaded							
1.85	2122	1107	2583	2.120	2.49	—	—
3.1.6 PART LOADS AT DIFFERENT ENGINE SPEEDS							
3.1.6.1 Maximum power at rated engine speed							
20.23	2300	1200	2800	6.940	8.14	343.1	2.48
3.1.6.2 80% of power obtained in 3.1.6.1 at max. speed setting							
16.13	2440	1273	2970	5.678	6.66	352.1	2.42
3.1.6.3 80% of power obtained in 3.1.6.1 with governor control set to 90% of rated engine speed							
16.18	2072	1081	2522	5.100	5.98	315.1	2.70
3.1.6.4 40% of power obtained in 3.1.6.1 with governor control set to 90% of rated engine speed							
8.14	2070	1080	2520	3.245	3.81	398.6	2.14
3.1.6.5 60% of power obtained in 3.1.6.1 with governor control set to 60% of rated engine speed							
12.14	1380	720	1680	3.365	3.95	277.3	3.07
3.1.6.6 40% of power obtained in 3.1.6.1 with governor control set to 60% of rated engine speed							
8.07	1380	720	1680	2.473	2.90	306.6	2.78

-No load maximum engine speed: 2484 rev/min
-Torque(equivalent crankshaft) at maximum power
.At rated engine speed: 84.0 Nm
.At 1-hour test: 84.0 Nm
-Maximum torque (equivalent crankshaft) (engine speed: 1710 rev/min): 101.7 Nm

Mean atmospheric conditions	
Temperature	25 ℃
Pressure	100.1 kPa
Relative humidity	50 %
Maximum Temperature:	
Coolant	85 ℃
Engine oil	115 ℃
Fuel	35 ℃
Engine air intake	35 ℃

3.2 Hydraulic power and lifting force

- Date and location of tests: Sep.17, 2007, COTTEC

3.2.1 Hydraulic power test

3.2.1.1 Hydraulic fluid data

- Hydraulic fluid type: SAE 80W/90
- Viscosity index (ISO3448+Corr 1:1993): 28.5 mm^2/s at 65 ℃

3.2.1.2 Compulsory Reporting (Test Results):

	Pressure	Reservoir oil Temperature ℃		Engine Speed	Flow rate	Power
	MPa	Min	Max	rev/min	L/min	kW
Rated Engine Speed (Manufactures Specification)				2300		
3.2.1.2.1 Maximum (sustained) pressure with relief valve open as measured at the coupler Pump stalled: Yes	15.5	60.1	69.3	2463		
3.2.1.2.2 Flow rate corresponding to a hydraulic pressure equivalent to 90 percent of the actual relief valve pressure setting and corresponding hydraulic power	14.0	68.6		2466	22.6	5.27
3.2.1.2.3 Maximum available flow and maximum power from one coupler pair:	13.8	68.1		2468	23.8	5.47
3.2.1.2.4 Maximum available flow and maximum power from coupler pairs operating simultaneously(flow through two or more coupler pairs if required):	13.8	67.3		2467	23.9	5.50

3.2.2 Compulsory power lift test

-Linkage settings for test-see Table 1.1 and Figure 1.1

	At the hitch point	On the frame
Height of lower hitch points above ground in down position	185 mm	158 mm
Vertical movement: without lifting force:	612 mm	827 mm
with lifting force:	603 mm	812 mm
Maximum corrected force exerted through full range	11.18 kN	7.49 kN
Corresponding pressure of hydraulic fluid	14.0 MPa	14.0 MPa
Moment about rear wheel axle	10.32 kNm	11.48 kNm
Maximum tilt angle of mast from vertical	—	17.6^0

Lifting heights relative to the horizontal plane including the lower link pivot points												
mm	-197	-170	-100	0	100	200	300	400	433	500	600	615
Lifting forces (the values of force measured are correspond to a hydraulic pressure equivalent to 90 % of the actual relief value pressure setting of the hydraulic lifting system) At the hitch point, corresponding pressure 14.0 MPa												
kN	—	11.18	11.74	12.47	12.93	13.02	13.27	13.42	13.85	—	—	—
At the frame, corresponding pressure 14.0 MPa												
kN	10.52	—	11.06	11.12	10.94	10.38	9.81	8.88	—	8.12	7.54	7.49

3.3 Compulsory drawbar power and fuel consumption test (unballasted tractor)

-Date and location of tests: Sep.18, 2007, COTTEC

-Type of track: Concrete

Height of drawbar above ground mm	Tyre inflation pressure	
	Front kPa	Rear kPa
589	120	120

Gear number and range	Power	Drawbar pull	Speed	Engine Speed	Fan Speed	Slip of wheels	Specific fuel consumption	Specific energy	Temperature			Atmospheric conditions		
									Fuel	Coolant	Engine oil	Temperature	Relative humidity	Pressure
	kW	kN	km/h	Min^{-1}	Min^{-1}	%	g/kWh	kWh/l	℃	℃	℃	℃	%	kPa
3.3.1 MAXIMUM POWER IN TESTED GEARS (unballasted tractor)														
L1	8.61	15.49	2.00	2466	3002	15.00	523	1.63	32	82	93	19	45	100.1
L2	12.05	15.28	2.84	2434	2963	15.02	463	1.84	32	82	95	19	45	100.1
L3	16.40	13.18	4.48	2300	2800	9.10	428	1.99	32	82	96	19	45	100.1
L4	17.36	9.92	6.30	2300	2800	5.36	406	2.10	33	82	96	19	45	100.1
H1	16.65	6.60	9.08	2305	2806	3.35	422	2.02	33	84	96	19	45	100.1
3.3.2 FUEL CONSUMPTION														
3.3.2.1 In selected gear/speed setting nearest 7.5 km/h, at maximum power at rated engine speed														
L4	17.36	9.92	6.30	2300	2800	5.36	406	2.10	33	82	96	19	45	100.1
3.3.2.1.1 75 % of pull corresponding to maximum power at rated engine speed														
L4	14.02	7.42	6.80	2440	2970	3.16	435	1.96	33	82	96	19	45	100.1
3.3.2.1.2 50 % of pull corresponding to maximum power at rated engine speed														
L4	9.57	4.91	7.02	2464	3000	1.63	487	1.75	33	82	97	19	45	100.1
3.3.2.1.3 Next higher gear/ speed setting at reduced engine speed; same pull and travelling speed as in 3.3.2.1.1														
H1	13.96	7.37	6.82	1740	2118	3.05	342	2.49	33	83	97	19	45	100.1
3.3.2.1.4 Same gear as 3.3.2.1.3 at reduced engine speed; same pull and travelling speed as in 3.3.2.1.2														
H1	9.72	4.94	7.08	1789	2178	2.21	382	2.23	34	84	97	19	45	100.1
3.3.2.2 In selected gear/speed setting nearest between 7 km/h and 10 km/h at rated engine speed														
H1	16.65	6.60	9.08	2305	2806	3.35	422	2.02	33	84	96	19	45	100.1
3.3.2.2.1 75 % of pull corresponding to maximum power at rated engine speed														
H1	13.27	4.90	9.75	2450	2983	2.13	456	1.87	33	84	96	19	45	100.1
3.3.2.2.2 50 % of pull corresponding to maximum power at rated engine speed														
H1	8.94	3.25	9.90	2465	3001	1.15	536	1.59	33	84	96	19	45	100.1
3.3.2.2.3 Next higher gear/speed setting at reduced engine speed: same pull and travelling speed as in 3.3.2.2.1														
H2	13.34	4.92	9.76	1688	2055	1.85	354	2.41	34	84	95	20	45	100.1
3.3.2.2.4 Same gear as 3.3.2.2.3 at reduced engine speed; same pull and travelling speed as in 3.3.2.2.2														
H2	8.85	3.21	9.92	1710	2082	1.21	400	2.13	34	85	96	20	45	100.1

4 OPTIONAL TEST RESULTS

4.1 Optional drawbar power and fuel consumption test (ballasted tractor)

-Date and location of tests: Sep.19, 2007, COTTEC

-Type of track: Concrete

Height of drawbar above ground mm	Tyre inflation pressure	
	Front kPa	Rear kPa
585	120	120

Gear number and range	Power	Drawbar pull	Speed	Engine Speed	Fan Speed	Slip of wheels	Specific fuel consumption	Specific energy	Temperature			Atmospheric conditions		
									Fuel	Coolant	Engine oil	Temperature	Relative hummidity	Pressure
	kW	kN	km/h	Min^{-1}	Min^{-1}	%	g/kWh	kW/l	℃	℃	℃	℃	%	kPa
4.1.1 OPTIONAL MAXIMUM POWER IN TESTED GEARS/SPEED SETTINGS														
L1	8.76	15.76	2.00	2465	3001	14.96	504	1.69	32	83	94	18	45	100.2
L2	12.21	15.48	2.84	2430	2958	15.00	461	1.85	33	83	95	18	45	100.2
L3	17.33	13.86	4.50	2300	2800	8.38	406	2.10	33	84	95	18	45	100.2
L4	18.39	10.54	6.28	2300	2800	4.93	382	2.23	34	84	96	18	45	100.2
H1	17.91	7.10	9.08	2300	2800	2.65	391	2.18	34	84	97	18	45	100.2
4.1.2 OPTIONAL FIVE-HOUR TESTS														
4.1.2.1 FIVE-HOUR TEST at 75% of the pull corresponding to maximum power at rated speed														
L4	14.70	7.85	6.74	2425	2952	3.26	420	2.03	32	83	96	19	45	100.2
4.1.2.2 FIVE-HOUR TEST at pull corresponding to 15% wheel slip , with additional ballast : 0 kg														
L1	8.73	15.71	2.00	2465	3001	15.02	507	1.68	32	84	97	19	45	100.2

Oil consumption during ten hours duration of tests 4.1.2.1 and 4.1.2.2: 17 g/h

4.2 Low temperature starting

-Date and location of tests: Oct.26, 2007, COTTEC

-Detail of the starting aids used for the tests, battery included:

-Fuel

.Type -35#

.Octane or cetane number: >50

.Pour-point and other specifications: -30 ℃

-Engine oil

.Type: SAE 10W/30 , API-CD

.Viscosity and other specifications: 11.4 cSt at 100 ℃

-Test results

.Starting procedure used for the tests: The manufacturer's procedure

.Lowest temperature at which the engine started: -5 ℃

4.3 Turning area and turning circle

	Without brakes	
	Right-hand m	Left-hand m
Radius of turning area	3.98	3.75
Radius of turning circle	3.88	3.65

4.4 Location of center of gravity

-Height above ground: 665 mm
-Distance from the vertical plane containing the axis of the rear-wheels: 768 mm
-Distance from the median longitudinal plane of the tractor: -2 mm
-If the angle of suspension of the tractor is less then 20° ,indicate its value: None

4.5 Braking

-Date and location of tests: Sep.28, 2007, COTTEC

4.5.1 Cold service braking device test


	Speed before application of brakes km/h	Braking device control force kN	Mean deceleration m/s^2	Minimum stopping distance without locking the wheels m
Ballasted tractor	30.6	0.1	1.07	33.9
	30.6	0.2	1.95	18.5
	30.6	0.3	2.53	14.3
	30.6	0.4	2.87	12.6
	30.6	0.5	3.06	11.8
	30.6	0.6	3.14	11.5
Unballasted tractor	30.6	0.1	1.14	31.7
	30.6	0.2	2.08	17.4
	30.6	0.3	2.74	13.2
	30.6	0.4	3.04	11.9
	30.6	0.5	3.23	11.2
	30.6	0.6	3.28	11.0

-Maximum deviation of tractor from its original course: 0 mm
-Abnormal vibration: None

4.5.2 Fade test

	Speed before application of brakes km/h	Braking device control force kN	Mean deceleration m/s^2	Minimum stopping distance without locking the wheels m
Ballasted tractor	30.6	0.1	0.97	37.4
	30.6	0.2	1.66	21.8
	30.6	0.3	2.32	15.6
	30.6	0.4	2.66	13.6
	30.6	0.5	2.89	12.5
	30.6	0.6	2.94	12.3

-Maximum deviation of tractor from its original course: 0 mm
-Abnormal vibration: None
-Brake heating method: Driving



4.5.3 Parking braking device test

	Uphill	Downhill
Braking device control force N	270	250


4.6 Measurement of external noise

-Date and location of tests:	Oct.17, 2007, COTTEC
-Sound level meter, make/mode/type:	ONO SOKKI LA-5111
-Type of track:	Concrete
-Gear number:	H4
-Travelling speed before acceleration:	23.0 km/h
-Sound level:	85.5 dB(A)

5. REPAIRS: None


6. REMARKS: None

Director of the COTTEC
Senior engineer




Sun Zhendong

Vice-director of the COTTEC
Senior engineer



Li Jingzhong

Responsible engineer for these tests and editor for the test report publish:
Senior engineer




Ren Yueguang


Members of the tractor test board:
Chen Zhiqiang Yan Xiaofang, Gao Bo
Zheng Zhigang, Li Yong, Zhao Jun,
Sun Zhennan, Yang Hongmei,Liu Hui
Sun Panpan,Liu Zhiqiang,Bai Demin,
Yi Xiaodong, Liu Hongqiang,

Date: Jan. 04,2008

ANNEX I


Main power take-off test curves 1






ANNEX Ⅱ

Main power take-off test curves 2





ANNEX III

Main power take-off test curves 3

