STÁTNÍ ZKUŠEBNA ZEMĚDĚLSKÝCH,
POTRAVINÁŘSKÝCH
A LESNICKÝCH STROJŮ

163 04 PRAHA 6, ŘEPY

Report on test in accordance with the O. E. C. D. STANDARD CODE
for the Official Testing of Agricultural Tractors

CODE II

Restricted Code

Date of approval: 21st June 1993

O.E.C.D. No. 1458



Agricultural Tractor
ZETOR 3320 (2WD)

Manufactured by:
ZETOR s.p.
632 00 Brno, CZ

Report No. 10743
Date of test: Oct. 1992 - Mar.1993

TABLE OF CONTENTS

	Page No.
I. SPECIFICATION OF TRACTOR	3
II. TEST CONDITIONS	15
III. TEST RESULTS	18
COMPULSORY TESTS RESULTS	
1. Main power take-off	18
2. Hydraulic power and lifting force	22
3. Drawbar power and fuel consumption	23
OPTIONAL TEST RESULTS	
4. Braking	26
5. Measurement of external noise level	27
6. Repairs	27
7. Remarks	27

Tractor manufacturer's name and address:	ZETOR s.p., 632 00 Brno, Czech Republic
Location of tractor assembly:	Brno, Czech Republic
Submitted for test by:	The manufacturer
Selected for test by:	The manufacturer
Place of running-in:	Brno, Czech Republic
Duration of running-in:	60 hours
Location of test:	SZZPLS Praha 6 - Řepy, Czech Republic

I. SPECIFICATIONS OF TRACTOR

TRACTOR

Make:	ZETOR
Model:	3320
Type:	Wheeled, unit construction, rear wheels drive
Number of driving wheels:	2
Serial No.:	047 333
1st Serial No.:	047 333

ENGINE

Make:	ZBROJOVKA
Model:	Zetor 5201
Type:	4-stroke diesel engine, direct injection, water cooled, naturally aspirated
Serial No.:	075 587

Cylinders

Number/disposition:	3, in-line, vertical
Bore/stroke:	102 mm/110 mm
Capacity:	2697 cm^3
Compression ratio:	17:1
Arrangement of valves:	Overhead

Cylinder liners:	Wet, replaceable
Supercharging	None
Fuel system	
Fuel feed system:	Lift pump piston-type, integral with fuel injection pump
Make, model and type of fuel filters:	AUTOBRZDY, 443 741 111 001, one-stage with paper cartridge
Capacity of fuel tank:	70 dm^3
Make, model and type of injection pump:	MOTORPAL, PP 3M 3143, in-line
Serial No.:	Dw 0552
Manufacturer's production setting of injection pump:	
Flow rate (rated engine speed and full load):	9.92±0.20 dm^3/h
Timing:	$25^{o}+1^{o}$ before TDC
Make, model and type of injection:	MOTORPAL, DOP 160S 430-1436, 4 holes
Injection pressure:	18.6-0.8 MPa
Governor	
Make, model and type:	MOTORPAL, RV 3M 350/1100-3303, centrifugal, variable speed
Governed range of engine speed:	700-2410 rev/min
Rated engine speed:	2200 rev/min
Air cleaner	
Make, model and type of pre-cleaner:	SANDRIK, PC 250, cyclon type
Location of air intake:	Under bonnet forward of radiator
Make, model and type of main cleaner:	SANDRIK, 9420.11, oil bath
Maintenance indicator:	None
Lubrication system	
Type of feed pump:	Gear
Type of filter:	Full flow, two-stage screen filter
Number:	2

Cooling system

Type of coolant:	Water and anti-freeze
Type of pump:	Centrifugal, belt driven
Specification of fan:	Axial, belt driven
Number of blades:	4
Fan diameter:	380 mm
Coolant capacity:	10.5 dm^3
Type of temperature control:	Thermostat
Superpressure system:	40±10 kPa

Starting system

Make, model and type:	PAL, 443 115 144 722, electrical, solenoid engaged
Starter motor power rating:	2.9 kW
Cold starting aid:	None
Safety device:	Clutch pedal to be fully depressed

Electrical system

Voltage:	12 V, negative earth
Generator:	
Make, model and type:	PAL, 443 113 516 651, alternator, belt driven
Power:	770 W
Battery:	
Number:	1
Rating:	150 Ah at 20 hours

Exhaust system

Make, model and type:	ZETOR, 78.014.010, expansion and absorption muffler
Location:	Left-hand side of engine, vertical

TRANSMISSION TO WHEELS

Clutch

Make, model and type:	ZBROJOVKA, 5201 1100, dry for travelling and P.T.O.
Number of plates:	2
Diameter of plates:	280 mm

Method of operation:	Hydraulically by pedal for travelling and P.T.O. and pneumatically by hand lever for P.T.O.

Gear box

Make, model and type:	ZETOR, 60.121.000, mechanical
Arrangement:	Synchromesh gear box with 5 forward and 1 reverse speeds, group gear box with two speed ranges (T and R)
Number of gears:	10 forward and 2 reverse
Available options:	Alternative mounting of torque multiplier, creeper reduction gear or reverser

Rear axle and final drives

Make, model and type:	ZETOR, 6211 2800, crown wheel and bevel pinion differential and spur gear final drives
Differential lock:	
Type:	Mechanical
Method of engagement:	Mechanically by pedal
Method of disengagement:	Self-disengaging

Front axle

Make, model and type:	ZETOR, 7211 3300, telescopic with adjustable track

Total ratios and travelling speeds

Gear	Group	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed at rated engine speed of 2200 rev/min km/h (*)
1	T	553.886	1.07
2		451.294	1.31
3		303.818	1.95
4		189.114	3.14
5		119.199	4.97
1	R	96.301	6.16
2		78.464	7.56
3		52.823	11.23
4		32.880	18.04
5		20.724	28.61
R	T	556.084	1.07
	R	96.683	6.13

T: Turtle range, R: Rabbit range

(*) Calculated with a tyre dynamic radius index of 715 mm (ISO 4251/1-1988).

POWER TAKE-OFF

Main power take-off

Type:	Independent, through second plate in main clutch
Method of engagement:	Pneumatically operated by hand lever or hydraulically by clutch pedal
Number of shafts:	1
Method of changing power take-off speeds:	Manually by exchanging shafts

Power take-off proportional to engine speed

Location: At rear of tractor

P.T.O.	Diameter of power take-off shaft end mm	Number of splines	In conformity with ISO 500/1991
540	34.9	6	Yes
1000	34.9	21	Yes

Height above ground: 722 mm

Distance from the median plane of tractor: 0 mm

Distance behind rear-wheel axis: 263 mm

P.T.O.	P.T.O. speed rev/min	Engine speed rev/min	Ratio of rotation speeds (engine/P.T.O.)	Power restriction kW
540	540	1994	3.6923	None
	596	2200		
1000	1000	2050	2.0500	None
	1073	2200		

Direction of rotation (viewed facing driving end): Clockwise

Power take-off proportional to ground speed

Indicate 540 or 1000 rev/min: The same

P.T.O. and range	Travelling distance for one revolution of P.T.O. shaft m	Number of P.T.O. shaft revolutions for one revol. of (rear) driving wheels
T	0.084	53.6395
R	0.482	9.3260

T: Turtle range, R: Rabbit range

Direction of rotation with forward gear engaged (viewed facing driving end): Clockwise


POWER LIFT


Make, model and type:	ZETOR, 5011 9485, hydraulic with mechanical position, draft or mixed control, top link sensing
Type of hydraulic system:	Open centre
Type and number of cylinders:	1 integral single-acting
Type of linkage lock for transport:	Hydraulic
Relief valve pressure setting:	18.0+2.0 MPa
Opening pressure of cylinder safety valve:	21.0+2.0 MPa
Lift pump type:	Gear
Transmission between pump and engine:	Gear driven from engine
Type and number of filters:	1 magnetic, 1 screen and 1 filter with paper cartridge in delivery side of distributor
Site of oil reservoir:	Transmission housing
Type, number and location of tapping points:	2 pressure and 1 return, quick release at rear of tractor
Maximum volume of oil available to external cylinders:	10 dm^3

Three-point linkage

Category: 2, in conformity with ISO 730/1-1990

Category adapter: None





Linkage geometry dimensions:

		Dimension or range mm	Settings used in test mm
Length of lift arms	(A)	320	320
Length of lower links	(B)	857	857
Distance of lift arm pivot point from :horizontally	(a)	30	30
rear-wheel axis :vertically	(b)	362	362
Horizontal distance between the 2 lower link points	(u)	636	636
Horizontal distance between the 2 lift arm end points	(v)	450	450
Length of upper link	(S)	590 to 770	648
Distance of upper link pivot point from :horizontally	(c)	288	288
rear-wheel axis :vertically	(d)	182, 229, 276, 323	276
Distance of lower link pivot point from :horizontally	(e)	83	83
rear-wheel axis :vertically	(f)	138	138
Distance of lower link pivot points to lift rod pivot points on lower links	(D)	401	401
Length of lift rods	(L)	436 to 572	560
Height of lower hitch points relative to the rear-wheel axis:			
- in low position	(h)	271 to 605	515
- in high position	(H)	99 to 370	180
Height above ground of lower hitch points when locked in transport position (*)		Any height withing lift range	

(*) Assuming the tyre dynamic radius index r=715 mm of ISO 4251/1-1988

SWINGING DRAWBAR

Type: Clevis

Height above ground:
Maximum: 614 mm
Minimum: 444 mm

Type of adjustment:	Inverting drawbar and clevis
Distance of hitch point from rear-wheel axis, horizontally:	653, 664 and 668 mm
Distance of hitch point from power take-off shaft end:	
Vertically:	108, 188, 198 and 278 mm
Horizontally:	390, 401 and 405 mm
Lateral adjustment:	
Right-hand:	80 and 160 mm
Left-hand:	80 and 160 mm
Distance of pivot point from rear-wheel axis, horizontally:	185 mm to front
Diameter drawbar pin hole:	32 mm
Maximum vertical permissible load:	6 kN

TRAILER HITCH

Type:	Automatic clevis
Hole diameter:	35 mm
Height above ground:	747, 797, 847, 897 and 947 mm
Distance of hitch point from rear-wheel axis, horizontally:	628 mm
Distance of hitch point from power take-off shaft end:	
Vertically:	25, 75, 125, 175 and 225 mm
Horizontally:	365 mm
Maximum vertical permissible load:	10 kN

HOLED DRAWBAR

Number of holes:	7
Distance between holes:	80 mm
Hole diameter:	32 mm
Thickness/width of the drawbar:	2x20 mm/90 mm
Height above ground:	
Maximum:	895 mm
Minimum:	200 mm
Horizontal distance to power take-off shaft end:	677 mm

FRONT TOWING HITCH

Height above ground:	628 mm
Diameter of pin hole:	31 mm

STEERING

Make, model and type:	DANFOSS, OSPC 80 ON, hydrostatic
Method of operation:	Independent hydraulic circuit for steering
Pump:	Gear, driven from engine
Ram:	Double-acting cylinder on the front axle, symmetrical design
Working pressure:	8.0 MPa

BRAKES

Service brake

Make, model and type:	ZETOR, 7245 2600, dry disc, multiplate, 2 discs each side
Method of operation:	Hydraulically by pedals, coupled or independent
Trailer braking take-off:	Air brake operated by tractor pedals

Parking brake

Type:	Common with service brake
Method of operation:	Mechanical by hand lever with ratchet

WHEELS

Number:	
Front:	2, steering
Rear:	2, driving
Wheelbase:	2114 mm

Track width adjustment:

	Minimum mm	Maximum mm	Adjustment method
Front	1350	1800	By extending of front axle
Rear	1345	1795	Reversing wheels and off-set lug rims

PROTECTIVE STRUCTURE

Make, model and type:	ROSTROJ, BK 6245, cab with integrated safety frame
Manufacturer's name and address:	ROSTROJ s.p., 683 01 Rousínov, Czech Republic
Protective device:	Cab, not tiltable
O.E.C.D. approval number:	CSD 1363/12

DRIVER'S SEAT

Make, model and type:	MARS, Zetor 5911-5400, upholstered seat
Type of suspension:	Parallelogram linkage adjustable for driver's weight
Type of damping:	Hydraulic
Range of adjustment:	
Longitudinal:	150 mm
Vertical:	60 mm

MISCELLANEOUS

Additional seat:	
Location:	Right-hand side of driver
Number of places:	1

LIGHTING

	Height above ground of centre mm	Size mm	Distance from outside edge of lights to median plane of tractor mm
Headlights	1005	120x120	188
Sidelights	1500	60x65	655
Rearlights	1560	105x70	765
Reflectors	1440	ϕ78	890

II. TEST CONDITIONS

Overall dimensions

Length mm	Width		Height at top of	
	minimum mm	maximum mm	protective structure mm	exhaust silencer mm
3640	1800	2180	2640	2595

Ground clearence
(unballasted tractor): 375 mm

Clearance-limiting part: Swinging drawbar in lowest position

Tractor mass (with cab)

	Without driver kg	With driver kg
Front	1005	1015
Rear	1890	1955
Total	2895	2970

Tyre and track width specifications

	Front	Rear
Tyres:		
Make	BARUM	BARUM
Dimensions	7.50-16	13.6-36
Ply rating	6	6
Type	diagonal	diagonal
Maximum load (tyre manufacturer's)	7.45 kN	16.15 kN
Maximum load (tractor manufacturer's)	6.50 kN	16.15 kN
Inflation pressure (tyre manufac.)	280 kPa	160 kPa
Dynamic radius index	364 mm	715 mm
Chosen track width:	1425 mm	1425 mm

Oils and lubrication

Capacity and change interval:

	Capacity dm^3	Oil change h	Filter change h
Engine	9.0	200	-
Gear box	25.0	1200	600
Rear axle	Common with gear box		
Final drive (rear)	2x1.9	1200	-
Hydraulic system	Common with gear box		
Steering	4.6	1200	1200
Air cleaner	1.3	100	-

Specifications:

	Recommended	Used during test
Engine oil: Type Viscosity Classification	 SAE 15W/50 16.5 cSt at 100 °C API SD/CB	As recommended
Transmission oils: Type Viscosity Classification	 SAE 80W 7.5 cSt at 100 °C API GL-4	As recommended
Steering oil: Type Viscosity Classification	 OH-HM 32 28.8 cSt at 40 °C ISO 6743 HM 32	As recommended

Hydraulic fluid: Same as transmission

Air cleaner filling: Same as engine

Grease:

Number of lubrication points: 19

Fuel

Type: Diesel fuel, in conformity with national standard ČSN 65 6506

Density at 15 °C: 0.835 g/cm^3 for P.T.O. tests
0.835 g/cm^3 for drawbar tests

III. TEST RESULTS

COMPULSORY TESTS RESULTS

1. MAIN POWER TAKE-OFF

Date and location of tests: 12th February 1992, SZZPLS Praha

Type of dynamometer: FROUDE AG 400

Power	Speed		Fuel consumption			Specific energy
	Engine	P.T.O.	Hourly		Specific	
kW	rev/min		kg/h	l/h	g/kWh	kWh/l
1.1 MAXIMUM POWER - TWO-HOUR TEST						
31.9	2200	1073	8.12	9.72	255	3.28
1.2 POWER AT RATED ENGINE SPEED						
31.9	2200	1073	8.12	9.72	255	3.28
1.3 STANDARD POWER TAKE-OFF SPEED 1000 rev/min						
31.2	2050	1000	7.78	9.32	249	3.35
1.4 PART LOADS 1.4.1 the torque corresponding to maximum power at rated engine speed						
31.9	2200	1073	8.12	9.72	255	3.28
1.4.2 85 % of torque obtained in 1.4.1						
28.5	2314	1129	7.56	9.05	265	3.15
1.4.3 75 % of torque defined in 1.4.2						
21.7	2351	1147	6.19	7.41	285	2.93
1.4.4 50 % of torque defined in 1.4.2						
14.8	2392	1167	4.91	5.88	332	2.52
1.4.5 25 % of torque defined in 1.4.2						
7.4	2409	1175	3.70	4.43	500	1.67
1.4.6 unloaded						
-	2450	1195	2.64	3.16	-	-

Power	Speed		Fuel consumption			Specific energy
	Engine	P.T.O.	Hourly		Specific	
kW	rev/min		kg/h	l/h	g/kWh	kWh/l
1.5 PART LOADS AT STANDARD POWER TAKE-OFF SPEED 1000 rev/min						
1.5.1 the torque corresponding to maximum power						
31.2	2050	1000	7.78	9.32	249	3.35
1.5.2 85 % of torque obtained in 1.5.1						
28.2	2177	1062	7.15	8.56	254	3.29
1.5.3 75 % of torque defined in 1.5.2						
21.4	2208	1077	5.83	6.98	272	3.07
1.5.4 50 % of torque defined in 1.5.2						
14.5	2247	1096	4.53	5.43	312	2.67
1.5.5 25 % of torque defined in 1.5.2						
7.4	2278	1111	3.33	3.99	450	1.85
1.5.6 unloaded						
-	2294	1119	2.30	2.75	-	-

No load maximum engine speed: 2450 rev/min

Torque (equivalent crankshaft) at maximum power: 138.5 Nm

Maximum torque (equivalent crankshaft): 157.7 Nm
(engine speed: 1550 rev/min)


Mean atmospheric conditions:


Temperature: 22 °C
Pressure: 99.1 kPa
Relative humidity: 55 %

Maximum temperatures:

Coolant: 88 °C
Engine oil: 111 °C
Fuel: 55 °C
Engine air intake: 28 °C

POWER TAKE-OFF TEST




POWER TAKE-OFF TEST
Specific fuel consumption, g/kWh
500
465
430
395
360
325
290
255
220
0
7
14
21
28
35
Power, kW

2. HYDRAULIC POWER AND LIFTING FORCE

Date of test: 16th and 17th February 1993

2.1 HYDRAULIC POWER TEST

Sustained pressure with relief valve open: 20.2 MPa

Pump delivery rate at minimum pressure: 32.0 l/min

	Flow rate l/min	Pressure MPa	Power kW
At 90 % of the actual relief valve pressure setting	24.6	18.2	7.5
At maximum hydraulic power	24.5	19.0	7.8

Tapping point used for test: External tapping

Temperature of hydraulic fluid: 63 °C

Opening and closing pressures of the unloading valve: Not applicable

2.2 POWER LIFT TEST

	At the hitch point	On the frame
Height of lower hitch points above ground in down position	200 mm	200 mm
Vertical movement	667 mm	838 mm
Maximum corrected force exerted through full range	19.9 kN	14.0 kN
Corresponding pressure of hydraulic fluid	18.2 MPa	18.2 MPa
Moment about rear-wheel axis	18.7 kNm	21.7 kNm
Maximum tilt angle of mast from vertical	-	10 degrees

Lifting heights relative to the horizontal plane including the lower link pivot points												
mm	-455	-400	-377	-300	-200	-100	0	+100	+200	+290	+300	+383
Lifting forces at the hitch points, corrected to 18.2 MPa												
kN	-	-	21.2	21.4	21.6	21.1	20.5	20.2	19.9	19.9	-	-
Lifting forces at the test frame, corrected to 18.2 MPa												
kN	18.9	18.8	-	18.6	18.1	17.5	16.7	16.0	15.0	-	14.4	14.0

3. DRAWBAR POWER AND FUEL CONSUMPTION (UNBALLASTED TRACTOR)

Date of test: 18th November 1992

Type of track: Bituminous-concrete surface

Height of drawbar above ground	Tyre inflation pressure	
	Front	Rear
444 mm	210 kPa	160 kPa

Gear and group	Power	Drawbar pull	Speed	Engine speed	Slip of wheels	Specific fuel consumption
	kW	kN	km/h	rev/min	%	g/kWh
3.1 MAXIMUM POWER IN TESTED GEARS						
1 T	5.6	19.5	1.03	2419	15.0	663
2 T	6.8	19.6	1.25	2409	15.0	566
3 T	10.0	19.3	1.86	2395	14.9	432
4 T	15.9	19.5	2.94	2360	15.0	348
5 T	24.4	19.1	4.60	2319	14.9	312
1 R	28.0	17.6	5.72	2200	9.9	285
2 R	28.4	14.1	7.25	2202	7.0	281
3 R	28.3	9.1	11.20	2204	3.5	281
4 R	27.2	5.4	18.14	2202	2.6	287
3.2 FUEL CONSUMPTION						
3.2.1 in selected gear, at maximum power at rated speed						
2 R	28.4	14.1	7.25	2202	7.0	281
3.2.1.1 75 % of pull at maximum power at rated speed						
2 R	23.4	10.7	7.86	2342	4.7	287
3.2.1.2 50 % of pull at maximum power at rated speed						
2 R	16.0	7.1	8.13	2376	2.8	327
3.2.1.3 next higher gear at reduced engine speed; same pull						
3 R	23.3	10.7	7.83	1513	4.7	255
3.2.1.4 next higher gear at reduced engine speed; same pull						
3 R	15.9	7.0	8.18	1612	2.8	294
3.2.2 in selected gear nearest to 7.5 km/h at rated speed						
2 R	28.4	14.1	7.25	2202	7.0	281
3.2.2.1 75 % of pull at maximum power at rated speed						
2 R	23.4	10.7	7.86	2342	4.7	287
3.2.2.2 50 % of pull at maximum power at rated speed						
2 R	16.0	7.1	8.13	2376	2.8	327
3.2.2.3 next higher gear at reduced engine speed; same pull						
3 R	23.3	10.7	7.83	1513	4.7	255
3.2.2.4 next higher gear at reduced engine speed; same pull						
3 R	15.9	7.0	8.18	1612	2.8	294

Specific energy	Temperature			Atmospheric conditions		
	Fuel	Coolant	Engine oil	Tempera-ture	Relative humidity	Pressure
kWh/l	°C	°C	°C	°C	%	kPa
1.26	16	76	84	4	88	96.7
1.47	20	77	85	4	88	96.7
1.93	18	78	86	4	88	96.7
2.40	20	78	87	4	88	96.7
2.68	23	77	90	4	89	96.7
2.93	21	77	89	4	89	96.8
2.97	22	77	89	4	89	96.8
2.98	17	77	89	4	89	96.8
2.90	20	77	88	4	89	96.8
2.97	22	77	89	4	89	96.8
2.91	22	77	90	3	87	96.8
2.55	23	77	91	3	87	96.8
and travelling speed as in 3.2.1.1						
3.27	23	77	84	3	87	96.8
and travelling speed as in 3.2.1.2						
2.84	23	76	87	3	87	96.8
2.97	22	77	89	4	89	96.8
2.91	22	77	90	3	87	96.8
2.55	23	77	91	3	87	96.8
and travelling speed as in 3.2.2.1						
3.27	23	77	84	3	87	96.8
and travelling speed as in 3.2.2.2						
2.84	23	76	87	3	87	96.8

OPTIONAL TEST RESULTS


4. BRAKING

Date of test: 18th March 1993

	Tractor mass (with driver)			Speed before application of brakes
	Front kg	Rear kg	Total kg	km/h
Ballasted	1300	3600	4900	31.2
Unballasted	1015	1955	2970	31.7

4.1 COLD SERVICE BRAKING DEVICE TEST (————————)

4.2 FADE TEST (- - - - - -)



Maximum deviation of tractor from its original course:	Not significant
Abnormal vibration:	None
Brake heating method:	Driven with brakes applied for 1 km at 80 % of maximum speed with a pedal force corresponding to a deceleration of 1 m/s^2

4.3 PARKING BRAKING DEVICE TEST

	Ballasted tractor on 18 % - slope	
	Uphill	Downhill
Braking device control force	275 N	270 N

5. MEASUREMENT OF EXTERNAL NOISE LEVEL

Date of test:	27th October 1992
Make and model of sound level meter:	BRÜEL & KJAER, 2231
Type of track:	Bituminous-concrete surface
Gear number:	5 R
Travelling speed before acceleration:	23.8 km/h
Sound level:	86.0 dB(A)

6. REPAIRS

None

7. REMARKS

None

Test carried out by: Dipl. Ing. Peter Pernis

Head of the Tractor Department	Director
Dipl. Ing. Peter Pernis	Dipl. Ing. Vladimír Hanzlík