STÁTNÍ ZKUŠEBNA
ZEMĚDĚLSKÝCH,
POTRAVINÁŘSKÝCH
A LESNICKÝCH STROJŮ

SZZPLS
Třanovského 173
CZ-163 04 Praha 6 - Řepy
Czech Republic
Tel.: +420 2 3038111
Fax: +420 2 3015226
E-mail: szzpls@szzpls.cz

Report on test in accordance with the O.E.C.D. STANDARD CODE 2 for the Official Testing of Agricultural and Forestry Tractors

Restricted Code

O.E.C.D. approval № 2/1470/3

Date of approval: 10th March 1999



Agricultural Tractor

ZETOR 63 20 Utility (2WD) 30 km/h version

Manufactured by: ZETOR a.s., CZ-632 00 Brno,
Czech Republic

Report № 14091

Date of test: December 1998 – January 1999

TABLE OF CONTENTS

1. SPECIFICATIONS OF TRACTOR 3
2. TEST CONDITIONS 15
3. COMPULSORY TESTS RESULTS 18
3.1 Main power take-off 18
3.2 Hydraulic power and lifting force 23
3.3 Drawbar power test (unballasted tractor) 24
4. OPTIONAL TESTS RESULTS 27
4.1 Braking 27
4.2 Measurement of external noise 28
5. REPAIRS 29
6. REMARKS 29

GENERAL NOTE

SZZPLS Praha is still the official Czech Republic Test Station for carrying out Tests in accordance with the OECD Standard Codes for the Official Testing of Agricultural and Forestry Tractors.

Checking for the extension test report

Location:	SZZPLS Praha, Czech Republic
Date of checking:	25th January 1999

This extension of validity for a original test has been approved by the OECD Co-ordinating Centre in Antony (France), as being in accordance with OECD Standard Code for the Official Testing of Agricultural and Forestry Tractors - Code 2.

O.E.C.D. approval number:	2/1470/3
Date of approval:	10th March 1999

ORIGINAL TEST REPORT

The specifications of the tractor and the results of the performance test are taken from the report number:

O.E.C.D. approval number:	1470 Restricted Code
Date of approval:	9th July 1993
Make, model and type of tractor:	ZETOR, 6320, two wheels drive
Manufactured by:	ZETOR s.p., CZ-632 00 Brno, Czech Republic
Submitted for test by:	The manufacturer

The differences between the tractors ZETOR 6320 (2WD) and ZETOR 6320 Utility (2WD) 30 m/h version are written in *italics*, taking into account these differences, SZZPLS Praha has reproduced the hydraulic power and lifting force test and external sound level test and considers that the other results of reference test are valid for the tractor for which the extension is asked.

Tractor manufacturer's name and address:	ZETOR s.p., 632 00 Brno, Czech Republic *ZETOR a.s., CZ-632 00 Brno, Czech Republic*
Location of tractor assembly:	Brno, Czech Republic
Submitted for test by:	The manufacturer
Selected for test by:	The manufacturer
Place of running-in:	Brno, Czech Republic
Duration of running-in:	60 hours
Location of test:	SZZPLS Praha, Czech Republic

1. SPECIFICATIONS OF TRACTOR

1.1 IDENTIFICATION

Make:	ZETOR
Model:	6320 *6320 Utility 30 km/h version*
Type:	Wheeled, unit construction, rear wheels drive
Number of driving wheels:	2
Serial №:	027 561 *010 960*
1st Serial №:	027 561 *010 960*

1.2 ENGINE

Make:	ZBROJOVKA *ZETOR*
Model:	Zetor 7701 *7701*
Type:	4-stroke diesel engine, direct injection, water cooled, naturally aspirated
Serial №:	*027 568* **7701-057462**

1.2.1 Cylinders

Number/disposition:	4, in-line, vertical
Bore/stroke:	102 mm/120 mm
Capacity:	3922 cm^3
Compression ratio:	17.0:1
Arrangement of valves:	Overhead
Cylinder liners:	Wet, replaceable
1.2.2 Supercharging	None

1.2.3 Fuel system

Fuel feed system:	Lift pump piston-type, integral with fuel injection pump
Make, model and type of fuel filter(s):	AUTOBRZDY, 443 741 111 001, one-stage with paper cartridge *ATESO, 443 741 111 001, one-stage with paper cartridge*
Capacity of fuel tank:	95 dm³ *43 dm³*
Make, model and type of injection pump:	MOTORPAL, PP 3M 3137, in-line *MOTORPAL, 3M 3137, in-line*
Serial №:	Bw 0478 *LD 0341*
Manufacturer's production setting of injection pump	
Flow rate (rated engine speed and full load):	13.60 to 14.12 dm³/h
Timing:	25°+1° before TDC
Make, model and type of injectors:	MOTORPAL, DOP 160S 430-1436, 4 hole
Injection pressure:	18.6-0.8 MPa

1.2.4 Governor

Make, model and type:	MOTORPAL, RV 3M 300 1100 3300, centrifugal, variable speed
Governed range of engine speed:	From 600 to 2410 rev/min
Rated engine speed:	2200 rev/min

1.2.5 Air cleaner

Pre-cleaner	
Make, model and type:	SANDRIK, PC 250, cyclon type *Integral with main cleaner, cyclon type*
Location of air intake:	Under bonnet forward of radiator
Main cleaner	
Make, model and type:	SANDRIK, 9420.11, oil bath *DONALDSON, FPG 07-0006, dry with paper primary and safety elements, integrated cyclon type pre-cleaner*
Maintenance indicator:	None *Indicator on air cleaner*

1.2.6 Lubrication system

Type of feed pump:	Gear
Type of filter(s):	Full flow, centrifugal *Full flow with replaceable paper element*
Number of filters:	1
Oil cooler:	None

1.2.7 Cooling system

Type of coolant:	Water and anti-freeze

Type of pump:	Centrifugal, belt driven
Specification of fan or blower:	Axial, belt driven
Number of fan blades:	6
Fan diameter:	380 mm
Coolant capacity:	11.6 dm³ *10.6 dm³*
Type of temperature control:	Thermostat
Superpressure system:	40±10 kPa

1.2.8 Starting system

Make, model and type:	PAL, 443 115 144 722, electrical, solenoid engaged *MAGNETON, 443 115 144 722, electrical, solenoid engaged*
Starter motor power rating:	2.9 kW
Cold starting aid:	None
Safety device:	Clutch pedal to be fully depressed

1.2.9 Electrical system

Voltage:	12 V, negative earth
Generator	
Make, model and type:	PAL, 443 113 516 651, alternator, belt driven *MAGNETON, 443 113 516 653, alternator, belt driven*
Power:	770 W
Battery of accumulators	
Number:	1
Rating:	150 Ah at 20 hours *88 Ah at 20 hours*

1.2.10 Exhaust system

Make, model and type:	ZETOR, 78.014.020, expansion and absorption muffler with additional muffler
Location:	Left-hand side of engine, vertical

1.3 TRANSMISSION

1.3.1 Clutch

Make, model and type:	ZBROJOVKA, 7901 1100, dry for travelling and p.t.o. *ZETOR, 7901 1100, dry for travelling and p.t.o.*
Number of plates:	2
Diameter of plates:	310 mm
Method of operation:	Hydraulically by pedal for travelling and p.t.o. and pneumatically by hand lever for p.t.o. *Mechanically by pedal for travelling and p.t.o. and mechanically by hand lever for p.t.o.*

1.3.2 Gear box

Make, model and type: ZETOR, 60.121.000, mechanical

Description: Synchromesh gear box with 5 forward and 1 reverse speeds, group gear box with two speed ranges (T and R)

	Forward	Reverse
Number of gears	5	1
Number of groups	2	2
Total of arrangements	10	2

Available options: Alternative mounting of torque multiplier, creeper reduction gear or reverser
None

Oil cooler: None

1.3.3 Rear axle and final drives

Make, model and type: ZETOR, 6211 2800, crown wheel and bevel pinion differential and spur gear final drives

Differential lock

Type: Dog clutch

Method of engagement: Mechanically by pedal

Method of disengagement: Self-disengaging

1.3.4 Front axle

Make, model and type: ZETOR, 7211 3300, telescopic with adjustable track

1.3.5 Total ratios and travelling speeds

Gear №	Group	Number of engine revolutions for one revolution of the driving wheels	Nominal travelling speed at rated engine speed of 2200 rev/min km/h (*)
1	T	553.886	1.12 *0.96*
2		451.294	1.37 *1.18*
3		303.818	2.03 *1.75*
4		189.114	3.27 *2.81*
5		119.199	5.18 *4.45*
1	R	96.301	6.42 *5.51*
2		78.464	7.87 *6.76*
3		52.823	11.70 *10.05*
4		32.880	18.79 *16.14*
5		20.724	29.82 *25.61*
R	T	556.084	1.11 ***0.95***
	R	96.683	6.39 *5.49*
(*) Calculated with a tyre dynamic radius index of 745 mm (ISO 4251/1-1988) *Calculated with a tyre dynamic radius index of 640 mm (ISO 4251-1:1992)*			

T: Turtle group, R: Rabbit group

1.4 POWER TAKE-OFF

1.4.1 Main power take-off

Type:	Independent, through second plate in main clutch
Method of engagement:	Pneumatically operated by hand lever or hydraulically by clutch pedal *Mechanically operated by hand lever or by clutch pedal*
Number of shafts:	1
Method of changing power take-off shaft ends and speeds:	Manually by exchanging shafts *None*

1.4.1.1 Power take-off proportional to engine speed

Location: At rear of tractor

P.T.O. type	Diameter of power take-off shaft end	Number of splines	In conformity with ISO 500:1991
	mm		
540	34.9	6	Yes
1000	34.9	21	Yes

Height above ground: 752 mm
647 mm

Distance from the median plane of the tractor: 0 mm

Distance behind rear-wheel axis: 263 mm

P.T.O. type	P.T.O. speed	Engine speed	Ratio of rotation speeds (engine speed/p.t.o. speed)	Power restriction/Maximum torque transmissible
	rev/min	rev/min		kW/Nm
540	540	1994	3.6923	None
	596	2200		
1000	1000	2050	2.0500	None
	1073	2200		

Direction of rotation (viewed from behind tractor): Clockwise

1.4.1.2 Power take-off proportional to ground speed

Indicate	Group	Travelling distance for one revolution of power take-off shaft	Number of power take-off shaft revolutions for one revolution of (rear) driving wheels
rev/min		m	
540 or 1000	T	0.087 *0.075*	53.6395
	R	0.502 *0.431*	9.3260

T: Turtle group, R: Rabbit group

Direction of rotation with forward gear engaged (viewed from behind tractor): Clockwise

1.4.2 Optional power take-off None

1.5 HYDRAULIC POWER LIFT

Make, model and type: ZETOR, 7211 9485, hydraulic with mechanical position, draft or mixed control, top link sensing
ZETOR, 5011 9485, hydraulic with mechanical position, draft or mixed control, top link sensing

Type of hydraulic system: Open centre


Type and number of cylinders: 1 integral single-acting and 2 external single-acting
1 integral single-acting


Type of linkage lock for transport: Hydraulic

Relief valve pressure setting (tolerance):	18.0+0.2 MPa
Opening pressure of cylinder safety valve:	21.0+2.0 MPa
Lift pump type:	Gear pump
Transmission between pump and engine:	Gear driven from engine *Gear driven from p.t.o. shaft*
Type and number of filters:	1 magnetic, 1 screen and 1 filter with paper cartridge in delivery side of distributor *1 magnetic and 1 screen filter*
Site of oil reservoir:	Transmission housing
Type, number and location of tapping points:	ISO standard couplings 12.5 mm, one double acting control valves, 2 pressure and 1 return couplings at rear of tractor
Maximum volume of oil available to external cylinders:	10 dm^3

1.6 THREE-POINT LINKAGE

Category:	2, in conformity with ISO 730-1:1994
Category adapter:	None





Linkage geometry dimensions:

			Dimension or range	Settings used in test
			mm	mm
Length of lift arms		(A)	320	320
Length of lower links		(B)	857	857
Distance of lift arm pivot point from rear-wheel axis:	horizontally	(a)	30	30
	vertically	(b)	362	362
Horizontal distance between the 2 lower link points		(u)	636	636
Horizontal distance between the 2 lift arm end points		(v)	450	450
Length of upper link		(S)	590 to 770	663
Distance of upper link pivot point from rear-wheel axis:	horizontally	(c)	288	288
	vertically	(d)	182, 229, 276, 323	229 *276*
Distance of lower link pivot point from rear-wheel axis:	horizontally	(e)	83	83
	vertically	(f)	138	138
Distance of lower link pivot points to lift rod pivot points on lower links		(D)	401	401
Length of lift rods		(L)	436 to 572	553 *512*
Height of lower hitch points relative to the rear-wheel axis:				
	in low position	(h)	271 to 605	545 *440*
	in high position	(H)	99 to 370	156 *195*
Height above ground of lower hitch points when locked in transport position (*)			Any height withing lift range	

(*) Assuming r=745 mm tyre dynamic radius index of ISO 4251/1-1988
Assuming r=640 mm tyre dynamic radius index of ISO 4251-1:1998

1.7 SWINGING DRAWBAR

Type:
Clevis on towing hook without pivot point
Clevis

Height above ground
Maximum:
450 mm
642 mm

Minimum:
450 mm
232 mm

Type of adjustment:
None
Inverting drawbar and clevis and sliding drawbar in two distance of the hitch point from power take-off shaft end – 335 and 405 mm

Distance of hitch point from rear-wheel axis, horizontally:
663 mm
604, 614, and 618 mm for 355 mm, 653, 664 and 668 mm for 405 mm

Distance of hitch point from power take-off shaft end	
Vertically:	302 mm *5, 115, 305 and 415 mm*
Horizontally:	400 mm *341, 351 and 355 mm for 355 mm, 390, 401 and 405 mm for 405 mm*
Lateral adjustment (centre of clevis)	
Right-hand:	0 mm *75 and 150 mm for 355 mm, 80 and 160 mm for 405 mm*
Left-hand:	0 mm *75 and 150 mm for 355 mm, 80 and 160 mm for 405 mm*
Distance of pivot point from rear-wheel axis, horizontally:	Pivot point not fitted *185 mm to front*
Diameter of drawbar pin hole:	32 mm
Maximum vertical permissible load:	6 kN *12 kN for the height above ground 342 and 642 mm and 6 kN for the height above ground 232 and 532 mm*

1.8 TRAILER HITCH *(on request available, not fitted to tested tractor)*

Type:	Automatic clevis
Hole diameter:	35 mm
Height above ground:	777, 827, 877, 927 and 977 mm *672, 722, 772, 822 and 872 mm*
Distance of hitch point from rear-wheel axis, horizontally:	628 mm
Distance of hitch point from power take-off shaft end	
Vertically:	25, 75, 125, 175 and 225 mm
Horizontally:	365 mm
Maximum vertical permissible load:	10 kN

1.9 HOLED DRAWBAR *(on request available, not fitted to tested tractor)*

Number of holes:	7
Distance between holes:	80 mm
Hole diameter:	32 mm
Thickness/width of the drawbar:	2×20 mm/90 mm
Height above ground	
Maximum:	901 mm *835 mm*
Minimum:	200 mm
Horizontal distance to power take-off shaft end (rear):	677 mm

1.10 SEMI-TRAILER HITCH *(on request available, not fitted to tested tractor)*

Type:	Towing hook
Hole diameter:	47 mm
Height above ground:	523 mm *418 mm*
Distance of hitch point from rear-wheel axis, horizontally:	443 mm
Distance of hitch point from power take-off shaft end	
Vertically:	229 mm
Horizontally:	180 mm
Maximum vertical permissible load:	15 kN

1.11 FRONT TOWING HITCH

Height above ground:	701 mm *619 mm*
Diameter of pin hole:	31 mm

1.12 STEERING

Make, model and type:	DANFOSS, OSPC 80 ON, hydrostatic *DANFOSS, OSPC 100 ON, hydrostatic*
Method of operation:	Independent hydraulic circuit for steering
Pump(s):	Gear pump, driven from engine
Ram(s):	Double-acting cylinder on the front axle, simmetrical design
Working pressure:	8.0 MPa

1.13 BRAKES

1.13.1 Service brake

Rear axle

Make, model and type:	ZETOR, 7245 2600, dry disc, multiplate, 2 discs on each side
Method of operation:	Hydraulically by pedals, coupled or independent
Front axle:	None
Trailer braking take-off:	Air brake operated by tractor pedals *None*

1.13.2 Parking brake

Type:	Common with service brake
Method of operation:	Mechanically by hand lever with ratchet

1.14 WHEELS

Number

Front:	2, steering
Rear:	2, driving
Wheelbase:	2256 mm

Track width adjustment:

	Minimum	Maximum	Adjustment method
	mm	mm	
Front	1420 *1380*	1795 *1830*	By extending of front axle
Rear	1420 *1350*	1795 *1800*	Reversing wheels and off-set lug rims

1.15 PROTECTIVE STRUCTURE *(not fitted to tested tractor)*

Make, model and type:	VĽAD, BK 7245, cab with integrated safety frame *VALMETAZ, OR 6320, rear roll bar frame*
Manufacturer's name and address:	VĽAD, Košická 20, SK-081 17 Prešov, Slovakia *VALMETAZ s.r.o., Kouty 037, CZ-757 01 Valašské Meziříčí, Czech Republic*
Protective device	
Cab/frame/rollguard/other:	Cab *Rollguard*
Tiltable/not tiltable:	Not tiltable
O.E.C.D. approval	
Approval number:	CSD 1375/4 *None*
Date of approval:	25th May 1993
Nos. of minor modification certificates, if any:	None

1.16 SEAT

1.16.1 Driver's seat

Make, model and type:	MARS, Zetor 5911-5400, upholstered seat *ZETOR, 6311 5400, upholstered seat*
Seat and steering wheel reversible:	No
Type of suspension:	Parallelogram linkage adjustable for driver's weight *Parallelogram linkage*
Type of damping:	Hydraulic *Mechanic*

Range of adjustment

Longitudinally:	150 mm *90 mm*
Vertically:	60 mm *0 mm*
Safety belt:	No
1.16.2 Optional driver's seat(s)	None
1.16.3 Passenger seat	None

1.17 LIGHTING

	Height above ground of centre	Size	Distance from outside edge of lights to median plane of tractor
	mm	mm	mm
Headlights	1080 *975*	120×120 *Ø137*	188 *195*
Sidelights	1515 *1455*	60×65	675 *650*
Rearlights	1505 *1465*	105×70	745 *615*
Reflectors	955 *675*	Ø78	740 *475*

2. TEST CONDITIONS

2.1 OVERALL DIMENSIONS (unballasted tractor)

Length	Width		Height at top of	
	minimum	maximum	protective structure	exhaust pipe
mm	mm	mm	mm	mm
3755	1875 *1745*	2250 *2195*	2665 -	2615 *2575*

2.2 GROUND CLEARANCE (unballasted tractor): 410 mm
278 mm

Clearance-limiting part: Semi-trailer hitch
Swinging drawbar in lowest position

2.3 TRACTOR MASS (unballasted tractor with cab)

	Without driver	With driver
	kg	kg
Front	1070 *820*	1080 *835*
Rear	2190 *1400*	2255 *1460*
Total	3260 *2220*	3335 *2295*

2.4 TYRES AND TRACK WIDTH SPECIFICATIONS

	Front	Rear
Tyres:		
Make	BARUM	BARUM
Model	TP 8 *TP 8P*	TZ 17 *TZ 19*
Dimensions	7.50-20 *6.00-16*	16.9-34 *14.9-28*
Ply rating	6 PR *6 PR*	8 PR *8 PR*
Type	Diagonal	Diagonal
Maximum load (tyre manufacturer's)	8.75 kN *5.70 kN*	23.80 kN *18.80 kN*
Maximum load (tractor manufacturer's)	8.75 kN *5.60 kN*	18.00 kN *16.80 kN*
Inflation pressure (tyre manufacturer's)	280 kPa *340 kPa*	170 kPa *180 kPa*
Dynamic radius index	430 mm *340 mm*	745 mm *640 mm*
Chosen track width:	1420 mm *1455 mm*	1420 mm *1425 mm*

2.5 FUEL

Type: Diesel fuel, in conformity with national standard ČSN EN 590

Density at 15 °C: 0.835 g/cm³ for p.t.o. tests
0.836 g/cm³ for drawbar tests

2.6 OILS AND LUBRICATIONS

2.6.1 Capacity and change interval

	Capacity	Oil change	Filter change
	dm³	h	h
Engine	12.0	200	- *200*
Gear box	25.0	1200	600
Rear axle		Common with gear box	
Final drive (rear)	2×1.9	1200	-
Hydraulic system		Common with gear box	
Steering	4.6	1200	1200
Air cleaner	1.3	100	-

2.6.2 Specifications

	Recommended	Used during test
Engine oil: Type Viscosity Classification	 SAE 15W-50 16.5 cSt at 100 °C API SD/CB	As recommended
Transmission oils: Type Viscosity Classification	 SAE 80W 7.5 cSt at 100 °C API GL-4	As recommended
Steering oil: Type Viscosity Classification	 OH – HM32 28.8 cSt at 40 °C ISO 6743-L-HM32	As recommended

Hydraulic fluid: Same as transmission

Air cleaner filling: Same as engine
None

2.6.3 Grease

Number of lubrication points: 24
17

3. COMPULSORY TESTS RESULTS

3.1 MAIN POWER TAKE-OFF

Date and location of tests: 19th February 1992, SZZPLS Praha

Type of dynamometer bench: FROUDE AG 400, eddy-current

Power	Speed		Fuel consumption			Specific energy
	Engine	P.T.O.	Hourly		Specific	
kW	rev/min	rev/min	kg/h	l/h	g/kWh	kWh/l
3.1.1 MAXIMUM POWER - TWO-HOUR TEST						
49.0	2200	1073	11.73	14.05	239	3.49
3.1.2 POWER AT RATED ENGINE SPEED						
49.0	2200	1073	11.73	14.05	239	3.49
3.1.3 STANDARD POWER TAKE-OFF SPEED [1000±25 rev/min]						
47.0	2050	1000	10.99	13.16	234	3.57
3.1.4 PART LOADS 3.1.4.1 the torque corresponding to maximum power at rated engine speed						
49.0	2200	1073	11.73	14.05	239	3.49
3.1.4.2 85 % of torque obtained in 3.1.4.1						
43.2	2282	1113	10.60	12.69	245	3.40
3.1.4.3 75 % of torque defined in 3.1.4.2						
33.1	2331	1137	8.64	10.35	261	3.20
3.1.4.4 50 % of torque defined in 3.1.4.2						
22.4	2364	1153	6.76	8.10	302	2.77
3.1.4.5 25 % of torque defined in 3.1.4.2						
11.3	2388	1165	5.02	6.01	444	1.88
3.1.4.6 unloaded						
-	2415	1178	3.38	4.05	-	-

Power	Speed		Fuel consumption			Specific energy
	Engine	P.T.O.	Hourly		Specific	
kW	rev/min	rev/min	kg/h	l/h	g/kWh	kWh/l
3.1.5 PART LOADS AT STANDARD POWER TAKE-OFF SPEED [1000±25 rev/min] 3.1.5.1 the torque corresponding to maximum power						
47.0	2050	1000	10.99	13.16	234	3.57
3.1.5.2 85 % of torque obtained in 3.1.5.1						
40.5	2077	1013	9.55	11.44	236	3.54
3.1.5.3 75 % of torque defined in 3.1.5.2						
31.0	2122	1035	7.72	9.25	249	3.35
3.1.5.4 50 % of torque defined in 3.1.5.2						
21.0	2159	1053	5.94	7.11	283	2.95
3.1.5.5 25 % of torque defined in 3.1.5.2						
10.7	2196	1071	4.35	5.21	407	2.05
3.1.5.6 unloaded						
-	2214	1080	2.87	3.44	-	-


No load maximum engine speed: 2415 rev/min


Torque (equivalent crankshaft)
At maximum power: 212.7 Nm
At rated engine speed: 212.7 Nm
At standard power take-off speed: 218.9 Nm

Maximum torque (equivalent crankshaft): 246.6 Nm
(engine speed: 1599 rev/min)


Mean atmospheric conditions:	
Temperature	22 °C
Pressure	102.3 kPa
Relative humidity	64 %
Maximum temperatures:	
Coolant	89 °C
Engine oil	114 °C
Fuel	47 °C
Engine air intake	27 °C


POWER TAKE-OFF TEST






POWER TAKE-OFF TEST





POWER TAKE-OFF TEST



3.2 HYDRAULIC POWER AND LIFTING FORCE

Date of tests: 7th and 19th January 1999

3.2.1 Hydraulic power test

Sustained pressure with relief valve open: 17.6 MPa

Pump stalled: Yes

Pump delivery rate at minimum pressure: 37.0 l/min

	Flow rate	Pressure	Power
	l/min	MPa	kW
Flow rate corresponding to a hydraulic pressure equivalent to 90 % of the actual relief valve pressure setting and corresponding hydraulic power	19.0	15.8	5.0
Flow rate and hydraulic pressure corresponding to maximum hydraulic power	25.0	14.5	6.0

Tapping point used for test: External tapping

Temperature of hydraulic fluid: 65 °C

Opening pressure of the unloading valve: Not applicable

Closing pressures of the unloading valve: Not applicable

3.2.2 Power lift test

Linkage setting for test - see page 11

	At the hitch point	On the frame
Height of lower hitch points above ground in down position	200 mm	200 mm
Vertical movement: without lifting force	635 mm	798 mm
with lifting force	609 mm	764 mm
Maximum corrected force exerted through full range	16.7 kN	13.4 kN
Corresponding pressure of hydraulic fluid	15.8 MPa	15.8 MPa
Moment about rear-wheel axis	15.7 kNm	20.8 kNm
Maximum tilt angle of mast from vertical	-	12 degrees

Lifting heights relative to the horizontal plane including the lower link pivot points											
mm	-366	-302	-300	-200	-100	0	+100	+200	+300	+307	+398
Lifting forces at the hitch points (the values of force measured shall be corrected to correspond to a hydraulic pressure equivalent to 90 % of the actual relief valve pressure setting of the hydraulic lift system)											
kN	-	24.0	24.1	23.7	23.4	22.7	22.1	21.5	20.0	16.7	-
Corresponding pressure: 15.8 MPa											
Lifting forces at the test frame											
kN	20.3	-	19.8	19.4	18.7	17.9	16.8	15.9	15.0	-	13.4
Corresponding pressure: 15.8 MPa											

3.3 DRAWBAR POWER TEST (unballasted tractor)

Date of tests: 27th April 1993

Type of track: Bituminous-concrete surface

Height of drawbar above ground	Tyre inflation pressure	
	Front	Rear
mm	kPa	kPa
450	230	130

Gear number and group	Power	Drawbar pull	Speed	Engine speed	Slip of wheels	Specific fuel consumption
	kW	kN	km/h	rev/min	%	g/kWh
3.3.1 MAXIMUM POWER IN TESTED GEARS (unballasted tractor)						
1 T	6.0	20.6	1.05	2390	14.8	777
2 T	7.4	20.8	1.28	2386	15.0	679
3 T	11.0	20.9	1.90	2376	15.0	520
4 T	17.7	21.1	3.02	2351	15.1	409
5 T	27.5	20.9	4.73	2320	15.0	345
1 R	34.2	21.4	5.75	2280	15.1	327
2 R	37.7	19.2	7.06	2205	12.3	302
3 R	39.0	12.7	11.05	2204	7.1	298
4 R	38.2	7.6	18.10	2199	3.5	305
3.3.2 FUEL CONSUMPTION 3.3.2.1 in selected gear, at maximum power at rated speed						
3 R	39.0	12.7	11.05	2204	7.1	298
3.3.2.1.1 75 % of pull at maximum power at rated speed						
3 R	31.6	9.5	11.98	2319	4.7	285
3.3.2.1.2 50 % of pull at maximum power at rated speed						
3 R	21.9	6.4	12.31	2353	3.1	312
3.3.2.1.3 next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.1						
4 R	31.3	9.5	11.87	1381	4.7	241
3.3.2.1.4 next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.1.2						
4 R	21.9	6.4	12.32	1462	3.1	275
3.3.2.2 in selected gear nearest to 7.5 km/h at rated speed						
2 R	37.7	19.2	7.06	2205	12.3	302
3.3.2.2.1 75 % of pull at maximum power at rated speed						
2 R	31.2	14.4	7.79	2314	8.4	314
3.3.2.2.2 50 % of pull at maximum power at rated speed						
2 R	21.6	9.6	8.11	2347	4.8	376
3.3.2.2.3 next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.1						
3 R	30.4	14.4	7.59	1480	8.4	257
3.3.2.2.4 next higher gear at reduced engine speed; same pull and travelling speed as in 3.3.2.2.2						
3 R	21.3	9.6	7.97	1550	4.8	265

Specific energy	Temperature			Atmospheric conditions		
	Fuel	Coolant	Engine oil	Temperature	Relative humidity	Pressure
kWh/l	°C	°C	°C	°C	%	kPa
1.08	38	78	92	27	35	97.7
1.23	35	78	93	27	35	97.7
1.61	40	78	94	27	35	97.7
2.04	38	78	94	27	35	97.7
2.43	39	78	95	27	34	97.7
2.56	40	77	96	27	34	97.7
2.77	42	80	97	28	29	97.7
2.81	39	79	95	28	29	97.7
2.74	41	79	96	28	29	97.7
2.81	39	79	95	28	29	97.7
2.94	34	78	96	26	30	97.7
2.68	35	77	97	26	30	97.7
3.46	37	76	88	26	30	97.7
3.04	36	77	88	26	30	97.7
2.77	42	80	97	28	29	97.7
2.66	39	77	95	28	29	97.7
2.22	38	77	96	28	29	97.7
3.25	38	78	90	26	30	97.7
3.16	38	76	91	26	30	97.7

4. OPTIONAL TESTS RESULTS

4.1 BRAKING

Date of tests: 1st April 1993

Tractor mass (with driver)

	Front	Rear	Total
	kg	kg	kg
Ballasted tractor	1750	3600	5350
Unballasted tractor	1080	2255	3335

4.1.1 Cold service braking device test

	Speed before application of brakes	Braking device control force	Mean deceleration
	km/h	N	m/s²
Ballasted tractor	31.7	85	0.34
		105	0.75
		155	1.49
		225	2.61
		280	2.97
		360	3.57
Unballasted tractor	32.0	80	0.50
		110	0.80
		150	1.50
		225	2.88
		300	3.23
		350	3.74

Maximum deviation of tractor from its original course: Not significant

Abnormal vibration: None


4.1.2 Fade test

	Speed before application of brakes	Braking device control force	Mean deceleration
	km/h	N	m/s²
Ballasted tractor	31.7	95	0.74
		170	1.70
		200	2.12
		290	3.12
		350	3.42
		365	3.67

Maximum deviation of tractor from its original course: Not significant

Abnormal vibration: None

Brake heating method: Driven with brakes applied for 1 km at 80 % of maximum speed with a pedal force corresponding to a deceleration of 1 m/s²



4.1.3 Parking braking device test

	Ballasted tractor on 18 % slope	
	Uphill	Downhill
	N	N
Braking device control force	280	280

4.2 MEASUREMENT OF EXTERNAL NOISE

Date of tests: 22nd January 1999

Make and model of sound level meter: BRÜEL & KJÆR, 2231

Type of track: Bituminous-concrete surface

4.2.1 According to OECD standard code 1

Gear number: 5 T

Travelling speed before acceleration: 21.0 km/h

Sound level: 87.0 dB(A)

4.2.2 According to EEC directives 74/151/EEC (Annex VI), 88/410/EEC and 97/54/EC

Gear number:	5 T
Travelling speed before acceleration:	21.0 km/h
Sound level:	86.0 dB(A)

5. REPAIRS

None

6. REMARKS

None

Extensions granted by:	Dipl. Ing. Peter Pernis
Signed:	
Date:	25th January 1999

Head of the Tractor Laboratory

Dipl. Ing. Peter Pernis

Director

Dipl. Ing. Vladimír Hanzlík