



Test Report

DOLMAR PS 5000

OWNER OF THE TEST CERTIFICATE:

Manufacturer and applicant:

Dolmar GmbH

Jenfelder Strasse 38

D-22045 Hamburg

www.dolmar.de



Test Results and Evaluation

DOLMAR PS 5000/ PS 5000 S chain saw with 38 cm cutting length

Type "S" with a higher max. engine speed

Dolmar GmbH, Jenfelder Strasse 38; D-22045 Hamburg



Test item	Test results				Evaluation
Function	Chain saw in the power class up to 3 kW; for professional use				
Engine power					
Power	Engine speed	Torque	Spec. fuel consumption		NE
max 2.8 kW	10000 min ⁻¹	2,7 Nm	56 kW/l		
2.2 kW	6500 min ⁻¹	max. 3,2 Nm	44 kW/l		
Fuel consumption					
	max. power		max. torque		
absolute / specific	1.6l/h	430 g/kWh	1.5 l/h	516 g/kWh	+
Exhaust emission complies with level 1 of the standard 2002/88 EG					
Chain lubrication					
Oil consumption	at 5000 min ⁻¹		at 9000 min ⁻¹		.
min / max	3 ml/min	5 ml/min	6 ml/min	9 ml/min	O
Sound pressure level					
	idling speed	full load speed	Full throttle no load		
at ear of the operator	83 dB(A)	104 dB(A)	105 dB(A)		-
Equivalent sound pressure level, total value 102 dB(A); (average between: idling/ full load/ full throttle)					
Acoustic power 112 dB(A) according to the standard 2000/14/EG					
Vibrations					
	idling speed	full load speed	Full throttle no load		
front handle	5.3 m ²	4.3 m ²	6.0 m ²		+
rear handle	3.5 m/s ²	4.4 m/s ²	3.1 m/s ²		
Total equivalent vibration front/rear 5.2 / 3.7 m/s ²					
Chain brake					
Handguard activation	Actuating force	aver. braking time	max. braking time		NE
	30 N	0.07 s	0.10 s		
Inertia activation	horizontal acceleration		vertical acceleration		NE
	325 m/s ²		848 m/s ²		

Kickback

Cutting equipment 38 cm, 0,325“ Full chisel tooth	Kickback angle with brake 28.8°	Chain stop angle 17.7°	NE
--	------------------------------------	---------------------------	----

Mass			
Weight per unit power	With cutting equipment	Without cutting equipment	
	2.2 kg/kW	1.9 kg/kW	+
Operability / handling			
Control elements	Easy to reach and use		+
Primer	Decompression valve optional		+
Chain assembly	easy, drive sprocket easily accessible		0
Chain tensioning	simple, on the side in the chain sprocket cover		0
Maintenance			
Air filter and spark plug cover, casing	Quick release for easy access, but requires combination wrench		+
Air filter	cleaning	No tools required	+
	soiling	low	+
Tank caps	The filler opening is insufficiently protected against dirt (some increase in maintenance effort)		-
Special features			
	Compensator for optimal fuel/air mixture when air filter is clogged-up		+
Reliability			
	A small defect occurred during the test (loosening of the fuel tank cap) has since been corrected (May 2005).		+
Operating manual			
	clear, well illustrated		+
Operator safety			
EG-type examination test	TÜV Product Service No. M6 0407 24243 056		
GS-Test	TÜV Product Service No. AL 0407 24243 055		

Rating: ++ / + / 0 / - / --. (0 = Standard / NE= no evaluation, complies with tolerance value)

Tolerance values and evaluation criteria are described in the "Informationen zur Gebrauchswertprüfung" ("Information about the type examination test"). This publication is available from the DLG and the KWF.

Description and Technical Data (measured values)

Engine

- Air-cooled single-cylinder two-stroke engine;
- engine displacement 50 cm³; bore 45m; stroke 31m;
- Fuel: minimum octane number 91ROZ; mixed lubrication, 2T-special fuel with "KWF-TEST"

- Spark plug Bosch WSR-6F or NGK BPMR 7A.
- Idling speed 2500 min⁻¹; max. speed 13500 min⁻¹/ "S" = 14500 min⁻¹
(electronic speed regulator)

Cutting equipment

- Clutch drum with external chain sprocket;
- Guide bar with sprocket nose
- full chisel tooth chain, 3/8" or 0.325" pitch, groove width 1.5 mm.

Additional equipment (not tested)

- Guide bars for 33 to 53 cm cutting lengths;
- Heated handle

Main dimensions and weights

Length,	incl. cutting equipment 38 cm	775 mm
	engine unit with spiked bumper	405 mm
Width,	engine unit	190 mm
	incl. handle	228 mm
Height,	engine unit	208 mm
	with front hand guard	282 mm
Stump height,	chain sprocket cover	15 mm
	handle	20 mm
Tank volume,	fuel	0.45l
	chain oil	0.28 l
Weight,	incl. cutting equipment 38 cm	6,1 kg
	without cutting equipment	5,2 kg

Test

Test carried out by

Kuratorium für Waldarbeit und Forsttechnik, Groß-Umstadt
DLG-Testzentrum Technik & Betriebsmittel, Groß-Umstadt

Field test

Forstl. Bildungszentrum Königsbronn, Itzelberg
Forstwirtschaftsschule Sachsen Anhalt, Magdeburgerforth
Revierförsterei Ehringshausen

Waldarbeitsschule Laubau, Ruhpolding

Authors

H. Krämer, DLG, Groß-Umstadt

D. Ruppert, KWF, Groß-Umstadt

FPA/DLG testing commission

“Geräte und Werkzeuge“ (“Equipment and tools”) with 16 members

Chairman: Josef Berthold, WAS Laubau

FPA / DIG-approval:

May 2005

FPA-Index: 1.01.4037

DLG-Test Report: 5495

The applicant is entitled to display the test mark on machines of this type according to the test regulations and to use the certification for advertising purposes.

DLG-Testzentrum Technik & Betriebsmittel Groß-Umstadt

Max-Eyth-Weg 1

D-64823 Groß-Umstadt

Telephone: 06078/96 35-0

Fax: 06078/963 5-90

E-mail: H.Kraemer@dlg.org

Internet: www.dlg-test.de

Kuratorium für Waldarbeit und Forsttechnik e.V. (KWF)

Forsttechnischer Prüfungsausschuss (FPA)

Spremberger Straße 1

D-64823 Groß-Umstadt

Telephone: 06078/785-0

Fax: 06078/785 50

E-mail: Dietmar.Ruppert@kwf-online.de

www.kwf-online.de



ENTAM European Network for Testing of Agricultural Machines, is a cooperation between European test stations. ENTAM aims to distribute test results for agricultural and forestry equipment throughout Europe.

For more information about the network visit www.entam.com or contact ENTAM at the following e-mail address: info@entam.com